

Australian Standard[®]

**SPEED FLUCTUATIONS IN
ANALOGUE SOUND RECORDING
AND REPRODUCING
EQUIPMENT—METHOD OF
MEASUREMENT**

This Australian Standard was prepared by Committee TE/8, Audio and Video Engineering and Recording. It was approved on behalf of the Council of the Standards Association of Australia on 9 May 1988 and published on 12 September 1988.

The following interests are represented on Committee TE/8:

Australian Broadcasting Corporation
Australian Electrical and Electronic Manufacturers Association
Confederation of Australian Industry
Consumer Electronics Suppliers Association
Department of Transport and Communications
Department of Defence
Federation of Australian Commercial Television Stations
Institution of Radio and Electronics Engineers Australia
National Acoustics Laboratories
Telecom Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

For details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 80216.

Australian Standard[®]

**SPEED FLUCTUATIONS IN
ANALOGUE SOUND RECORDING
AND REPRODUCING
EQUIPMENT—METHOD OF
MEASUREMENT**

First published as AS 3561—1988.

Incorporating:
Amdt 1—1989

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5147 X

PREFACE

This Standard was prepared by the Association's Committee on Audio and Video Engineering and Recording. It is technically identical with IEC 386, *Method of measurement of speed fluctuations in sound recording and reproducing equipment*, as amended by Amendment No 1, March 1988. The major departure from the IEC Publication concerns the explanation given in Clause 3(d) of the 2σ (sigma) method of measuring wow and flutter which has been expanded in clarification without introducing technical changes.

The purpose of the Standard is to specify a method of measurement for short-term variations in the speed of the sound recording medium, whether it be tape or disc, which is generally known as 'wow' or 'flutter' and which occurs through lack of precision in the mechanical drive of the equipment. A method of measuring drift (i.e. longer term variations), is also described. The characteristics of the required instrumentation are also specified.

The Standard was prepared for reference purposes as part of the necessary background to the preparation of a Standard on high fidelity audio recording and reproducing equipment.

CONTENTS

	<i>Page</i>
1 SCOPE	3
2 DEFINITIONS	3
3 MEASUREMENT OF FLUTTER OR WOW	3
4 MEASURING EQUIPMENT	3
 APPENDICES	
A EXPLANATION OF VARIATION OF SPEED OF RECORDING	6
B DESIRABLE CHARACTERISTICS FOR MEASURING EQUIPMENT ..	8

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

STANDARDS ASSOCIATION OF AUSTRALIA

Australian Standard

SPEED FLUCTUATIONS IN ANALOGUE SOUND RECORDING AND REPRODUCING EQUIPMENT—METHODS OF MEASUREMENT

1 SCOPE. This Standard uses a method of measurement applying the weighted peak technique.

Explanatory notes concerning flutter and wow measurement are given in Appendix A. Details of suitable measuring equipment are given in Appendix B.

2 DEFINITIONS. For the purposes of this Standard, the following definitions shall apply.

2.1 Flutter—undesired form of frequency modulation introduced into the signal by an irregular motion of the recording medium during the recording/reproducing process, at frequencies above 10 Hz.

2.2 Wow—undesired form of frequency modulation introduced into the signal by an irregular motion of the recording medium during the recording/ reproducing process, at frequencies from 0.1 Hz to 10 Hz.

2.3 Drift—slow variation of the velocity of the recording medium during recording and reproducing.

3 MEASUREMENT OF FLUTTER OR WOW. In analogue sound recording, it is virtually impossible to obtain completely constant speed of the recording medium because of variations in the mechanical drive. (See Appendix A.)

A method giving the peak value shall be used for the measurement of both flutter and wow for analogue sound recording and reproduction equipment with the following specific requirements:

- The measurements shall be made at a nominal frequency of 3150 Hz.
- Ideally the measurement should be made on one element only of the system (either the recorder or the reproducer, but not on both) under such conditions that the flutter and wow in the remaining parts of the system is negligible. In testing record players or tape replay units, it must be assumed that test disc or test tape contains negligible wow and flutter. When testing a tape recorder, the test signal at 3150 Hz shall be recorded on a blank test tape which shall then be replayed on a tape deck contributing negligible wow and flutter. The output of the unit is then fed into the wow and flutter meter, the indication on the meter being the wow and flutter of the recorder under test.

Where this condition cannot be fulfilled, a complete recorder/reproducer system may be measured by recording a 3150 Hz test frequency and reproducing this recording several times, measuring in each case the total flutter and wow and forming the arithmetic average value of these measurements. Since this method would seem to be the most suitable manner in which to measure tape recorders, the importance of Clause 3(c) cannot be over emphasized.

Flutter and wow shall not be measured while simultaneously recording and reproducing.

- The measuring conditions shall always be stated namely: reproducer only, recorder only or complete recording/reproducing system.
- In order to obtain a stable and reproducible value of the value for wow and flutter, the use of the 2σ (sigma) method is recommended, thereby eliminating random peaks.

The 2σ method is based on the property of a random (Gaussian) distribution that its excursions exceed 2σ , i.e. twice the standard deviation, sigma (the r.m.s. value), for 5% of the time.

The probability, p , of exceeding a limit $\pm r$ times the r.m.s. value (σ) is

$$p = 1 - \text{erf}(r/\sqrt{2})$$

When $r = 2$, then $p = 0.0455$.

NOTE: See Clause 2, where $\text{erf}(x)$ is described as the error integral $\int_0^x \frac{2}{\sqrt{\pi}} e^{-t^2} dt$, $\phi(x) = \text{erf}(x)$.

Thus on the assumption that the speed deviation follows a Gaussian distribution, the measurement is implemented as follows:

During a time interval T , see Figure 3, of at least 10 s, the instantaneous speed deviations are first stored in a memory. These deviation values are then compared with a threshold Δv_0 , which initially is chosen arbitrarily.

The cumulative time Σt_i , within the given time interval T , during which the instantaneous speed deviations exceed the threshold Δv_0 in a positive or negative direction, is calculated. A new threshold value Δv_0 is then estimated, to produce a value of Σt_i nearer to $0.05T$, and the calculation of Σt_i repeated.

The measuring equipment thus searches for that threshold Δv_0 for which the cumulative time Σt_i is equal to 5% of the time interval T .

The measured value Δv_0 shall be expressed as a percentage of the average speed.

4 MEASURING EQUIPMENT.

4.1 General requirements. In addition to the characteristics desirable in the measuring equipment given in Appendix B, it shall have the following characteristics.

4.2 Response curve. As specified in Table 1 and Figure 1.

NOTE: An unweighted response curve, flat at least between 0.1 Hz and 200 Hz would provide useful additional information about the source of flutter and wow. Tolerances and dynamic characteristics are not specified for the unweighted response curve.

- Fink, D.O., *Television Engineering Handbook*, McGraw-Hill, New York, 1953, p.16-9 and Fig. 16-6, Probability of occurrence of any value of noise voltage.
- Jahnke, E. and Emde, F., *Tables of Functions*, 4th Ed., Dover, New York, 1945, p.24.