

*under revision
see DR 94326*

Joint AS/NZS Amendment 1 - October 1992

AS 3629.1—1991

NZS 5466:Part 1:1991

Superseded by AS/NZS 3629.1:1995

Australian Standard®
New Zealand Standard

Methods of testing child restraints
Part 1: Dynamic testing

AUS CC
NZ DD



Standards Association
of New Zealand

STANDARDS AUSTRALIA



This Standard was prepared under a joint arrangement by Standards Australia and the Standards Association of New Zealand. It was approved for publication on behalf of the Council of Standards Australia on 26 November 1991 and on behalf of the Standards Council of New Zealand on 23 December 1991. It was published on 24 December 1991.

The following organizations are represented on the Committees responsible for this Standard:

Standards Australia Committee CS/75, Automotive Occupant Restraints

Australian Automobile Association
Australian Automotive Aftermarket Association
Australian Consumers Association
Australian Federation of Consumer Organizations
Australian Retailers Association
Business and Consumer Affairs, N.S.W.
Confederation of Australian Industry
Department of Transport and Communications
Department of Transport, S.A.
Federal Bureau of Consumer Affairs
Federal Chamber of Automotive Industries
Federation of Automotive Products Manufacturers
Ministry of Consumer Affairs, Vic.
National Association of Testing Authorities, Australia
National Health and Medical Research Council
Retail Traders Associations of Australia
Roads and Traffic Authority, N.S.W.
Royal Australasian College of Surgeons
University of New South Wales

Additional interests participating in preparation of Standard:
VicRoads

Standards Association of New Zealand Committee 50/-, Mechanical and General Board

Accident Compensation Corporation
Consumers Institute
Department of Labour
Department of Scientific & Industrial Research
Institution of Professional Engineers of N.Z.
Medical Association
Ministry of Commerce
Ministry of Transport
National Council of Women
N.Z. Chemical Industry Council
N.Z. Manufacturers Federation

Review of Standards

To keep abreast of progress in industry, Australian and New Zealand Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

All details of all publications of the Standards Association of New Zealand and Standards Australia will be found in the Catalogue of Publications of the respective organization; this information is supplemented in their monthly magazines, which subscribing members receive, and which give details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian and New Zealand Standards, addressed to the head office of the relevant organizations, are welcomed. Notification of any inaccuracy or ambiguity found in either an Australian or New Zealand Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in Australia in draft form for comment as DR 91036 and in New Zealand as DZ 5466:Part 1.

AS 3629.1/NZS 5466.1/Amdt 1/1992-10-12



STANDARDS AUSTRALIA

Amendment No. 1

to

AS 3629.1—1991/NZS 5466.1:1991

Methods of testing child restraints

Part 1: Dynamic testing

REVISED TEXT

The 1991 edition of AS 3629.1/NZS 5466.1 is amended as follows; the amendments should be inserted in the appropriate place.

SUMMARY: This Amendment applies to clauses 8 and 9, Figure 5 and Appendix A.

Published on 12 October 1992.

Approved for publication in New Zealand on behalf of the Standards Council of New Zealand on 9 July 1992.

AS 3629.1—1991
NZS 5466:Part 1:1991

Australian Standard®
New Zealand Standard

Methods of testing child restraints
Part 1: Dynamic testing

In Australia
First published as part of AS E46—1970.
Revised and redesignated AS 1754—1975.
Revised and redesignated in part as
AS 3629.1—1989.
Second edition 1991.

In New Zealand
First published as NZS 5411:1973.
Revised as NZS 5411:1982.
Revised and redesignated as
AS 3629.1/NZS 5466:Part 1:1991.

PUBLISHED JOINTLY BY:

STANDARDS AUSTRALIA
(Standards Association of Australia) 80 Arthur Street, North Sydney
NSW, Australia

STANDARDS ASSOCIATION OF NEW ZEALAND
6th floor, Wellington Trade Centre, 181-187 Victoria Street
Wellington 1, New Zealand

ISBN 0 7262 7237 X

PREFACE

This Standard is issued as a joint Standard under the terms of the Memorandum of Understanding between Standards Australia and the Standards Association of New Zealand with the objective of reducing technical barriers to trade between the two nations. The Standard was prepared to supersede AS 3629.1—1989/NZS 5411:1982 (in part).

As in the previous edition, the dynamic testing of child restraints is required to be performed with the child restraint in the frontal, sideways and rearwards mode. In this edition, a more severe rearward dynamic test is required and an additional dynamic test in an inverted mode is introduced. Because of the addition of inverted dynamic testing, the previous method of rotating the test rig in a static condition and measuring the force required to operate the quick-release device while the test rig was in a 180° position has been replaced by a new method of testing the force required to operate the quick-release device.

CONTENTS

	<i>Page</i>
1 SCOPE	3
2 APPLICATION	3
3 REFERENCED DOCUMENTS	3
4 DEFINITIONS	3
5 PRINCIPLE	3
6 APPARATUS	3
7 TEST SAMPLES	3
8 PROCEDURE	3
9 REPORT	4
 APPENDICES	
A CALIBRATION OF THE TEST RIG	8
B CONSTRUCTION OF THE TEST SEAT	9

© Copyright — STANDARDS ASSOCIATION OF NEW ZEALAND

The New Zealand copyright in this document is the property of the Standards Council. No part of it may be reproduced by photocopying or by any other means without prior written permission of the Director of the Standards Association of New Zealand unless the circumstances are covered by the exemption sections (19 and 21) of the Copyright Act 1962.

© Copyright — STANDARDS AUSTRALIA

Members of Standards Australia are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Delete the existing Item (b) and *substitute* the following:

- (b) Install the child restraint system on the test seat with the test seat in the position for the required mode of testing.

Where the child restraint can be installed with either an adult lap or a lap/sash seat belt, a lap/sash seat belt shall be used and it shall incorporate an emergency locking retractor.

The child restraint shall be installed according to the instructions provided by the manufacturer and with the upper anchorage connected at point A1 in Figure 1. The anchorage fitting shall be tested with all spacers supplied, and with the orientation of the anchor bracket as shown in Figure 3.

For testing in the inverted mode, the orientation of the child restraint shall be as shown in Figure 4.

STANDARDS AUSTRALIA/STANDARDS ASSOCIATION OF NEW ZEALAND

Australian/New Zealand Standard
Methods of testing child restraints

Part 1: Dynamic testing

1 SCOPE This Standard sets out the method for determining the dynamic performance of a child restraint system.

2 APPLICATION The dynamic test set out in this Standard applies to all types of child restraints specified in AS 1754/NZS 5411.

3 REFERENCED DOCUMENTS The following documents are referred to in this Standard.

AS
1754/NZS 5411 Child restraint systems for use in motor vehicles

SAE
J117 Dynamic test procedure—Type 1 and Type 2 seat belt assemblies

J211 Instrumentation for impact tests

4 DEFINITIONS For the purpose of this Standard, the definitions given in AS 1754/NZS 5411 apply.

5 PRINCIPLE The child restraint system is subjected to a series of dynamic forces to cause nominated decelerations of a test rig to simulate frontal, rearwards, sideways, and inverted vehicle impacts.

6 APPARATUS The following apparatus is required.

- (a) A test rig of mass not less than 380 kg, and which consists of a trolley, a test seat conforming to Figure 1, and a structure for providing seat belt anchorages.
 - (b) A dummy as specified in AS 1754/NZS 5411.
 - (c) Where required, a spacer conforming to Figure 2.
 - (d) A means of measuring deceleration of the test rig for calibration purposes. Instrumentation shall comply with the requirements of SAE J211 for Channel Class 60.
 - (e) Where required, pressure-sensitive tape fixed in place over the genital region of the dummy.
 - (f) A means of measuring the quick-release device force with the aid of a test finger terminating in a 7.5 ± 0.5 mm radius hemispherical surface.
 - (g) Self-adjusting slings for attachment to the dummy's wrists and ankles as shown in Figure 5.
 - (h) A means of applying a force of 200 N to the dummy through the self-adjusting slings referred to in Item (g).
 - (i) A means of measuring the force referred to in Item (h).
 - (j) Where required, a break-away retention system for the dummy's head which will ensure that light head contact is maintained with the child restraint during the run-down to impact.
 - (k) Where required, a means of measuring the head deceleration. Instrumentation shall comply with the requirements of SAE J117 for Channel Class 1000. The location of accelerometers shall be according to the manual supplied by TNO with the test dummies (see AS 1754/NZS 5411).
- NOTE: A tri-axial accelerometer is considered to be the minimum required.

7 TEST SAMPLES Test samples shall be new, unused, and not previously tested child restraints.

8 PROCEDURE The procedure shall be as follows:

- (a) Calibrate the test rig (see Appendix A).
- (b) ~~Install the child restraint system on the test seat with the test seat in the position for the required mode of testing.~~
 The child restraint shall be installed according to the instructions provided by the manufacturer and with the upper anchorage connected at point A1 in Figure 1. The anchor fitting shall be tested with all spacers supplied, and with the orientation of the anchor fitting as shown in Figure 3. For testing in the inverted mode, the orientation of the child restraint shall be as shown in Figure 4.
- (c) Place the appropriate test dummy as specified in AS 1754/NZS 5411 in the child restraint and insert the appropriate spacer between the back of the dummy and the test seat.