

AS 3635—1990  
Reconfirmed 2017

Australian Standard<sup>®</sup>

---

**Unified (ISO inch) screw threads,  
associated gauges, and gauging  
practice**

---

This Australian Standard was prepared by Committee ME/28, Screw Threads. It was approved on behalf of the Council of Standards Australia on 6 January 1988 and published on 12 November 1990.

---

The following interests are represented on Committee ME/28:

Confederation of Australian Industry  
CSIRO, Division of Applied Physics  
Department of Defence  
Department of Technical and Further Education, N.S.W.  
Fasteners Institute of Australia  
Federal Chamber of Automotive Industries  
Institution of Engineers Australia  
Institution of Production Engineers  
Metal Trades Industry Association of Australia  
Railways of Australia Committee

---

**Review of Australian Standards.** To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important, therefore, that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

---

*This Standard was issued in draft form for comment as DR 87198.*

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 3635—1990

Unified (ISO inch) screw threads, associated gauges, and gauging practice

RECONFIRMATION NOTICE

Technical Committee ME-029 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 16 June 2017.

The following are represented on Technical Committee ME-029:

Association of Accredited Certification Bodies  
Association of Wall and Ceiling Industries of Australia  
Australian Chamber of Commerce and Industry  
Australian Engineered Fasteners and Anchors Council  
Australian Industry Group  
Australian Steel Institute  
AUSTROADS  
Bureau of Steel Manufacturers of Australia  
Galvanizers Association of Australia  
Materials Australia  
National Association of Steel-Framed Housing  
National Association of Testing Authorities Australia  
New Zealand Heavy Engineering Research Association  
Society of Automotive Engineers- Australasia  
Steel Construction New Zealand  
Swinburne University of Technology

NOTES

Currently in preview, click buy full vers.

Australian Standard®

---

**Unified (ISO inch) screw threads,  
associated gauges, and gauging  
practice**

---

First published as part of AS B133—1955  
(endorsement of BS 1580:1953 without amendment).  
Revised and redesignated AS B133, Parts 1 and 2—1963  
(endorsement of BS 1580:Parts 1 and 2:1962 without  
amendment).  
AS B133.3 first published 1963 (endorsement of  
BS 1580:Part 3:1965 without amendment).  
AS B121.1 first published 1962 (endorsement of  
BS 919:Part 1:1960 with amendment).  
AS B121.4 first published 1965 (endorsement of  
BS 919:Part 4:1965 without amendment).  
AS B133, Parts 1 and 2—1963, AS B133.3—1963,  
AS B121.1—1962 and AS B121.4—1965 revised,  
amalgamated and redesignated AS 3635—1990.

PUBLISHED BY STANDARDS AUSTRALIA  
(STANDARDS ASSOCIATION OF AUSTRALIA)  
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 5364 2

## PREFACE

This Standard was prepared by the Standards Australia Committee on Screw Threads to supersede the following Standards:

AS

- B121 *Screw gauge limits and tolerances*  
 B121.1 Part 1: *Gauges for screw threads of unified form*  
 B121.4 Part 4: *Limits of size for gauges for screw threads of unified form; diameters 1/4 in and larger*
- B133 *Unified screw threads*  
 B133.1 & 2 Parts 1 and 2: *Diameters 1/4 in and larger* (AS B133.1 and AS B133.2)  
 B133.3 Part 3: *Diameters below 1/4 in* (AS B133.3)

In the preparation of this Standard, several points were noted by the committee. One was that although inch-based screw thread systems were theoretically obsolescent, the reality was that there would be a continuing requirement for such threads well into the foreseeable future for maintenance purposes. Additionally, with respect to Unified screw threads, these are used in a wide range of currently manufactured products, and are also used in a number of specialized applications, e.g. high and low temperature bolting for the petrochemical and similar industries. A second point was that the previous Standards for the Unified screw thread system, and for associated gauge and gauging practice, were endorsements of British Standards, which could be withdrawn by the British Standards Institution at any time, and consequently become unavailable in Australia. With respect to this point it was realized that the demand pattern for Unified screw threads in the United Kingdom was likely to be vastly different from Australia, e.g. because of the influence of the EEC. A third point was that the form of presenting the information was far from ideal, as a user required some four Standards to cover the subject. The final point was that in some instances the Standards contained technical ambiguities and included obsolescent terminology.

A further important consideration which influenced the committee in its decision to prepare a new Standard was that Unified screw threads have been standardized internationally by the International Organization for Standardization, and are featured in the following Standards:

ISO

- 68 *ISO general purpose screw threads—Basic profile*  
 263 *ISO inch screw thread—General plan and selection for screws, bolts and nuts—Diameter range 1/6 to 6 in*  
 725 *ISO inch screw threads—Basic dimensions*  
 5864 *ISO inch screw threads—Allowances and tolerances*

Thus it was agreed that a completely new Australian Standard for Unified screw threads, including gauges, gauging practice, and gauge limits, should be prepared. This Standard contains no technical changes whatsoever, i.e. it includes all the Unified diameter/pitch combinations (UNC, UNF, UNEF, 4 UN, 6 UN, 8 UN, 12 UN, 16 UN, 20 UN, 28 UN, and 32 UN), together with the vulgar fractional and decimal fractional UNS thread series. It also includes associated gauges and gauging practice, and limiting dimensions of gauges for the more popular sizes, again with no technical changes. However, the terminology is aligned with contemporary practices.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

## CONTENTS

	<i>Page</i>
SECTION 1. SCOPE AND GENERAL	
1.1 SCOPE . . . . .	5
1.2 APPLICATION . . . . .	5
1.3 THE UNIFIED SCREW THREAD SYSTEM . . . . .	5
1.4 REFERENCED DOCUMENTS . . . . .	5
1.5 NOTATION . . . . .	5
SECTION 2. SCREW THREAD PROFILES	
2.1 SCOPE OF SECTION . . . . .	6
2.2 BASIC PROFILE AND THREAD DATA . . . . .	6
2.3 MAXIMUM MATERIAL (DESIGN) PROFILE . . . . .	7
2.4 LIMITING PROFILES . . . . .	8
2.5 ROOT CONTOURS . . . . .	8
SECTION 3. GENERAL PLAN	
3.1 SCOPE OF SECTION . . . . .	12
3.2 THREAD SERIES . . . . .	12
3.3 SELECTION OF DIAMETER/PITCH COMBINATIONS . . . . .	12
3.4 BASIC DIMENSIONS . . . . .	12
SECTION 4. THREAD CLASSES, DEVIATIONS AND TOLERANCES	
4.1 SCOPE OF SECTION . . . . .	23
4.2 FUNDAMENTAL DEVIATIONS . . . . .	23
4.3 TOLERANCES . . . . .	23
4.4 THREAD CLASSES . . . . .	23
4.5 LENGTH OF AXIAL THREAD ENGAGEMENT . . . . .	24
4.6 COATED THREADS . . . . .	24
SECTION 5. LIMITS OF SIZE	
5.1 SCOPE OF SECTION . . . . .	27
5.2 LIMITS OF SIZE . . . . .	27
SECTION 6. DESIGNATION	
6.1 UNCOATED THREADS . . . . .	47
6.2 COATED THREADS . . . . .	47
6.3 THREADS WITH SPECIAL REQUIREMENTS . . . . .	47
SECTION 7. GAUGING OF UNIFIED SCREW THREADS	
7.1 SCOPE OF SECTION . . . . .	48
7.2 TYPES OF GAUGES . . . . .	48
7.3 MATERIALS AND HARDNESS . . . . .	48
7.4 REFERENCE TEMPERATURE . . . . .	48
7.5 MARKING . . . . .	48
7.6 INSPECTION OF SCREW THREADS . . . . .	48
7.7 DESIGN FEATURES OF SCREW GAUGES . . . . .	49
7.8 LIMITS OF SIZE OF GAUGING ELEMENTS . . . . .	50

## APPENDICES

A	SUPPLEMENTARY UNIFIED (UNS) THREADS . . . . .	71
B	BASES FOR THE DERIVATION OF TOLERANCE GRADES AND FUNDAMENTAL DEVIATIONS . . . . .	87
C	EXAMPLES FOR CALCULATING LIMITS OF SIZE OF UNS THREADS . . . . .	92
D	NOTES ON THE PRODUCTION OF EXTERNAL THREADS . . . . .	97
E	FUNCTION, USE, AND CHECKING OF SCREW GAUGES . . . . .	99
F	PITCH DIAMETER EQUIVALENT OF PITCH AND FLANK ANGLE ERRORS . . . . .	102
G	A RECOMMENDED SYSTEM OF GAUGES FOR COATED SCREW THREADS . . . . .	105
H	NOTES ON SETTING ADJUSTABLE SCREW RING GAUGES . . . . .	109
I	SCREW GAUGE LIMITS . . . . .	110

Currently in preview, click buy full version

## STANDARDS AUSTRALIA

## Australian Standard

## Unified (ISO inch) screw threads, associated gauges, and gauging practice

## SECTION 1. SCOPE AND GENERAL

**1.1 SCOPE.** This Standard specifies requirements for parallel screw threads, associated gauges, and gauging practice, having the Unified thread form and covering the diameter size range No 0 (0.060 in) to 6 in inclusive.

The Standard gives information on tolerances, deviations, thread classes, and designations.

A supplementary series of Unified threads (UNS) is given in Appendix A for guidance on Unified threads of diameter greater than 6 in, and non-standard diameter/pitch combinations, which may be required for special applications.

Appendices give the basis of the tabulated values (Appendix B), examples for calculating the limits of size of untabulated screw threads (Appendix C), notes on the production of external threads (Appendix D), notes on pitch and flank angle errors (Appendix F), notes on the function and checking of gauges (Appendix E), notes on a recommended system for gauging coated threads (Appendix G), notes on the setting of adjustable screw ring gauges (Appendix H), and the limiting dimensions of screw gauges for the more commonly used Unified threads (Appendix I).

## NOTES:

1. Unified screw threads are also known as the ISO inch series screw threads. These screw threads are obsolescent and should not be used in new designs.
2. Because of the methods adopted for rounding the tabulated values (see Appendix B), the values for the various parameters given in the tables are to be taken as authoritative for the application of this Standard.
3. The information given in Appendix A may also be used for calculating screw thread parameters for diameters greater than 6 in.

**1.2 APPLICATION.** The Standard is intended for adoption by industry and government authorities concerned with the manufacture, measurement, or use of Unified screw threads.

**1.3 THE UNIFIED SCREW THREAD SYSTEM.** The Unified screw thread system comprises the following series:

- (a) The Unified coarse thread series (UNC), which gives graded diameter/pitch combinations in diameters from 1/4 in to 4 in inclusive.
- (b) The Unified fine thread series (UNF), which gives graded diameter/pitch combinations in diameters from 1/4 in to 1 1/2 in inclusive.
- (c) The Unified extra fine thread series (UNEF), which gives graded diameter/pitch combinations in diameters from 1/4 in to 1 11/16 in inclusive.
- (d) The Unified 'numbered' series which gives graded diameter/pitch combinations for UNC, UNF; and UNEF series in diameters from No 0 (0.060 in) to No 12 (0.216 in) inclusive.
- (e) The Unified constant pitch series, which are intended for applications where the UNC, UNF,

or UNEF series are unsuitable or inadequate. They are arranged to give a graded system of diameter/pitch combinations as follows:

- (i) 4 t.p.i. series (6 UN) from 2 5/8 in to 6 in diameter.
- (ii) 6 t.p.i. series (6 UN) from 1 7/16 in to 6 in diameter.
- (iii) 8 t.p.i. series (8 UN) from 1 1/16 in to 6 in diameter.
- (iv) 12 t.p.i. series (12 UN) from 5/8 in to 6 in diameter.
- (v) 16 t.p.i. series (16 UN) from 7/16 in to 6 in diameter.
- (vi) 20 t.p.i. series (20 UN) from 5/16 in to 3 in diameter.
- (vii) 28 t.p.i. series (28 UN) from 5/16 in to 1 in diameter.
- (viii) 32 t.p.i. series (32 UN) from 7/16 in to 1 in diameter.
- (f) A further series of Unified threads (UNS) for diameters over 6 in diameter, or where the departure from the diameter/pitch combinations given in the Standard cannot be avoided.

**1.4 REFERENCED DOCUMENTS.** The following Standards are referred to in this Standard:

AS	
1014	Gauging of metric screw threads
2710	Screw gauges—Verification
B129	Designs for geometric limit gauges (plain and screwed in inch units)

**1.5 NOTATION.** The quantity symbols used in this Standard are listed in Table 1.1.

TABLE 1.1  
QUANTITY SYMBOLS

Symbol	Quantity
$D$	Basic major diameter
$D_{1, \max}$	Maximum minor diameter of internal thread
$D_2$	Basic pitch diameter
$d_{\min}$	Minimum major diameter of external thread
$G$	Fundamental deviation for external thread
$H$	Height of fundamental triangle
$L_e$	Length of axial engagement
$P$	Pitch
$R$	Root radius of external thread
$T_{D, 1}$	Tolerance on minor diameter of internal threads
$T_{D, 2}$	Tolerance on pitch diameter of external thread
$T_d$	Tolerance on major diameter of external thread
$\theta$	Flank angle