

AS 3718:2021



STANDARDS
Australia



Water supply — Tap ware

Currently in preview, click buy full version

AS 3718:2021

This Australian Standard ® was prepared by WS-001, Water and Gas fittings. It was approved on behalf of the Council of Standards Australia on 01 September 2021.

This Standard was published on 17 September 2021.

The following are represented on Committee WS-001:

- Association of Accredited Certification Bodies
- Australian Building Codes Board
- Australian Chamber of Commerce and Industry
- Australian Industry Group
- Department of Agriculture, Water and the Environment
- Gas Technical Regulators Committee
- Housing Industry Association
- International Copper Association Australia
- Master Plumbers Australia and New Zealand
- National Association of Testing Authorities Australia
- Plastics Industry Pipe Association of Australia
- Plumbing Products Industry Group
- Queensland Brassware Association
- The Institute of Plumbing Australia
- Water Services Association of Australia

Additional Interests

- Plastics New Zealand
- Plumbing Distributors Association of New Zealand

This Standard was issued in draft form for comment as L22.003718:2021.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 499 9

Water supply — Tap ware

Originated in part as part of AS B1—1928T and MP 52—2001.
AS 171—1992, AS 3496—1999, AS/NZS 3718:1997 and part of MP 52—2001 jointly
revised, amalgamated and redesignated as AS/NZS 3718:2003.
Previous edition AS/NZS 3718:2005.
This edition AS 3718:2021.

© Standards Australia Limited 2021

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee WS-001, Water Fittings, to supersede AS/NZS 3718:2005.

After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard.

The objective of this Standard is to provide requirements for tap ware in nominal sizes ranging from DN 6 to DN 50 that is designed to be used generally for continuous operating temperatures not exceeding 80 °C and maximum dynamic operating pressure 500 kPa. Requirements are also provided for outlets of a tap or mixing tap and for tapset breaching piece assemblies.

The major changes in this edition are as follows:

- (a) Additional finish and coating information including PVD coating.
- (b) Additional water shut-off device classifications and changes to endurance test cycles.
- (c) Additional information on electrical and electromagnetic requirements.
- (d) Addition of an endurance test for rotating or swivelling outlets.

The term “normative” is used in Standards to define the application of the appendix to which it applies. A “normative” appendix is an integral part of a Standard.

Contents

| | |
|--|-----------|
| Preface | ii |
| Section 1 Scope and general | 1 |
| 1.1 Scope..... | 1 |
| 1.2 Normative references..... | 1 |
| 1.3 Terms and definitions..... | 3 |
| 1.4 Size designation..... | 6 |
| 1.5 Marking requirements..... | 6 |
| 1.5.1 Taps..... | 6 |
| 1.5.2 Components..... | 7 |
| 1.6 Packaging and installation instructions..... | 8 |
| 1.6.1 Intended application..... | 8 |
| 1.6.2 Installation instructions..... | 8 |
| Section 2 Materials | 9 |
| 2.1 Scope of Section..... | 9 |
| 2.2 Metallic materials..... | 9 |
| 2.2.1 Use of metallic material..... | 9 |
| 2.2.2 Corrosion-resistant metallic materials..... | 9 |
| 2.2.3 Copper..... | 9 |
| 2.2.4 Copper alloy..... | 9 |
| 2.2.5 Dezincification-resistant (DR) copper alloy..... | 10 |
| 2.2.6 Stainless steel..... | 10 |
| 2.3 Plastic and elastomeric materials..... | 10 |
| 2.3.1 General..... | 10 |
| 2.3.2 Acetal..... | 10 |
| 2.3.3 UV resistance..... | 10 |
| 2.3.4 Resistance to chemical degradation..... | 10 |
| 2.4 Other materials..... | 11 |
| Section 3 Design and manufacture | 12 |
| 3.1 Scope of section..... | 12 |
| 3.2 End connectors..... | 12 |
| 3.2.1 Copper and copper alloy end connectors..... | 12 |
| 3.2.2 Other end connectors..... | 12 |
| 3.3 Screw threads..... | 12 |
| 3.3.1 General..... | 12 |
| 3.3.2 Thread engagement..... | 12 |
| 3.4 Water shut-off devices..... | 12 |
| 3.4.1 General..... | 12 |
| 3.4.2 Single and combination taps jumper valve..... | 13 |
| 3.4.3 Other water shut-off valves..... | 13 |
| 3.5 Thickness of metal parts..... | 13 |
| 3.5.1 General..... | 13 |
| 3.5.2 Copper, copper alloy and stainless steel tubes..... | 13 |
| 3.5.3 Other sections..... | 14 |
| 3.6 Fabricated assemblies..... | 14 |
| 3.7 Outlets..... | 14 |
| 3.7.1 Unit construction outlets..... | 14 |
| 3.7.2 Other outlets..... | 14 |
| 3.7.3 Flexible hoses..... | 14 |
| 3.7.4 Hose tap outlets..... | 15 |
| 3.7.5 Showerheads for personal bathing..... | 15 |
| 3.8 Operating mechanisms..... | 15 |
| 3.9 Finish and workmanship..... | 16 |
| 3.10 Accessories or components supplied with tap products..... | 16 |
| 3.10.1 General..... | 16 |

| | | |
|-------------------|--|-----------|
| 3.10.2 | Flexible hose connectors | 16 |
| 3.10.3 | Integral backflow devices | 16 |
| 3.10.4 | Flow control devices | 16 |
| 3.11 | Taps and tap components to suit industry-specific dimensional characteristics | 16 |
| 3.11.1 | General | 16 |
| 3.11.2 | Valve seating, valve chamber and tap head connection | 17 |
| 3.11.3 | Tap head | 17 |
| 3.11.4 | Spindle end | 17 |
| 3.11.5 | Loose jumper valves | 17 |
| 3.11.6 | Tapset breaching piece assemblies | 17 |
| 3.11.7 | Replacement tap seats | 17 |
| 3.12 | Electronic taps and/or valves | 17 |
| 3.12.1 | General | 17 |
| 3.12.2 | Power failure | 17 |
| 3.12.3 | Electrical safety | 17 |
| 3.12.4 | Electromagnetic compatibility | 17 |
| Section 4 | Performance requirements | 18 |
| 4.1 | General | 18 |
| 4.2 | Plastic materials used for plastic-bodied taps | 18 |
| 4.3 | Hydraulic strength test | 18 |
| 4.4 | Surface-mounting strength test for taps | 18 |
| 4.5 | Watertightness under pressure | 18 |
| 4.6 | Nominal flow rate | 18 |
| 4.6.1 | General | 18 |
| 4.6.2 | Outlets where conformance to AS/NZS 6400 is mandatory | 18 |
| 4.6.3 | Other taps and outlets | 19 |
| 4.7 | Contamination of water | 19 |
| 4.8 | Torque of fabricated joints | 19 |
| 4.9 | Torque of head to body | 19 |
| 4.10 | Torque of operating mechanism | 19 |
| 4.11 | Endurance test for taps and tap components | 19 |
| 4.11.1 | Endurance test for tap operating mechanisms | 19 |
| 4.12 | Strength of connector nut and assembly | 20 |
| 4.13 | Strength of button-operated and foot-operated taps | 20 |
| 4.14 | Resistance of handle to removal | 20 |
| 4.15 | Power failure for electronically controlled taps | 20 |
| 4.16 | Rotating or swivel outlet | 21 |
| Appendix A | (normative) Product conformity | 22 |
| Appendix B | (normative) Resistance of plastic-bodied taps to chemical degradation | 27 |
| Appendix C | (normative) Hydraulic strength test for tap assemblies | 29 |
| Appendix D | (normative) Surface-mounting strength test for taps | 32 |
| Appendix E | (normative) Determination of watertightness | 35 |
| Appendix F | (normative) Determination of the nominal flow rate of taps and tap outlets for use with high pressure | 39 |
| Appendix G | (normative) Torque test for fabricated joints | 42 |
| Appendix H | (normative) Torque test for head-to-body connection | 44 |
| Appendix I | (normative) Torque test for operating mechanism of tap | 46 |
| Appendix J | (normative) Endurance test for single and combined taps and components | 49 |
| Appendix K | (normative) Strength test for connector nuts and assembly | 53 |
| Appendix L | (normative) Load test for button-operated and foot-operated taps | 55 |
| Appendix M | (normative) Dimensions of taps | 57 |

| | |
|---|-----------|
| Appendix N (normative) Simulated samples | 72 |
| Appendix O (normative) Determination of the nominal flow rate of taps and tap outlets for use with low and unequal pressures | 74 |
| Appendix P (normative) Endurance test for rotating or swivelling outlets | 76 |
| Appendix Q (normative) Endurance test for mixing taps mechanical (non-thermostatic) | 79 |
| Appendix R (normative) Endurance test for automatic shut-off valves | 85 |
| Appendix S (normative) Endurance test for electronic opening and closing valves | 88 |
| Appendix T (informative) Finishes and coatings | 92 |

Currently in preview, click buy full version

NOTES

Currently in preview, click buy full version

Australian Standard[®]

Water supply — Tap ware

Section 1 Scope and general

1.1 Scope

This Standard specifies requirements for metallic taps, plastic taps, mixing taps, sensor taps, lever taps, timed flow taps, mixing taps mechanical (non-thermostatic), and tapsets in nominal sizes ranging from DN 6 to DN 50 that are designed to be used generally for continuous operating temperatures not exceeding 80 °C and maximum dynamic operating pressure 500 kPa.

This Standard does not prevent the use of products designed for other temperature ranges provided they meet the performance requirements specified herein.

The Standard also specifies requirements for outlets of a tap or mixing tap and for tapset breaching piece assemblies.

Means for demonstrating conformance to this Standard are given in [Appendix A](#).

NOTE Where the static hot and cold water supply systems pressures are below 50 kPa, then water-efficient tap ware may not need to be fitted.

1.2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document.

AS 681, *Elastomeric seals — Material requirements for pipe joint seals used in water and drainage applications (series)*

AS 1167.1, *Welding and brazing — Filler metals, Part 1: Filler metal for brazing and braze welding*

AS 1199.1, *Sampling procedures for inspection by attributes, Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection*

AS 1349, *Bourdon tube pressure and vacuum gauges*

AS 1432, *Copper tubes for plumbing, gasfitting and drainage applications*

AS 1565, *Copper and copper alloys — Ingots and castings*

AS 1572, *Copper and copper alloys — Seamless tubes for engineering purposes*

AS 1646, *Elastomeric seals for waterworks purposes*

AS 1722.2, *Pipe threads of Whitworth form, Part 2: Fastening pipe threads*

AS 1861, *Zinc alloys — Casting ingots and castings — Quality requirements*

AS 2331.3.1, *Methods of test for metallic and related coatings, Method 3.1: Corrosion and related property tests — Neutral salt spray test (NSS test)*

AS 2331.3.2, *Methods of test for metallic and related coatings, Method 3.2: Corrosion and related property tests — Acetic acid salt spray test (ASS test)*

AS 2331.3.3, *Methods of test for metallic and related coatings, Method 3.3: Corrosion and related property tests — Copper accelerated acetic acid salt spray test (CASS test)*

AS 2331.3.7, *Methods of test for metallic and related coatings, Method 3.7: Corrosion and related property tests — Corrodokote (Corr) test (ISO 4541:1978, MOD)*