

(Identical with and reproduced from IEC 623-1983)

Australian Standard®

**Stationary batteries -
Nickel-cadmium**

Part 1: Vented type

[IEC Title: Open nickel cadmium prismatic rechargeable cells]

[Title allocated by Defence Cataloguing Authority: BATTERY,
STORAGE (Nickel-cadmium, vented type) NSC 6140]



STANDARDS AUSTRALIA



This Australian Standard was prepared by Committee EL/5, Secondary Batteries. It was approved on behalf of the Council of Standards Australia on 30 June 1989 and published on 6 November 1989.

The following interests are represented on Committee EL/5:

Australian Automobile Aftermarket Association
Australian Automobile Association
Australian Electrical and Electronic Manufacturers Association
Australian Federation of Consumer Organizations
Australian Lead Development Association
Confederation of Australian Industry
Department of Administrative Services—Australian Construction Services
Department of Defence
Electricity Supply Association of Australia
Federal Chamber of Automotive Industries
Railways of Australia
Telecom Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic revision and are kept up-to-date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard' which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 88195 ✓

AS 3731.1—1989

Australian Standard®

**Stationary batteries—
Nickel-cadmium**

Part 1: Vented type

✓ First published as AS 3731.1—1989.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
STANDARDS HOUSE, 80 ARTHUR ST, NORTH SYDNEY NSW
ISBN 0 7262 5838 5

PREFACE

✓ This Standard was prepared by the Standards Australia Committee on Secondary Batteries. It is identical with and has been reproduced from IEC 623 (1983) (including Amendment No 1), *Open nickel-cadmium prismatic rechargeable cells*.

Statements referenced in mandatory terms in Notes to tables and figures are deemed to be requirements of this Standard.

For the purposes of this Australian Standard the word 'prismatic' should be deleted wherever it appears in the IEC text.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the Head Office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

Page

SECTION ONE – GENERAL

Clause

1.1 Scope	4
1.2 Definitions	4
1.3 Measuring instruments	

SECTION TWO – DESIGNATION AND MARKING

2.1 Cell designation	4
2.2 Cell termination	5
2.3 Marking	5

SECTION THREE – DIMENSIONS

3.1 Dimensions	6
----------------------	---

SECTION FOUR – ELECTRICAL TESTS

4.1 Charging procedure for test purposes	8
4.2 Discharge performance	8
4.3 Charge retention	9
4.4 Endurance	10
4.5 Charge acceptance at constant voltage	11
4.6 Overcharge	11
4.7 Vent operation	11
4.8 Storage	11

SECTION FIVE – MECHANICAL TESTS

5.1 Mechanical test	12
---------------------------	----

SECTION SIX – SEQUENCE OF TESTS

Sequence of tests	12
-------------------------	----

STANDARDS AUSTRALIA

Australian Standard
Stationary batteries—Nickel-cadmium**Part 1: Vented type****1.1 Scope**

This standard specifies tests and requirements for open nickel-cadmium prismatic rechargeable single cells.

Note. — In this context, "prismatic" refers to cells having rectangular sides and base.

1.2 Definitions

For the purpose of this standard the following definitions apply.

1.2.1 Open cells

Cells having a permanent cover provided with an opening through which gaseous products may freely escape. The opening may be fitted with a vent.

1.2.2 Nominal voltage

The nominal voltage of a single open rechargeable nickel-cadmium cell is 1.2 V.

1.2.3 Rated capacity

The rated capacity in ampere-hours is the capacity at the 5 h (C_5) discharge rate to an end voltage of 1.0 V at 20 °C.

1.3 Measuring instruments

No requirements at present.

SECTION TWO — DESIGNATION AND MARKING**1 Cell designation**

Open nickel-cadmium prismatic rechargeable cells shall be designated by the letter "K" followed by a second letter referring to the type of positive plates:

- P for cells with pocket plates;
- S for cells with sintered plates.