

AS 3755—1990
ISO 7779:1988

Australian Standard[®]

**Acoustics—Measurement of
airborne noise emitted by
computer and business
equipment**

This Australian Standard was prepared by Committee AV/7, Acoustics, Noise from Office and Household Equipment. It was approved on behalf of the Council of Standards Australia on 28 November 1989 and published on 14 May 1990.

The following interests are represented on Committee AV/7:

Association of Consulting Engineers Australia
Australian Acoustical Society
Australian Consumer Association
Australian Electrical and Electronic Manufacturers Association
Australian Environment Council
CSIRO, Division of Applied Physics

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments, etc.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Acoustics—Measurement of
airborne noise emitted by
computer and business
equipment**

First published as AS 3755—1990.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6074 6

PREFACE

This Standard was prepared by the Standards Australia Committee on Acoustics—Noise from Office and Household Equipment.

It is identical with and has been reproduced from ISO 7779 (1988), Acoustics—Measurement of airborne noise emitted by computer and business equipment.

For the purpose of this Australian Standard the ISO text should be modified as follows:

- (a) *Subclause 5.3.2*: In line 4, delete '300 m³' and substitute '350 m³'.
- (b) *References*. The references to other publications should be replaced by references to Australian Standard.

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
266	Acoustics—Preferred frequencies for measurements	2533	Acoustics—Preferred frequencies for measurements
3740	Acoustics—Determination of sound power levels of noise sources—Guidelines for the use of basic standards and for the preparation of noise test codes	1217.1	Acoustics—Determination of sound power levels of noise sources, Part 1: Guidelines for the use of basic standards for the preparation of noise test codes
3741	Acoustics—Determination of sound power levels of noise sources—Precision methods for broad-band sources in reverberation rooms	1217.2	Acoustics—Determination of sound power levels of noise sources, Part 2: Precision methods for broad-band sources in reverberation rooms
3742	Acoustics—Determination of sound power levels of noise sources—Precision methods for discrete-frequency and narrow-band sources in reverberation room	1217.3	Acoustics—Determination of sound power levels of noise sources, Part 3: Precision methods for discrete-frequency and narrow-band sources in reverberation room
3743	Acoustics—Determination of sound power levels of noise sources—Engineering methods for special reverberation test rooms	1217.4	Acoustics—Determination of sound power levels of noise sources, Part 4: Engineering methods for special reverberation test rooms
3744	Acoustics—Determination of sound power levels of noise sources—Engineering methods for free-field conditions over a reflecting plane	1217.5	Acoustics—Determination of sound power levels of noise sources, Part 5: Engineering methods for free-field conditions over a reflecting plane
3745	Acoustics—Determination of sound power levels of noise sources—Precision methods for anechoic and semi-anechoic rooms	1217.6	Acoustics—Determination of sound power levels of noise sources, Part 6: Precision methods for anechoic and semi-anechoic rooms
9295	Acoustics—Measurement of high-frequency noise emitted by computer and business equipment	3756	Acoustics—Measurement of high frequency noise emitted by computer and business equipment
9296	Acoustics—Declared noise emission values of computer and business equipment	3757	Acoustics—Declared noise emission values of computer and business equipment
IEC		AS	
227	Octave, half-octave and third-octave band filters intended for the analysis of sounds and vibrations	Z41	Octave, half-octave and one-third octave band pass filters intended for analysis of sound and vibrations
601	Sound level meters	1259	Sound level meters

CONTENTS

	<i>Page</i>
0 Introduction	4
1 Scope and field of application	4
2 Conformance	5
3 References	5
4 Definitions	5
5 Method for determining sound power levels of equipment in reverberation rooms	6
6 Method for determining sound power levels of equipment under essentially free-field conditions over a reflecting plane	13
7 Method for measuring sound pressure levels at the operator and bystander positions	22
 Annexes	
A Standard test table	26
B Alternative measurement surfaces for sound power measurements in accordance with clause 6	27
C Installation and operating conditions for specific equipment categories	29
D Measurement of impulsive sound pressure levels and discrete tones at the operator position	38

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Acoustics—Measurement of airborne noise emitted by computer and business equipment

0 Introduction

This International Standard specifies methods for the measurement of airborne noise emitted by computer and business equipment. Hitherto, a wide variety of methods has been applied by individual manufacturers and users to satisfy particular equipment or application needs. These diverse practices have, in many cases, made comparison of noise emission difficult. This International Standard simplifies such comparisons and is the basis for declaration of the noise emission level of computer and business equipment.

In order to ensure accuracy, validity and acceptability, this International Standard is based on the basic International Standards for determining the sound power level (ISO 3741, ISO 3742, ISO 3744 and ISO 3745) and the sound pressure level at the operator position(s) (ISO 6081). Furthermore, implementation is simplified by conformance to these International Standards.

In many cases, free-field conditions over a reflecting plane are obtained by semi-anechoic rooms. These rooms may be particularly useful during product design to locate and to improve individual contributing noise sources. Reverberation rooms may be more economical for production control and for obtaining sound power levels for declaration purposes.

The method for measuring the sound pressure level at the operator or bystander positions (see ISO 6081) is specified in a separate clause, as this level is not considered to be primary declaration information. The measurements can, however, be carried out at the same time as those for sound power determination in a free field over a reflecting plane.

For comparison of similar equipment it is essential that the installation conditions and mode of operation be the same. In annex C these parameters are standardized for many categories of equipment. It is intended to extend annex C to other categories in a future revision.

1 Scope and field of application

1.1 Scope

This International Standard specifies procedures for measuring and reporting the noise emitted by computer and business equipment. It is based on the measurement procedures specified in ISO 3740, ISO 3741, ISO 3742, ISO 3744 and ISO 3745. The basic emission quantity is the A-weighted sound power level which may be used for

comparing equipment of the same type, but from different manufacturers, or for comparing different equipment.

The A-weighted sound power level is supplemented by the A-weighted sound pressure level measured at the operator position(s) or the bystander positions. This sound pressure level is not a measurement of total occupational noise exposure of workers (noise immission).

Two methods for determining the sound power levels are specified in this International Standard in order to avoid undue restriction on existing facilities and experience. The first method is based on reverberant room measurements (see ISO 3741 and ISO 3742); the second is based on measurements in an essentially free field over a reflecting plane (see ISO 3744 and ISO 3745). Either method may be used in accordance with this International Standard. They are comparable in accuracy and yield the same A-weighted sound power level within the tolerance range of the methods specified in this International Standard.

1.2 Field of application

This International Standard is suitable for type tests and provides methods for manufacturers and testing laboratories to obtain comparable results.

The method specified in clause 5 provides a comparison procedure for determining sound power levels in a reverberation room. The method specified in clause 6 provides a direct procedure for determining sound power levels using essentially free-field conditions over a reflecting plane. The method specified in clause 7 provides a procedure for measuring noise at the operator or bystander positions. The procedures in this International Standard may be applied to equipment which radiates broad-band noise, narrow-band noise, noise which contains discrete-frequency components or impulsive noise.

The methods specified in this International Standard allow the determination of noise emission levels for a unit tested individually.

The sound power levels and sound pressure levels are used for noise emission declaration and comparison purposes. They are not to be considered as installation noise levels, however they may be used for installation planning.

If sound power levels obtained are determined for several units of the same production series, the result can be used to determine a statistical value for that production series.