

AS 3764—1990
ISO 4867—1984

Australian Standard[®]

**The measurement and reporting
of shipboard vibration data**

This Australian Standard was prepared by Committee AV/8, Vibration and Shock — Instrumentation and Measurement. It was approved on behalf of the Council of Standards Australia on 14 December 1989 and published on 11 June 1990.

The following interests are represented on Committee AV/8:

Australian Environment Council
Australian Gas Association
Confederation of Australian Industry
CSIRO, Division of Applied Physics
Department of Defence
Department of Industrial Relations and Employment, N.S.W.
Monash University
National Association of Testing Authorities Australia
Royal Institution of Naval Architects
Water Board Sydney

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications, the information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**The measurement and reporting
of shipboard vibration data**

First published as AS 3764—1990.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6106 8

PREFACE

This Standard was prepared by the Standards Australia Committee on Vibration and Shock—Instrumentation and Measurement. It is identical with and has been reproduced from ISO 4867—1984, *Code for the measurement and reporting of shipboard vibration data*.

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (a) Substitute a point (.) for a comma (,) as a decimal marker.
- (b) The references to other publications should be replaced by references to Australian Standards:

<i>Reference to International Standard</i>	<i>Australian Standard</i>
ISO	AS
4868 Code for the measurement and reporting of local vibration data of ship structures and equipment	3762 Measurement and reporting of local vibration data of ship structures and equipment
6954 Mechanical vibration and shock—Guidelines for the overall evaluation of vibration in merchant ships	3763 Mechanical vibration and shock—Guidelines for the overall evaluation of vibration in merchant ships

Contents

	<i>Page</i>
0 Introduction	3
1 Scope and field of application	3
2 References	4
3 Definitions	4
4 Measurement of data	4
5 Analysis and reporting of data	6
6 Rules for presentation of vibration test results	7
Tables 1 to 7	8
Figures 1 to 5	15
Bibliography	20

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Measurement and reporting of shipboard vibration data

0 Introduction

The need for comparative data on ship vibration requires uniform test conditions. In general, comparative data can best be obtained during ship trials with known ballast loading. The relatively uniform vibration resulting from propulsion machinery excitation (turbine or diesel drive) can be masked or distorted by transient vibrations due to wave impact or slamming. Changes in wake distribution due to rudder angle and yaw can produce large increases in exciting forces. Operation in shallow water also has a significant effect on hull vibration. Propeller emergence, whether continuous or periodic, causes large increases in exciting forces. The effect of lateral vibration of the aft part of line shafting on hull and superstructure vibration should also be considered.

The aft part of the line shaft may have a lateral resonant frequency within the speed range of the ship which can be excited to strong vibrations by either unbalance or propeller forces.

Alternating thrust forces may cause dangerous vibration of the thrust bearing or machinery as a result of a longitudinal resonance in the propulsion system.

Diesel engines may vibrate about the three rotational axes and three translational axes and generate large forces which in turn may cause largeship vibrations.

The principal response of a ship hull is usually similar to that of a free-free beam in its lower modes. At higher frequencies, the response of the hull girder is equivalent to a forced response with ill-defined resonances and maximum response in the stern area. The stern area is an antinode for all bending and torsional modes excited by the propulsion system and is an appropriate reference point for the measurement of beam-like vibration and forced response. The response of superstructures and local structures may be evaluated in terms of the ratio of their vibratory amplitude to the amplitude of hull girder vibration at that location.

In this International Standard, the term "vibration severity" is used to describe the vibration conditions in the ship and, based on long-established practice in the industry, the peak value of vibration velocity has been chosen as the primary quantity of measurement; since, however, much data have been accumulated in terms of vibration acceleration and vibration displacement, a plotting sheet has been adopted on which data may easily be plotted using any of these quantities of measurement.

1 Scope and field of application

This International Standard establishes uniform procedures for gathering and presenting data:

- a) on hull vibration in single or multiple-shaft sea-going merchant ships;
- b) for vibration of propulsion-shaft systems as it affects hull vibration.

Such data are necessary to establish uniformly the vibration characteristics of hull and propulsion-shaft systems and to provide a basis for design predictions, improvements and comparison against vibration reference levels.

The procedures, where applicable, can also be used for inland ships and tug boats. In special cases, where objectionable vibration is found to exist, specific investigative studies may be required.

This International Standard is concerned with:

- a) vibration of the main hull girder and superstructure excited by the propulsion system
 - at shaft rotational frequency,
 - at propeller blade rate, harmonics of blade rate and
 - at frequencies associated with the major components of machinery;
- b) excitation of the propulsion shaft and main machinery system.

It does not deal with other aspects of ship vibration at this time. Local vibration is dealt with in ISO 4868.

Anchor drop-and-snub tests in calm water may be an effective means of obtaining the first few vertical hull modes of vibration and their damping constants (see warning in 4.5.5).

Detailed design information on the ship is required to assist in developing empirical constants useful in evaluating the vibration of hull and machinery vibratory characteristics.

This International Standard gives general principles of vibration measurement on board ships to improve vibration engineering. Therefore, in individual cases, items to be measured may be selected or added to meet the aims of the vibration measurement of each ship.