

Australian Standard[®]

**Measurement of water flow in open
channels**

**Part 2.3: General—Determination
of the stage-discharge relation**

This Australian Standard was prepared by Committee CE/24, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 9 April 1990 and published on 10 December 1990.

The following interests are represented on Committee CE/24:

Association of Consulting Engineers of Australia
Australian Water and Wastewater Association
Board of Works, Melbourne
Department of Water Resources, NSW
Engineering and Water Supply Department of South Australia
Forestry Commission, NSW
Institute of Instrumentation and Control
Monash University
Public Works Department, NSW
Snowy Mountains Engineering Corporation
University of New South Wales
University of Queensland
Water Authority of Western Australia
Water Board, Sydney
Water Resources Commission, Queensland

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

Measurement of water flow in open channels

Part 2.3: General—Determination of the stage-discharge relation

First published as AS 3778.2.3—1990.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6291 9

PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 1100/2-1982, *Liquid flow measurement in open channels—Part 2: Determination of the stage-discharge relation*.

This Standard is one of a series which deals with methods of measurement of water flow in open channels. The series when complete will consist of the following parts:

- Part 1: Vocabulary and symbols
- Part 2.1: General—Guidelines for the selection of methods of measurement
- Part 2.2: General—Establishment and operation of a gauging station
- Part 2.3: General—Determination of the stage-discharge relation (this Standard)
- Part 2.4: General—Estimation of uncertainty of a flow-rate measurement
- Part 2.5: General—Guidelines for the selection of flow gauging structures
- Part 3: Velocity-area methods—
 - Method 3.1: Measurement by current-meters and floats
 - Method 3.2: Measurement by moving-boat method
 - Method 3.3: Measurement by slope-area method
 - Method 3.4: Collection and processing of data for determination of errors in measurement
 - Method 3.5: Investigation of total error
 - Method 3.6: Measurement of flow in tidal channels
 - Method 3.7: Measurement by ultrasonic (acoustic) method
 - Method 3.8: Electromagnetic method using a full-channel-width coil
- Part 4: Measurement using flow gauging structures—
 - Method 4.1: Thin-plate weirs
 - Method 4.2: Rectangular broad-crested weirs
 - Method 4.3: Round-nose horizontal broad-crested weirs
 - Method 4.4: V-shaped broad-crested weirs
 - Method 4.5: Triangular profile weirs
 - Method 4.6: Flat-V weirs
 - Method 4.7: Rectangular trapezoidal and U-flumes
 - Method 4.8: Trapezoidal profile weirs
 - Method 4.9: Parshall and Saniiri flumes
 - Method 4.10: End-depth method for estimation of flow in rectangular channels with a free overfall
 - Method 4.11: End-depth method for estimation of flow in non-rectangular channels with a free overfall (approximate method)
- Part 5: Dilution methods—
 - Method 5.1: Constant-rate injection method for the measurement of steady flow
 - Method 5.2: Integration method for the measurement of steady flow
- Part 6.1: Measuring devices, instruments and equipment—Rotating element current-meters
- Part 6.2: Measuring devices, instruments and equipment—Direct depth sounding and suspension equipment
- Part 6.3: Measuring devices, instruments and equipment—Calibration of rotating element current-meters in straight open tanks
- Part 6.4: Measuring devices, instruments and equipment—Echo sounders for water depth measurement
- Part 6.5: Measuring devices, instruments and equipment—Water level measuring devices
- Part 6.6: Measuring devices, instruments and equipment—Cableway system for stream gauging
- Part 6.7: Measuring devices, instruments and equipment—Ultrasonic (acoustic) velocity meters
- Part 6.8: Measuring devices, instruments and equipment—Position fixing equipment for hydrometric boats

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (a) Wherever the words 'International Standard' appear referring to this Standard, they should be read as 'Australian Standard'
- (b) Wherever the word 'fluid' appears, it should be read as 'water'.
- (c) Substitute a point (.) for a comma (,) as a decimal marker.
- (d) The references to other publications should be replaced by references to Australian Standards.

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
1000	SI units and recommendations for the use of their multiples and of certain other units.	1000	The international system of units (SI) and its application
31	Quantities, units and symbols	2900	Quantities units and symbols
		3778	Measurement of water flow in open channels

772	Liquid flow measurement in open channels—Vocabulary and symbols	3778.1	Part 1: Vocabulary and symbols
1100/1	Liquid flow measurement in open channels—Part 1: Establishment and operation of a gauging station	3778.2.2	Part 2.2: General—Establishment and operation of a gauging station
5168	Measurement of fluid flow—Estimation of uncertainty of a flow-rate measurement	3778.2.4	Part 2.4: General estimation of uncertainty of a flow-rate measurement
778	Liquid flow measurement in open channels—Velocity-area methods	3778.3.1	Part 3: Velocity-area methods—Method 3.1: Measurement by current-meters and floats
4369	Measurement of liquid flow in open channels—Moving-boat method	3778.3.2	Part 3: Velocity-area methods—Method 3.2: Measurement by moving-boat method
1070	Liquid flow measurement in open channels—Slope-area method	3778.3.3	Part 3: Velocity-area methods—Methods 3.3: Measurement by slope-area method
1088	Liquid flow measurement in open channels—Velocity-area methods—collection of data for determination of errors in measurement	3778.3.4	Part 3: Velocity-area methods—Method 3.4: Collection and processing of data for determination of errors in measurement
TR 7178	Measurement of liquid in open channels—Investigation of the total error in measurement of flow by velocity—area methods	3778.3.5	Part 3: Velocity-area methods—Method 3.5: Investigation of total error

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Measurement of water flow in open channels

Part 2.3: General—Determination of the stage-discharge relation

1 Scope and field of application

This International Standard specifies methods of determining the stage-discharge relation for a gauging station. A sufficient number of discharge measurements complete with corresponding stage measurements is required to permit the stage-discharge relation to be determined to the accuracy required by this International Standard.

Stable and unstable channels are considered, including those subject to ice conditions, but considerable care must be taken if this International Standard is applied to flow conditions which suddenly or rapidly vary.

An analysis is included of the uncertainties involved in the preparation and the use of the stage-discharge relation.

2 References

ISO 31, *Quantities, units and symbols*.

ISO 555/1, *Liquid flow measurement in open channels — Dilution methods for measurement of steady flow — Part 1: Constant rate injection method*.

ISO 555/2, *Liquid flow measurement in open channels — Dilution methods for measurement of steady flow — Part 2: Integration (sudden injection) method*.

ISO 748, *Liquid flow measurement in open channels — Velocity-area methods*.

ISO 772, *Liquid flow measurement in open channels — Vocabulary and symbols*.

ISO 1000, *SI units and recommendations for the use of their multiples and of certain other units*.

ISO 1070, *Liquid flow measurement in open channels — Slope-area method*.

ISO 1088, *Liquid flow measurement in open channels — Velocity-area methods — Collection of data for determination of errors in measurement*.

ISO 1100/1, *Liquid flow measurement in open channels — Part 1: Establishment and operation of a gauging station*.

ISO 1438/1, *Liquid flow measurement in open channels using weirs and venturi flumes — Part 1: Thin-plate weirs*.

ISO 2537, *Liquid flow measurement in open channels — Cup-type and propeller-type current meters*.

ISO 3454, *Liquid flow measurement in open channels — Sounding and suspension equipment*.

ISO 3455, *Liquid flow measurement in open channels — Calibration of rotating-element current-meters in straight open tank*.

ISO 3846, *Liquid flow measurement in open channels by weirs and flumes — Free overall weirs of finite crest width (rectangular broad-crested weirs)*.

ISO 3847, *Liquid flow measurement in open channels by weirs and flumes — End-depth method for estimation of flow in rectangular channels with a free overfall*.

ISO 4359, *Liquid flow measurement in open channels using flumes*.¹⁾

ISO 4360, *Liquid flow measurement in open channels by weirs and flumes — Triangular profile weirs*.

ISO 4383, *Liquid flow measurement in open channels — Methods for measurement of suspended sediment*.

ISO 4364, *Liquid flow measurement in open channels — Bed material sampling*.

ISO 4366, *Echo sounders for water depth measurement*.

ISO 4369, *Measurement of liquid flow in open channels — Moving boat method*.

ISO 4373, *Measurement of liquid flow in open channels — Water level measuring devices*.

ISO 4375, *Measurement of liquid flow in open channels — Cableway system for stream gauging*.