

AS 3778.3.1—1990
ISO 748: 1979

Australian Standard[®]

**Measurement of water flow in open
channels**

**Part 3: Velocity-area methods
Method 3.1: Measurement by
current-meters and floats**

This Australian Standard was prepared by Committee CE/24, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 9 April 1999 and published on 10 December 1990.

The following interests are represented on Committee CE/24:

Association of Consulting Engineers of Australia
Australian Water and Wastewater Association
Board of Works, Melbourne
Department of Water Resources, NSW
Engineering and Water Supply Department of South Australia
Forestry Commission, NSW
Institute of Instrumentation and Control
Monash University
Public Works Department, NSW
Snowy Mountains Engineering Corporation
University of New South Wales
University of Queensland
Water Authority of Western Australia
Water Board, Sydney
Water Resources Commission, Queensland

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

AS 3778.3.1—1990

Australian Standard[®]

Measurement of water flow in open channels

**Part 3: Velocity-area methods
Method 3.1: Measurement by current-meters and floats**

First published as AS 3778.3.1—1990.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6294 3

PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 748—1979, *Liquid flow measurement in open channels—Velocity-area methods*.

This Standard is one of a series which deals with methods of measurement of water flow in open channels. The series when complete will consist of the following parts:

- Part 1: Vocabulary and symbols
- Part 2.1: General—Guidelines for the selection of methods of measurement
- Part 2.2: General—Establishment and operation of a gauging station
- Part 2.3: General—Determination of the stage-discharge relation
- Part 2.4: General—Estimation of uncertainty of a flow-rate measurement
- Part 2.5: General—Guidelines for the selection of flow gauging structures
- Part 3: Velocity-area methods—
- Method 3.1: Measurement by current-meters and floats (this Standard)
- Method 3.2: Measurement by moving-boat method
- Method 3.3: Measurement by slope-area method
- Method 3.4: Collection and processing of data for determination of errors in measurement
- Method 3.5: Investigation of total error
- Method 3.6: Measurement of flow in tidal channels
- Method 3.7: Measurement by ultrasonic (acoustic) method
- Method 3.8: Electromagnetic method using a full-channel-width coil
- Part 4: Measurement structure methods—
- Method 4.1: Thin-plate weirs
- Method 4.2: Rectangular broad-crested weirs
- Method 4.3: Round-nose horizontal broad-crested weirs
- Method 4.4: V-shaped broad-crested weirs
- Method 4.5: Triangular profile weirs
- Method 4.6: Flat-V weirs
- Method 4.7: Rectangular, trapezoidal and U-shaped flumes
- Method 4.8: Trapezoidal profile weirs
- Method 4.9: Parshall and Saniiri flumes
- Method 4.10: End-depth method for estimation of flow in rectangular channels with a free overfall
- Method 4.11: End-depth method for estimation of flow in non-rectangular channels with a free overfall (approximate method)
- Part 5: Dilution methods—
- Method 5.1: Constant-rate injection method for the measurement of steady flow
- Method 5.2: Integration method for the measurement of steady flow
- Part 6.1: Measuring devices, instruments and equipment—Rotating element current-meters
- Part 6.2: Measuring devices, instruments and equipment—Direct depth sounding and suspension equipment
- Part 6.3: Measuring devices, instruments and equipment—Calibration of rotating element current-meters in straight open tanks
- Part 6.4: Measuring devices, instruments and equipment—Echo sounders for water depth measurements
- Part 6.5: Measuring devices, instruments and equipment—Water level measuring devices
- Part 6.6: Measuring devices, instruments and equipment—Cableway system for stream gauging
- Part 6.7: Measuring devices, instruments and equipment—Ultrasonic (acoustic) velocity meters
- Part 6.8: Measuring devices, instruments and equipment—Position fixing equipment for hydrographic boats

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (a) Whenever the words 'International Standard' appear, referring to this Standard, they should be read as 'Australian Standard'.
- (b) Whenever the word 'fluid' appears, it should be read as 'water'.
- (c) Substitute a point (.) for a comma (,) as a decimal marker.
- (d) The references to other publications should be replaced by references to Australian Standards.

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
1000	SI units and recommendations for the use of their multiples and of certain other units	1000	The international system of units (SI) and its application
31	Quantities, units and symbols	2900	Quantities units and symbols
		3778	Measurement of water flow in open channels

772	Liquid flow measurement in open channels—Vocabulary and symbols	3778.1	Part 1: Vocabulary and symbols
1100/1	Liquid flow measurement in open channels—Part 1: Establishment and operation of a gauging station	3778.2.2	Part 2.2: General—Establishment and operation of a gauging station
1100/2	Liquid flow measurement in open channels—Part 2: Determination of the stage-discharge relation	3778.2.3	Part 2.3: General—Determination of the stage-discharge relation
5168	Measurement of fluid flow—Estimation of uncertainty of a flow-rate measurement	3778.2.4	Part 2.4: General—Estimation of uncertainty of a flow-rate measurement

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Measurement of water flow in open channels

Part 3: Velocity-area methods

Method 3.1: Measurement by current-meters and floats

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies methods for determining the velocity and cross-sectional area of water flowing in open channels (with or without ice cover), and or computing the discharge therefrom.

It covers methods of employing current-meters and floats to measure the velocities. Although, in most cases, these measurements are intended to determine the stage-discharge relation by means of readings at several stages, this International Standard deals only with single measurements of the discharge; the continuous recording of discharges over a period of time is covered in ISO 1100.

NOTE — Measurements for the purpose of determining the discharge in efficiency tests of hydraulic turbines are specified in IEC Publication 41, International code for the field acceptance tests of hydraulic turbines.

2 REFERENCES

ISO 31, *Quantities, units and symbols*.

ISO 772, *Liquid flow measurement in open channels — Vocabulary and symbols*.

ISO 1000, *SI units and recommendations for the use of their multiples and of certain other units*.

ISO 1088, *Collection of data for determination of errors in measurement of liquid flow by velocity area methods*.

ISO 1100, *Liquid flow measurement in open channels — Establishment and operation of a gauging-station and determination of the stage-discharge relation*.

ISO 2537, *Liquid flow measurement in open channels — Cup-type and propeller-type current meters*.

ISO 3474, *Liquid flow measurement in open channels — Sounding and suspension equipment*.

ISO 3455, *Liquid flow measurement in open channels — Calibration of rotating-element current-meters in straight open tanks*.

ISO 4366, *Liquid flow measurement in open channels — Echo sounders*.

ISO 4373, *Liquid flow measurement in open channels — Water level measuring devices*.

ISO 5168, *Calculation of the uncertainty of a measurement of flowrate*.

ISO/DATA No. 2, *Investigation of the total error in measurement of flow by velocity-area methods*.

3 TERMINOLOGY

For the purposes of this International Standard, in addition to the definition given in ISO 772, the following definitions shall apply

3.1 frazil ice: Fine spicules or plates of ice suspended in water that are generally formed by supercooling of turbulent water. Frazil ice may float under an ice cover and accumulate as slush.

3.2 rime ice: White mass of tiny ice crystals or granular ice formed on exposed objects due to atmospheric moisture.

UNITS OF MEASUREMENT

The units of measurement used in this International Standard are SI units.

5 PRINCIPLE OF THE METHODS OF MEASUREMENTS

5.1 The principle of these methods consists in measuring flow velocity and cross-sectional area. A measuring site is chosen conforming to the specified requirements; the width, depending on its magnitude, is measured either by means of steel tape or by some other surveying method, and the depth is measured at a number of verticals along the width, sufficient to determine the shape and area of cross-section.

Velocity observations are made at each vertical preferably at the same time as measurement of depth, especially in the case of unstable beds; they are made by any one of the standard methods using current-meters. The principle involved is based on the proportionality between the local flow velocity and the speed of the rotor. Under certain circumstances, velocity observations are also made using surface-floats and velocity rods. The mean velocity is generally computed from the individual observations; however, in certain methods such as the integration method, the mean velocity is obtained directly.

5.2 The discharge is computed either arithmetically or graphically by summing the products of the velocity and corresponding area for a series of observations in a cross-section.