

Australian Standard[®]

**Measurement of water flow in
open channels**

**Part 3: Velocity-area methods
Method 3.3: Measurement by
slope-area method**

This Australian Standard was prepared by Committee CE/24, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 9 April 1990 and published on 10 December 1990.

The following interests are represented on Committee CE/24:

Association of Consulting Engineers of Australia
Australian Water and Wastewater Association
Board of Works, Melbourne
Department of Water Resources, NSW
Engineering and Water Supply Department of South Australia
Forestry Commission, NSW
Institute of Instrumentation and Control
Monash University
Public Works Department, NSW
Snowy Mountains Engineering Corporation
University of New South Wales
University of Queensland
Water Authority of Western Australia
Water Board, Sydney
Water Resources Commission, Queensland

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Measurement of water flow in
open channels**

**Part 3: Velocity-area methods
Method 3.3: Measurement by
slope-area method**

First published as AS 3778.3.3—1990

Incorporating:
Amdt 1—1991

PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 1070 — 1973, *Liquid flow measurement In open channels — Slope-area method*.

This Standard is one of a series which deals with methods of measurement of water flow in open channels. The series when complete will consist of the following parts:

- Part 1: Vocabulary and symbols
- Part 2.1: General—Guidelines for the selection of methods of measurement
- Part 2.2: General—Establishment and operation of a gauging station
- Part 2.3: General—Determination of the stage-discharge relation
- Part 2.4: General—Estimation of uncertainty of a flow-rate measurement
- Part 2.5: General—Guidelines for the selection of flow gauging structures

- Part 3: Velocity-area methods
 - Method 3.1: Measurement by current-meters and floats
 - Method 3.2: Measurement by moving-boat method
 - Method 3.3: Measurement by slope-area method (This Standard)
 - Method 3.4: Collection and processing of data for determination of errors in measurement
 - Method 3.5: Investigation of total error
 - Method 3.6: Measurement of flow in tidal channels
 - Method 3.7: Measurement by ultrasonic (acoustic) method
 - Method 3.8: Electromagnetic method using a full-channel-width coil

- Part 4: Measurement structure methods
 - Method 4.1: Thin-plate weirs
 - Method 4.2: Rectangular broad-crested weirs
 - Method 4.3: Round-nose horizontal broad-crested weirs
 - Method 4.4: V-shaped broad-crested weirs
 - Method 4.5: Triangular profile weirs
 - Method 4.6: Flat-V weirs
 - Method 4.7: Rectangular, trapezoidal and U-shaped flumes
 - Method 4.8: Trapezoidal profile weirs
 - Method 4.9: Parshall and Saniiri flumes
 - Method 4.10: End-depth method for estimation of flow in rectangular channels with a free overfall
 - Method 4.11: End-depth method for estimation of flow in non-rectangular channels with a free overfall (approximate method)

- Part 5: Dilution methods
 - Method 5.1: Constant-rate injection method for the measurement of steady flow
 - Method 5.2: Integration method for the measurement of steady flow

- Part 6.1: Measuring devices, instruments and equipment —Rotating element current-meters
- Part 6.2: Measuring devices, instruments and equipment —Direct depth sounding
- Part 6.3: Measuring devices, instruments and equipment —Calibration of rotating element current-meters in straight open tanks
- Part 6.4: Measuring devices, instruments and equipment —Echo sounders for water depth measurements
- Part 6.5: Measuring devices, instruments and equipment —Water level measuring devices
- Part 6.6: Measuring devices, instruments and equipment —Cableway system for stream gauging
- Part 6.7: Measuring devices, instruments and equipment —Ultrasonic (acoustic) velocity meters
- Part 6.8: Measuring devices, instruments and equipment —Position fixing equipment for hydrometric boats

For the purpose of this Australian Standard, the ISO text should be modified as follows:

- (a) Wherever the words 'International Standard' appear, referring to this Standard, they should be read as 'Australian Standard'.
- (b) Wherever the word 'fluid' appears, it should be read as 'water'.
- (c) Substitute a point (.) for a comma (,) as a decimal marker.
- (d) The references to other publications should be replaced by references to Australian Standards as follows.

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
772	Liquid flow measurement in open channels—Vocabulary and symbols	3778	Measurement of water flow in open channels
		3778.1	Part 1: Vocabulary and symbols
1100/1	Liquid flow measurement in open channels—Part 1: Establishment and operation of a gauging station	3778.2.2	Part 2.2: General— Establishment and operation of a gauging station
1100/2	Liquid flow measurement in open channels—Part 2: Determination of the stage—discharge relation	3778.2.3	Part 2.3: General—Determination of the stage-discharge relation
748	Liquid flow measurement in open channels-Velocity-area methods	3778.3	Part 3: Velocity-area methods
		3778.3.1	Method 3.1: Measurement by current-meters and floats

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

Measurement of water flow in open channels

Part 3: Velocity-area methods

Method 3.3: Measurement by slope-area method

1 SCOPE AND FIELD OF APPLICATION

This International Standard specifies the method of determining the slope and area of cross-section of the stream, and of computing the discharge therefrom. The method provides an approximate estimate of the discharge in somewhat special conditions in the stream and is used when estimation of discharge by more accurate methods, like the velocity-area methods, is not possible. The slope-area method can be used with some degree of accuracy in channels with stable boundaries such as rock (or very cohesive clay) bed and sides, and in channels with relatively coarse bed material; this method may also be used in other cases such as alluvial channels including channels with defined spills or non-uniform channel sections, subject to the acceptance of larger errors involved in the selection of the value of the Manning's coefficient n or Chezy's coefficient C . It is, however, not desirable to use this method in the case of very large channels or channels with very flat slopes of high sediment concentration or channels with significant curvature.

This International Standard deals only with ad hoc measurements of discharge and should not be employed for establishing rating-curves. Although the accuracy of results from applying the slope-area method is less than that from applying the velocity-area methods, it is sometimes necessary to use the slope-area method to define the extreme high-stage end of rating-curves because the magnitude of extremely rare floods is such that other methods of measuring discharge cannot be used.

2 REFERENCES

ISO 748, *Liquid flow measurement in open channels by velocity-area method*.

ISO 772, *Liquid flow measurement in open channels — Vocabulary and symbols*.

ISO 106, *Liquid flow measurement in open channels — Establishment and operation of a gauging-station and determination of the stage-discharge relation*.

3 DEFINITIONS

For the purpose of this International Standard, the definitions given in ISO 772 apply.

4 UNITS OF MEASUREMENT

The units of measurement used in this International Standard are seconds and metres (or feet).

5 PRINCIPLE OF THE METHOD OF MEASUREMENT

A measuring-reach is chosen for which the mean area of cross-section of the stream is determined and the surface slope of the flowing water in that reach is measured. The mean velocity is then established by using known empirical formulae which relate the velocity to the hydraulic mean depth, the surface slope corrected for kinetic energy of the flowing water and the characteristics of the bed and bed material. The discharge is computed as the product of the mean velocity and the mean area of cross-section of the stream.

6 SELECTION AND DEMARCATION OF SITE

6.1 Initial survey of site

It is desirable that approximate measurements of widths, depths and surface slopes should be made in a preliminary survey to decide on the suitability of a site conforming, as far as possible, with the conditions given in 6.2 and 6.3. It is intended that these measurements should only serve as a guide.

6.2 Selection of site

6.2.1 The accuracy of the determination of discharge by the slope-area method is increased if the river-banks and bed are reasonably stable and the river-reach fairly straight and uniform in section and free from obstructions and disturbances.

6.2.2 The length of the reach depends upon river slopes at very low stages and flood stages. The slope shall be such that the surface fall in the length of the reach used at each site is at least ten times the expected error in "measurement of fall".

6.2.3 The flow in the reach shall be free from significant disturbances due to the effect of tributaries joining upstream or downstream or of any structure. The reach shall be one in which no substantial expansion occurs.