

Australian Standard<sup>®</sup>

**Measurement of water flow in open  
channels**

**Method 4.4: Measurement using flow  
gauging structures—V-shaped broad-  
crested weirs**

**STANDARDS**  
Australia



This Australian Standard® was prepared by Committee CE-024, Measurement of Water Flow in Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 12 July 1991.  
This Standard was published on 23 September 1991.

---

The following are represented on Committee CE-024:

- Association of Consulting Engineers, Australia
  - Australian Water and Wastewater Association
  - Board of Works, Melbourne
  - Department of Water Resources, N.S.W.
  - Engineering and Water Supply Department of South Australia
  - Forestry Commission, N.S.W.
  - Institute of Instrumentation and Control
  - Monash University
  - Snowy Mountains Engineering Corporation
  - University of New South Wales
  - University of Queensland
  - Water Authority of Western Australia
  - Water Board, Sydney—Illawarra—Blue Mountains
  - Water Resources Commission, Queensland
- 

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee.

---

#### **Keeping Standards up-to-date**

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using the current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting [www.standards.org.au](http://www.standards.org.au)

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at [mail@standards.org.au](mailto:mail@standards.org.au), or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

---

STANDARDS AUSTRALIA

---

RECONFIRMATION

OF

AS 3778.4.4—1991

Measurement of water flow in open channels  
Method 4.4: Measurement using flow gauging structures—  
V-shaped broad-crested weirs

---

RECONFIRMATION NOTICE

Technical Committee CE-024 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 28 November 2019.

The following are represented on Technical Committee CE-024:

Australian Bureau of Meteorology  
Australian Hydrographers Association  
Australian Industry Group  
Institute of Instrumentation, Control & Automation  
Irrigation Australia Limited  
National Measurement Institute  
Office of Finance & Services (NSW)

NOTES

Currently in preview, click buy full vers.

Australian Standard<sup>®</sup>

**Measurement of water flow in open channels**

**Method 4.4: Measurement using flow gauging structures—V-shaped broad-crested weirs**

First published as AS 3778.4.4—1991.  
Reconfirmed 2009.

**COPYRIGHT**

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7262 7062 8

## PREFACE

This Standard was prepared by the Standards Australia Committee on Measurement of Water Flow in Open Channels and Closed Conduits. It is identical with and has been reproduced from ISO 8333:1985, *Liquid flow measurement in open channels by weirs and flumes—V-shaped broad-crested weirs*.

Under arrangements made between Standards Australia and the International Standards Bodies, ISO and IEC, as well as certain other Standards organizations, users of this Australian Standard are advised of the following:

- (a) Copyright is vested in Standards Australia.
- (b) The number of this Standard is not reproduced on each page; its identity is shown only on the cover and title pages.
- (c) There may be occasional dual language sections, but English is always one of the languages reproduced.
- (d) Where any cross-references to page numbers appear within the text, these relate to page numbering in the International Standard and are to be disregarded.

This Standard is one of a series which deals with methods of measurement of water flow in open channels. The series when complete will consist of the following parts:

- Part 1: *Vocabulary and symbols*
- Part 2.1: *General—Guidelines for the selection of methods of measurement*
- Part 2.2: *General—Establishment and operation of a gauging station*
- Part 2.3: *General—Determination of the stage-discharge relation*
- Part 2.4: *General—Estimation of uncertainty of a flow-rate measurement*
- Part 2.5: *General—Guidelines for the selection of flow gauging structures*
- Part 3: *Velocity-area methods*
- Method 3.1: *Measurement by current-meters and floats*
- Method 3.2: *Measurement by moving-boat method*
- Method 3.3: *Measurement by slope-area method*
- Method 3.4: *Collection and processing of data for determination of errors in measurement*
- Method 3.5: *Investigation of total error*
- Method 3.6: *Measurement of flow in tidal channels*
- Method 3.7: *Measurement by ultrasonic (acoustic) method*
- Method 3.8: *Electromagnetic method using a full-channel-width coil*
- Part 4: *Measurement using flow gauging structures.*
- Method 4.1: *Thin-plate weirs*
- Method 4.2: *Rectangular broad-crested weirs*
- Method 4.3: *Round-nose horizontal broad-crested weirs*
- Method 4.4: *V-shaped broad-crested weirs (this Standard)*
- Method 4.5: *Triangular profile weirs*
- Method 4.6: *Flat-V weirs*
- Method 4.7: *Rectangular, trapezoidal and U-shaped flumes*
- Method 4.8: *Trapezoidal profile weirs*
- Method 4.9: *Parshall and Saniiri flumes*
- Method 4.10: *End-depth method for estimation of flow in rectangular channels with a free overfall*
- Method 4.11: *End-depth method for estimation of flow in non-rectangular channels with a free overfall (approximate method)*
- Part 5: *Dilution methods*
- Method 5.1: *Constant-rate injection method for the measurement of steady flow*
- Method 5.2: *Integration method for the measurement of steady flow*
- Part 6.1: *Measuring devices, instruments and equipment—Rotating element current-meters*
- Part 6.2: *Measuring devices, instruments and equipment—Direct depth sounding and suspension equipment*
- Part 6.3: *Measuring devices, instruments and equipment—Calibration of rotating element current-meters in straight open tanks*
- Part 6.4: *Measuring devices, instruments and equipment—Echo sounders for water depth measurements*
- Part 6.5: *Measuring devices, instruments and equipment—Water level measuring devices*
- Part 6.6: *Measuring devices, instruments and equipment—Cableway system for stream gauging*
- Part 6.7: *Measuring devices, instruments and equipment—Ultrasonic (acoustic) velocity meters*
- Part 6.8: *Measuring devices, instruments and equipment—Position fixing equipment for hydrometric boats*

For the purposes of this Australian Standard, the ISO text should be modified as follows:

- (i) Wherever the words 'International Standard' appear, referring to this Standard, they should be read as 'Australian Standard'.
- (ii) Wherever the word 'fluid' appears, it should be read as 'water'.
- (iii) Substitute a full point (.) for a comma (,) as a decimal marker.
- (iv) The references to other publications should be replaced by references to Australian Standards as follows:

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
		3778	Measurement of water flow in open channels
772	Liquid flow measurement in open channels—Vocabulary and symbols	3778.1	Part 1: Vocabulary and symbols
5168	Measurement of fluid flow—Estimation of uncertainty of a flow-rate measurement	3778.2.4	Part 2.4: General—Estimation of uncertainty of a flow-rate measurement
4374	Liquid flow measurement in open channels—Round-nose horizontal broad-crested weirs	3778.4.3	Part 4: Measurement using flow gauging structures Method for Round-nose horizontal broad-crested weirs
4373	Measurement of liquid flow in open channels—Water level measuring devices	—	

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

# Measurement of water flow in open channels

## Part 4: Measurement using flow gauging structures

### Method 4.4: V-shaped broad-crested weirs

#### 1 Scope and field of application

This International Standard specifies a method for the measurement of subcritical flow in small rivers and artificial channels using V-shaped broad-crested weirs.

The advantages of this type of weir are described in clause 8.

NOTE – A comparison of the different types of weirs and flumes will form the subject of a future International Standard.

#### 2 References

ISO 772, *Liquid flow measurement in open channels – Vocabulary and symbols.*

ISO 4373, *Measurement of liquid flow in open channels – Water level measuring devices.*

ISO 4374, *Liquid flow measurement in open channels – Round-nose horizontal crest weirs.*

ISO 5168, *Measurement of fluid flow – Estimation of uncertainty of flow-rate measurement.*

#### 3 Definitions

For the purposes of this International Standard, the definitions given in ISO 772 apply.

#### 4 Units of measurement

The units of measurement used in this International Standard are SI units.

#### 5 Installation

##### 5.1 Selection of site

A preliminary survey shall be made of the physical and hydraulic features of the proposed site to check that it conforms (or may be made to conform) to the requirements necessary for measurement using the weir.

Particular attention shall be paid to the following features in selecting the site of the weir:

- a) the availability of an adequate length of channel of regular cross-section;
- b) the existing velocity distribution;
- c) the avoidance of channels having gradients greater than 1 in 250;
- d) the consequential effects of any increased upstream water level due to the measuring structure;
- e) the consequential conditions downstream, including such influences as tides, confluences with other streams, sluice gates, mill dams and other controlling features which might cause drowning;
- f) the impermeability of the ground on which the structure is to be founded, and the necessity for piling, grouting or other sealing in river installations;
- g) the necessity for flood banks to confine the maximum discharge to the channel;