

AS 3778.6.2:2022
ISO 3454:2008



STANDARDS
Australia



Measurement of water flow in open channels

Part 6.2: Measuring devices, instruments and equipment — Direct depth sounding and suspension equipment (ISO 3454:2008, IDT)



currently in preview, click buy full version

AS 3778.6.2:2022

This Australian Standard ® was prepared by CE-024, Measurement Of Water Flow In Open Channels and Closed Conduits. It was approved on behalf of the Council of Standards Australia on 16 May 2022.

This Standard was published on 10 June 2022.

The following are represented on Committee CE-024:

- Australian Bureau of Meteorology
- Australian Hydrographers Association
- Australian Industry Group
- Department of Planning, Industry and Environment, NSW
- Engineers Australia
- Institute of Instrumentation, Control & Automation Australia
- Irrigation Australia
- Joint Accreditation System of Australia & New Zealand
- National Measurement Institute
- Water NSW

This Standard was issued in draft form for comment as DR AS 3778.6.2:2022.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 809 6

Measurement of water flow in open channels

Part 6.2: Measuring devices, instruments and equipment — Direct depth sounding and suspension equipment (ISO 3454:2008, IDT)

Originates as AS 3778.6.2—1992.
Second edition 2022.

COPYRIGHT

© ISO 2022 — All rights reserved
© Standards Australia Limited 2022

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee CE-024, Measurement of water flow in open channels and closed conduits, to supersede AS 3778.6.2—1992, *Measurement of water flow in open channels, Part 6.2: Measuring devices, instruments and equipment — Direct depth sounding and suspension equipment*.

The objective of this document is to specify the functional requirements of the equipment, excluding bankside cableway systems, used in the measurement of liquid flow in open channels for sounding (by direct method), and suspending the measuring equipment (e.g. current-meter or sediment sampler) at the point of measurement.

This document is identical with, and has been reproduced from, ISO 3454:2008, *Hydrometry — Direct depth sounding and suspension equipment*.

As this document has been reproduced from an International document, the following apply:

- (a) In the source text “this International Standard” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical or options of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Sounding equipment	1
4.1 General	1
4.2 Sounding rod, wading rod and sounding line	1
5 Suspension equipment	1
5.1 Basic requirements	1
5.2 Types of suspension	2
5.2.1 General	2
5.2.2 Rigid-rod suspension equipment	2
5.2.3 Cable suspension equipment	2
6 Performance requirements	3
6.1 Rigid rods for sounding and suspension	3
6.1.1 Sounding rod	3
6.1.2 Suspension rod	3
6.2 Cable suspension equipment	3
6.2.1 General	3
6.2.2 Cable	4
6.2.3 Gauging reel	4
6.2.4 Vehicle- and boat-mounted cranes	5
6.2.5 Sounding weights	5
Annex A (informative) Selection of sounding (sinker) weight	6
Annex B (informative) Corrections for length of sounding line when measuring depth with the line not normal to the surface	7
Bibliography	9

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 3454 was prepared by Technical Committee ISO/TC 113, *Hydrometry*, Subcommittee SC 5, *Instruments, equipment and data management*.

This third edition cancels and replaces the second edition (ISO 3454:1983), which has been technically revised.

Introduction

The choice of suspension and sounding equipment depends on the depth of flow, the velocity of the current and the method of discharge measurement (by wading, from a boat, from a manned cableway or from a bridge).

Currently in preview, click buy full version

NOTES

Currently in preview, click buy full version

Australian Standard®

Measurement of water flow in open channels

Part 6.2: Measuring devices, instruments and equipment — Direct depth sounding and suspension equipment (ISO 3454:2008, IDT)

1 Scope

This International Standard specifies the functional requirements of the equipment, excluding bank-side cableway systems, used in the measurement of liquid flow in open channels for

- a) sounding (by direct method), and
- b) suspending the measuring equipment (for example, current-meter or sediment sampler) at the point of measurement.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 772, *Hydrometry — Vocabulary and symbols*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 772 apply.

4 Sounding equipment

4.1 General

To obtain the correct vertical depth of water from surface to bed, either a sounding-rod or a sounding line is used depending on the velocity and depth of flow. The sounding rod can also be a wading rod. For measurements by either sounding rod or wading rod, the rod shall be held in a vertical position. For measurements by sounding line, appropriate weights shall be attached to keep it as close as practicable to vertical. Sounding equipment can also be employed as suspension equipment. Requirements for the deployment of suspension equipment, as described in [Clause 5](#), also apply to sounding equipment.

4.2 Sounding rod, wading rod and sounding line

A sounding rod is a graduated rigid rod with a base plate; it is used for measurement of depths up to 5 m to 6 m in medium velocities (up to 2 m/s). For smaller depths and velocities, a wading rod is used; for greater depths, a sounding line is used.

5 Suspension equipment

5.1 Basic requirements

The basic requirements for making observations in flowing water with the help of meter-suspension equipment are as follows.

- a) Measuring equipment shall be placed at the point of measurement in such a way that it does not cause appreciable disturbances, irrespective of the depth of water and velocity of flow.