

Australian Standard[®]

**Underground mining—Shaft
equipment**

**Part 1: Drum winding overwind
safety catch systems**

This Australian Standard was prepared by Committee ME/18, Mining Equipment. It was approved on behalf of the Council of Standards Australia on 21 May 1990 and published on 17 September 1990.

The following interests are represented on Committee ME/18:

Australian Coal Association
Australian Mining Industry Council
Broken Hill Mining Managers Association
Bureau of Steel Manufacturers of Australia
Chamber of Mines of Western Australia
Confederation of Australian Industry
Department of Industry and Economic Planning, Victoria
Department of Minerals and Energy, New South Wales
Department of Mines and Energy, Tasmania
Department of Mines, Western Australia
Department of Resources Industries, Qld
Institution of Engineers, Australia
Institution of Mining Electrical and Mining Mechanical Engineers
New South Wales Coal Association
Queensland Chamber of Mines
Queensland Coal Association
Queensland Coal Board
South Australian Chamber of Mines
The Australasian Institute of Mining and Metallurgy
University of New South Wales

Additional interests participating in preparation of Standard:

Mining Companies
Mining Equipment Manufacturers and Suppliers
Mining Consultants

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

**Underground mining—Shaft
equipment**

**Part 1: Drum winding overwind
safety catch systems**

First published as AS 3785.1—1990.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6369 9

PREFACE

This Standard was prepared by the Standards Australia Committee on Mining Equipment.

It is one of a series of Standards on mine shaft equipment. The other Standards in the series are as follows:

- (a) *Underground mining—Shaft equipment, Part 2: Friction winding arresting and overwind safety catch systems.*
- (b) *Underground mining—Shaft equipment, Part 3: Drum winding gripper systems*
- (c) *Underground mining—Shaft equipment, Part 4: Conveyances, for vertical shafts.*
- (d) *Underground mining—Shaft equipment, Part 5: Headframes.*
- (e) *Underground mining—Shaft equipment, Part 6: Guides and rubbing ropes for conveyance*
- (f) *Underground mining—Shaft equipment, Part 7: Sheaves.*

 CONTENTS

	<i>Page</i>
FOREWORD	3
1 SCOPE	4
2 DEFINITIONS	4
3 MATERIAL	4
4 DESIGN	8
5 TESTING	8
6 TEST CERTIFICATES	8
APPENDICES	
A INFORMATION TO BE PROVIDED BY THE PURCHASER	10
B INFORMATION TO BE PROVIDED BY THE SUPPLIER	10

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

FOREWORD

Overwind safety catch systems should be incorporated in drum winding installations to provide a safeguard against malfunction of the detaching hook catch mechanism or failure of the suspension gear in the event of an overwind.

During an overwind which causes the detaching hook to be drawn into the catchplate or detaching bell and the rope to be detached, the conveyance will continue upward until its kinetic energy is dissipated either by potentially destructive impact or by harmless conversion to gravitational potential energy. The possibility of damage to the conveyance, the conveyance suspension gear, and the conveyance contents should be avoided by designing the conveyance suspension equipment with sufficient length and freedom of movement to ensure that the conveyance can rise unimpeded until the kinetic energy is harmlessly dissipated.

This free upward movement will result in slack suspension equipment which can be severely stretched and possibly broken if the conveyance is allowed to fall back through an excessive distance. The overwind safety catch system should act to limit the distance that a conveyance can fall back following such an overwind.

STANDARDS AUSTRALIA

Australian Standard

Underground mining—Shaft equipment

Part 1: Drum winding overwind safety catch systems

1 SCOPE This Standard specifies requirements for overwind safety catch systems in vertical shaft drum winding installations.

This Standard does not apply to vertical shaft friction winding installations and it makes no provision for an overwind with a detach velocity greater than the maximum detach velocity.

NOTE: Guidelines on information to be provided by the purchaser and the supplier are given in Appendices A and B.

2 DEFINITIONS For the purpose of this Standard, the definitions below apply.

2.1 Shall—indicates that a statement is mandatory.

2.2 Should—indicates that a statement is advisory.

2.3 Statutory Authority—an authority having statutory powers to approve mine hoisting installations in the State or Territory within the Commonwealth of Australia.

2.4 Approved and approval—approved by or approval of the Statutory Authority.

2.5 Safe working load—the maximum static load permitted to be carried by the suspension equipment.

2.6 Overwind safety catch system—a system of devices mounted in the head frame and on the conveyance to prevent the conveyance from falling an excessive distance after the winding rope has been detached from the conveyance.

2.7 Detaching hook—a device located between the end of a winding rope and a conveyance so that in the event of an overwind an ascending drum-wound conveyance is detached from the rope and held in the headframe.

2.8 Catchplate/Detaching bell—an apparatus in a headframe which operates a detaching hook in the event of an overwind and from which the detached conveyance is suspended.

2.9 Conveyance—any car, carriage, cage, bin, kibble, or stage in which persons, minerals, or materials are wound through a shaft or any counterweight.

2.10 Headframe—the structure, including its footings, which supports the rope loads in a winding installation.

2.11 Overwind—unintentional travel of an ascending conveyance beyond its normal operating limits.

2.12 Point of entry—the lowest position of the conveyance in the headframe at which lowering of the conveyance is prevented by the overwind safety catch system. (See Figure 1.)

2.13 Point of engagement—the lowest position of the conveyance in the headframe at which those parts of the overwind safety catch system which are mounted on the conveyance are engaged in accordance with the design intent with the interlocking parts mounted in the headframe. (See Figure 2.)

2.14 Point of detach—the position of the conveyance in the headframe when the hoist rope is detached from the conveyance.

2.15 Point of impact—the lowest position of the conveyance in the headframe during an overwind when further upward movement is prevented by either—

- (a) the conveyance striking the headframe or skyshaft; or
- (b) the conveyance attachments jamming between the conveyance and the headframe or skyshaft.

2.16 Fall-back distance—the maximum distance that an overwound conveyance which has passed the point of engagement can descend before being halted by the overwind safety catch system. (See Figure 3.)

2.17 Detach velocity—the velocity of the ascending conveyance at the point of detach.

2.18 Operating distance—the distance from the point of detach to the point of impact.

3 MATERIALS The materials used in the fabrication of the overwind safety catch system shall be selected with due regard to their impact properties at the lowest expected ambient temperature.