

Australian Standard[®]

**Underground mining—Shaft
equipment**

**Part 6: Guides and rubbing ropes
for conveyances**

This Australian Standard was prepared by Committee ME/18, Mining Equipment. It was approved on behalf of the Council of Standards Australia on 14 September 1992 and published on 14 December 1992.

The following interests are represented on Committee ME/18:

Australasian Institute of Mining and Metallurgy
Australian Chamber of Commerce and Industry
Australian Coal Association
Australian Mining Industry Council
Bureau of Steel Manufacturers of Australia
Chamber of Mines of Western Australia
Department of Manufacturing and Industry Development, Vic
Department of Mineral Resources, N.S.W.
Department of Minerals and Energy, W.A.
Department of Mines, Tas.
Department of Resource Industries, Qld
Institution of Engineers, Australia
Institution of Mining Electrical and Mining Mechanical Engineers
Queensland Coal Association
Queensland Coal Board
Queensland Mining Council
South Australian Chamber of Mines
University of New South Wales

Additional interests participating in preparation of this Standard:

Mining companies
Mining consultants
Mining equipment manufacturers and suppliers

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 91125.

Australian Standard[®]

**Underground mining—Shaft
equipment**

**Part 6: Guides and rubbing ropes
for conveyances**

First published as AS 3785.6—1992.

Incorporating:
Amdt 1—1993

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 7866 1

PREFACE

This Standard was prepared by the Standards Australia Committee on Mining Equipment.

It is one of a series of Standards on shaft equipment for underground mines. The other Standards in the series are as follows:

- AS 3785.1 *Underground mining—Shaft equipment, Part 1: Drum winding overwind safety catch systems.*
- AS 3785.2 *Underground mining—Shaft equipment, Part 2: Friction winding arresting systems.*
- AS 3785.3 *Underground mining—Shaft equipment, Part 3: Drum winding gripper systems.*
- AS 3785.4 *Underground mining—Shaft equipment, Part 4: Conveyances for vertical shafts.*
- AS 3785.5 *Underground mining—Shaft equipment, Part 5: Headframes.*
- AS 3785.7 *Underground mining—Shaft equipment, Part 7: Sheaves.*

CONTENTS

	<i>Page</i>
FOREWORD	3
1 SCOPE	4
2 REFERENCED DOCUMENTS	4
3 DEFINITIONS	4
4 MATERIALS	5
5 STRUCTURAL DESIGN	5
6 CONSTRUCTION DESIGN	6
7 MANUFACTURE	7
APPENDIX A TYPICAL GUIDE LOAD DETERMINATION METHODS FOR RIGID GUIDES	9

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

FOREWORD

Guides, either rigid or flexible, are incorporated in vertical shafts to limit the lateral movement of a conveyance in service in the shaft or skyshaft (or both), so maintaining an unhindered passage.

Flexible steel rubbing ropes are installed and suspended between rope-guided conveyances to prevent collision at the passing point.

Currently in preview, click buy full version

STANDARDS AUSTRALIA

Australian Standard

Underground mining—Shaft equipment

Part 6: Guides and rubbing ropes for conveyances

1 SCOPE This Standard specifies requirements for guides and rubbing ropes used in vertical mine shafts. It does not cover the variations in the physical arrangements possible of the guides and rubbing ropes.

2 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

1720 SAA Timber Structures Code

1720.1 Part 1: Design methods

3569 Steel wire ropes

3637 Underground mining—Winding suspension equipment

3637.1 Part 1: General requirements

3990 Steelwork for engineering applications

4100 Steel structures

O22 Grading rule for mine guides

3 DEFINITIONS For the purpose of this Standard, the definitions below apply.

3.1 Approved and approval—approved by or approval of the statutory authority.

3.2 Bunton/dividers—horizontal structural members installed in some shafts, to support rigid guides.

3.3 Chairing—the operation of supporting a conveyance at some point in its normal vertical path by means other than the winding rope or gripper system.

3.4 Conveyance—any car, carriage, cage, skip, kibble or stage in which persons, minerals or materials are wound through a shaft, and any counterweight.

3.5 Conveyance guide assemblies—consist of guide wheels, guide shoes or guide slippers, fixed to the conveyance and operating in conjunction with the guides in the shaft.

3.6 Dead loads—the load due to the mass of all permanent components of the guides.

3.7 Gripper system—a mechanism mounted on a conveyance which is designed to engage with the guides in response to a loss of winding rope tension.

3.8 Guides—fixed structural members or suspended steel wire ropes located in a mine shaft or sky shaft or both, to limit lateral movement of the conveyance.

3.9 Live load—the load resulting on the guides from the operation of the conveyance.

3.10 Overwind—unintentional travel of either an ascending or descending conveyance beyond its normal operating limits.

3.11 Rope break force—the minimum breaking force of a rope, as given by the rope manufacturer's catalogue or specification.

3.12 Rubbing ropes—suspended steel wire ropes, installed between closely spaced rope-guided conveyances.

3.13 Shall—indicates that a requirement is mandatory.

3.14 Should—indicates a recommendation.