

Australian Standard[®]

**Motor vehicle controls—Adaptive
systems for people with disabilities**

**Part 2: Hand controls—Product
requirements**

This Australian Standard was prepared by Committee ME/67, Mobility Appliances for People with Disabilities. It was approved on behalf of the Council of Standards Australia on 8 May 1991 and published on 12 July 1991.

The following interests are represented on Committee ME/67:

ACROD
Attorney-Generals Department
Australian Association of Occupational Therapists
Commercial Vehicle Industry Association of Australia
Confederation of Australian Industry
Crippled Childrens Association of South Australia
Department of Health, New South Wales
Department of Health, Queensland
Department of the Premier and Cabinet, South Australia
Department of Veterans Affairs
Disability Advisory Council of Australia
Disabled Peoples International (Australia)
Federal Chamber of Automotive Industries
Health Department, Victoria
Institution of Engineers, Australia
Metal Trades Industry Association of Australia
Natational Committee Independent Living Centres
Paraplegic and Quadriplegic Association of New South Wales
Paraplegic and Quadriplegic Association of Victoria
Royal North Shore Hospital
Royal Perth Hospital
Technical Aid to the Disabled
University of Adelaide
University of Canberra
University of Melbourne
WorkCover Authority, New South Wales

Additional interests participating in the preparation of this Standard:

Australian Association of Engineers for Disable Drivers
Commonwealth Department of Community Services and Health
Cumberland College of Health Sciences
Department of Motor Transport, South Australia
Disabled Motorists (Victoria)
The Salvation Army Bethesda Hospital, Victoria
VIC ROAD.

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 90100.

Australian Standard[®]

**Motor vehicle controls—Adaptive
systems for people with disabilities**

**Part 2: Hand controls—Product
requirements**

First published as AS 3954.2—1991.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 6965 4

PREFACE

This Standard was prepared by the Standards Australia Committee on Mobility Appliances for People with Disabilities following a request by the New South Wales Association of Occupational Therapists for an Australian Standard for the design, installation and maintenance of adaptive control systems for motor vehicles. This Association expressed concern that there currently was no regulation of such adaptations in motor vehicles and no document giving guidelines on minimum requirements for safety and quality of adaptive motor vehicle controls.

The Committee decided to publish a Standard in two parts: Part 1, *General requirements*, covering general design, construction and installation requirements for a wide range of adaptive motor vehicle controls, and this Standard specifically for hand controls. Whereas Part 1 specifies performance tests to be carried out on driving controls that have been installed in a vehicle, in this Standard, tests for determining strength and fatigue resistance are required to be conducted with the hand controls mounted in a test rig.

CONTENTS

	<i>Page</i>
FOREWORD	3
1 SCOPE	4
2 APPLICATION	4
3 REFERENCED DOCUMENTS	4
4 DEFINITIONS	4
5 DESIGN AND CONSTRUCTION REQUIREMENTS	4
6 PERFORMANCE REQUIREMENTS	4
7 TESTING	5
8 MARKING	5
9 INFORMATIVE LABELLING	5
APPENDICES	
A TEST FOR STRENGTH	6
B DYNAMIC TEST FOR DETERMINING FATIGUE RESISTANCE	7
C TEST FOR RETENTION OF TORQUE ON FASTENERS	8

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

FOREWORD

Driving a motor vehicle is a major step towards independence for people with disabilities. Without this, the opportunities for achieving a full and independent life are limited, along with the freedom of choice that such a level of independence gives.

Overall, in the past, low priority has been given to ensuring the quality and safety of products and services available to meet the mobility needs of disabled people.

Users of mobility appliances need the assurance that the product they choose will be reliable, will meet a satisfactory level of performance and will be able to be effectively serviced and maintained. This is particularly so because of the level of dependency on these products by the consumer and the added difficulties often encountered by disabled people in gaining access to maintenance and repairs.

STANDARDS AUSTRALIA

Australian Standard

Motor vehicle controls—Adaptive systems for people with disabilities

Part 2: Hand controls—Product requirements

1 SCOPE This Standard specifies requirements for mechanical-type, manually operated hand controls offered for installation (other than those provided by the vehicle manufacturer) for use by drivers who are physically disabled, to enable them to operate vehicles. This Standard does not cover electromechanical-type controls.

2 APPLICATION This Standard shall be used in conjunction with Part 1.

3 REFERENCED DOCUMENTS The following documents are referred to in this Standard:

AS

- | | |
|--------|--|
| 1065 | Non-destructive testing—Ultrasonic testing of carbon and low alloy steel forgings |
| 1171 | Methods for magnetic particle testing of ferromagnetic products and components |
| 2062 | Methods for non-destructive penetrant testing of products and components |
| 2084 | Non-destructive testing—Eddy current testing of metal tubes |
| 2177 | Radiography of welded butt joints in metal |
| 2207 | Methods for the ultrasonic testing of fusion welded joints in steel |
| 2679 | Vibration and shock—Mechanical vibration of rotating and reciprocating machinery—Requirements for instruments for measuring vibration severity |
| 2775 | Vibration and shock—Mechanical mounting of accelerometers |
| 3954 | Motor vehicle controls—Adaptive systems for people with disabilities |
| 3954.1 | Part 1: General requirements |

4 DEFINITIONS For the purpose of this Standard, the definitions below apply.

4.1 Electromechanical-type control—a device that is electrically operated and has mechanical motion, such as relays or servos.

4.2 Hand control—a control which enables controls on a vehicle which are normally operated by foot to be operated by hand.

4.3 Shall—indicates that a requirement is mandatory.

4.4 Should—indicates a recommendation.

5 DESIGN AND CONSTRUCTION REQUIREMENTS Hand controls shall comply with AS 3954.1 and with the following:

- (a) Hand controls shall be designed to require distinctly different motions for acceleration, brake actuation and clutch application where applicable.

NOTE: The intention is to prevent the inadvertent operation of these controls.

- (b) Hand controls shall be designed so that neither the brake nor the accelerator is actuated in the 'hands-off' mode, and so that if released, the controls shall revert to a neutral position.

- (c) Unless otherwise approved by the relevant authority, hand controls shall not permit actuation of the accelerator by forward inertial movement of the driver.

PERFORMANCE REQUIREMENTS

6.1 Strength When tested in accordance with Appendix A, there shall be no failure, no changes in alignment, no loosening of parts, and no permanent deformation of any part of the hand control.

6.2 Fatigue resistance When tested in accordance with Appendix B, there shall be no failure, no changes in alignment that would be likely to affect normal operation, no appreciable wear of structural components and no loosening of fasteners.

6.2.1 Fatigue crack inspection Following testing specified in Clause 6.1 and Clause 6.2, crack detection shall be carried out in accordance with either AS 1065, AS 1171, AS 2062, AS 2084, AS 2177 or AS 2207, as appropriate, and no cracks shall have occurred in any part of the hand control.