

Australian Standard™

**Safety of machinery**

**Part 1802: Safety distances and safety gaps—Safety distances to prevent danger zones being reached by the lower limbs**

**STANDARDS**  
Australia



This Australian Standard was prepared by Committee SF-041, General Principles for the Guarding of Machinery. It was approved on behalf of the Council of Standards Australia on 18 April 2006.  
This Standard was published on 29 June 2006.

---

The following are represented on Committee SF-041:

Australian Chamber of Commerce and Industry  
Australian Electrical and Electronic Manufacturers Association  
Department for Administration and Information Services, SA  
Department of Consumer and Employment Protection, WorkSafe Division, WA  
Department of Primary Industries, Mine Safety, NSW  
Engineers Australia  
Federal Chamber of Automotive Industries  
Human Factors and Ergonomics Society of Australia  
Institution of Instrumentation, Control and Automation Australia  
National Electrical and Communications Association  
National Safety Council of Australia  
Office of the Australian Safety and Compensation Council  
Safety Institute of Australia  
The University of Melbourne  
Tractor and Machinery Association of Australia  
Victorian WorkCover Authority

---

#### **Keep your Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at [www.standards.com.au](http://www.standards.com.au) and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at [mail@standards.org.au](mailto:mail@standards.org.au), or write to the Chief Executive, Standards Australia, GPO Box 476, Sydney, NSW 2001.

---

Australian Standard™

## Safety of machinery

### Part 1802: Safety distances and safety gaps—Safety distances to prevent danger zones being reached by the lower limbs

Originally as part of AS 4024.1(Int)—1992.  
Previous edition part of AS 4024.1—1996.  
Revised in part and redesignated as AS 4024.1802—2006.

#### COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 7415 6

## PREFACE

This Standard was prepared by the Standards Australia Committee SF-041, General Principles for the Guarding of Machinery, as a revision (in part) of AS 4024.1—1996, *Safeguarding of machinery, Part 1: General principles*.

During its work, the Committee considered a number of Standards originating within the European Community in the field of safety of machinery. Many of these European Standards are being adopted virtually unchanged as International Standards by the International Organization for Standardization (ISO) and the Committee has agreed to continue to use material emanating from both CEN and ISO in this new edition. This action will maintain consistency with previous editions of AS 4024.1 and other machine-specific Australian Standards.

This edition has been published as a series rather than the single Standard previously published as AS 4024.1. In doing this, the Committee has cleared the way for simple revisions in the future. When a new edition of a relevant Standard becomes available at the international level, it will be adopted and published within the framework of AS 4024 with a minimum delay, so ensuring continued international alignment.

## CONTENTS

	<i>Page</i>
FOREWORD.....	4
1 SCOPE.....	5
2 OBJECTIVE .....	5
3 REFERENCED DOCUMENTS.....	5
4 DEFINITIONS.....	5
5 SAFETY DISTANCES TO PREVENT ACCESS BY LOWER LIMBS.....	6

Currently in preview, click buy full version

## FOREWORD

In accordance with AS 4024.1201, machinery is said to be safe if it is probable that the machinery can perform its function, to be transported, installed, adjusted, maintained, dismantled and disposed of under the conditions of its intended use without causing injury or damaging human health.

One method of eliminating or reducing risks caused by machinery is to make use of safety distances preventing danger zones from being reached. This Standard specifies safety distances only for the lower limbs. Safety distances for the upper limbs are covered by AS 4024.1801.

Sometimes reasonably foreseeable reach situations can occur, e.g. while persons—

- (a) try to use a foot to clean out discharge or feed openings; or
- (b) operate foot-controlled machinery.

In specifying safety distances to prevent lower-limb access and distances to impede free access, a number of aspects have to be taken into consideration, such as—

- (i) reach situations of the lower limbs occurring when machinery is being used;
- (ii) reliable surveys of anthropometric data, taking into account ethnic groups likely to be found in the countries concerned;
- (iii) biomechanical facts, such as compression and stretching of parts of the human body and limits of joint rotation; and
- (iv) technical and practical aspects.

If these aspects were further developed, the current state of the art reflected in this Standard could be improved.

## STANDARDS AUSTRALIA

### Australian Standard Safety of machinery

#### Part 1802: Safety distances and safety gaps—Safety distances to prevent danger zones being reached by the lower limbs

### 1 SCOPE

This Standard establishes values for safety distances to prevent access and distance to impede free access to machinery danger zones to prevent their being reached by the lower limbs of persons of 14 years of age and above.

NOTE: The values given are based on practical experience which has been found to be adequate for this group of persons.

These distances apply when adequate safety can be achieved by distance alone, and when access by the upper limbs is not foreseeable according to the risk assessment.

NOTE: These safety distances will not provide sufficient protection against certain hazards, for example radiation and emission of substances. For such hazards additional or other measures need to be taken.

The safety distances to prevent access relate to opening and serve to protect those persons trying to reach danger zones under the conditions specified for different reaching situations.

The distances to impede free access relate to the height from ground level to the protective structure, and serve to reduce risk to persons by limiting the free movement of the lower limbs.

NOTE: If persons below 14 years of age are to be taken into account, it is not relevant to establish values other than those for upper limbs. In this case the safety distances to prevent danger zones being reached by the upper limbs derived from AS 4024.1801 will apply.

For certain applications, there are justifiable reasons to deviate from these distances. Standards dealing with these applications should indicate how adequate safety can be achieved.

### 2 OBJECTIVE

The objective of this Standard is to enable designers, manufacturers, suppliers, employers and users of machinery to minimize risks to the health and safety of employees and others working with or otherwise near machinery by providing safety distances to prevent entry to the danger zone by the lower limbs.

### 3 REFERENCED DOCUMENTS

AS 4024	Safety of machinery
4024.1201	Part 1201: General principles—Basic terminology and methodology
4024.1301	Part 1301: Risk assessment—Principles for risk assessment
4024.1801	Part 1801: Safety distances and safety gaps—Safety distances to prevent danger zones being reached by the upper limbs