

Australian Standard[®]

Wind loads for housing

STANDARDS
Australia



This Australian Standard® was prepared by Committee BD-099, Wind Loads for Housing. It was approved on behalf of the Council of Standards Australia on 7 November 2005. This Standard was published on 6 January 2006.

The following are represented on Committee BD-099:

- Australian Building Codes Board
 - Australian Glass and Glazing Association
 - Australian Institute of Building Surveyors
 - Australian Windows Association
 - Building Designers Association of Australia
 - Clay Brick and Paver Institute
 - Concrete Masonry Association of Australia
 - Cyclone Testing Station (JCU)
 - Housing Industry Association
 - Master Builders Australia
 - National Timber Development Council
 - Roofing Tile Association of Australia
-

This Standard was issued in draft form for comment as DR 04347.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

Wind loads for housing

First published as AS 4055—1992.
Second edition 2006.
Revised incorporating Amendment No. 1 (July 2008).

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia
ISBN 0 7337 7087 8

PREFACE

This Standard was prepared by the Standards Australia Committee BD-099, *Wind loads for housing* to supersede AS 4055—1992.

This Standard incorporates Amendment No. 1 (July 2008). The changes required by the Amendment are indicated in the text by a marginal bar and amendment number against the clause, note, table, figure or part thereof affected.

This Standard will be referenced in the Building Code of Australia 2006 edition (BCA 2006), thereby superseding in part the previous edition, AS 4055—1992, which will be withdrawn 12 months from the date of publication of this edition.

The objective of this Standard is to provide designers, builders and manufacturers of building products that are affected by wind loading with a range of wind speed classes that can be used to design and specify such products for use in housing that are within the limitations in this Standard.

This edition differs from the previous edition as follows:

- (a) Wind speeds are specified for the serviceability and ultimate strength/stability limit states only. Permissible stress has been omitted.
- (b) The Standard has been updated to reflect the latest technical knowledge on wind forces as represented by the 2002 edition of AS/NZS 1170.2.
- (c) The table of classes for site conditions has been updated.
- (d) Pressure factors have been made normative and calculation methods given for determining pressures and forces.
- (e) New racking tables have been included in limit states format.
- (f) A more detailed commentary has been added (Appendix A) to clarify the relationship of this Standard to AS/NZS 1170.2 and to give background to some of the clauses.

The term 'informative' has been used in this Standard to define the application of the Appendix to which it applies. A 'informative' appendix is only for information and guidance.

Notes to the text contain information and guidance. They are not an integral part of the Standard.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	4
1.2 LIMITATIONS	4
1.3 NORMATIVE REFERENCES	4
1.4 DEFINITIONS	5
1.5 NOTATION	6
SECTION 2 WIND LOADS	
2.1 CLASSIFICATION	8
2.2 RELATIONSHIP TO WIND REGION AND SITE CONDITIONS	8
2.3 SELECTION OF TERRAIN CATEGORY	11
2.4 SELECTION OF TOPOGRAPHIC CLASS	11
2.5 SELECTION OF SHIELDING CLASS	13
SECTION 3 CALCULATION OF PRESSURES AND FORCES	
3.1 PRESSURE COEFFICIENTS	15
3.2 CALCULATION OF PRESSURES	16
3.3 CALCULATION OF FORCES	16
3.4 PRESSURES FOR TYPICAL APPLICATIONS	17
SECTION 4 UPLIFT FORCES	19
SECTION 5 RACKING FORCES	
5.1 RACKING FORCES	20
5.2 AREA OF ELEVATION	20
APPENDICES	
A COMMENTARY	37
B WORKED EXAMPLE FOR THE DETERMINATION OF TOPOGRAPHY	46
C WORKED EXAMPLES FOR THE SELECTION OF TERRAIN CATEGORY AND SHIELDING CLASS	48
D WORKED EXAMPLE FOR RACKING FORCES	50

STANDARDS AUSTRALIA

Australian Standard
Wind loads for housing

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies site wind speed classes for determining design wind speed and wind loads for housing within the geometric limits given in Clause 1.2. The classes are for use in the design of housing and for design, manufacturing and specifying of building products and systems used for housing.

Wind loads for houses not complying with the geometric limits given in Clause 1.2 are outside the scope of this Standard.

NOTES:

- 1 Commentary on the clauses of this Standard is given in Appendix A.
- 2 A worked example for the determination of topography is given in Appendix B.
- 3 Worked examples for the determination of terrain category and shielding class are given in Appendix C.
- 4 A worked example for racking forces is given in Appendix D.
- 5 Where houses do not comply with the geometric and other limitations of this Standard, use AS/NZS 1170.0 and AS/NZS 1170.2.

1.2 LIMITATIONS

For the purpose of this Standard, the following conditions (geometric limits) shall apply (see Figure 1.1):

- (a) The distance from ground level to the underside of eaves shall not exceed 6.0 m from ground level to the highest point of the roof, neglecting chimneys shall not exceed 8.5 m.
- (b) The width (W) including roofed verandas, excluding eaves, shall not exceed 16.0 m, and the length (L) shall not exceed five times the width.
- (c) The roof pitch shall not exceed 35°.

The tables in Section 5 are based on floor to ceiling height of 2.4 m and a floor depth of 0.3 m (floor level down to ceiling below).

1.3 NORMATIVE REFERENCES

The following referenced documents are indispensable for the application of this Standard:

AS/NZS	
1170	Structural design actions
1170.0	Part 0: General principles
1170.2	Part 2: Wind actions
ABCB	
BCA	Building Code of Australia