

Australian Standard™

Fibre-reinforced concrete pipes and fittings

Currently in preview, click buy full version

This Australian Standard was prepared by Committee WS-008, Fibre Reinforced Concrete Pipes and Fittings. It was approved on behalf of the Council of Standards Australia on 3 June 2003 and published on 5 August 2003.

The following are represented on Committee WS-008:

Australian Chamber of Commerce and Industry
Australian Institute of Building
Austroads
Brisbane City Council
CSIRO Building, Construction and Engineering
Department of Land and Water Conservation NSW
Institution of Engineers Australia
University of Tasmania

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 02287.

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS 4139–2003

Fibre-reinforced concrete pipes and fittings

RECONFIRMATION NOTICE

Major stakeholders of this publication have reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 29 August 2018.

NOTES

Currently in preview, click buy full vers.

Australian Standard™

Fibre-reinforced concrete pipes and fittings

Revised as AS 4139—1993.
Second edition 2003.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5356 6

PREFACE

This Standard was prepared by the Standards Australia Committee WS-008, Fibre-Reinforced Concrete Pipes and Fittings, to supersede AS 4139—1993, *Fibre-reinforced concrete pipes and fittings*, which is withdrawn.

The objective of this Standard is to provide manufacturers and purchasers with uniform requirements for fibre-reinforced concrete pipes and fittings.

The Standard has been written as a performance specification avoiding as far as possible any requirements that may restrict innovation in design. Pipe Classes 2, 3 and 4, specified in this Standard, correspond to the equivalent classes for steel-reinforced concrete pipe given in AS 4058, *Precast concrete pipes (pressure and non-pressure)*.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
FOREWORD.....	4
1 SCOPE.....	5
2 REFERENCED DOCUMENTS	5
3 DEFINITIONS.....	6
4 NOTATION.....	7
5 CLASSIFICATION	8
6 MATERIALS.....	9
7 FITTINGS.....	10
8 ELASTOMERIC SEAL JOINTS	11
9 DEFECTS	11
10 DIMENSIONS AND TOLERANCES.....	11
11 PERFORMANCE REQUIREMENTS	12
12 MARKING.....	13
13 HANDLING AND STORAGE	14
APPENDICES	
A PURCHASING RECOMMENDATIONS.....	15
B GUIDE TO CONCENTRATION LIMITS APPLICABLE TO SOME CONSTITUENTS OF THE BURIED ENVIRONMENT.....	16
C DESIGN PRINCIPLES FOR DETERMINING THE RELATIONSHIP BETWEEN LONG-TERM AND SHORT TERM PERFORMANCE OF PIPE	18
D CRITERIA FOR CLASSIFYING A COMPLYING SEMI-RIGID PIPE	20
E METHOD FOR CRUSH LOAD TESTING OF PIPES.....	24
F LONG-TERM STIFFNESS OF SATURATED PIPE	28
G METHOD FOR DETERMINING THE DRY/WET STRENGTH FACTOR (<i>C</i>).....	33
H DETERMINATION OF REGRESSION FACTOR (<i>R</i>).....	34
I METHOD FOR FLEXURAL STRENGTH TEST	39
J MODULUS OF ELASTICITY OF PIPE	41
K METHOD FOR WATER ABSORPTION TEST	45
L METHOD FOR HYDROSTATIC PRESSURE TEST.....	47
M TYPICAL JOINT CONFIGURATIONS.....	49
N MEANS FOR DEMONSTRATING COMPLIANCE WITH THIS STANDARD	50

FOREWORD

Fibre-reinforced concrete pipe may be either rigid pipe or semi-rigid pipe.

Rigid pipe is assumed to be incapable of having sufficient deflection to gain support from the surrounding soil and must have sufficient ring bending strength to support the full soil prism load to maintain its integrity for its design life.

Semi-rigid pipe must have sufficient ring bending strength to initially support the full soil prism load, and sufficient deflection capability to deflect as its stiffness reduces with age, to obtain support from the surrounding soil to maintain its integrity for its design life.

A flexible pipe has insufficient ring bending strength to support the full soil prism load and relies on support from the surrounding soil to maintain its integrity for its full design life.

In common with other materials, fibre-reinforced concrete pipe may exhibit creep under sustained loading conditions. In order that this may be accommodated into the design of the product, the change is quantified by type-testing, either through the application of regression analysis or a stress relaxation methodology.

The minimum allowable test load for a pipe is determined by predicting the design life load that the pipe will be capable of withstanding in a saturated condition. A safety factor of 1.5 has been assumed for the purposes of design calculation. In addition, pipes satisfying the definition of being semi-rigid in this Standard have a further safety factor of 2 on long-term deflection.

The required design life and class of the pipe shall be determined using informed engineering judgment of the conditions of installation and operation of the pipe.

This Standard has been developed with a focus on cellulose-reinforcing fibres. The Standard, however, covers a number of fibre types and does not restrict the method of pipe manufacture.

STANDARDS AUSTRALIA

Australian Standard Fibre-reinforced concrete pipes and fittings

1 SCOPE

This Standard specifies minimum requirements for pipes and fittings manufactured from fibre-reinforced concrete using standard curing, including autoclaving, for the conveyance of gravity water supply, and stormwater, waste water and sewage drainage.

Four classes of pipes are covered by this Standard, distinguished on the basis of long-term design load: Class 1, Class 2, Class 3, and Class 4. Other classes of pipe may be designed using the principles described in this Standard.

This Standard addresses the effect of creep under load by either, regression analysis of pipe materials (see Appendix H), or long-term stiffness prediction.

NOTES:

- 1 Fibre-reinforced concrete pipe is herein referred to as 'pipe'.
- 2 The load classes correspond with those of AS 4058.
- 3 This Standard does not cover the assessment of external service loads to which a pipe will be subjected to in a particular installation. Purchasers should, therefore, satisfy themselves that the class of pipe specified or selected on the basis of this Standard is suitable for its intended application. For buried pipes, reference to AS 3725 is required.
- 4 Guidance on the information to be supplied by the purchaser at the time of enquiry or order is given in Appendix A.
- 5 Appendix B provides concentration limits for commonly occurring soil/terrain constituents of the buried environment, but does not provide special requirements for pipes intended for use in environments aggressive to concrete. Where such applications are envisaged, the advice of the manufacturer should be sought.

2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

AS	
1199	Sampling procedures and tables for inspection by attributes
1379	Specification and supply of concrete
1399	Guide to AS 1199—Sampling procedures and tables for inspection by attributes
1478	Chemical admixtures for concrete, mortar and grout
1478.1	Part 1: Admixtures for concrete
1546	Elastomeric seals for waterworks purposes (all parts)
2193	Calibration and classification of force-measuring systems
2490	Sampling procedures and charts for inspection by variables for percent nonconforming (ISO 3951:1989)
2758	Aggregates and rock for engineering purposes
2758.1	Part 1: Concrete aggregates
3582	Supplementary cementitious materials for use with portland cement (all parts)
3725	Loads on buried concrete pipes