

Australian Standard[®]

Gaseous fire extinguishing systems

**Part 5: NAF S-III (HCFC Blend A)
Total flooding systems**

This Australian Standard was prepared by Committee FP/11, Fire Extinguishing Systems. It was approved on behalf of the Council of Standards Australia on 28 February 1995 and published on 5 June 1995.

The following interests are represented on Committee FP/11:

Australian Chamber of Commerce and Industry
Australian Construction Services—Department of the Arts and Administrative Services
Australian Fire Authorities Council
Australian Fire Protection Association
Commonwealth Fire Board
Department of Defence, Australia
Fire Protection Industry Association of Australia
Fire Trainers Association of Australia
Insurance Council of Australia
NZ Fire Equipment Association
NZ Fire Protection Association
NZ Fire Protection Industry Contractors Association
Railways of Australia
Society of Fire Protection Engineers Australian Chapter
Telecom Australia

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

Gaseous fire extinguishing systems

**Part 5: NAF S-110 (HCFC Blend A)
Total flooding systems**

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee FP/11 on Fire Extinguishing Systems.

This Standard is the result of consensus among representatives on the Joint Committee to provide it as an Australian Standard.

In order to maintain a compatible format in each part of AS 4214, *Gaseous fire extinguishing systems*, the section numbers have been maintained throughout the suite whether or not they are applicable to the particular part.

The objective of this Standard is to provide the users of NAF S-III systems with specific requirements for the control of fires of Classes A, B or C and E type. It does not cover the design of explosion suppression systems.

It is essential that fire extinguishing equipment be carefully maintained to ensure instant readiness when required. The importance of maintenance cannot be too highly emphasised. The maintenance requirements for NAF S-III system for fire protection equipment are detailed in another Standard.

NAF S-III containers, manufactured for use in Australia, are required to meet the design parameters as set out in AS 2030.1, *The approval, filling, inspection, testing and maintenance of cylinders for the storage and transport of compressed gases* (known as the SAA Gas Cylinders Code), Part 1: *Cylinders for compressed gases other than acetylene*.

Attention is drawn to AS 2030.1 as it requires cylinders to be designed for the pressure developed at 65°C. This is some 10°C higher than that nominated in overseas codes. Accordingly, this aspect should be kept in mind for any imported NAF S-III containers.

It is a basic assumption in all technical standard work that each Standard be used only by persons competent in the field of application with which it deals. This is of particular importance in fire protection work. Accordingly, it is emphasised that the design requirements in this Standard are to be interpreted only by trained and experienced designers.

This Standard does not include specific requirements for NAF S-III systems for marine or mobile applications. However, the method of calculation in this Standard may be of some assistance in the design of such systems.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

	<i>Page</i>
FOREWORD	5
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE	6
1.2 APPLICATION	6
1.3 REFERENCED DOCUMENTS	6
1.4 DEFINITIONS	7
1.5 USES AND LIMITATIONS OF NAF S-III SYSTEMS	7
SECTION 2 SAFETY REQUIREMENTS	
2.1 SAFETY OF PERSONNEL	8
2.2 SAFETY PRECAUTIONS AND LIMITS	8
SECTION 3 SYSTEM DESIGN	
3.1 GENERAL	9
3.2 DESIGN	9
3.3 DURATION OF DISCHARGE	9
3.4 CONCENTRATION, DISTRIBUTION AND HOLDING	9
3.5 FLAME EXTINGUISHMENT	9
3.6 INERTING REQUIREMENTS	12
3.7 COMBUSTIBLE SOLIDS	12
3.8 TOTAL FLOODING QUANTITY	12
3.9 PRESSURE ADJUSTMENT	12
3.10 COMPATIBILITY	12
SECTION 4 PROTECTED ENCLOSURE REQUIREMENTS	
	16
SECTION 5 NAF S-III SUPPLY	
5.1 QUALITY NAF S-III	17
5.2 STORAGE CONTAINERS	17
5.3 STORAGE CONTAINER ARRANGEMENT	17
SECTION 6 DISTRIBUTION SYSTEM	
6.1 GENERAL	19
6.2 STEEL PIPE	19
6.3 COPPER PIPE	19
6.4 PIPING JOINTS	19
6.5 SAFETY DEVICES	20
SECTION 7 CONTROL SYSTEMS	
	21
SECTION 8 MARKING	
8.1 IDENTIFICATION	22
8.2 MARKING	22

SECTION 9 COMMISSIONING AND ACCEPTANCE TESTING

9.1	CRITERIA FOR ACCEPTANCE	23
9.2	COMMISSIONING CERTIFICATION	23
9.3	FAILURE	23

APPENDICES

A	SAFETY OF PERSONNEL	24
B	DISCHARGE TEST	26
C	NOTICE OF COMPLETION	28
D	CHARACTERISTICS OF NAF S-III (HCFC BLEND A)	30

Currently in preview, click buy full vers.

First published as AS 4214.5— 1995.
Incorporating:
Amdt 1—1997

FOREWORD

It is important that the fire protection of a building or plant be considered as a whole. NAF S-III total flooding systems form only a part, though an important part, of the available facilities. However, it should not be assumed that their adoption necessarily removes the need to consider supplementary measures, such as the provision of portable fire extinguishers or mobile appliances for first aid or emergency use, or measures to deal with special hazards.

NAF S-III is recognised as effective for extinguishing Class A, Class B and Class C fires where electrical risks are present. Nevertheless, it should not be forgotten in the planning of the comprehensive schemes that there may be hazards for which this technique is not suitable, or that, in certain circumstances or situations, there may be dangers in its use, requiring special precautions.

Advice on these matters can be obtained from organizations involved with the installation of NAF S-III total flooding systems.

STANDARDS AUSTRALIA

Australian Standard

Gaseous fire extinguishing systems

Part 5: NAF S-III (HCFC Blend A)

Total flooding systems

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE This Standard complements AS 4214.1 and sets out requirements for total flooding fire extinguishing systems, utilising HCFC Blend A for use in enclosed spaces. It applies to single supply or distributed supply systems.

The HCFC Blend A shall be referred to as NAF S-III in this Standard.

1.2 APPLICATION NAF S-III total flooding fire extinguishing systems, described as NAF S-III systems hereafter, shall comply with AS 4214.1 and the requirements of this Standard. Where requirements differ, this Standard takes precedence.

1.3 REFERENCED DOCUMENTS The following documents are referred to in this Standard.

AS

- 1650 Hot-dipped galvanized coatings on ferrous articles
- 1722 Pipe threads of Whitworth form
- 1722.1 Part 1: Sealing pipe threads
- 1850 Portable fire extinguishers—Classification, rating and performance testing
- 2030 The approval, filling, inspection, testing and maintenance of cylinders for the storage and transport of compressed gases (known as the SAA Gas Cylinders Code)
- 2030.1 Part 1: Cylinders for compressed gases other than acetylene
- 2129 Flanges for pipes, valves and fittings
- 2700 Colour standards for general purposes
- 3672 Wrought steel threaded pipe fittings
- 4041 Pressure piping
- 4214 Gaseous fire extinguishing systems
- 4214.1 Part 1: General requirements
- 4215.0 Methods of determining fire extinguishing and inerting concentrations for flammable liquids and gases
- 4215.1 Method 1: Determination of fire extinguishing concentrations
- 4215.2 Method 2: Determination of fire inerting concentrations

ASTM

- A53 Specification for pipe, steel, black and hot-dipped, zinc coated welded and seamless
- A106 Specification for seamless carbon steel pipe for high-temperature service