

Australian Standard[®]

**Liquid hydrocarbons—
Dynamic measurement—
Proving systems for
volumetric meters**

Part 5: Dynamic measurement

[ISO title: Petroleum and liquid petroleum products—
Calculation of oil quantities, Part 2: Dynamic measurement]

This Australian Standard was prepared by Committee ME/49, Oil and Gas Measurement. It was approved on behalf of the Council of Standards Australia on 15 August 1994 and published on 5 January 1995.

The following interests are represented on Committee ME/49:

Australian Custom Service
Australian Gas Association
Australian Institute of Petroleum
Australian Institute of Physics
Australian Liquefied Petroleum Gas Association
Australian Petroleum Exploration Association
CSIRO, Division of Applied Physics
Department of Primary Industries and Energy
Institute of Instrumentation and Control, Australia
Institution of Engineers Australia
National Association of Testing Authorities
National Standards Commission
Pipeline Authority

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

This Standard was issued in draft form for comment as DR 93328.

Australian Standard[®]

**Liquid hydrocarbons—
Dynamic measurement—
Proving systems for
volumetric meters**

Part 5: Dynamic measurement

First published as AS 4250.5—1995.

PUBLISHED BY STANDARDS AUSTRALIA
(STANDARDS ASSOCIATION OF AUSTRALIA)
1 THE CRESCENT, HOMEBUSH, NSW 2140

ISBN 0 7262 9259 1

PREFACE

This Standard was prepared by the Standards Australia Committee on Oil and Gas Measurement and is designated Part 5 of a series of Standards dealing with petroleum liquid measurement systems under the general title *Liquid hydrocarbons—Dynamic measurement—Proving systems for volumetric meters*. Part 5 covers *Dynamic measurement*.

Other Standards or proposed Standards in this series are as follows:

Part 1: General principles

Part 2: Pipe provers

Part 3: Pulse interpolation

Part 4: Temperature corrections in volumetric calibration by water transfer method

This Standard is technically equivalent to ISO 4267.2:1988, *Petroleum and liquid petroleum products—Calculation of oil quantities, Part 2: Dynamic measurement*.

For the purposes of this Standard, the ISO text is amended as set out in Appendix ZZ. Each change is indicated in the text by a marginal bar.

The term 'normative' has been used in this Standard to define the application of Appendix ZZ. A 'normative' appendix is an integral part of a Standard.

Replace any references to 'International Standard' with 'Australian Standard'.

Reference to International Standard

Australian Standard

ISO

AS

91 Petroleum measurement tables
91-1 Part 1: Tables based on reference temperatures of 15°C and 60°F

2520 Petroleum measurement tables

2715 Liquid hydrocarbons—
Volumetric measurement by turbine meter systems

2651 Liquid hydrocarbons—
Volumetric measurement by turbine meter systems

5024 Petroleum liquids and gases—
Measurement—Standard reference conditions

2649 Petroleum liquids and gases—
Measurement—Standard reference conditions

7278 Liquid hydrocarbons—
Dynamic measurement—
Proving systems for volumetric meters

4250 Liquid hydrocarbons—
Dynamic measurement—
Proving systems for volumetric meters

7278.2 Part 2: Pipe provers

4250.2 Pipe provers

8222 Petroleum measurement systems—
Calibration—Temperature corrections for use with volumetric reference measuring systems

—

9770 Petroleum products—Compressibility factors for hydrocarbons in the range 638 kg/m³ to 1 074 kg/m³

—

Under arrangements made between Standards Australia and the International Standards bodies, ISO and IEC, as well as certain other Standards organizations, users of this Australian Standard are advised that the number of this Standard is not reproduced on each page; its identity is shown only on the cover and title pages.

CONTENTS

	<i>Page</i>
0 Introduction	1
1 Scope and field of application	1
2 References	1
3 Definitions	2
4 Hierarchy of accuracies	2
4.1 Purpose and implications	2
4.2 Hierarchy	2
5 Principal correction factors	2
5.1 Purpose and implications	2
5.2 C_{fs}	3
5.3 C_{ps}	4
5.4 C_{pl}	4
5.5 C_{tl}	5
6 Calculation of prover volume	5
6.1 Purpose and implications	5
6.2 Volume standard measures	5
6.3 Rule for rounding — Prover	5
6.4 Temperature and pressure	6
6.5 Calculation of base volumes	6
6.6 Corrections applied to measured-volume water draw method	6
6.7 Example of calculation — Calibration of pipe prover by water draw method using field standards	6
6.8 Example of calculation — Calibration of tank prover by water draw method using field standards	8
6.9 Example of calculation — Calibration of pipe prover by master meter method	9

	<i>Page</i>
7 Calculation of meter factor	11
7.1 Purpose and implications	11
7.2 Temperature and pressure	13
7.3 Rule for rounding — Meter factors	13
7.4 Calculation of standard meter factor for a displacement meter, using a prover tank	13
7.5 Calculation of standard meter factor for a turbine meter, using a pipe prover	14
7.6 Calculation of meter factor at standard conditions for a displacement meter, using a master meter	17
8 Calculation of <i>K</i> -factor	19
8.1 Purpose and implications	19
8.2 Temperature and pressure	19
8.3 Rule for rounding — <i>K</i> -factors	19
8.4 Calculation of <i>K</i> -factor for a turbine meter, using a pipe prover	19
9 Calculation of measurement tickets	20
9.1 Purpose and implications	20
9.2 Rule for rounding — Measurement tickets	20
9.3 Correction factors and accuracy	20
Annex A Correction factors for the effect of temperature and pressure on steel	22
APPENDIX ZZ LIST OF VARIATIONS BETWEEN THIS STANDARD AND ISO 4267-2	25

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

AUSTRALIAN STANDARD

Liquid hydrocarbons—Dynamic measurement— Proving systems for volumetric meters

Part 5: Dynamic measurement

0 Introduction

Before the compilation of this publication, words and expressions employed in dynamic measurement calculations were interpreted slightly differently by different people, and there was a lack of coherence in their use. In addition, because data were spread over so many standards, there was difficulty in readily comparing the finer points of calculations.

Rules for rounding, and the choice of how many significant figures entered each calculation, were open to a variety of interpretations. For different operators to obtain identical results from the same data, the rules for sequence, rounding and significant figures have to be defined. This International Standard aims, among other things, at defining the minimum set of rules required. Nothing in this International Standard precludes the use of more precise determinations of temperature, pressure and density or the use of more significant digits, by mutual agreement among the parties involved.

This International Standard aims at consolidating and standardizing calculations pertaining to the measuring of petroleum liquids, and at clarifying terms and expressions by eliminating local variations of such terms. The purpose of standardizing calculations is to produce the same answer from the same data regardless of the computing system used.

Although ISO/TC 28 standards use 15 °C as a standard reference temperature, it is recognized that individual countries may use other reference temperatures, for example 20 °C, 12 °C or 60 °F.

This standard sets minimum levels of accuracy for industrial calculations, but, if parties consider agreeing to set tighter requirements, it is important to demonstrate whether such requirements can be met. Future technological progress in meter proving and operation may justify a tighter specification for calculation procedures.

1 Scope and field of application

This International Standard defines the various terms (be they words or symbols) employed in the calculation of metered

petroleum quantities. Where two or more terms are customarily employed in the oil industry for the same quantity, a preferred term is selected.

This International Standard also specifies the equations which allow the values of correction factors to be computed. It also gives rules for the sequence, rounding and significant figures to be employed in a calculation. It provides tables which may be used to look up specific correction factors should it not be desired to calculate them by manual as well as computer methods. The calculation of prover base volumes, meter factors and measurement tickets is also covered.

The field of application of this International Standard is the volumetric measurement of liquid hydrocarbons, including liquefied petroleum gases, by meter and prover. It does not include two-phase fluids (though it may be found useful in such situations) except in so far as sediment and water may be mixed in with crude oil.

2 References

ISO 91-1, *Petroleum measurement tables — Part 1: Tables based on reference temperatures of 15 °C and 60 °F.*

ISO 2715, *Liquid hydrocarbons — Volumetric measurement by turbine meter systems.*

ISO 5024, *Petroleum liquids and gases — Measurement Standard reference conditions.*

ISO 7278-2, *Liquid hydrocarbons — Dynamic measurement — Proving systems for volumetric meters — Part 2: Pipe provers.*¹⁾

ISO 8222, *Petroleum measurement systems — Calibration — Temperature corrections for use with volumetric reference measuring systems.*

ISO 9770, *Petroleum products — Compressibility factors for hydrocarbons in the range 638 kg/m³ to 1 074 kg/m³.*¹⁾

1) At the stage of draft.