

Australian Standard™

**Installation of nailplated timber roof  
trusses**



**STANDARDS  
AUSTRALIA**

Currently in preview, click buy full version

This Australian Standard was prepared by Committee TM-002, Timber Framing. It was approved on behalf of the Council of Standards Australia on 7 April 2004 and published on 1 June 2004.

---

The following are represented on Committee TM-002:

Association of Consulting Engineers, Australia  
Australian Building Codes Board  
Australian Institute of Building  
Building Research Association of New Zealand  
CSIRO Manufacturing and Infrastructures Technology  
Engineers Australia  
Forest Industries Federation (WA)  
Housing Industry Association  
Master Builders, Australia  
New Zealand Forest Industries Council  
New Zealand Forest Research Institute  
New Zealand Timber Industry Federation  
Plantation Timber Association Australia  
Plywood Association of Australasia  
South Australian Housing Trust  
Structural Engineered Timber Manufacturers Association, New Zealand  
Timber and Building Materials Association, NSW  
Timber Development Association, NSW  
Timber Development Association of South Australia  
Timber Merchants Association of Victoria  
Timber Promotion Council  
Timber Queensland

---

### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at [www.standards.com.au](http://www.standards.com.au) and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at [mail@standards.org.au](mailto:mail@standards.org.au), or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

---

*This Standard was issued in draft form for comment as DR 02024.*

Australian Standard™

**Installation of nailplated timber roof  
trusses**

Originated as AS 4440—1997.  
Second edition 2004.

**COPYRIGHT**

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd  
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 6041 4

## PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee TM/2, Timber Framing, to supersede AS 4440—1997, *Installation of nailplated timber trusses*.

The Standard is the result of a consensus among Australian and New Zealand representatives on the Joint Committee to produce it as an Australian Standard.

The objective of this Standard is to provide basic performance requirements and specifications for the bracing, connection and installation of nailplated timber trusses.

The objective of this revision is to incorporate latest technical information and performance criteria, which resulted from the continued development of timber framing systems in Australia and overseas. Reflected in this Standard, the following have been included in this revision:

- (a) Provision for limit state design methods.
- (b) Requirement for fixing to non-loadbearing external walls (Clause 2.2.3(a)).
- (c) Amendment to the definitions of bow (Clause 3.4.2) and plumb (Clause 3.4.3).
- (d) Provision for intermediate ceiling joists (Clause 3.6 and Appendix D).
- (e) Provision for internal top chord ties for north-light trusses (Clause 4.2.2.2) and top-hat trusses (Clause 4.2.2.3).
- (f) Deletion of the informative Appendix for the non-variant bottom chord ties (the original Appendix G).

This Standard is intended to promote an agreement across different industries, and to replace the various installation manuals and inconsistent bracing details currently in use. It provides a unique method of bracing, connection and installation yet does not preclude the use of other methods that are approved and authorized.

Statements expressed in mandatory forms in notes to tables and figures are deemed to be requirements of this Standard.

The term 'informative' has been used in this Standard to define the application of the appendix to which it applies. An 'informative' appendix is only for information and guidance.

## CONTENTS

	<i>Page</i>
<b>SECTION 1 SCOPE AND GENERAL</b>	
1.1 SCOPE .....	5
1.2 APPLICATION .....	5
1.3 REFERENCED DOCUMENTS .....	6
1.4 USE OF ALTERNATIVE MATERIALS OR METHODS .....	6
1.5 DEFINITIONS .....	6
1.6 LOADS.....	11
1.7 DOCUMENTATION AT APPROVAL STAGE AND DELIVERY .....	11
1.8 NAILS .....	11
<b>SECTION 2 SUPPORTING STRUCTURES</b>	
2.1 GENERAL .....	12
2.2 WALLS .....	12
<b>SECTION 3 TRUSS INSTALLATION</b>	
3.1 TRUSS LAYOUT.....	15
3.2 STABILITY DURING INSTALLATION .....	15
3.3 TEMPORARY BRACING .....	15
3.4 INSTALLATION TOLERANCES .....	16
3.5 PLASTERBOARD FIXED DIRECTLY TO BOTTOM CHORDS .....	17
3.6 INTERMEDIATE CEILING JOISTS .....	17
3.7 TIE-DOWN REQUIREMENTS .....	17
3.8 MULTIPLE (MULTI-PLY) TRUSS.....	17
3.9 TRUSS MODIFICATION .....	17
3.10 REJECTION CRITERIA.....	18
3.11 TRANSPORT, STORAGE, LIFTING AND HANDLING .....	18
<b>SECTION 4 ROOF BRACING</b>	
4.1 GENERAL .....	19
4.2 ROOF BATTENS.....	19
4.3 TOP CHORD BRACING .....	22
4.4 BOTTOM CHORD BRACING .....	37
4.5 WEB BRACING .....	38
<b>SECTION 5 TRUSS CONNECTION</b>	
5.1 GENERAL .....	39
5.2 HIG ENDS .....	39
5.3 GIRDER TRUSSES .....	45
5.4 VALLEY (SADDLE) TRUSSES.....	47
<b>SECTION 6 TRUSS OVERHANGS</b>	
6.1 STANDARD TRUSS-OVERHANGS .....	49
6.2 GABLE VERGE.....	50
6.3 BOXED GABLE ENDS .....	53
6.4 VERANDAHS.....	53
6.5 PERGOLAS .....	53

## APPENDICES

A	DOCUMENTATION AT APPROVAL STAGE AND ON DELIVERY .....	54
B	RECOMMENDED PRACTICE FOR TRUSS INSTALLATION.....	56
C	RECOMMENDATIONS FOR TEMPORARY BRACING .....	57
D	INTERMEDIATE CEILING JOISTS AND HANGERS .....	60
E	TRANSPORT, STORAGE, LIFTING AND HANDLING OF TRUSSES.....	61
F	TYPICAL SPECIFICATION FOR, AND EXAMPLE OF, A STEELBRACE .....	63
G	FIXING DETAILS FOR TYPICAL GIRDER BRACKETS (TRUSS BOOTS) .....	64

Currently in preview, click buy full vers.

## STANDARDS AUSTRALIA

**Australian Standard**  
**Installation of nailplated timber roof trusses**

## SECTION 1 SCOPE AND GENERAL

**1.1 SCOPE**

This Standard specifies requirements for the bracing, connection and installation of nailplated timber trusses in roof structures for typical application.

**1.2 APPLICATION**

This Standard is intended to apply to nailplated timber roof trusses within the following general limitations:

- (a) Residential structures (BCA Classes 1, 2, 3 and 10) and light commercial structures.
- (b) Maximum roof pitch of 45° (100:100).  
NOTE: For roof pitch greater than 35°, supporting structure may need special consideration.
- (c) Shape in plan view to be rectangular or near rectangular, or a series or combination of rectangular shapes or near-rectangular shapes, including splayed-end and boomerang-shaped buildings and the like, and projections such as bay windows.
- (d) Maximum truss span of 16 m.
- (e) Maximum truss spacing of—
  - (i) 900 mm; or
  - (ii) 1200 mm, for lightweight roofs (e.g., metal sheet roofs) in wind classification N3 or lower.
- (f) Maximum design gust wind speed of 74 m/s (wind classification C3) for ultimate limit state method in accordance with either AS/NZS 1170.2 or AS 4055.

This Standard may also be applicable to the design and construction of other classes of buildings where the design criteria, loadings and other parameters applicable to those classes of building are within the limitations of this Standard.

## NOTES:

- 1 Additional limitations are also included in the relevant Clauses of this Standard.
- 2 Subject to approval, this Standard may be used for other structures similar to those specified herein.
- 3 AS 1720.1 provides for the design of timber elements within nailplated timber trusses, which is not covered by this Standard.
- 4 Roof bracing and truss connection specified in this Standard does not cover nailplated timber truss subjected to snow load.
- 5 Specifications in this Standard are applicable for use in conjunction with non-trussed hip-end components.