

Australian Standard®

Small craft—Steering systems

Part 3: Remote systems for single outboard motors of 15 kW to 40 kW power

[ISO title: Small craft—Remote steering systems for single outboard
motors of 15 kW to 40 kW power]

This Australian Standard was prepared by Committee CS/1, Small Pleasure Boats. It was approved on behalf of the Council of Standards Australia on 31 December 1996 and published on 5 March 1997.

The following interests are represented on Committee CS/1:

Aluminium Development Council
Australasian Corrosion Association
Australian Boating Industry Association
Australian Customs Service
Australian Maritime Safety Authority
Australian Yachting Federation
Boat Owners Association of N.S.W.
Department of Defence
Institute of Marine Engineers
Police Department, N.S.W.
Queensland Department of Transport
University of New South Wales
Waterways Authority

Review of Australian Standards. To keep abreast of progress in industry, Australian Standards are subject to periodic review and are kept up to date by the issue of amendments or new editions as necessary. It is important therefore that Standards users ensure that they are in possession of the latest edition, and any amendments thereto.

Full details of all Australian Standards and related publications will be found in the Standards Australia Catalogue of Publications; this information is supplemented each month by the magazine 'The Australian Standard', which subscribing members receive, and which gives details of new publications, new editions and amendments, and of withdrawn Standards.

Suggestions for improvements to Australian Standards, addressed to the head office of Standards Australia, are welcomed. Notification of any inaccuracy or ambiguity found in an Australian Standard should be made without delay in order that the matter may be investigated and appropriate action taken.

Australian Standard[®]

Small craft—Steering systems

**Part 3: Remote systems for single
outboard motors of 15 kW to 40 kW
power**

Originated as part of AS 1799—1975.
Previous edition part of AS 1799.3—1985.
Revised and redesignated in part as AS 4451.3—1997.

PREFACE

This Standard was prepared by the Standards Australia Committee CS/1, Small Pleasure Boats, to supersede (in part) AS 1799.3—1985, *Small Pleasure Boats Code*, Part 3: *Engineering*.

The objective of this Standard is to provide the minimum requirements for remote steering systems in small craft with single outboard motors of 15 kW to 40 kW power.

This Standard is identical with and has been reproduced from ISO 9775:1990, *Small craft—Remote steering systems for single outboard motors of 15 kW to 40 kW power*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number appears on the cover and title page while the International Standard number appears only on the cover.
- (b) In the source text 'this International Standard' should read 'this Australian Standard'.
- (c) A full point substitutes for a comma when referring to a decimal marker.

© Copyright — STANDARDS AUSTRALIA

Users of Standards are reminded that copyright subsists in all Standards Australia publications and software. Except where the Copyright Act allows and except where provided for below no publications or software produced by Standards Australia may be reproduced, stored in a retrieval system in any form or transmitted by any means without prior permission in writing from Standards Australia. Permission may be conditional on an appropriate royalty payment. Requests for permission and information on commercial software royalties should be directed to the head office of Standards Australia.

Standards Australia will permit up to 10 percent of the technical content pages of a Standard to be copied for use exclusively in-house by purchasers of the Standard without payment of a royalty or advice to Standards Australia.

Standards Australia will also permit the inclusion of its copyright material in computer software programs for no royalty payment provided such programs are used exclusively in-house by the creators of the programs.

Care should be taken to ensure that material used is from the current edition of the Standard and that it is updated whenever the Standard is amended or revised. The number and date of the Standard should therefore be clearly identified.

The use of material in print form or in computer software programs to be used commercially, with or without payment, or in commercial contracts is subject to the payment of a royalty. This policy may be varied by Standards Australia at any time.

CONTENTS

1	Scope	1
2	Definitions	1
3	General requirements	1
4	Outboard motor requirements	3
5	Steering system requirements	4
6	Installation	5
7	Test requirements	7

Currently in preview, click buy full version

Currently in preview, click buy full version

AUSTRALIAN STANDARD

Small craft—Steering Systems

Part 3:

Remote systems for single outboard motors of 15 kW to 40 kW power

1 Scope

This International Standard specifies requirements and test methods for remote push-pull cable steering systems and their major component items, used for small craft with a single outboard motor of 15 kW to 40 kW power.

2 Definitions

For the purposes of this International Standard, the following definitions apply.

2.1 steering system: Assembly including all components necessary to transmit remote manual effort to the outboard motor.

2.2 boat-mounted steering system: System in which an output ram guide tube is secured to the boat.

2.3 motor-mounted steering system: System in which an output ram guide tube is secured to the engine.

2.4 drag link: Device in a motor-mounted steering system by which the linear force of the output ram is transmitted to the motor steering arm.

2.5 helm: Mechanism, exclusive of steering wheel or other means for manual application of controlling force, by which controlling force is fed into a steering system cable or other force-transmission means.

2.6 minimum retained system performance: System capability after tests, such that at least 90 % of the steering arc normally available each side of the mid-position may be obtained by exertion of no more than 27 N·m of torque at the helm, through the wheel or other manual control.

This criterion does not define steering system performance while a boat is underway but is intended to provide quantitative limits for design and test purposes.

3 General requirements

3.1 When steering systems are factory-installed in the boat, the complete system shall be supplied. In outboard motor-boats, the system shall be supplied complete to the interface point at the ram output end as shown in figure 1.