

Australian Standard™

Quick-connect devices for gas

This Australian Standard was prepared by Committee AG-011, Gas Components and Industrial Equipment. It was approved on behalf of the Council of Standards Australia on 14 April 2005. This Standard was published on 31 May 2005.

The following are represented on Committee AG-011:

AGA Certification Services
Appliance and Component Testing
Energy Networks Association
Engineers Australia
Gas Appliance Manufacturers Association of Australia
Gas Appliances and Services Association
Gas Technical Regulators Committee
LPG Australia
Major Industrial Gas Installations

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Quick-connect devices for gas

Original standard AS 12—1975.
Previous edition 1998.
Republished and designated AS 4627—2005.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia, GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 6692 7

PREFACE

This Standard was reviewed by the Standards Australia Committee, AG-011, Gas Components and Industrial Equipment, to supersede AG 212—1998, *Approval requirements for quick-connect devices*. The Standard is republished without technical alterations.

The objective of this Standard is to provide manufacturers, designers, regulatory authorities, testing laboratories and similar organizations with uniform minimum requirements for the safety, performance and use of quick-connect devices.

This Standard should not be regarded as a design specification or as an instruction manual.

In its preparation, consideration has been given to—

- (a) continuity of satisfactory operation;
- (b) the prevention of fire hazards, and explosions;
- (c) the prevention of injury to persons or property;
- (d) gas rules and regulations now in force; and
- (e) relevant International Standards.

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

Statements expressed in mandatory terms in notes to tables and figures are deemed to be requirements of this Standard.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND DEFINITIONS	
1.1 SCOPE	4
1.2 CLASSIFICATION	4
1.3 DEFINITIONS	4
SECTION 2 DESIGN AND CONSTRUCTION	
2.1 MATERIALS	6
2.2 CONSTRUCTION	6
2.3 DESIGN	7
2.4 MARKINGS	9
SECTION 3 PERFORMANCE REQUIREMENTS	
3.1 GENERAL	10
3.2 GAS LEAKAGE	10
3.3 PRESSURE LOSS	10
3.4 MECHANICAL STRENGTH	10
3.5 DURABILITY	11
APPENDICES	
A FIGURES A1 TO A5	12
B METHODS OF TEST	18
C LIST OF REFERENCED DOCUMENTS	34

STANDARDS AUSTRALIA

Australian Standard

Quick-connect devices for gas

SECTION 1 SCOPE AND DEFINITIONS

1.1 SCOPE

These requirements apply to quick-connect devices up to 50 mm size for use on natural gas (NG), simulated natural gas (SNG), town gas (TG), tempered liquefied petroleum gas (TLP), and liquefied petroleum gas (LPG vapour).

Compliance of a quick-connect device with these requirements does not imply that it is acceptable for use without supplemental tests in its intended application.

1.2 CLASSIFICATION

The quick-connect device shall be classified according to type.

1.2.1 Type

Three types of quick-connect device shall be:

- (a) Type 1—A quick-connect device permitting gas flow only when the mating parts are connected, for use with all gases at inlet pressures up to 7 kPa, consisting of a plug and socket which may be approved and used separately. The Type 1 plug shall conform to the dimensions shown in Figure A1. The Type 1 socket shall be compatible with the plug shown in Figure A1.
- (b) Type 2—A quick-connect device with safety shut off permitting gas flow only when the mating parts are connected.
- (c) Type 3—A quick-connect device without shut off.

1.3 DEFINITIONS

For the purposes of this Standard, the following definitions apply:

1.3.1 Authority

Means the authority having jurisdiction or such authority as delegated. (Technical Regulator).

1.3.2 Certified

Assessed by a Certifying body, and having a certificate number to demonstrate compliance with a Standard.

1.3.3 Certifying body

A body acceptable to the Technical Regulator that provides assurance of compliance of appliances and components with nominated standards or other accepted safety criteria.

1.3.4 Bayonet fitting

A bayonet-style plug and mating socket designed for attachment so that the gas is turned on only when the plug is inserted and secured in a lock-fit recess.

1.3.5 Connector ends

The end fittings permanently attached to the hose that may be of a screw type or quick-connect type.