

Australian Standard™

**Water supply—Metal-bodied and
plastic-bodied ball valves for property
service connection**



Standards Australia

This Australian Standard was prepared by Committee WS-022, Valves for Water Supply Purposes. It was approved on behalf of the Council of Standards Australia on 3 April, 2001 and published on 5 May 2001.

The following interests are represented on Committee WS-022:

Auspoly
Australian Chamber of Commerce and Industry
Australian Industry Group
Australian Valve Manufacturers Association
Master Plumbers, Australia
New Zealand Metal Casting Industry Association
New Zealand Water and Wastes Association
Society of Mechanical Engineers of Australia
Water Services Association of Australia

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.com.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

Australian Standard™

Water supply—Metal-bodied and plastic-bodied ball valves for property service connection

First published as AS 4796—2001.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 3869 9

PREFACE

This Standard was prepared by the Joint Standards Australia/Standards New Zealand Committee WS-022, Valves for Water Supply Purposes, in response to a request from the Water Services Association of Australia (WSAA) to provide a suitable product Standard for ball valves for property service connection for above- and below-ground situations.

The objective of this Standard is to provide suitable materials and performance tests for metal and plastic bodied ball valves used on property service connections, together with compliance requirements for the use of manufacturers and certification bodies.

Statements expressed in mandatory terms in notes to tables and figures are deemed to be requirements of this Standard.

Support and contribution is acknowledged from the Water Services Association of Australia (WSAA).

The terms 'normative' and 'informative' have been used in this Standard to define the application of the appendix to which they apply. A 'normative' appendix is an integral part of a Standard, whereas an 'informative' appendix is only for information and guidance.

CONTENTS

	<i>Page</i>
SECTION 1 SCOPE AND GENERAL	
1.1 SCOPE.....	4
1.2 REFERENCED DOCUMENTS.....	4
1.3 DEFINITIONS.....	4
1.4 MARKING.....	5
1.5 SUPPLY.....	5
1.6 PURCHASING GUIDELINES.....	5
SECTION 2 MATERIALS	
2.1 SCOPE OF SECTION.....	8
2.2 DEZINCIFICATION-RESISTANT COPPER ALLOY.....	8
2.3 STAINLESS STEEL.....	8
2.4 PLASTIC MATERIALS.....	8
2.5 CONTAMINATION OF WATER.....	8
SECTION 3 DESIGN AND MANUFACTURE	
3.1 SCOPE OF SECTION.....	9
3.2 END CONNECTORS.....	9
3.3 WATER SHUT-OFF DEVICE.....	9
3.4 LEVER HANDLE.....	9
3.5 ACCESSORIES OR COMPONENTS.....	9
3.6 THICKNESS OF METAL PARTS.....	9
SECTION 4 PERFORMANCE REQUIREMENTS	
4.1 GENERAL.....	10
4.2 BODY RESISTANCE TO BENDING MOMENT (PLASTIC-BODIED VALVES).....	10
4.3 FLOW CAPABILITY.....	10
4.4 WATERTIGHTNESS.....	10
4.5 STRENGTH OF METAL BODIED BALL VALVES.....	11
4.6 STRENGTH OF PLASTIC BODIED BALL VALVES.....	11
4.7 TORQUE TEST FOR CONNECTOR NUTS AND BODY ASSEMBLIES.....	11
4.8 TORQUE TEST FOR VALVE OPERATION.....	11
4.9 PROTECTION COVER.....	11
APPENDICES	
A MEANS FOR DEMONSTRATING COMPLIANCE WITH THIS STANDARD.....	12
B LIST OF REFERENCED DOCUMENTS.....	14
C PURCHASING GUIDELINES.....	15
D PLASTIC MATERIALS USED IN BALL VALVES.....	16
E BODY RESISTANCE TO BENDING MOMENT (PLASTIC-BODIED VALVES).....	18
F DETERMINATION OF WATERTIGHTNESS.....	20
G STRENGTH TEST FOR METAL-BODIED BALL VALVES.....	23
H TORQUE TEST FOR CONNECTOR NUTS AND VALVE BODY ASSEMBLIES.....	26
I TORQUE TEST FOR VALVE OPERATION.....	28

STANDARDS AUSTRALIA

Australian Standard

Water supply—Metal-bodied and plastic-bodied ball valves for property service connection

SECTION 1 SCOPE AND GENERAL

1.1 SCOPE

This Standard specifies requirements for metal-bodied and plastic-bodied ball valves for installation between the reticulation water main and the property water meter in nominal sizes DN 15, DN 20, DN 25, DN 32, DN 40 and DN 50, with the valve operating at continuous working pressures not exceeding 1.6 Mpa, and continuous operating temperatures not exceeding 60°C.

This Standard describes the service connection ball valve, service connection termination ball valve and its protection cover and the right angle meter assembly ball valve. It also covers the minimum requirements for health and safety and the protection of the environment.

Means for demonstrating compliance with this Standard are given in Appendix A.

1.2 REFERENCED DOCUMENTS

A list of the documents referred to in this Standard is given in Appendix B.

1.3 DEFINITIONS

For the purpose of this Standard, the definitions given in AS/NZS 3500.0 and those below apply.

1.3.1 Ball valve

A shut-off device, having a ball, which can be turned to move its port or ports relative to the body seat-ports to control the flow of liquid.

1.3.2 Component

A part or a subassembly of parts that contributes to the construction of a total assembly by choice or design, and which may offer variations of fitment for the application to the major element of the product, whether produced by the same manufacturer or not.

NOTE: The component is deemed to be a vital part of the total assembly and should not inhibit the product from complying with this Specification and any relevant Australian Standard, when submitted for type testing.

1.3.3 Distortion

That which is obvious to the eye without resorting to dimensional checking or physically inhibits the operation of the valve.

1.3.4 Service connection ball valve (See Figure 1.1.)

A below ground valve for insertion into the water reticulation pipeline tapping fixture to deliver water to the property service pipe and which is shut only for maintenance, failure or disconnection of the downstream installation.