

Australian Standard™

Closed circuit television (CCTV)

Part 3: PAL signal timings and levels

STANDARDS
Australia



This Australian Standard was prepared by Committee EL-051, Non-Broadcast Television. It was approved on behalf of the Council of Standards Australia on 22 May 2006.
This Standard was published on 21 June 2006.

The following are represented on Committee EL-051:

Australian Communications and Media Authority
Australian Federal Police
Australasian Railway Association
Engineers Australia
Australian Security Industry Association
National Security Association of Australia
Society of Motion Picture and Television Engineers

Keeping Standards up to date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia, GPO Box 476, Sydney, NSW 2001.

This Standard was issued in draft form for comment as DR 05407.

Australian Standard™

Closed circuit television (CCTV)

Part 3: PAL signal timings and levels

First published as AS 4806.3—2006.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 7524 1

PREFACE

This Standard was prepared by the Standards Australia Committee EL-031, Intruder Alarm Equipment and Installations. This is a new Joint Australian/New Zealand Standard.

The objective of this Standard is to provide requirements for phase alternating line (PAL) closed circuit television (CCTV) signal timings and levels.

The CCTV PAL signal timings and levels given in this Standard are based on the Australian Communications and Media Authority Technical Planning Guidelines.

Currently in preview, click buy full version

CONTENTS

	<i>Page</i>
1 SCOPE.....	4
2 REFERENCED DOCUMENTS.....	4
3 PAL VIDEO CHARACTERISTICS	4

Currently in preview, click buy full version

STANDARDS AUSTRALIA

Australian Standard Closed circuit television (CCTV)

Part 3: PAL signal timings and levels

1 SCOPE

This Standard provides requirements for PAL signals used in closed circuit television (CCTV) equipment and systems with an analogue input or an analogue output or both.

2 REFERENCED DOCUMENTS

The following documents are referred to in this Standard:

ACMA Australian Communication and Media Authority
Technical Planning Guidelines for the Planning of Individual Services that use the
Broadcasting Services Bands

ITU-R International Telecommunications Union—Radio communication
BT.470 Conventional analogue television systems

3 PAL VIDEO CHARACTERISTICS

3.1 General

Equipment used in closed circuit television (CCTV) systems with an analogue input and/or an analogue output should comply with the CCTV PAL signal timings and levels specified in this Standard.

3.2 Scanning

3.2.1 General

Clause 3.2 specifies the timing intervals of the video signal and Figure 1 illustrates this relationship.

3.2.2 Aspect ratio

The aspect ratio of the television picture shall be four units horizontally to three units vertically (4:3).

3.2.3 Scanning sequence

During active scanning intervals, the scene shall be scanned from left to right horizontally, and from top to bottom vertically, at uniform velocities (as seen when sitting in front of a CCTV monitor).

3.2.4 Number of lines and interlacing

The number of scanning lines per picture shall be 625, interlaced two to one (2:1).

3.2.5 TV frame and TV field frequencies

The nominal television frame (TV frame) and television field (TV field) frequencies shall be 25 Hz and 50 Hz respectively, and equal to the appropriate submultiples (625 and 312.5 respectively) of the line frequency. Two subsequent TV fields make up one TV frame.