



**Fork-lift trucks—Hook-on type fork arms
and fork arm carriages—Mounting
dimensions**

STANDARDS
Australia

Currently in preview, click buy full version

This Australian Standard® was prepared by Committee ME-026, Industrial Trucks. It was approved on behalf of the Council of Standards Australia on 10 June 2015. This Standard was published on 30 June 2015.

The following are represented on Committee ME-026:

- Australian Industrial Truck Association
 - Australian Industry Group
 - Construction and Mining Equipment Industry Group
 - Hire and Rental Industry Association of Australia
 - Safety Institute of Australia
 - WorkCover New South Wales
 - WorkSafe Victoria
-

This Standard was issued in draft form for comment as DIS S 5143:2015.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

**Fork-lift trucks—Hook-on type fork arms
and fork arm carriages—Mounting
dimensions**

Originally as part of AS B270—1968.

Revised and redesignated AS 2359.1—1980.

Revised and redesignated in part as AS 2359.11—1995.

Revised and redesignated in part as AS 5143:2015.

COPYRIGHT

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 978 1 76035 111 3

PREFACE

This Standard was prepared by the Standards Australia Committee ME-026, Industrial Trucks, to supersede AS 2359.11, *Powered industrial trucks; Part 11: Fork-lift trucks—Hook-on type fork arms and fork carriers—Mounting dimensions*.

The objective of this Standard is to provide designers and manufacturers of powered industrial trucks with dimensions for fork arms and carriages to permit interchangeability of fork arms and attachments.

This Standard is identical with, and has been reproduced from, ISO 2328:2011, *Fork-lift trucks—Hook-on type fork arms and fork arm carriages—Mounting dimensions*.

The fourth edition (ISO 2328:2011) cancels and replaces the third edition (ISO 2328:2007), which has been technically revised.

As this Standard is reproduced from an International Standard, the following apply:

- (a) In the source text ‘this International Standard’ should read ‘Australian Standard’.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO will not be held responsible for identifying any or all such patent rights.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standards, as follows:

<i>Reference to International Standard</i>	<i>Australian Standard</i>
ISO	AS
2331 Fork lift trucks—Hook-on type fork arms—Vocabulary	2359 Powered industrial trucks 2359.10 Part 10: Fork-lift trucks—Hook-on type fork arms—Vocabulary
3691 Industrial trucks—Safety requirements and verification	
3691-1 Part 1: Self-propelled industrial trucks, other than driverless, variable-reach trucks and burden-carrier trucks	2359.6 Part 6: Self-propelled industrial trucks, other than driverless trucks, variable-reach trucks and burden-carrier trucks (ISO 3691-1:2011, MOD)

AUSTRALIAN STANDARD

**Fork-lift trucks—Hook-on type fork arms and fork arm carriages—
Mounting dimensions****1 Scope**

This International Standard specifies the dimensions of, and additional requirements for, fork carriers and hook-on type fork arms, to permit the interchangeability of these fork arms and/or other attachments, relative to the truck-rated capacity and fork arm type, on fork-lift trucks up to and including a rated capacity of 10 999 kg.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 2331, *Fork lift trucks — Hook-on type fork arms — Vocabulary*

ISO 3691-1, *Industrial trucks — Safety requirements and verification — Part 1: Self-propelled industrial trucks, other than driverless trucks, variable-reach trucks and burden-carrier trucks*

3 Terms and definitions

For the purposes of this document, the terms and definitions given in ISO 2331 and ISO 3691-1 apply.

4 Requirements**4.1 Dimensions**

The mounting dimensions of the fork arm and fork carrier for type A (short drop) and type B (long drop) fork arms (the position of the lower hook determining the type of fork arm) shall be in accordance with Figures 1, 2 and 3 and Tables 1 and 2. The fork arm removal/mounting slot on the lower fork carrier is optional and shall be in accordance with 4.3. Fork arm location slots to the dimensions specified in Table 2 shall be provided at a suitable spacing on the fork carrier. In order to locate attachments, one slot shall be situated on the top edge of the fork carrier centreline. However, when an offset lower slot is provided to avoid unintentional disengagement, then the lower slot shall be offset from the fork carrier centreline by dimension w (see Figure 1); this slot shall be 3 mm deeper than k_2 (see Figure 3), to facilitate the attachment and fork arm mounting.

4.2 Stops

Stops shall be provided in order to prevent lateral disengagement of the fork arms from the extremities of the fork carrier. These stops are not permanent, i.e. welded, then the instruction handbook shall contain warnings that the truck is not to be used if the stops are not correctly in place.

4.3 Slot on the lower carriage

If a fork arm removal/mounting slot is provided in the lower edge of the fork carrier, it shall be positioned as shown in Figure 3, that shown in the detailed view X–X being optional. If the positioning of the slots in the upper and lower fork carrier could enable the fork arm or attachment to become inadvertently disengaged from the carrier, then other means (e.g. mechanical) shall be provided to prevent this from occurring.

Where the exclusive means of preventing unintentional fork arm disengagement is by an offset lower slot, then the instruction handbook shall contain the following warning notice: