



**Classification of subsurface
utility information**

Part 2: Subsurface utility engineering

STANDARDS
Australia



Currently in preview, click buy full version

AS 5488.2:2019

This Australian Standard® was prepared by IT-036, Subsurface Utility Engineering Information. It was approved on behalf of the Council of Standards Australia on 4 April 2019.

This Standard was published on 6 May 2019.

The following are represented on Committee IT-036:

Australian Industry Group
Australian Institute of Mine Surveyors
AUSTROADS
Dial Before You Dig
Energy Networks Australia
Engineers Australia
Geospatial Information & Technology Association
National Utility Locating Contractors Association
NBN Co
Roads Australia
SafeWork NSW
Surveying & Spatial Sciences Institute
Water Services Association of Australia

This Standard was issued in draft form for comment as DR AS 5488.2:2018.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76072 440 5



Classification of subsurface utility information

Part 2: Subsurface utility engineering

First published as AS 5488—2013.
Revised and redesignated in part as AS 5488.2:2019.

COPYRIGHT

© Standards Australia Limited 2019

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee IT-036, *Subsurface Utility Engineering Information*.

The objective of this Standard is to provide a framework for the consistent engineering management of subsurface utilities. It has been written as an informative Standard, designed to aid in the proper understanding and use of information surrounding such utilities. Engineers may have received or compiled by various means, a mixture of evidence of the existence, type, condition and location of utilities. Such evidence may vary widely as to its credibility, primarily by virtue of disclaimers from the providers of the information. Application of this Standard and the establishment of a credible approach to the management of subsurface utilities will improve the critical items of time, cost, quality and safety, and reduce risk across projects involving subsurface utilities.

This Part 2 of AS 5488 should be read in conjunction with Part 1. Part 1 focuses on the classification of Subsurface Utility Information (SUI), while Part 2 focuses on Subsurface Utility Engineering (SUE).

The terms “normative” and “informative” are used in Standards to define the application of the appendices to which they apply. A “normative” appendix is an integral part of a Standard, whereas an “informative” appendix is only for information and guidance.

Contents

Preface	ii
Foreword	v
1 Scope and general	1
1.1 Scope	1
1.2 Application	1
1.3 Normative references	1
1.4 Terms and definitions	1
2 Subsurface utility model creation and data naming conventions	4
2.1 Justification of a utility	4
2.2 String naming conventions	6
2.3 Specific attribute data	7
2.4 Appropriate level of model creation	7
2.4.1 General	7
2.4.2 Model Level 1	8
2.4.3 Model Level 2	8
2.4.4 Model Level 3	9
2.4.5 Model Level 4	10
2.4.6 Model Level 5	11
2.4.7 Model Level 6	11
3 Utility project roles and utility clash detection approach	12
3.1 General project roles	12
3.2 Design or utility engineer	12
3.3 Project owner	13
3.4 Utility authority	14
3.5 Memorandum of Understanding (MOU)	15
3.5.1 General	15
3.5.2 MOU purpose and scope	15
3.5.3 Principles of cooperation	15
4 Utility clash detection	16
4.1 General	16
4.2 Options of clash detection	17
4.2.1 General	17
4.2.2 Option 1 — Design change to eliminate potential utility clash or conflict	17
4.2.3 Option 2 — Approval of reduced cover or clearance	18
4.2.4 Option 3 — Protective treatments to eliminate utility conflict	18
4.2.5 Option 4 — Utility relocations	18
5 Utility design	18
5.1 Minimum utility design deliverable	18
5.1.1 General	18
5.1.2 Utility design and co-ordination throughout a project lifecycle	19
5.2 Conflict management process	19
5.3 Inspection and testing	19
Appendix A (informative) Subsurface utility information model schema	20
Appendix B (informative) Risk assessment matrix	37
Appendix C (informative) AS 5488 process flowchart	38
Appendix D (informative) Utility conflict matrix	39
Appendix E (informative) Public Utility Plant (PUP) conflict register	41
Appendix F (informative) AS 5488 legend	42
Appendix G (informative) Utility coordination spreadsheet	43

Appendix H (informative) Utility detection means	47
Appendix I (informative) Procedure for asset handover	52
Bibliography	53

Currently in preview, click buy full version

Foreword

Due to the age, complexity of the environments in which they operate, and changes in technology and requirements, the information available to (and from) utility owners and operators is often limited. Additional sources of data, including physical checks, can augment the information available from the utility owner, enabling better decision making when working with subsurface utilities.

Any available Dial Before You Dig (DBYD) data should be requested as a first step of interacting with utility authorities.

For reliable information during design and construction, the engineer, owner, and constructor should be certain —

- (a) that utilities, whether active, abandoned, or unknown, are identified;
- (b) that the utilities are recorded correctly;
- (c) that the numbers of actual utility pipes or cables under the ground are known or represented by correctly understood multiple numbers;
- (d) that the width of utilities is correct; and
- (e) that the depths of utilities are known and utility access needs are understood.

Traditionally, projects where subsurface utilities require amendment encounter issues that are routinely handled through variation orders, insurance payouts, contingency pricing and, especially in the construction sector, after a design has been completed. When problems create significant costs and safety risks, blame is pointed everywhere, including at the design or utility engineer who has documented their designs, regardless of disclaimer. All stakeholders will benefit from improved management of subsurface utilities.

Australian Standard®

Classification of subsurface utility information

Part 2: Subsurface utility engineering

1 Scope and general

1.1 Scope

This Standard provides a framework for the management of information and decision-making tools for projects that may impact subsurface utilities. It has been written primarily from an engineering perspective, and applies to all existing (including redundant) and under-construction subsurface utility infrastructure and associated surface features. This Standard does not apply to utility infrastructure that is above the surface, such as overhead power and telecommunication lines.

As such, any reference within this standard to above ground utilities is in the context of spatial constraints of plant and machinery to the overhead utility while working on subsurface utilities.

NOTE Although this Standard does not apply to above-surface utilities, the same principles of conflict identification might well be applied to these aerial assets, as their replacement may involve sub-surface activities and solutions.

1.2 Application

This Standard is intended for use by all entities or individuals involved in the management of subsurface utilities. This Standard, as a reference or as part of a specification, will assist design or utility engineers, project and utility owners and authorities, and constructors in understanding the management of utility data.

1.3 Normative references

There are no normative references in this document.

1.4 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

1.4.1

absolute spatial position

location of a point on the utility shown by reference to a three dimensional coordinate system from which can be derived horizontal Map Grid of Australia (MGA) coordinates in Easting and Northing, and related to the relevant MGA zone and Geocentric datum, and a vertical position referenced to a datum based on mean sea level (such as the Australian Height Datum)

Note 1 to entry: See also “reduced level”.

1.4.2

as-built record

representation of the utility infrastructure as it exists in the field, showing a relationship to a defined absolute or relative reference system. As-built records can include both hardcopy plans and computer-generated geographic information systems

Note 1 to entry: Also referred to as “work-as-executed” or “as-constructed”.

Note 2 to entry: See also “record”.