

Australian Standard™

Environmental testing

**Part 2.46: Tests—Guidance to test Kd:
Hydrogen sulphide test for contacts and
connections**



**STANDARDS
AUSTRALIA**

This Australian Standard was prepared by Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment. It was approved on behalf of the Council of Standards Australia on 5 July 2004. This Standard was published on 10 August 2004.

The following are represented on Committee EL-026:

Australian Chamber of Commerce and Industry
Australian Electrical and Electronic Manufacturers Association
Electrical Compliance Testing Association
Electrical Regulatory Authorities Council
Energy Supply Association of Australia
Testing Interests (Australia)

Keeping Standards up-to-date

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Web Shop at www.standards.com.au and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Global Standard*, has a full listing of revisions and amendments published each month.

Australian Standards™ and other products and services developed by Standards Australia are published and distributed under contract by SAI Global, which operates the Standards Web Shop.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 1501.

Australian Standard™

Environmental testing

**Part 2.46: Tests—Guidance to test Kd:
Hydrogen sulphide test for contacts and
connections**

First published as AS 60068.2.46—2004.

COPYRIGHT

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 6221 2

PREFACE

This Standard was prepared by the Standards Australia Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment.

The objective of this Standard is to provide the electrotechnology industry with a complete set of environmental test procedures published as a series under AS 60068 *Environmental testing*. This Standard is Part 2.46 of that series.

This Standard is identical with, and has been reproduced from, IEC 60068-2-46:1982, *Environmental testing – Part 2-46: Tests—Guidance to test Kd: Hydrogen sulphide test for contacts and connections*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text ‘this international standard’ should read ‘this Australian Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.
- (d) French text on figures should be ignored.

In this Standard, the following print types are used:

- requirements proper: in arial type;
- *test specifications: in italic type;*
- explanatory matter: in smaller arial type.

Any international Standard referenced should be replaced by an equivalent Australian Standard where one is available. The availability of equivalent Australian Standards can be determined either from the Standards Australia catalogue or from the Standards Australia website (www.standards.com.au).

CONTENTS

	<i>Page</i>
1 Introduction	1
2 Hydrogen sulphide in the atmosphere	1
3 Object and scope of the test.....	2
3.1 Types of contacts and connections	2
3.2 Object of the test	2
4 Parameters of the test.....	3
4.1 Concentration of hydrogen sulphide.....	3
4.2 Relative humidity	3
4.3 Temperature	3
4.4 Flow rate.....	4
4.5 Test duration.....	4
4.6 Illumination	4
4.7 Control of test conditions	4
5 Severity of the test.....	4
6 Evaluation of results	5
7 Notes for the user of the test and for authors of specifications	5
References.....	8

Currently in preview, click buy full version

STANDARDS AUSTRALIA

Australian Standard

Environmental testing

Part 2.46: Tests—Guidance to test Kd: Hydrogen sulphide test for contacts and connections

1 Introduction

Satisfactory performance during the desired lifetime of contacts and connections depends on many parameters, some of them determined by their design (type, materials, forces, etc.) and others by the environment in which they have to function. Concerning the effects of the environment, special attention must be paid to the polluting substances contained – usually in very small amounts – in the atmosphere.

Silver and some of its alloys are peculiarly susceptible to tarnishing by the minute quantities of hydrogen sulphide that occur in many environments. The tarnish product is dark in colour and consists largely of β -silver sulphide.

Separable electrical connections employing these metals as contact materials may therefore suffer from increased contact resistance and contact noise as a result.

2 Hydrogen sulphide in the atmosphere

Hydrogen sulphide is evolved by bacterial reduction of sulphates in vegetation, soil, stagnant water and animal waste. In the atmosphere it is readily oxidized to sulphur dioxide, which is brought to the ground by rain. Where the soil is aerobic, certain bacteria turn the sulphur dioxide to sulphates. When or where rotting organic matter generates anaerobic conditions, sulphate reducing bacteria complete the cycle and turn the sulphate to hydrogen sulphide, which is the principal natural sulphur input in the atmosphere. It is therefore a widespread pollutant in air.

Sulphur dioxide will accumulate in the atmosphere when it is not rinsed by rain. In urban areas burning of fossil fuels emits sulphur dioxide into the atmosphere. The content can be 10 times to 1000 times that of hydrogen sulphide and becomes the dominant cause of corrosion. In equal concentration, hydrogen sulphide is the more corrosive of the two, particularly on silver and copper (See IEC 60068-2-42: Part 2: Tests – Test Kc: Sulphur dioxide test for contacts and connections.)

Although the major input to the sulphur cycle is by hydrogen sulphide through natural processes, industrial processes also play a part. Oil refineries, chemical plants and gas works are accessible sources. Atmospheric concentrations of 1 ppb to 30 ppb (parts in 10^9 by volume) are commonly reported. At many sites peak values exceed this, and much higher concentrations are found close to sources. Table I illustrates a typical statistical distribution of measurements of hydrogen sulphide concentration. Table II lists representative concentrations at a range of sites. These levels are sufficient to account for the natural tarnishing of silver. Other sulphurous pollutants are much less important.

Sulphur dioxide has little effect on silver unless the concentration and humidity are high, and then it produces a tarnish product that is rarely found in practice. The two commonest organic sulphurous pollutants: methyl mercaptan and carbon disulphide do not tarnish silver at all. Some organic sulphur derivatives do tarnish silver, as does elemental sulphur vapour, but these materials probably occur only in a small minority of environments.