

Australian Standard™

**Environmental testing**

**Part 2.57: Tests—Test M: Vibration—  
Time-history method**

This Australian Standard was prepared by Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment. It was approved on behalf of the Council of Standards Australia on 23 April 2003 and published on 19 June 2003.

---

The following are represented on Committee EL-026:

Australian Chamber of Commerce and Industry  
Australian Electrical and Electronic Manufacturer's Association  
Electrical Compliance Testing Association  
Electrical Regulatory Authorities Council  
Electricity Supply Association of Australia  
Testing Interests (Australia)

---

#### **Keeping Standards up-to-date**

Standards are living documents which reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued. Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments which may have been published since the Standard was purchased.

Detailed information about Standards can be found by visiting the Standards Australia web site at [www.standards.com.au](http://www.standards.com.au) and looking up the relevant Standard in the on-line catalogue.

Alternatively, the printed Catalogue provides information current at 1 January each year, and the monthly magazine, *The Australian Standard*, has a full listing of revisions and amendments published each month.

We also welcome suggestions for improvement in our Standards, and especially encourage readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at [mail@standards.com.au](mailto:mail@standards.com.au), or write to the Chief Executive, Standards Australia International Ltd, GPO Box 5420, Sydney, NSW 2001.

---

Australian Standard™

**Environmental testing**

**Part 2.57: Tests—Test No. Vibration—  
Time-history method**

First published as AS 60068.2.57—2003.

**COPYRIGHT**

© Standards Australia International

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia International Ltd  
GPO Box 5420, Sydney, NSW 2001, Australia

ISBN 0 7337 5294 2

## PREFACE

This Standard was prepared by the Standards Australia Committee EL-026, Protective Enclosures and Environmental Testing for Electrical/Electronic Equipment.

The objective of this Standard is to provide the electrotechnology industry with a complete set of environmental test procedures published as a series under AS 60068 *Environmental testing*. This Standard is Part 2.57 of that series.

This Standard is identical with, and has been reproduced from, IEC 60068-2-57:1999, *Environmental testing – Part 2-57: Tests—Test Ff: Vibration—Time-history method*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- (b) In the source text ‘this international standard’ should read ‘this Australian Standard’.
- (c) A full point should be substituted for a comma when referring to a decimal marker.
- (d) Any French text on figures should be ignored.

In this Standard, the following print types are used:

- requirements proper: in arial type;
- *test specifications: in italic type;*
- explanatory matter: in smaller arial type.

Any international Standard referenced should be replaced by an equivalent Australian Standard when one is available. The availability of equivalent Australian Standards can be determined either from the Standards Australia catalogue or from the Standards Australia website ([www.standards.com.au](http://www.standards.com.au)).

The terms ‘normative’ and ‘informative’ are used to define the application of the annex to which they apply. A normative annex is an integral part of a standard, whereas an informative annex is only for information and guidance.

## CONTENTS

	<i>Page</i>
Introduction.....	v
1 Scope and object.....	1
2 Normative references .....	1
3 Definitions .....	1
4 General requirements .....	5
5 Requirements for testing .....	5
5.1 Vibration response investigation.....	5
5.1.1 Basic motion.....	5
5.1.2 Spurious motion .....	5
5.1.3 Signal tolerance .....	6
5.1.4 Vibration amplitude tolerances.....	6
5.1.5 Frequency tolerances .....	7
5.1.6 Sweeping .....	7
5.1.7 Damping ratio .....	7
5.2 Time-history testing.....	7
5.2.1 Basic motion.....	7
5.2.2 Transverse motion.....	8
5.2.3 Rotational motion .....	8
5.2.4 Tolerance zone for the required response spectrum .....	8
5.2.5 Frequency range .....	8
5.2.6 Calculation of the test response spectrum .....	8
5.3 Mounting .....	9
6 Severities .....	9
6.1 Test frequency range .....	10
6.2 Required response spectrum .....	10
6.3 Number and duration of time-histories .....	10
6.3.1 Number of time-histories.....	10
6.3.2 Time-history duration.....	11
6.3.3 Duration of the strong part of the time-history .....	11
6.4 Number of high peaks of the response .....	11
7 Preconditioning .....	11
8 Initial measurements .....	11
9 Testing .....	12
9.1 General.....	12
9.2 Vibration response investigation.....	12
9.3 Time-history testing.....	12
9.3.1 Single axis testing .....	13
9.3.2 Biaxial testing.....	13
9.3.3 Triaxial testing.....	13
10 Intermediate measurements .....	13
11 Recovery.....	13
12 Final measurements .....	13
13 Information to be given in the relevant specification .....	14

Annex A (informative) Synthesis of the artificial time-history: Guidance .....	21
Annex B (informative) Test frequency ranges.....	25
Figure 1 – Flow chart for vibration, time-history .....	15
Figure 2 – Example of a typical response of an oscillator excited by a specific time-history (specified threshold value of 70 %) .....	16
Figure 3 – Example of identification of the peaks of the response higher than a specified (70 %) threshold value.....	16
Figure 4 – Typical envelope response spectrum.....	17
Figure 5 – Typical time-history .....	18
Figure 6 – Typical plot of a required response spectrum .....	18
Figure 7 – Category 1: recommended shape of a required response spectrum in generalized form.....	19
Figure 8 – Category 2: recommended shape of a required response spectrum in generalized form.....	20

Currently in preview, click buy full version

## INTRODUCTION

This part of IEC 60068 details a method for testing components, equipment and other electrotechnical products, hereinafter referred to as "specimens", which in service can be subjected to short-duration random-type dynamic forces of which typical examples are the stresses induced in equipment as a result of earthquakes, explosions and during transport and operation of different kinds of vehicles.

The characteristics of these forces and the damping of the specimen may be such that the vibration response of the specimen will not reach a steady-state condition.

The test consists, after any preliminary vibration response investigation with sinusoidal or random vibration has been performed, of subjecting the specimen to a vibration time-history specified by a response spectrum with characteristics simulating the effects of the dynamic forces.

A time-history may be developed or obtained from:

- a natural event (natural time-history);
  - a random sample, or
  - a synthesized signal
- } artificial time-history

In general, some modification is necessary in order to adapt to the required testing severity.

The use of a time-history allows a single test wave to envelop a broadband response spectrum.

It is possible for all the modes of the specimen in the excitation axis (or axes) to be excited at the same time and consequently the stresses derived from the combined effects of the coupled modes are generally taken into account.

Procedures are described for conducting the test and for the measurement of the vibration at given points. The requirements for the vibration motion and for the choice of severities, that is frequency range, required response spectrum, number of high-peaks of the response and number and duration of time-histories, are also detailed.

Specification writers will find in clause 13 a list of details to be considered for inclusion in specifications, in annex A, on the guidance, and in annex B, on recommended test frequency ranges.

It is emphasized that vibration testing always demands a certain degree of engineering judgement and both supplier and purchaser should be fully aware of this fact. The writer of the relevant specification is expected to select the testing procedure and the values of severity appropriate to the specimen and its use.

Currently in preview, click buy full version

## STANDARDS AUSTRALIA

---

**Australian Standard****Environmental testing****Part 2.57: Tests—Test Ff: Vibration—Time-history method**

---

**1 Scope and object**

This part of IEC 60068 aims to provide a standard procedure for determining, by the time-history method, the ability of a specimen to withstand specified severities of transient vibration.

**2 Normative references**

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of IEC 60068. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of IEC 60068 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of IEC and ISO maintain registers of currently valid International Standards.

IEC 60068-1:1988, *Environmental testing – Part 1: General and guidance*

IEC 60068-2-6:1995, *Environmental testing – Part 2: Tests – Test Fc: Vibration (sinusoidal)*

IEC 60068-2-27:1987, *Environmental testing – Part 2: Tests – Test Ea and guidance: Shock*

IEC 60068-2-47:1982, *Environmental testing – Part 2: Tests – Mounting of components, equipment and other articles for dynamic tests including shock (Ea), bump (Eb), vibration (Fc and Fd) and steady-state acceleration (Ga) and guidance*

IEC 60068-2-64:1993, *Environmental testing – Part 2: Tests – Test Fh: Vibration, broad-band random (digital control) and guidance*

IEC 60068-3-3:1991, *Environmental testing – Part 3: Guidance – Seismic test methods for equipment*

ISO 266:1967, *Acoustics – Preferred frequencies*

ISO 2041:1990, *Vibration and shock – Vocabulary*

**3 Definitions**

For the purpose of this part of IEC 60068, the terms and definitions given in ISO 2041, IEC 60068-1, IEC 60068-2-6, IEC 60068-2-64 and the following apply.