

Australian Standard[®]

**Elastomeric seals—Material
requirements for pipe joint seals used in
water and drainage applications**

Part 2: Thermoplastic elastomers

STANDARDS
Australia



This Australian Standard® was prepared by Committee WS-010, Flexible Jointing Gaskets. It was approved on behalf of the Council of Standards Australia on 10 July 2007. This Standard was published on 5 February 2008.

The following are represented on Committee WS-010:

- Australasian Plastics and Rubber Institute
 - Australian Chamber of Commerce and Industry
 - Australian Industry Group
 - Certification Interests (Australia)
 - Plastics Industry Pipe Association of Australia
 - Rubber Manufacturers Association of Australasia
 - Water Services Association of Australia
-

This Standard was issued in draft form for comment as DR 26712.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

**Elastomeric seals—Material
requirements for pipe joint seals used in
water and drainage applications**

Part 2: Thermoplastic elastomers

First published as AS 1646.4—2005.
AS 1646.4 revised and redesignated as AS 681.2—2008.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia

ISBN 0 7337 8540 9

PREFACE

This Standard was prepared by the Standards Australia Committee WS-010, Flexible Jointing Gaskets to supersede AS 1646.4.

The objective of this Standard is to set out requirements for thermoplastic elastomer and thermoplastic vulcanizate seals used in gravity sewerage, drainage and rainwater harvesting systems and non-pressure non-drinking water supply, including the material requirements for specific applications.

This Standard is identical with, and has been reproduced from EN 681-2—2000, *Elastomeric seals—Material requirements for pipe joint seals used in water and drainage application, Part 2: Thermoplastic elastomers*.

As this Standard is reproduced from an International Standard, the following applies:

- Its number does not appear on each page of text and its identity is shown only on the cover and title page.
- In the source text 'EN 681-2' should read 'AS 681.2'.
- A full point should be substituted for a comma when referring to a decimal number.
- Any French text on figures should be ignored.

References to International Standards should be replaced by references to Australian Standards, as follows:

<i>Reference to International Standard</i>		<i>Australian Standard</i>	
ISO		AS	
37	Rubber, vulcanized or thermoplastic—Determination of tensile stress-strain properties	1683.11	Methods of test for elastomers Tension testing of vulcanized or thermoplastic rubber
48	Rubber, vulcanized or thermoplastic—Determination of hardness (hardness between 10 IRHD and 100 IRHD)	1683.15.1	International rubber hardness
188	Rubber, vulcanized or thermoplastic—Accelerated ageing and heat resistance tests	1683.26	Rubber, vulcanized or thermoplastic—Accelerated ageing and heat resistance tests
471	Rubber—Temperatures, humidities and times for conditioning and testing	1683.20	Standard temperatures, humidities and times for conditioning and testing
1431-1	Rubber, vulcanized or thermoplastic; resistance to ozone cracking; Part 1: static strain test	1683.24	Methods of test for rubber—Determination of the resistance of vulcanized or thermoplastic rubbers to ozone cracking—Static strain test
1683.7	Rubber, vulcanized—Determination of the effect of liquids	1683.23	Rubber—Vulcanized—Determination of resistance to liquids
2859-1	Sampling procedures for inspection by attributes—Part 1: Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection	1199 1199.1	Sampling procedures for inspection by attributes Sampling schemes indexed by acceptance quality limit (AQL) for lot-by-lot inspection

3951	Sampling procedures and charts for inspection by variables for percent nonconforming	2490	Sampling procedures and charts for inspection by variables for percent nonconforming
------	--	------	--

Currently in preview, click buy full vers.

CONTENTS

1	Scope	1
2	Normative references.....	1
3	Definitions	2
4	Classification	2
5	Finished seal requirements	2
6	Test pieces and temperature	7
7	Factory production control.....	7
8	Factory product control tests.....	8
9	Storage.....	11
10	Designation	11
11	Marking and labelling.....	11
	Annex A (informative) Guidance on storage of seals	12
	Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive.....	13

Currently in preview, click buy full version

STANDARDS AUSTRALIA

Australian Standard

Elastomeric seals—Material requirements for pipe joint seals used in water and drainage applications

Part 2: Thermoplastic elastomers

1 Scope

This standard specifies requirements for materials used for moulded seals only of thermoplastic elastomers (TPE) used in joints of:

- 1) thermoplastic piping systems for non pressure waste water discharge (intermittent flow up to 95 °C) inside buildings;
- 2) thermoplastic piping systems for non-pressure underground drainage and sewerage (continuous flow up to 45 °C and intermittent flow up to 95 °C);
- 3) thermoplastic rainwater piping systems.

General requirements for finished joint seals are also given; any additional requirements called for by the particular application are specified in the relevant product standards taking into account that the performance of pipe joints is a function of the seal material properties, seal geometry and pipe joint design.

2 Normative references

This European Standard incorporates, by dated or undated reference, provisions from other publications. These normative references are cited at the appropriate places in the text and the publications are listed hereafter. For dated references, subsequent amendments to or revisions of any of these publications apply to this European Standard only when incorporated in it by amendment or revision. For undated references the latest edition of the publication referred to applies.

- | | |
|-------------|--|
| ISO 37, | <i>Rubber, vulcanized or thermoplastic - Determination of tensile stress-strain properties</i> |
| ISO 48, | <i>Rubber, vulcanized or thermoplastic - Determination of hardness (hardness between 10 and 100 IRHD)</i> |
| ISO 588, | <i>Rubber, vulcanized - Accelerated ageing or heat-resistance tests</i> |
| ISO 471, | <i>Rubber - Temperatures, humidities and times for conditioning and testing</i> |
| ISO 815, | <i>Rubber, vulcanized or thermoplastic - Determination of compression set at ambient, elevated or low temperatures</i> |
| ISO 1431-1, | <i>Rubber, vulcanized or thermoplastic - Resistance to ozone cracking - Part 1: Static strain test</i> |