

AS IEC 62209.3:2020  
IEC 62209-3:2019



STANDARDS  
Australia



# Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices

Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)



AS IEC 62209.3:2020

This Australian Standard® was prepared by TE-007, Human Exposure to Electromagnetic Fields. It was approved on behalf of the Council of Standards Australia on 26 August 2020.

This Standard was published on 11 September 2020.

The following are represented on Committee TE-007:

Australian Centre for Radiofrequency Bioeffects Research  
Australian Communications and Media Authority  
Australian Industry Group  
Australian Mobile Telecommunications Association  
Australian Radiation Protection and Nuclear Safety Agency  
Commercial Radio Australia  
Communications, Electrical and Plumbing Union — Electrical Trades Division  
Department of Defence (Australian Government)  
Engineers Australia  
National Measurement Institute

Additional Interests

Telstra Corporation

This Standard was issued in draft form for comment as DR AS IEC 62209.3: 2020.

#### **Keeping Standards up-to-date**

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

[www.standards.org.au](http://www.standards.org.au)

ISBN 978 1 76072 967 7

# Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices

## Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)

First published as AS IEC 62209.3:2020.



© IEC 2020 — All rights reserved  
© Standards Australia Limited 2020

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of either the IEC or the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth). If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please see the contact details on the back cover or the contact us page of the website for further information.

## Preface

This Standard was prepared by the Australian members of the Joint Standards Australia/Standards New Zealand Committee TE-007, Human Exposure to Electromagnetic Fields.

After consultation with stakeholders in both countries, Standards Australia and Standards New Zealand decided to develop this Standard as an Australian Standard rather than an Australian/New Zealand Standard.

The objective of this document is to specify measurement protocols and test procedures for the reproducible measurement of peak spatial-average specific absorption rate (psSAR) induced inside a simplified model of a human head or body by radio-frequency (RF) transmitting devices, with a specified measurement uncertainty. Requirements are provided for psSAR assessment using vector measurement-based systems. Such systems determine the psSAR by three-dimensional (3D) field reconstruction within the volume of interest in accordance with the requirements here for the measurement system, calibration, uncertainty assessment and validation methods. The protocols and procedures apply for the psSAR assessments covering a significant majority of people including children during use of wireless communication devices operated in close proximity to the head or body.

This document is applicable to wireless communication devices intended to be used at a position near the human head or body at distances up to and including 200 mm. This document may be employed to evaluate SAR compliance of different types of wireless communication devices used next to the ear, in front of the face, mounted on the body, combined with other RF-transmitting or non-transmitting devices or accessories (e.g. belt-clip), or embedded in garments. The document applicable frequency range is from 600 MHz to 6 GHz.

The system validation procedures provided within this document cover frequencies from 600 MHz to 6 GHz.

With a vector measurement-based system this document can be employed to evaluate SAR compliance of different types of wireless communication devices.

The wireless communication device categories covered include but are not limited to mobile telephones, cordless microphones, auxiliary broadcast devices and radio-transmitters in personal computers, desktop and laptop devices, multi-band, multi-antenna, and push-to-talk devices.

This document is identical with, and has been reproduced from, IEC 62209-3:2019, *Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices — Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this part of IEC 62209” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

NOTES

Currently in preview, click buy full version

## CONTENTS

FOREWORD.....	9
INTRODUCTION.....	11
1 Scope.....	12
2 Normative references .....	12
3 Terms and definitions .....	13
4 Symbols and abbreviated terms.....	14
5 Overview of the measurement procedure.....	14
6 Measurement system specifications.....	17
6.1 General requirements .....	17
6.2 Phantom specifications .....	19
6.2.1 Head phantom specifications – shell.....	19
6.2.2 Body phantom specifications – shell .....	19
6.2.3 Tissue-equivalent medium properties.....	19
6.3 Measurement system requirements.....	19
6.3.1 General .....	19
6.3.2 Scanning measurement system specifications .....	19
6.3.3 Array measurement system specifications .....	20
6.4 Device holder specification .....	21
6.5 Reconstruction algorithm and peak spatial-averaging specifications .....	22
7 Protocol for SAR assessments .....	22
7.1 Measurement preparation .....	22
7.1.1 General .....	22
7.1.2 Preparation of tissue-equivalent medium .....	22
7.1.3 System check .....	23
7.1.4 Preparation of the device under test (DUT).....	23
7.1.5 Operating modes .....	23
7.1.6 Position of the DUT in relation to the phantom .....	23
7.1.7 Positions of the DUT in relation to the flat phantom for large DUT .....	23
7.1.8 Test frequency for DUT.....	24
7.2 Tests to be performed.....	24
7.3 General measurement procedure.....	25
7.3.1 General .....	25
7.3.2 Measurement procedure for scanning systems .....	25
7.3.3 Measurement procedure for array systems .....	26
7.4 SAR measurements for simultaneous transmission .....	26
7.4.1 General .....	26
7.4.2 SAR measurements for uncorrelated signals .....	27
7.4.3 SAR measurements for correlated signals .....	31
8 Measurement uncertainty estimation.....	32
8.1 General.....	32
8.2 Requirements on the measurement uncertainty evaluation.....	32
8.3 Description of measurement uncertainty models .....	33
8.3.1 General .....	33
8.3.2 Uncertainty models for array measurement system and scanning measurement systems .....	34
8.3.3 Example uncertainty budget templates .....	35

9	Measurement report .....	39
	Annex A (normative) Phantom specifications .....	40
	A.1 SAM phantom specifications .....	40
	A.1.1 Justification .....	40
	A.1.2 SAM phantom geometry.....	40
	A.1.3 Tissue-equivalent medium .....	40
	A.2 Flat phantom specifications.....	41
	A.3 Specific phantoms.....	42
	A.4 Tissue-equivalent medium .....	43
	Annex B (normative) Calibration and characterization of dosimetric probes.....	44
	B.1 General.....	44
	B.2 Types of calibration.....	44
	B.2.1 Amplitude calibration with analytical fields .....	44
	B.2.2 Amplitude and phase calibration by transfer calibration .....	45
	B.2.3 Amplitude and phase calibration using numerical reference .....	47
	Annex C (informative) Field reconstruction techniques.....	49
	C.1 General.....	49
	C.2 Objective of field reconstruction techniques .....	49
	C.3 Background.....	49
	C.4 Reconstruction techniques .....	51
	C.4.1 Expansion techniques.....	51
	C.4.2 Source reconstruction techniques .....	52
	C.4.3 Source base function decomposition.....	52
	C.4.4 Phase reconstruction .....	52
	C.5 Source reconstruction and SAR estimation from fields measured outside the phantom.....	53
	C.6 Additional considerations for field reconstruction in scanning systems .....	53
	Annex D (normative) SAR measurement system verification and system validation.....	54
	D.1 Objectives and purpose .....	54
	D.1.1 General .....	54
	D.1.2 Objectives and purpose of <i>system check</i> .....	54
	D.1.3 Objectives of <i>system validation</i> .....	54
	D.2 SAR measurement setup and procedure for <i>system check</i> and <i>system validation</i> .....	55
	D.2.1 General .....	55
	D.2.2 Power measurement setups.....	55
	D.2.3 Procedure to measure and normalize SAR.....	57
	D.2.4 Power measurement uncertainty.....	59
	D.3 <i>System check</i> .....	61
	D.3.1 <i>System check</i> antennas and test conditions.....	61
	D.3.2 <i>System check</i> antennas and test conditions for scanning systems .....	61
	D.3.3 <i>System check</i> antennas and test conditions for array systems .....	61
	D.3.4 <i>System check</i> acceptance criteria.....	62
	D.4 <i>System validation</i> .....	62
	D.4.1 Validation of array systems and scanning systems .....	62
	D.4.2 Requirements for <i>system validation</i> antennas and test conditions.....	62
	D.4.3 Requirements for array systems and scanning systems .....	62
	D.4.4 Test positions for <i>system validation</i> .....	64
	D.4.5 <i>System validation</i> procedure based on peak spatial-average SAR .....	71

D.4.6	On-site <i>system validation</i> after installation .....	79
D.4.7	<i>System validation</i> acceptance criteria .....	80
Annex E (informative)	Interlaboratory comparisons .....	82
E.1	Purpose .....	82
E.2	Monitor laboratory .....	82
E.3	Phantom set-up .....	82
E.4	Reference devices .....	82
E.5	Power set-up .....	83
E.6	Interlaboratory comparison – Procedure .....	83
Annex F (normative)	<i>System validation</i> antennas .....	84
F.1	General requirements .....	84
F.2	Return loss requirements .....	84
F.3	Standard dipole antenna .....	85
F.4	VPIFA .....	88
F.5	2-PEAK CPIFA .....	90
F.6	Additional antennas .....	94
Annex G (normative)	SAR calibration of reference antennas .....	95
G.1	Purpose .....	95
G.2	Parameters or quantities and ranges to be determined by calibration method .....	96
G.3	Reference antenna calibration setup .....	96
G.4	Reference antenna calibration procedure .....	97
G.4.1	Verification of return loss .....	97
G.4.2	Calibration of reference antennas: step-by-step procedure .....	97
G.4.3	Uncertainty budget of reference antenna calibration .....	98
G.5	Method and uncertainties for the transfer of calibration between two or more antennas of the same type using the array system .....	102
Annex H (informative)	General considerations on uncertainty estimation .....	105
H.1	Concept of uncertainty estimation .....	105
H.2	Type A and Type B evaluations .....	106
H.3	Degrees of freedom and coverage factor .....	106
H.4	Combined and expanded uncertainties .....	107
H.5	Analytical reference functions .....	108
Annex I (normative)	Evaluation of measurement uncertainty of SAR results from scanning vector measurement-based systems with single probes .....	111
I.1	Measurement uncertainties to be evaluated by the system manufacturer <i>MM</i> .....	111
I.1.1	General .....	111
I.1.2	Calibration <i>CF</i> .....	111
I.1.3	Isotropy <i>ISO</i> .....	111
I.1.4	System linearity <i>LIN</i> .....	112
I.1.5	Sensitivity limit <i>SL</i> .....	112
I.1.6	Boundary effect <i>BE</i> .....	112
I.1.7	Readout electronics <i>RE</i> .....	113
I.1.8	Response time <i>RT</i> .....	113
I.1.9	Probe positioning <i>PP</i> .....	113
I.1.10	Sampling error <i>SE</i> .....	113
I.1.11	Phantom shell <i>PS</i> .....	114
I.1.12	Tissue-equivalent medium parameters <i>MAT</i> .....	114
I.1.13	Measurement system immunity/secondary reception <i>MSI</i> .....	116

I.2	Uncertainty of reconstruction corrections and post-processing to be specified by the manufacturer <i>MN</i> .....	116
I.2.1	General .....	116
I.2.2	Evaluation of uncertainty due to reconstruction <i>REC</i> .....	116
I.2.3	Impact of noise on reconstruction <i>POL</i> .....	117
I.2.4	SAR averaging <i>SAV</i> .....	117
I.2.5	SAR scaling <i>SARS</i> .....	117
I.2.6	SAR correction for deviations in permittivity and conductivity <i>SC</i> .....	118
I.3	Uncertainties that are dependent on the DUT <i>MD</i> .....	119
I.3.1	General .....	119
I.3.2	Probe coupling with the DUT <i>PC</i> .....	119
I.3.3	Modulation Response <i>MOD</i> .....	119
I.3.4	Integration time <i>IT</i> .....	120
I.3.5	Measured SAR drift <i>SD</i> .....	120
I.4	Uncertainties related to the measurement environment <i>ME</i> .....	120
I.4.1	General .....	120
I.4.2	Device holder <i>DH</i> .....	120
I.4.3	Device positioning <i>DP</i> .....	121
I.4.4	RF ambient conditions <i>AC</i> .....	121
I.4.5	Measurement system drift and noise <i>DN</i> .....	121
I.5	Uncertainties of validation antennas <i>MV</i> .....	122
I.5.1	General .....	122
I.5.2	Deviation of experimental antennas <i>DEV</i> .....	122
I.5.3	Power measurement uncertainty <i>PMU</i> .....	122
I.5.4	Other uncertainty contributions when using validation antennas <i>OVS</i> .....	122
Annex J (normative)	Evaluation of the measurement system uncertainty of fixed array or scanning array vector measurement base systems .....	123
J.1	Measuring system uncertainties to be evaluated by the manufacturer <i>MM</i> .....	123
J.1.1	General .....	123
J.1.2	Calibration <i>CF</i> .....	123
J.1.3	Isotropy <i>ISO</i> .....	123
J.1.4	Mutual sensor coupling <i>MSC</i> .....	124
J.1.5	Scattering due to the presence of the array <i>AS</i> .....	125
J.1.6	System linearity <i>LIN</i> .....	126
J.1.7	Sensitivity limit <i>SL</i> .....	126
J.1.8	Boundary effect <i>BE</i> .....	126
J.1.9	Readout electronics <i>RE</i> .....	127
J.1.10	Response time <i>RT</i> .....	127
J.1.11	Probe position <i>PP</i> .....	127
J.1.12	Sampling error <i>SE</i> .....	128
J.1.13	Array boundaries <i>AB</i> .....	128
J.1.14	Phantom shell <i>PS</i> .....	129
J.1.15	Tissue-equivalent medium parameters <i>MAT</i> .....	129
J.1.16	Phantom homogeneity <i>HOM</i> .....	131
J.1.17	Measurement system immunity/secondary reception <i>MSI</i> .....	132
J.2	Uncertainty of reconstruction, corrections, and post-processing to be specified by the manufacturer <i>MN</i> .....	132
J.2.1	General .....	132
J.2.2	Evaluation of uncertainty due to reconstruction <i>REC</i> .....	132

J.2.3	Impact of noise on reconstruction <i>POL</i> .....	132
J.2.4	SAR averaging <i>SAV</i> .....	132
J.2.5	SAR scaling <i>SARS</i> .....	132
J.2.6	SAR correction for deviations in permittivity and conductivity <i>SC</i> .....	132
J.3	Measurement system uncertainties that are dependent on the DUT <i>MD</i> .....	132
J.3.1	General.....	132
J.3.2	Probe or probe-array coupling with the DUT <i>PC</i> .....	132
J.3.3	Modulation response <i>MOD</i> .....	133
J.3.4	Integration time <i>IT</i> .....	133
J.3.5	Measurement system drift and noise <i>DN</i> .....	133
J.4	Uncertainties related to the source or noise <i>ME</i> .....	133
J.4.1	General.....	133
J.4.2	Device holder <i>DH</i> .....	133
J.4.3	Device positioning <i>DP</i> .....	133
J.4.4	RF ambient conditions <i>AC</i> .....	134
J.4.5	Measurement system drift and noise <i>DN</i> .....	134
J.5	Uncertainties of validation antennas <i>MV</i> .....	134
J.5.1	General.....	134
J.5.2	Deviation of experimental antennas <i>DEX</i> .....	134
J.5.3	Power measurement uncertainty <i>PMU</i> .....	134
J.5.4	Other uncertainty contributions when using validation antennas <i>OVS</i> .....	134
	Bibliography.....	135
	Figure 1 – Evaluation plan checklist.....	15
	Figure 2 – Illustration of the shape and orientation relative to a curved phantom surface of the distorted cubic volume for computing psSAR.....	22
	Figure 3 – Measurements performed by shifting a large device over the efficient measurement area of the system including overlapping areas – in this case: six tests performed.....	24
	Figure 4 – Flow chart for SAR measurements of uncorrelated signals at different frequencies using a measurement system able to distinguish between different frequency components (Method 2).....	27
	Figure 5 – Illustration of the amplitude spectrum, as function of frequency, for simultaneously transmitted signals of multiple frequency bands emitted by a DUT.....	28
	Figure 6 – Illustration of a completely covered signal bandwidth $B_S$ by the measurement system analysis bandwidth $B_A$ at single transmission mode.....	29
	Figure 7 – Illustration of a completely covered signal bandwidths $B_{Si}$ (for $i = 2$ to $N$ ) by the measurement system analysis bandwidth $B_A$ for simultaneous multiple-frequency transmission mode.....	29
	Figure 8 – Illustration of a non-coverage of the signal bandwidths $B_{Si}$ (for $i = 2$ to $N$ ) by the measurement system analysis bandwidth $B_A$ for simultaneous multiple-frequency transmission mode.....	29
	Figure 9 – Illustration of a partial-coverage of the signal bandwidths $B_{Si}$ (for $i = 2$ to $N$ ) by the measurement system analysis bandwidth $B_A$ for simultaneous multiple-frequency transmission mode.....	30
	Figure 10 – Illustration of reduction of the measurement system analysis bandwidth $B_A$ to cover only one signal bandwidth $B_{Si}$ (for $i = 1$ to $N$ ) for simultaneous multiple-frequency transmission mode.....	30
	Figure 11 – Illustration of increasing or moving the measurement system analysis bandwidth $B_A$ to cover one or more signal bandwidth $B_{Si}$ (for $i = 1$ to $N$ ) for simultaneous multiple-frequency transmission mode.....	30

Figure A.1 – Sagittally-bisected phantom with extended perimeter, used for scanning measurement systems .....	41
Figure A.2 – Dimensions of the elliptical phantom .....	42
Figure C.1 – Coordinate system for 2D planar measurement-system .....	50
Figure C.2 – Generic configuration of SAR measurement system.....	50
Figure C.3 – Schematic representation of 2D planar measurement-based SAR system and its coordinate system .....	52
Figure C.4 – Source reconstruction from fields outside a phantom .....	53
Figure D.1 – Recommended power measurement setup for <i>system check</i> and <i>system validation</i> .....	56
Figure D.2 – Equipment setup for measurement of forward power $P_f$ and forward coupled power $P_{fc}$ .....	57
Figure D.3 – Equipment setup for measuring the shorted reverse coupled power $P_{rcs}$ .....	58
Figure D.4 – Equipment setup for measuring the power with the reference antenna connected .....	58
Figure D.5 – Port numbering for the $S$ -parameter measurements of the directional coupler .....	60
Figure D.6 – SAM masks for positioning dipole antennas and VPIFAs on the head phantoms, including holes where the antenna spacer is inserted .....	65
Figure D.7 – Flat masks for positioning VPIFAs on the flat phantoms, including a hole in the centre where the VPIFA spacer is inserted .....	66
Figure D.8 – Dipole showing the distance of $s = 15$ mm .....	67
Figure D.9 – 2-PEAK CPIFA showing the fixed distance of $s = 7$ mm .....	67
Figure D.10 – VPIFA positioned showing the fixed distance of $s = 2$ mm .....	68
Figure D.11 – <i>System check</i> and validation locations for the flat phantom.....	69
Figure D.12 – <i>System check</i> and validation locations for the head phantom.....	70
Figure D.13 – Definition of rotation angles for dipoles .....	71
Figure F.1 – Mechanical details of the standard dipole.....	87
Figure F.2 – VPIFA validation antenna.....	89
Figure F.3 – 2-PEAK CPIFA at 2 450 MHz .....	92
Figure F.4 – Detail of the tuning structure and matching structure.....	93
Figure G.1 – Measurement setup for waveguide calibration of dosimetric probe, and similar setup (same tissue-equivalent liquid, dielectric spacer, power sensors and coupler) for antenna calibration.....	95
Figure G.2 – Setup for calibration of a reference antenna .....	96
Figure G.3 – Method for the transfer of calibration between two antennas of the same type using the array system .....	103
Figure I.1 – Illustration of SAR measurement results during 8 h and the centred moving average .....	122
Table 1 – Evaluation plan checklist .....	16
Table 2 – Uncertainty budget template for the evaluation of the measurement system uncertainty of the 1 g or 10 g psSAR to be carried out by the system manufacturer .....	36
Table 3 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from a DUT .....	37
Table 4 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from a validation antenna.....	38

Table 5 – Uncertainty budget template for evaluating the uncertainty in the measured value of 1 g SAR or 10 g SAR from the <i>system check</i> .....	39
Table A.1 – Dielectric properties of the tissue-equivalent medium .....	43
Table B.1 – Uncertainty analysis for single-probe calibration in waveguide .....	45
Table B.2 – Uncertainty analysis for transfer calibration of array systems .....	46
Table B.3 – Uncertainty analysis of transfer calibration of array systems .....	48
Table D.1 – Example of power measurement uncertainty in % .....	60
Table D.2 – Modulations and multiplexing modes used by radio systems .....	64
Table D.3 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values for the flat phantom filled with tissue-equivalent medium for the antennas specified in Annex F .....	72
Table D.4 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values for antenna generating two peaks on the flat phantom filled with tissue-equivalent medium for the antennas specified in Annex F .....	73
Table D.5 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values on the head left and right phantom for the antennas specified in Annex F .....	74
Table D.6 – Peak spatial-average SAR (psSAR) averaged over 1 g and 10 g values for antenna generating two peaks on the head left and right phantom for the antennas specified in Annex F. Modulations are as specified in Table D.2 .....	79
Table D.7 – Set of randomised tests for on-site <i>system validation</i> using flat phantom 1 g and 10 g psSAR, normalized to 1 W forward power, using the antennas specified in Annex F .....	79
Table D.8 – Set of tests for on-site <i>system validation</i> using left and right head phantoms for 1 g and 10 g psSAR for the antennas specified in Annex F .....	80
Table F.1 – Return loss values for antennas specified in Annex F and flat phantom filled with tissue-equivalent medium .....	85
Table F.2 – Mechanical dimensions of the reference dipoles .....	86
Table F.3 – Dimensions for VPIFA antennas at different frequencies .....	90
Table F.4 – Dielectric properties of the dielectric layers for VPIFA antennas .....	90
Table F.5 – Thickness of substrates and planar metallization .....	93
Table F.6 – Dielectric properties of FR4 .....	93
Table F.7 – Values for the antenna dimensions in Figures F.4 and F.5 .....	94
Table G.1 – Example uncertainty budget for reference dipole antenna calibration for 1 g and 10 g averaged SAR (750 MHz to 3 GHz) .....	99
Table G.2 – Example uncertainty budget for reference antenna calibration (PIFA) for 1 g and 10 g averaged SAR (750 MHz to 3 GHz) .....	100
Table G.3 – Example uncertainty budget for reference antenna (dipole) calibration for 1 g and 10 g averaged SAR (3 GHz to 6 GHz) .....	101
Table G.4 – Example uncertainty budget for the calibration of an antenna using the transfer method, as percentages .....	104
Table H.1 – Parameters of analytical reference functions and associated reference peak 10 g SAR value .....	109

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**MEASUREMENT PROCEDURE FOR THE ASSESSMENT  
OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE  
TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND  
BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –**

**Part 3: Vector measurement-based systems  
(Frequency range of 600 MHz to 6 GHz)**

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

IEC 62209-3 has been prepared by IEC technical committee 106: Methods for the assessment of electric, magnetic and electromagnetic fields associated with human exposure.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
106/494/FDIS	106/497/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

In this standard, the following print types are used:

- specific test protocols: in *italic* type.

This standard contains attached files in the form of four \*.IGS files of inner and outer surfaces for the left and right halves extracted from the CAD model of the SAM phantom (see A.1.2). These files are available in the supporting documents folder at [www.iec.ch/tc106/supportingdocuments](http://www.iec.ch/tc106/supportingdocuments).

This standard contains attached files for the analytical functions that are to be used for the evaluation of the reconstruction algorithm uncertainty in Table H.1. These files are available in the supporting documents folder at [www.iec.ch/tc106/supportingdocuments](http://www.iec.ch/tc106/supportingdocuments).

The committee has decided that the contents of this publication will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT – The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its contents. Users should therefore print this document using a colour printer.**

## INTRODUCTION

This document specifies the requirements for vector measurement-based systems to measure the Specific Absorption Rate (SAR) of devices that are used in close proximity to the human body or head.

Because SAR measurement systems are used for showing compliance with national and international exposure limits, the test procedures have to be standardized. This standardization aims at achieving comparable results for the equipment approval process.

Vector measurement-based systems and the associated protocols can differ from traditional SAR measurement systems and protocols. These systems use more advanced field reconstruction methods, allowing the application of indirect measurement approaches in which the SAR is evaluated in three dimensions from a limited number of measurement points that may be located in a limited part of the volume of interest, or even outside this volume. Such new SAR assessment approaches result in significantly reduced SAR measurement times.

# MEASUREMENT PROCEDURE FOR THE ASSESSMENT OF SPECIFIC ABSORPTION RATE OF HUMAN EXPOSURE TO RADIO FREQUENCY FIELDS FROM HAND-HELD AND BODY-MOUNTED WIRELESS COMMUNICATION DEVICES –

## Part 3: Vector measurement-based systems (Frequency range of 600 MHz to 6 GHz)

### 1 Scope

This part of IEC 62209 specifies measurement protocols and test procedures for the reproducible measurement of peak spatial-average specific absorption rate (psSAR) induced inside a simplified model of a human head or body by radio-frequency (RF) transmitting devices, with a specified measurement uncertainty. Requirements are provided for psSAR assessment using vector measurement-based systems. Such systems determine the psSAR by three-dimensional (3D) field reconstruction within the volume of interest in accordance with the requirements herein for the measurement system, calibration, uncertainty assessment and validation methods. The protocols and procedures apply for the psSAR assessments covering a significant majority of people including children during use of wireless communication devices operated in close proximity to the head or body.

This document is applicable to wireless communication devices intended to be used at a position near the human head or body at distances up to and including 200 mm. This document may be employed to evaluate SAR compliance of different types of wireless communication devices used next to the ear, in front of the face, mounted on the body, combined with other RF-transmitting or non-transmitting devices or accessories (e.g. belt-clip), or embedded in garments. The overall applicable frequency range is from 600 MHz to 6 GHz.

The *system validation* procedures provided within this document cover frequencies from 600 MHz to 6 GHz.

With a vector measurement-based system this document can be employed to evaluate SAR compliance of different types of wireless communication devices.

The wireless communication device categories covered include but are not limited to mobile telephones, cordless microphones, auxiliary broadcast devices and radio transmitters in personal computers, desktop and laptop devices, multi-band, multi-antenna, and push-to-talk devices.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 62209-1:2016, *Measurement procedure for the assessment of specific absorption rate of human exposure to radio frequency fields from hand-held and body-mounted wireless communication devices – Part 1: Devices used next to the ear (Frequency range of 300 MHz to 6 GHz)*