

AS IEC 62282.8.101:2024  
IEC 62282-8-101:2020



STANDARDS  
Australia



# Fuel cell technologies

**Part 8.101: Energy storage systems using fuel cell modules in reverse mode — Test procedures for the performance of solid oxide single cells and stacks, including reversible operation**



currently in review, click buy full version

AS IEC 62282.8.101:2024

This Australian Standard® was prepared by ME-093, Hydrogen Technologies. It was approved on behalf of Standards Australia's Standards Development and Accreditation Committee on 06 November 2024.

This Standard was published on 15 November 2024.

The following are represented on Committee ME-093:

- Australian Gas Association
- Australian Hydrogen Council
- Australian Industry Group
- Chemistry Australia
- Energy Networks Australia
- Engineers Australia
- Gas Energy Australia
- Gas Technical Regulators Committee
- Institute of Electrical Inspectors
- National Association of Testing Authorities Australia
- The University of Adelaide

This Standard was issued in draft form for comment as DR AS IEC 62282.8.101. 024.

#### **Keeping Standards up-to-date**

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

[www.standards.org.au](http://www.standards.org.au)

ISBN 978 1 76139 901 5

# Fuel cell technologies

## Part 8.101: Energy storage systems using fuel cell modules in reverse mode — Test procedures for the performance of solid oxide single cells and stacks, including reversible operation

First published as AS IEC 62282.8.101:2024.



© IEC Geneva Switzerland 2024 — All rights reserved  
© Standards Australia Limited 2024

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of either the IEC or the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth). If you have any questions about IEC copyright or have an enquiry about obtaining additional rights to this publication, please see the contact details on the back cover or the contact us page of the website for further information.

## Preface

This Standard was prepared by the Standards Australia Committee ME-093, Hydrogen Technologies.

The objective of this document is to address solid oxide cell (SOC) and stack assembly unit(s). It provides for testing systems, instruments and measuring methods to test the performance of SOC cell/stack assembly units for energy storage purposes. It assesses performance in fuel cell mode, in electrolysis mode and/or in reversible operation.

This document is not applicable to small button cells that are designed for SOC material testing and provide no practical means of reactant utilization measurement, or to single-chamber SOC. This document is not intended to be applied to fuel cell/stack assembly units for power generation purposes only, since this is covered in IEC TS 62282-7-2. Therefore, test methods are not included in this document that are applicable to fuel cell mode only and that are already described in IEC TS 62282-7-2.

This document is intended for data exchanges in commercial transactions between cell/stack manufacturers and system developers or for acquiring data on a cell or stack in order to estimate the performance of a system based on it. Users of this document may selectively execute test items suitable for their purposes from those described in this document. Users can also substitute selected test methods of this document with equivalent test methods of IEC TS 62282-7-2 for SOC operation in fuel cell mode only.

In the context of this document, the term “reversible” does not refer to the thermodynamic meaning of an ideal process. It is common practice in the fuel cell community to call the operation mode of a solid oxide cell that alternates between fuel cell mode and electrolysis mode “reversible”.

This document considers only steam electrolysis. Other reactants in electrolysis mode can be used, provided appropriate measures are taken for handling the specific reactants and products, and the guidelines as regards the measurement, control and post-test analysis of results are adapted accordingly.

This document is identical with, and has been reproduced from, IEC 62282-8-101:2020, *Fuel cell technologies – Part 8-101: Energy storage systems using fuel cell modules in reverse mode – Test procedures for the performance of solid oxide single cells and stacks, including reversible operation*.

As this document has been reproduced from an international document, the following apply:

- (a) In the source text “this part of IEC 62282” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

# Contents

Preface .....	ii
FOREWORD .....	vii
INTRODUCTION .....	ix
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms, definitions, abbreviated terms and symbols .....</b>	<b>2</b>
3.1 Terms and definitions .....	2
3.2 Abbreviated terms and symbols .....	8
3.2.1 Abbreviated terms .....	8
3.2.2 Symbols .....	8
3.3 Flow rates .....	12
<b>4 General safety conditions .....</b>	<b>12</b>
<b>5 Test environment .....</b>	<b>13</b>
5.1 General .....	13
5.2 Cell .....	13
5.3 Stack .....	14
5.4 Experimental set-up .....	15
5.4.1 General .....	15
5.4.2 Electrode gas control equipment .....	15
5.4.3 Thermal management equipment .....	15
5.4.4 Electric power supply/load control equipment .....	16
5.4.5 Measurement and data acquisition equipment .....	16
5.4.6 Safety equipment .....	16
5.4.7 Compression force control equipment .....	16
5.4.8 Pressure control equipment .....	16
5.5 Interface between test object and experimental set-up .....	16
5.6 Parameter control and measurement .....	18
5.7 Measurement uncertainty of TIRs and TOPs .....	19
5.8 Mounting of the test object into the experimental set-up .....	19
5.9 Stability criteria .....	20
<b>6 Measurement instruments and methods .....</b>	<b>20</b>
6.1 General .....	20
6.2 Instrument uncertainty .....	20
6.3 Recommended measurement instruments and methods .....	21
6.3.1 Electrode inlet gas flow rate measurement .....	21
6.3.2 Electrode gas composition measurement .....	21
6.3.3 Electrode gas temperature measurement .....	22
6.3.4 Electrode gas pressure measurement .....	22
6.3.5 Electrode exhaust gas flow rate measurement .....	22
6.3.6 Cell/stack assembly unit voltage measurement .....	23
6.3.7 Cell/stack assembly unit current measurement .....	23
6.3.8 Cell/stack assembly unit temperature measurement .....	23
6.3.9 Compression force measurement .....	23
6.3.10 Total impedance measurement .....	23
6.3.11 Ambient condition measurement .....	23
6.4 Test conditions and manufacturer recommendations .....	23
6.4.1 Start-up and shut-down conditions .....	23
6.4.2 Range of test conditions .....	24
6.4.3 Stabilization, initialization conditions and stable state .....	24
6.4.4 Dwell time, equilibration time, acquisition time .....	24
6.5 Data acquisition method .....	25
<b>7 Test procedures and computation of results .....</b>	<b>25</b>

7.1	General	25
7.2	Current-voltage characteristics test	25
	7.2.1 Objective of this test	25
	7.2.2 Test method	25
	7.2.3 Data post-processing	26
7.3	Effective reactant utilization test	26
	7.3.1 Objective of this test	26
	7.3.2 Test method	26
	7.3.3 Data post-processing	27
7.4	Durability test	27
	7.4.1 Objective of this test	27
	7.4.2 Test method	27
	7.4.3 Data post-processing	28
7.5	Temperature sensitivity test	28
	7.5.1 Objective of this test	28
	7.5.2 Test method	28
	7.5.3 Data post-processing	29
7.6	Separation of resistance components test via electrochemical impedance spectroscopy	29
	7.6.1 Objective of this test	29
	7.6.2 Test method	29
	7.6.3 Data post-processing	30
7.7	Current cycling durability test	31
	7.7.1 Objective of this test	31
	7.7.2 Test method	31
	7.7.3 Data post-processing	31
7.8	Thermal cycling test	32
	7.8.1 Objective	32
	7.8.2 Test method	32
	7.8.3 Data post-processing	32
7.9	Pressurized test	32
	7.9.1 Objective of this test	32
	7.9.2 Test method	33
	7.9.3 Data post-processing	33
<b>8</b>	<b>Test report</b>	<b>33</b>
	8.1 General	33
	8.2 Report items	33
	8.3 Test unit data description	34
	8.4 Test condition description	34
	8.5 Test data description	34
	8.6 Uncertainty evaluation	35
<b>Annex A</b>	<b>(normative) Detailed test procedures</b>	<b>36</b>
<b>Annex B</b>	<b>(informative) Guidelines for electrochemical impedance spectroscopy (EIS)</b>	<b>61</b>
<b>Annex C</b>	<b>(normative) Formulae for calculation of utilization values</b>	<b>66</b>
<b>Bibliography</b>		<b>68</b>

## List of Figures

Figure 1	— Exploded schematic representation of a planar-type single cell test object consisting of a SOC in a cell housing	14
Figure 2	— Schematic representation of a planar-geometry SOC stack test object with $N$ RU including supporting structure (top and bottom plates)	15
Figure 3	— Schematic representation of a test environment for a SOC cell/stack assembly unit	15
Figure 4	— Test environment with interfaces between SOC cell and experimental set-up	17
Figure 5	— Test environment with interfaces between SOC stack and experimental set-up	18
Figure A.1	— Qualitative representation of TIPs when carrying out a current-voltage characteristics test for combined (SOFC and SOEC) operation	39

Figure A.2 — Schematic representation of the current-voltage characteristics test procedure for two consecutive set points $k$ and $k + 1$ .....	39
Figure A.3 — Schematic representation of a $J$ - $V$ curve in both electrolysis and fuel cell modes.....	40
Figure A.4 — Qualitative representation of TIPs when carrying out an effective reactant utilization test varying the negative electrode reactant flow rate ( $q_{V,neg,in}$ ), consisting of hydrogen and nitrogen.....	43
Figure A.5 — Qualitative representation of TIPs when carrying out a durability test (in galvanostatic mode).....	46
Figure A.6 — Qualitative representation of TIPs when carrying out a temperature sensitivity test.....	46
Figure A.7 — Qualitative representation of TIPs when carrying out a current cycling durability test.....	44
Figure A.8 — Current profile of a SOEC system with fast switch on/off at thermoneutral conditions.....	54
Figure A.9 — Current profile of a SOEC system with fast switch on/off at exothermal conditions.....	54
Figure A.10 — Current profile of a load-following SOEC system and thermoneutral conditions.....	54
Figure A.11 — Current profile of a load-following SOEC system and exothermal conditions.....	55
Figure A.12 — General evolution of TIPs during test: continuous thermal cycling above 600 °C (in this case with zero electric current).....	57
Figure A.13 — General evolution of TIPs during test: thermal cycling below 600 °C with gas and current changes (coupling with operation at constant current for instance).....	58
Figure B.1 — Input/output signals during electrochemical impedance spectroscopy (EIS) of a solid oxide fuel/electrolysis cell.....	62
Figure B.2 — Test set-up for electrochemical impedance spectroscopy of a planar solid oxide fuel cell/electrolysis stack with 5 RUs.....	63
Figure B.3 — Bode plot representing the modulus of impedance and phase angle against excitation frequency.....	64
Figure B.4 — Nyquist plot, representing conjugate imaginary part against real part of impedance.....	65

## List of Tables

Table 1 — Symbols.....	8
Table 2 — Stability criteria for TIPs and TOPs as a reference.....	20
Table 3 — Instrument uncertainty for each quantity to be measured.....	20
Table A.1 — Test input parameters (TIPs) for current-voltage characteristics test.....	37
Table A.2 — Test output parameters (TOPs) for current-voltage characteristics test.....	37
Table A.3 — Derived quantities for current-voltage characteristics test.....	38
Table A.4 — Test input parameters (TIPs) for negative electrode reactant utilization test.....	41
Table A.5 — Test input parameters (TIPs) for positive electrode reactant utilization test.....	41
Table A.6 — Test output parameters (TOPs) for effective reactant utilization test.....	42
Table A.7 — Derived quantities for effective reactant utilization test.....	42
Table A.8 — Test input parameters (TIPs) for durability test.....	44
Table A.9 — Test output parameters (TOPs) for durability test.....	44
Table A.10 — Derived quantities for constant load durability test.....	45
Table A.11 — Test input parameters (TIPs) for temperature sensitivity test.....	46
Table A.12 — Test output parameters (TOPs) for temperature sensitivity test.....	47
Table A.13 — Derived quantities for temperature sensitivity test.....	47
Table A.14 — Test input parameters (TIPs) for EIS test.....	49
Table A.15 — Test output parameters (TOPs) for EIS test.....	49
Table A.16 — Derived quantities for EIS test.....	50
Table A.17 — Test input parameters (TIPs) for current cycling durability test within a single operating mode (fuel cell or electrolysis).....	51
Table A.18 — Test input parameters (TIPs) for current cycling durability test covering both operating modes (fuel cell and electrolysis).....	51
Table A.19 — Test output parameters (TOPs) for current cycling durability test.....	51
Table A.20 — Derived quantities for current cycling durability test.....	52
Table A.21 — Test input parameters (TIPs) for thermal cycling.....	55
Table A.22 — Test output parameters (TOPs) for thermal cycling.....	55
Table A.23 — Derived quantities for thermal cycling test.....	56
Table A.24 — Test input parameters (TIPs) for pressurized testing.....	59
Table A.25 — Test output parameters (TOPs) for pressurized testing.....	59

Table A.26 — Derived quantities for pressurized test.....	59
Table C.1 — Generic formulae.....	66

Currently in preview, click buy full version

## FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62282-8-101 has been prepared by IEC technical committee 105: Fuel cell technologies.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
105/765/FDIS	105/779/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62282 series, published under the general title *Fuel cell technologies*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

**IMPORTANT** The 'colour inside' logo on the cover page of this publication indicates that it contains colours which are considered to be useful for the correct understanding of its content. Users should therefore print this document using a colour printer.

## INTRODUCTION

This document describes test methods for a single cell or stack (denoted as "cell/stack" hereafter) that are intended for application to energy storage systems using solid oxide fuel cells (SOFC) in combination with solid oxide electrolysis cells (SOEC), or directly using reversible solid oxide cells (Re-SOC, see [Note in Clause 1](#)). The test methods aim to provide guidelines for the characterization of real-time performance and durability of the cell/stack.

SOFC, SOEC and Re-SOC have a broad range of geometries (e.g. planar, tubular and their variations) and size. As such, in general, peripherals like current collectors and gas manifolds are unique to each cell or stack and are often incorporated into a cell or stack to form one integrated unit. In addition, they tend to have a significant effect on the power generation characteristics of the cell or stack. This document therefore introduces as its subject "cell/stack assembly units", which are defined as those units containing not only a cell or a stack but also peripherals.

This document is generally applicable to all types or geometries of SOFC, SOEC and Re-SOC, unless where explicitly mentioned.

IEC 62282-8 (all parts) aims to develop performance test methods for power storage and buffering systems based on electrochemical modules (combining electrolysis and fuel cells, in particular reversible fuel cells), taking into consideration both options of re-electrification and substance (and heat) production for sustainable integration of renewable energy sources.

Under the general title "Energy storage systems using fuel cell modules in reverse mode", the IEC 62282-8 series will consist of the following parts:

- IEC 62282-8-101: *Test procedures for the performance of solid oxide single cells and stacks, including reversible operation*
- IEC 62282-8-102: *Test procedures for the performance of single cells and stacks with proton exchange membranes, including reversible operation*
- IEC 62282-8-103<sup>1)</sup>: *Alkaline single cell and stack performance including reversible operation*
- IEC 62282-8-201: *Test procedures for the performance of power-to-power systems*
- IEC 62282-8-202<sup>2)</sup>: *Power-to-power systems – Safety*
- IEC 62282-8-300 series<sup>3)</sup>: *Power-to-substance systems*

As a priority dictated by the emerging needs for industry and opportunities for technological development, IEC 62282-8-101, IEC 62282-8-102 and IEC 62282-8-201 have been initiated jointly and as a priority. These documents are presented as a package to highlight the need for an integrated approach as regards the system application (i.e. a solution for energy storage) and its fundamental constituent components (i.e. fuel cells operated in reverse or reversible mode).

IEC 62282-8-103, IEC 62282-8-202 and IEC 62282-8-300 (all parts) are suggested but are left for initiation at a later stage.

---

1) Under consideration.  
2) Under consideration.  
3) Under consideration.

## NOTES

# Australian Standard®

## Fuel cell technologies

### Part 8.101: Energy storage systems using fuel cell modules in reverse mode — Test procedures for the performance of solid oxide single cells and stacks, including reversible operation

#### 1 Scope

This part of IEC 62282 addresses solid oxide cell (SOC) and stack assembly unit(s). It provides for testing systems, instruments and measuring methods to test the performance of SOC cell/stack assembly units for energy storage purposes. It assesses performance in fuel cell mode, in electrolysis mode and/or in reversible operation.

This document is not applicable to small button cells that are designed for SOC material testing and provide no practical means of reactant utilization measurement, or to single-chamber SOC. This document is not intended to be applied to fuel cell/stack assembly units for power generation purposes only, since this is covered in IEC TS 62282-7-2. Therefore, test methods are not included in this document that are applicable to fuel cell mode only and that are already described in IEC TS 62282-7-2.

This document is intended for data exchanges in commercial transactions between cell/stack manufacturers and system developers or for acquiring data on a cell or stack in order to estimate the performance of a system based on it. Users of this document may selectively execute test items suitable for their purposes from those described in this document. Users can also substitute selected test methods of this document with equivalent test methods of IEC TS 62282-7-2 for SOC operation in fuel cell mode only.

NOTE 1 In the context of this document, the term "reversible" does not refer to the thermodynamic meaning of an ideal process. It is common practice in the fuel cell community to call the operation mode of a solid oxide cell that alternates between fuel cell mode and electrolysis mode "reversible".

NOTE 2 This document considers only steam electrolysis. Other reactants in electrolysis mode can be used, provided appropriate measures are taken for handling the specific reactants and products, and the guidelines as regards the measurement, control and post-test analysis of results are adapted accordingly.

#### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60050-485, *International Electrotechnical Vocabulary – Part 485: Fuel cell technologies*(available at [www.electropedia.org](http://www.electropedia.org))

IEC 61515:2016, *Mineral insulated metal-sheathed thermocouple cables and thermocouples*

IEC 60584-1, *Thermocouples – Part 1: EMF specifications and tolerances*

IEC 60584-3, *Thermocouples – Part 3: Extension and compensating cables – Tolerances and identification system*

ISO 5168, *Measurement of fluid flow – Procedures for the evaluation of uncertainties*

ISO 6141, *Gas analysis – Contents of certificates for calibration gas mixtures*

ISO 6142-1, *Gas analysis – Preparation of calibration gas mixtures – Part 1: Gravimetric method for Class I mixtures*