

AS ISO 10570:2021  
ISO 10570:2004



STANDARDS  
Australia



# Earth-moving machinery — Articulated frame lock — Performance requirements

currently in preview, click buy full version

AS ISO 10570:2021

This Australian Standard® was prepared by ME-063, Earthmoving Equipment. It was approved on behalf of the Council of Standards Australia on 11 December 2020.

This Standard was published on 22 January 2021.

The following are represented on Committee ME-063:

Australian Industry Group  
Better Regulation Division — SafeWork NSW  
Construction and Mining Equipment Industry Group  
Department of Natural Resources, Mines and Energy, Qld  
Department of Regional NSW  
Engineers Australia/Mining Electrical and Mining Mechanical Engineering Society  
Institute of Instrumentation, Control & Automation Australia  
Minerals Council of Australia  
University of Queensland

This Standard was issued in draft form for comment as DR AS ISO 10570:2020.

**Keeping Standards up-to-date**

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

[www.standards.org.au](http://www.standards.org.au)

ISBN 978 1 76113 153 0

# Earth-moving machinery — Articulated frame loader — Performance requirements

First published as AS ISO 10570:2021.

## **COPYRIGHT**

© ISO 2021 — All rights reserved  
© Standards Australia Limited 2021

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

## Preface

This Standard was prepared by the Standards Australia Committee ME-063, Earthmoving Equipment.

The objective of this document is to define performance requirements for an articulated frame lock designed to prevent unintended machine articulation of earth-moving machinery as defined in ISO 6165 and with an articulated frame during either shipment or maintenance.

This document is identical with, and has been reproduced from, ISO 10570:2004, *Earth-moving machinery — Articulated frame lock — Performance requirements*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this International Standard” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

## Contents

<b>Preface</b> .....	<b>ii</b>
<b>Foreword</b> .....	<b>iv</b>
<b>1 Scope</b> .....	<b>1</b>
<b>2 Normative references</b> .....	<b>1</b>
<b>3 Terms and definitions</b> .....	<b>1</b>
<b>4 Requirements</b> .....	<b>1</b>
4.1 Mounting positions .....	1
4.2 Attachment to machine .....	1
4.3 Colour .....	1
4.4 Performance test requirements .....	2
<b>Bibliography</b> .....	<b>3</b>

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 10570 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 2, *Safety requirements and human factors*.

This second edition cancels and replaces the first edition (ISO 10570:1992), which has been technically revised.

# Australian Standard®

## Earth-moving machinery — Articulated frame lock — Performance requirements

### 1 Scope

This International Standard defines performance requirements for an articulated frame lock designed to prevent unintended machine articulation of earth-moving machinery as defined in ISO 6165 and with an articulated frame during either shipment or maintenance.

### 2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 6165, *Earth-moving machinery — Basic types — Vocabulary*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

#### 3.1

##### **articulated frame lock**

link(s), bar(s), pin(s) or equivalent, including attaching parts and attachment points to the machine frame, designed to prevent unintended articulation of an earth-moving machine with an articulated frame during either shipment or maintenance

Note 1 to entry: The articulated frame lock is not intended for use while the machine is moving/travelling by its own means.

### 4 Requirements

#### 4.1 Mounting positions

The articulated frame lock shall be capable of securing the machine in a straight-ahead position and shall be mounted either on the side normally used for access to the operator's station or at the discretion of the manufacturer.

If it is necessary that the machine be articulated so that routine maintenance functions can be performed, the articulated frame lock shall be capable of securing the machine in the articulated position required for such functions.

The articulated frame lock shall be so designed that its mounting is possible without frequent adjustment of the two parts of the machine frame.

#### 4.2 Attachment to machine

The articulated frame lock shall be attached to the machine such that none of its parts become separated from the machine during use or storage.

#### 4.3 Colour

The articulated frame lock link parts shall be coloured red, which colour shall be clearly visible in both the stored and installed positions. However, when the machine is itself red, another, clearly contrasting, colour shall be used.