

AS ISO 11862:2021
ISO 11862:1993



STANDARDS
Australia



Earth-moving machinery — Auxiliary starting aid electrical connector

currently in preview, click buy full version

AS ISO 11862:2021

This Australian Standard ® was prepared by ME-063, Earthmoving Equipment. It was approved on behalf of the Council of Standards Australia on 27 May 2021.

This Standard was published on 11 June 2021.

The following are represented on Committee ME-063:

Australian Industry Group
Better Regulation Division — SafeWork NSW
Construction and Mining Equipment Industry Group
Department of Regional NSW
Department of Resources, Qld
Engineers Australia
Institute of Instrumentation, Control & Automation Australia
Minerals Council of Australia
Mining Electrical and Mining Mechanical Engineering Society
University of Queensland

This Standard was issued in draft form for comment as DR AS ISO 11862:2021.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 384 8

Earth-moving machinery — Auxiliary starting aid electrical connector

First published as AS ISO 11862:2021.

COPYRIGHT

© ISO 2021 — All rights reserved
© Standards Australia Limited 2021

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee ME-063, Earthmoving Equipment.

The objective of this document is to specify the details, dimensions and design of both plug (male) and receptacle (female) which must mate properly to permit interchangeable use of different makes of electrical connectors providing an auxiliary starting circuit for earth-moving machinery as defined in ISO 6165.

This document also lays down a universal connecting device, with correct polarity, standard circuit coding and protection from electrical shorts, which may be used with any other machinery, vehicle or automotive equipment with the same electrical system voltage range.

This document is identical with, and has been reproduced from, ISO 11862:1993, *Earth moving machinery — Auxiliary starting aid electrical connector*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this International Standard” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adaptations of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	iv
1 Scope	1
2 Normative references	1
3 General requirements	1
3.1 Receptacle	1
3.2 Plug assembly	1
4 Construction	1
4.1 Materials	1
4.2 Terminals	2
4.3 Cables	2
4.4 Fuses	2
4.5 Identification of cables	2
5 Location of receptacle on machine	2

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 11862 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Sub-Committee SC 3, *Operation and maintenance*.

Currently in preview, click buy full version.

Australian Standard[®]

Earth-moving machinery — Auxiliary starting aid electrical connector

1 Scope

This International Standard specifies the details, dimensions and design of both plug (male) and receptacle (female) which must mate properly to permit interchangeable use of different makes of electrical connectors providing an auxiliary starting circuit for earth-moving machinery as defined in ISO 6165. It lays down a universal connecting device, with correct polarity, standard circuit coding and protection from electrical shorts, which may also be used with any other machinery, vehicle or automotive equipment with the same electrical system voltage range.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 6165:1987, *Earth-moving machinery — Basic types — Vocabulary*.

ISO 9247:1990, *Earth-moving machinery — Electrical wires and cables — Principles of identification and marking*.

IEC 228:1978, *Conductors of insulated cables*.

IEC 245-4:1980, *Rubber insulated cables of rated voltages up to and including 450/750 V — Part 4: Cords and flexible cables*.

IEC 269-1:1986, *Low-voltage fuses — Part 1: General requirements*.

3 General requirements

3.1 Receptacle

The receptacle assembly shall be as shown in [figure 1](#) and shall be permanently installed in a machine. The receptacle contains three male terminals [see [figure 3 b](#)]; the configuration shall provide positive means of ensuring correct polarity when coupled with the mating plug.

3.2 Plug assembly

The plug assembly shall be as shown in [figure 2](#); it provides auxiliary starting from one machine to another [see [figure 2 a](#)], or from an external power source, such as a battery cart, to the machine [see [figure 2 b](#)]. The plug contains the female terminals [see [figure 3 a](#)] and mates with the receptacle assembly in [3.1](#).

4 Construction

4.1 Materials

Connector bodies shall be made of glass-fibre-reinforced nylon or other mouldable insulating material of equal or superior properties. The contact parts shall be coated to ensure low deterioration and low electrical resistance.