

AS ISO 12117.2:2020
ISO 12117-2:2008
ISO 12117-2:2008/Cor 1:2010
ISO 12117-2:2008/Amd 1:2016



STANDARDS
Australia



Earth-moving machinery — Laboratory tests and performance requirements for protective structures of excavators

Part 2: Roll-over protective structures (ROPS) for excavators of over 6 t



currently in review, click buy full version

AS ISO 12117.2:2020

This Australian Standard® was prepared by ME-063, Earthmoving Equipment. It was approved on behalf of the Council of Standards Australia on 30 October 2020.

This Standard was published on 13 November 2020.

The following are represented on Committee ME-063:

Australian Industry Group
Better Regulation Division — SafeWork NSW
Construction and Mining Equipment Industry Group
Department of Natural Resources, Mines and Energy, Qld
Department of Regional NSW
Engineers Australia / Mining Electrical and Mining Mechanical Engineering Society
Institute of Instrumentation, Control & Automation Australia
Minerals Council of Australia
University of Queensland

This Standard was issued in draft form for comment as DR AS ISO 12117.2:2020.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 042 7

Earth-moving machinery — Laboratory tests and performance requirements for protective structures of excavators

Part 2: Roll-over protective structures (ROPS) for excavators of over 6 t

First published as AS ISO 12117.2:2020.

COPYRIGHT

© ISO 2020 — All rights reserved
© Standards Australia Limited 2020

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee ME-063, Earthmoving Equipment.

The objective of this document is to establish a consistent and reproducible means of evaluating the load-carrying characteristics of roll-over protective structures (ROPS) for excavators under static loading, and prescribes performance requirements of a representative specimen under such loading. ROPS are to be used where the risk of roll-over exists.

This document applies to ROPS of hydraulic excavators as defined in ISO 6165 with a mass of over 6 t and less than 50 t. It also applies to ROPS for excavator-based or derivated excavators used in object or material handling, demolition or with attachments such as in log-handling and forestry applications.

This document does not apply to excavators with elevating cab risers.

This document is identical with, and has been reproduced from, ISO 12117-2:2008, *Earthmoving machinery — Laboratory tests and performance requirements for protective structures of excavators — Part 2: Roll-over protective structures (ROPS) for excavators of over 6 t*, its Corrigendum 1 (2010), and Amendment 1 (2016), which have been added at the end of the source text.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this part of ISO 12117” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal number.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	6
5 Test method and facilities	12
5.1 General	12
5.2 Instrumentation	13
5.3 Test facilities	13
5.4 ROPS-revolving frame assembly and attachment to bedplate	13
6 Test loading procedure	14
6.1 General	14
6.2 Lateral loading	15
6.3 Longitudinal loading for ROPS	16
6.4 Vertical loading onto ROPS	19
7 Material temperature criteria	20
8 Acceptance criteria	21
9 Labelling of the ROPS	25
9.1 General	25
9.2 Label specifications	26
9.3 Label content	26
10 Reported results	26
11 Operator's manual	26
Annex A (normative) Test report for ROPS conforming to ISO 12117-2	27
Annex B (informative) Design changes, physical testing and alterations	30
Annex C (informative) Rationale — ROPS performance requirements	31
Bibliography	34
Technical corrigendum 1	35
Amendment 1	36

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 2.

The main task of technical committees is to prepare International Standards. Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights.

ISO 12117-2 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Subcommittee SC 2, *Safety, ergonomics and general requirements*.

ISO 12117 consists of the following parts, under the general title *Earth-moving machinery — Laboratory tests and performance requirements for protective structures of excavators*:

- Part 1: *Tip over protective structures (TOPS) for compact excavators*
- Part 2: *Roll-over protective structures (ROPS) for excavators of over 6 t*

Introduction

It was long thought that hydraulic excavators did not overturn as easily as other earth-moving machines because their large attachments support the machine bodies once they start inclining. However, in some regions of the world, accident data have shown a need for roll-over protection of hydraulic excavators. Standardization was thus needed.

This part of ISO 12117 provides a test method for roll-over protective structures (ROPS) for hydraulic excavators of over 6 t used in earth-moving. Unlike the machines covered by ISO 3471, hydraulic excavators feature large attachments which affect the required performance capability of the ROPS. Therefore, the test method and criteria required for hydraulic excavators are different from those needed for the other earth-moving machines.

It is also applicable to hydraulic excavators used in forestry applications. The criteria of ROPS for hydraulic excavators, used in forestry, with cab riser, have been included for information.

Currently in preview, click buy full version.

NOTES

Currently in preview, click buy full version

Australian Standard®

Earth-moving machinery — Laboratory tests and performance requirements for protective structures of excavators

Part 2: Roll—over protective structures (ROPS) for excavators of over 6 t

1 Scope

This part of ISO 12117 establishes a consistent and reproducible means of evaluating the load-carrying characteristics of roll-over protective structures (ROPS) for excavators under static loading, and prescribes performance requirements of a representative specimen under such loading.

It applies to ROPS of hydraulic excavators as defined in ISO 6165 with a mass of over 6 t and less than 50 t. ROPS will ensure minimum crush protection space for a seat-belted operator when the machine rolls 360° about longitudinal axis of its revolving frames without losing contact with a hard clay slope of less than 30°. ROPS is to be applied where the risk of roll-over exists.

It also applies to ROPS for excavator-based or derivated excavators used in object or material handling, demolition or with attachments such as magnets, clamshell, grab or multi-claw grab.

It does not apply to excavators with elevating cab risers.

NOTE This part of ISO 12117 is intended to be applied to excavators having a gross operating mass up to 50 000 kg due to the limitation of the experimental and statistical data set used to derive acceptance criteria. This does not preclude the possibility of applying the procedure described in this part of ISO 12117 to excavators having larger or smaller masses, with the exclusion of excavators specially designed for mining application, where the requirements may lead to impractical design.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendment) applies.

ISO 3164, *Earth-moving machinery — Laboratory evaluations of protective structures — Specifications for deflection-limiting volume*

ISO 5353, *Earth-moving machinery, and tractors and machinery for agriculture and forestry — Seat index point*

ISO 6165, *Earth-moving machinery — Basic types — Identification and terms and definitions*

ISO 9248, *Earth-moving machinery — Units for dimensions, performance and capacities, and their measurement accuracies*

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

3.1

attachment

assembly of components that can be mounted onto the base machine or equipment for specific use

[SOURCE: ISO 6016:—, definition 3.1.4]