

Australian Standard[®]

**Graphic technology—Process control
for the production of half-tone colour
separations, proof and production prints**

**Part 1: Parameters and measurement
methods**

STANDARDS
Australia



This Australian Standard® was prepared by Committee EX-004, Graphic Technology. It was approved on behalf of the Council of Standards Australia on 13 January 2012. This Standard was published on 31 January 2012.

The following are represented on Committee EX-004:

- Australian Paper Industry
 - Lithographic Institute of Australia, NSW
 - Printing Industries Association of Australia
 - TAFE NSW
-

This Standard was issued in draft form for comment as DP A/NZS 12647.1.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through the public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard[®]

**Graphic technology—Process control
for the production of multi-tone colour
separations, proof and production prints**

**Part 1: Parameters and measurement
methods**

First published as AS ISO 12647.1:2012.

COPYRIGHT

© Standards Australia Limited

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968.

Published by SAI Global Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia

ISBN 978 1 74342 019 5

PREFACE

This Standard was prepared by the Standards Australia Committee EX-004, Graphic Technology.

The objective of this Standard is to list and explain the minimum set of primary process parameters required to uniquely define the visual characteristics and related technical properties of a proof or production print produced directly from digital data or from a set of half-tone separation films.

This Standard is identical with, and has been reproduced from ISO 12647-1:2004, *Graphic technology—Process control for the production of half-tone colour separations, proof and production prints—Part 1: Parameters and measurement methods*.

As this Standard is reproduced from an International Standard, the following applies:

- (a) Its number appears on the cover and title page while the International Standard number appears only on the cover.
- (b) In the source text ‘this part of ISO 12647’ should read ‘this part of AS ISO 12647’.
- (c) A full point substitutes for a comma when referring to a decimal marker.

None of the normative references in the source document have been adopted as Australian or Australian/New Zealand Standards.

The terms ‘normative’ and ‘informative’ have been used in this Standard to define the application of the annex to which they apply. A ‘normative’ annex is an integral part of a Standard, whereas an ‘informative’ annex is only for information and guidance.

CONTENTS

	<i>Page</i>
1	Scope..... 1
2	Normative references 1
3	Terms and definitions..... 2
4	Requirements 9
4.1	General 9
4.2	Data file, colour separation films and printing formes 9
4.3	Proof or production print 11
5	Test methods 13
5.1	Screen angles 13
5.2	Tone value on a colour-separation film or of a data file 14
5.3	Tone value on the print..... 14
5.4	Tone value increase on the print..... 15
5.5	Gloss 15
5.6	Spectral measurement, computation of CIELAB colour co-ordinates and CIELAB colour differences 15
Annex A (normative)	Reporting 17
Annex B (informative)	Determination of quality parameters of half-tone dots on a colour separation film..... 19
Bibliography 21

INTRODUCTION

When producing a colour reproduction, it is important that the persons responsible for colour separation, proofing and printing operations have previously agreed on a minimum set of parameters that uniquely defines the visual characteristics and other technical properties of the planned print product. Such an agreement enables the correct production of suitable separations (without recourse to “trial-and-error”) and subsequent production of analogue or digital off-press or on-press proof prints from these separations whose purpose is to simulate the visual characteristics of the finished print product as closely as possible.

It is the purpose of this part of ISO 12647 to list and explain the minimum set of primary process parameters (see below) required to uniquely define the visual characteristics and related technical properties of a proof or production print produced directly from digital data or from a set of half-tone separation films. Other parts of ISO 12647 define specific values for these parameters that are appropriate for specific processes (such as lithography, gravure, flexography, screen printing). For some processes certain parameters are more significant than others and may be specified as mandatory while the remainder are optional. However, in this part of ISO 12647, all parameters are treated equally.

Primary parameters are defined here as having a direct bearing on the visual characteristics of the image; secondary parameters are defined as those which may influence the image indirectly by changing the values of primary parameters. Secondary parameters include

- colour separation film thickness;
- image orientation (wrong-reading or right-reading);
- film polarity (negative or positive);
- roughness of the film emulsion surface;
- presence of colour marking or register marks;
- printing sequence.

Where necessary for specific process applications, secondary parameters and further related details may be specified in addition to primary parameters, but they are not included in this part of ISO 12647 except in the definitions.

During the process of colour separation for multi-colour printing, a digital data set comprising CMYK tone values ready for printing is normally produced from digital data that relate to a multi-coloured continuous-tone original. This usually consists of a photographic transparency or a reflection copy print, although any multicoloured graphic in analogue or digital form may be used as input.

The majority of printing processes covered by ISO 12647 requires continuous-tone images to be broken up into half-tone screens before they can be put on a printing forme. However, there are new processes like digital offset that do not require screening. For these processes, this part of ISO 12647 may be equally applied, with the exception of the specifications for screen width, screen angle, half-tone dot shape and, of course, film quality. It should be noted that a number of off-press proofing systems produce images without recourse to half-toning. In this case, the proof cannot be used to predict artefacts like moiré that may be caused by interferences between periodic structures of the image and half-tones used in production printing.

The process of colour separation does not provide a unique transformation of the colour values of the original into those of the production print. For every distinguishable spot of the original, the colour (characterizable by three colorimetric values, e.g. X , Y , Z or L^* , a^* , b^* or hue, saturation and lightness) has to be separated into tone values for four or more process colours. However, in most cases, the density range (and, hence, the

colour gamut) of the original is wider than that achievable in printing. As a result, the classical colour separation process requires some degree of interpretation of the original by the operator and the resultant transformation may differ from one original to another. With ICC colour management, the mentioned ambiguity is reduced to vendor-specific options for the user; within a given option set the results are reproducible. A further source of variation is the degree and manner by which the achromatic component of a colour is generated with black ink rather than by a suitable mix of the chromatic inks. Here again, a number of options exist, which may to some degree be vendor-specific.

Whatever freedom exists for the colour separation process, it is important that it take account of the values of the process parameters of the printing condition to be used for production. This is because the process steps that follow colour separation, namely output on film (if required), proofing (on- or off-press), the production of the printing forme (if required), production printing and print surface finishing, are normally carried out with a rigid set of process parameters which include

- the properties of the print substrate;
- the optical properties of solid prints of the process inks;
- the tone value increase curve.

Maintaining consistent values for the parameters at all steps in the process is important to ensure predictable reproduction. Any unforeseen variation of these values is usually to the detriment of the visual characteristics of the image.

The technical background discussed so far shows that the processes of colour separation and proofing require prior knowledge of the values of the process parameters encountered in production printing. It is virtually impossible to print all jobs with the same set of process parameters, irrespective of the type of printing press or digital printing unit, printing forme, printing ink, print substrate, or surface finishing used. Therefore, there has to be an efficient information exchange between the pre-press service provider, the proof printer and the production printer which defines the specific parameters for the job.

To facilitate the information interchange, this part of ISO 12647 defines a complete set of parameters whose values should be specified as a minimum when a pre-press job consisting of a digital file or a set of colour-separation films, both with accompanying proof print, is being ordered. Specific values for each parameter are assigned in other parts of ISO 12647; this part is only concerned with definitions, principal requirements, reporting and test methods.

Because the proof print is the principal means of communication between pre-press, print-buyer and printer, it is important that

- the proof print be made using the best achievable simulation of the intended printing condition, and
- production printing attempt to match the visual characteristics of the approved proof print.

One of the major variations between and within printing processes is between tone-value-increase curves (formerly “dot gain curves”), examples of which are shown schematically in Figure 1. One such curve, with appropriate tolerances, may be specified for every process colour, for each specific combination of print substrate type and printing process.

AUSTRALIAN STANDARD

Graphic technology—Process control for the production of half-tone colour separations, proof and production prints**Part 1:
Parameters and measurement methods****1 Scope**

This and other parts of ISO 12647 specify parameters that define printing conditions for the various processes used in the graphic arts industry. Practitioners wishing to work to common goals may use the values of the parameters specified in the exchange of data to characterize the intended printing condition and/or for the process control of printing.

This part of ISO 12647

- defines vocabulary and establishes a minimum set of process parameters that uniquely determine a printed four-colour half-tone image (which are also referenced in other parts of ISO 12647). The parameters were selected based on the following process steps “colour separation”, “making of the printing forme”, “proofing”, “production printing” and “surface finishing”. These are directly applicable to proofing and printing processes that use colour separation films as input;
- is directly applicable to proofing and printing from printing surfaces produced by filmless methods as long as direct analogies to film production systems are maintained;
- is applicable to proofing and printing with more than four process colours as long as direct analogies to four-colour printing are maintained, such as for data and screening, for print substrates and printing parameters;
- is applicable to line screens and, where relevant, to those that do not have regular screen angles or regular screen rulings.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 520, *Photography — Density measurements — Part 2: Geometric conditions for transmission density*

ISO 521, *Photography — Density measurement — Part 3: Spectral conditions*

ISO 524, *Photography — Density measurements — Part 4: Geometric conditions for reflection density*

ISO 13655, *Graphic technology — Spectral measurement and colorimetric computation for graphic arts images*