



**Transportable gas storage devices
— Hydrogen absorbed in reversible
metal hydride**

STANDARDS
Australia



Currently in preview, click buy full version

AS ISO 16111:2020

This Australian Standard® was prepared by ME-093, Hydrogen Technologies. It was approved on behalf of the Council of Standards Australia on 20 May 2020.

This Standard was published on 29 May 2020.

The following are represented on Committee ME-093:

Association of Accredited Certification Bodies
Australasian Fire and Emergency Service Authorities Council
Australia New Zealand Industrial Gas Association
Australian Energy Market Operator
Australian Gas Association
Australian Hydrogen Council
Australian Industry Group
Australian Pipelines and Gas Association
Chemistry Australia
CSIRO
Department of Infrastructure, Regional Development and Cities
Energy Networks Australia
Engineers Australia
Future Fuels Cooperative Research Centre
Gas Appliance Manufacturers Association of Australia
Gas Energy Australia
Gas Technical Regulators Committee
Institute of Chemical Engineers
Institute of Electrical Inspectors
National Energy Resources Australia
University of Adelaide

This Standard was issued in draft form for comment as DR AS ISO 16111:2020.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76072 858 8



Transportable gas storage devices — Hydrogen absorbed in reversible metal hydride

First published as AS ISO 16111:2020.

COPYRIGHT

© ISO 2020 — All rights reserved
© Standards Australia Limited 2020

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee ME-093, Hydrogen Technologies.

The objective of this document is to define the requirements applicable to the material, design, construction, and testing of transportable hydrogen gas storage systems, referred to as "metal hydride assemblies" (MH assemblies) which utilize shells not exceeding 150 L internal volume and having a maximum developed pressure (MDP) not exceeding 25 MPa.

This document is applicable to refillable storage MH assemblies where hydrogen is the only transferred media.

This document is not applicable to storage MH assemblies intended to be used as fixed fuel-storage onboard hydrogen fuelled vehicles.

This document is identical with, and has been reproduced from, ISO 16111:2018, *Transportable gas storage devices — Hydrogen absorbed in reversible metal hydride*.

As this document has been reproduced from an International Standard, a full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical or options of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms "normative" and "informative" are used in Standards to define the application of the appendices or annexes to which they apply. A "normative" appendix or annex is an integral part of a Standard, whereas an "informative" appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	v
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	2
4 Service conditions	4
4.1 Pressures	4
4.1.1 Maximum developed pressure (MDP)	4
4.1.2 Rated charging pressure (RCP)	4
4.1.3 Stress level at MDP	4
4.2 Rated capacity	4
4.3 Temperature ranges	5
4.3.1 Operating temperature range	5
4.3.2 Service temperature range	5
4.4 Environmental conditions	5
4.5 Service life	5
4.6 Hydrogen quality	5
4.7 Special service conditions	5
5 Design considerations	5
5.1 General	5
5.2 Material selection	5
5.2.1 General	5
5.2.2 External surfaces	6
5.2.3 Compatibility	6
5.2.4 Temperature	6
5.3 Shell design	6
5.3.1 Shells with internal volume greater than 120 ml	6
5.3.2 Shells with internal volume of 120 ml or less	7
5.4 Design strength	7
5.5 Overpressure and fire protection	7
5.5.1 General	7
5.5.2 PPR activation pressure	8
5.5.3 PPD activation temperature	8
5.6 Loading of hydrogen absorbing alloy	8
5.7 Shut-off valves	8
5.7.1 General	8
5.7.2 MH assemblies with internal volume greater than 120 ml	8
5.7.3 MH assemblies with internal volume of 120 ml or less	9
5.7.4 Integral shut-off valve protection	10
5.7.5 Removable shut-off valve protection	10
5.8 Actively cooled MH assemblies	10
5.9 Particulate containment	10
6 Inspection and testing	10
6.1 General	10
6.2 Type/qualification tests	10
6.2.1 General	10
6.2.2 Fire test	11
6.2.3 Initial burst tests for MH assemblies with an internal volume of 120 ml or less	13
6.2.4 Drop or impact test	13
6.2.5 Leak test	17

6.2.6	Hydrogen cycling and strain measurement test.....	17
6.2.7	Shut-off valve impact test.....	21
6.2.8	Thermal cycling test.....	22
6.2.9	Type test reports.....	23
6.3	Batch tests.....	23
6.3.1	General requirements.....	23
6.3.2	Burst test for shell-batch.....	24
6.3.3	MDP Test for hydride-batch.....	24
6.4	Routine tests and inspections.....	24
6.4.1	Routine tests.....	24
6.4.2	Certificates of manufacture.....	24
7	Marking, labelling, and documentation.....	25
7.1	Marking.....	25
7.2	Labelling.....	25
7.2.1	General.....	25
7.2.2	Hazards associated with the solid materials.....	25
7.2.3	Labelling concerning removable valve protection.....	25
7.2.4	Temperature warning labelling.....	25
8	Documentation accompanying the product.....	26
8.1	Safety data sheets.....	26
8.2	User's or operating manual.....	26
8.2.1	General.....	26
8.2.2	Initial fill and refill procedures.....	26
Annex A	(informative) Material compatibility for hydrogen service.....	28
Annex B	(normative) Environmental tests.....	31
Annex C	(informative) Type approval certificate.....	37
Annex D	(informative) Acceptance certificate.....	39
Bibliography	42

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the voluntary nature of standards, the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the World Trade Organization (WTO) principles in the Technical Barriers to Trade (TBT) see www.iso.org/iso/foreword.html.

This document was prepared by ISO/TC 197, *Hydrogen technologies*.

This second edition cancels and replaces the first edition (ISO 16111:2008), which has been technically revised.

The following clauses have been modified with respect to the previous edition: [2](#); [3.4](#); [3.5](#); [3.9](#); [3.10](#); [3.11](#); [3.12](#); [3.13](#); [3.14](#); [3.15](#); [3.16](#); [3.17](#); [3.18](#); [3.19](#); [3.20](#); [3.21](#); [3.22](#); [4.1](#); [4.3](#); [5.2.1](#); [5.3](#); [5.5](#); [5.8](#); [6.2](#); [6.3](#); [7.2](#); [8.1](#) and [Annex D](#).

The main changes compared to the previous edition concern the following:

- service temperature conditions have been described in further detail ([4.3.2](#));
- shell design has been extended to ISO 11119-3 standard reference ([5.3](#));
- drop test conditions have been modified ([6.2.4](#));
- acceptance criteria have been modified for leak testing ([6.2.5](#));
- hydrogen cycling conditions have been modified ([6.2.6](#));
- new warning labelling has been proposed ([7.2](#));
- information in safety data sheets has been updated ([8.1](#)).

Any feedback or questions on this document should be directed to the user's national standards body. A complete listing of these bodies can be found at www.iso.org/members.html.

Introduction

As the utilization of gaseous hydrogen evolves from the chemical industry into various emerging applications, such as fuel for fuel cells and internal combustion engines and other specialty hydrogen applications, the importance of new and improved storage techniques has become essential. One of these techniques employs the absorption of hydrogen into specially formulated alloys. The material can be stored and transported in a solid form, and the hydrogen later released and used under specific thermodynamic conditions. This document describes the service conditions, design criteria, type tests, batch tests and routine tests for transportable hydride-based hydrogen storage systems, referred to as “metal hydride assemblies” (MH assemblies). Types of MH assemblies may serve as: fuel cell cartridges; hydrogen fuel storage containers; high-purity hydrogen supplies as well as other uses.

Currently in preview, click buy full version.

Australian Standard®

Transportable gas storage devices — Hydrogen absorbed in reversible metal hydride

1 Scope

This document defines the requirements applicable to the material, design, construction, and testing of transportable hydrogen gas storage systems, referred to as “metal hydride assemblies” (MH assemblies), which utilize shells not exceeding 150 l internal volume and having a maximum developed pressure (MDP) not exceeding 25 MPa.

This document is applicable to refillable storage MH assemblies where hydrogen is the only transferred media. It is not applicable to storage MH assemblies intended to be used as fixed fuel-storage onboard hydrogen fuelled vehicles.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 7225, *Gas cylinders — Precautionary labels*

ISO 7866, *Gas cylinders — Refillable seamless aluminium alloy gas cylinders — Design, construction and testing*

ISO 9809-1, *Gas cylinders — Refillable seamless steel gas cylinders — Design, construction and testing — Part 1: Quenched and tempered steel cylinders with tensile strength less than 1 100 MPa*

ISO 9809-2, *Gas cylinders — Refillable seamless steel gas cylinders — Design, construction and testing — Part 2: Quenched and tempered steel cylinders with tensile strength greater than or equal to 1 100 MPa*

ISO 9809-3, *Gas cylinders — Refillable seamless steel gas cylinders — Design, construction and testing — Part 3: Normalized steel cylinders*

ISO 10297:2014, *Gas cylinders — Cylinder valves — Specification and type testing*

ISO 11114-1, *Gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 1: Metallic materials*

ISO 11114-2, *Gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 2: Non-metallic materials*

ISO 11114-4, *Transportable gas cylinders — Compatibility of cylinder and valve materials with gas contents — Part 4: Test methods for selecting steels resistant to hydrogen embrittlement*

ISO 11119-1, *Gas cylinders — Refillable composite gas cylinders and tubes — Design, construction and testing — Part 1: Hoop wrapped fibre reinforced composite gas cylinders and tubes up to 450 l*

ISO 11119-2:2012, *Gas cylinders — Refillable composite gas cylinders and tubes — Design, construction and testing — Part 2: Fully wrapped fibre reinforced composite gas cylinders and tubes up to 450 l with load-sharing metal liners*

ISO 11119-3, *Gas cylinders — Refillable composite gas cylinders and tubes — Design, construction and testing — Part 3: Fully wrapped fibre reinforced composite gas cylinders and tubes up to 450L with non-load-sharing metallic or non-metallic liners*

ISO 14246, *Gas cylinders — Cylinder valves — Manufacturing tests and examinations*

ISO 14687 (all parts), *Hydrogen fuel — Product specification*