



Industrial trucks—Verification of stability

Part 1: General



Currently in preview, click buy full version

AS ISO 22915.1:2018

This Australian Standard® was prepared by ME-026, Industrial Trucks. It was approved on behalf of the Council of Standards Australia on 6 September 2018.

This Standard was published on 21 September 2018.

The following are represented on Committee ME-026:

- Australian Industrial Truck Association
- Australian Industry Group
- Construction and Mining Equipment Industry Group
- Hire and Rental Industry Association of Australia
- Safety Institute of Australia
- SafeWork NSW
- Telescopic Handler Association of Australia
- WorkSafe Victoria

This Standard was issued in draft form for comment as DR AS ISO 22915.1:2018.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

www.saiglobal.com (sales and distribution)

ISBN 978 1 76072 179 4



Industrial trucks—Verification of stability

Part 1: General

First published as AS ISO 22915.1:2015.
Second edition 2018.

COPYRIGHT

© ISO 2018 — All rights reserved
© Standards Australia Limited 2018

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Published by SAI Global Pty Limited under licence from Standards Australia Limited, GPO Box 476, Sydney, NSW 2001, Australia.

Preface

This Standard was prepared by the Standards Australia Committee ME-026, Industrial Trucks, to supersede AS ISO 22915.1:2015.

The objective of this Standard is to specify basic test criteria and requirements for verifying the stability of industrial trucks, hereafter referred to as trucks.

This Standard applies to the following truck types and special conditions:

- (a) Counterbalanced trucks with mast as specified in AS ISO 22915.2.
- (b) Reach and straddle trucks as specified in AS ISO 22915.3.
- (c) Pallet stackers, double stackers, and order-picking trucks with operator position elevating up to and including 1 200 mm lift height as specified in AS ISO 22915.4.
- (d) Single-side-loading trucks as specified in ISO 22915-5.
- (e) Bidirectional and multidirectional trucks as specified in ISO 22915-7.
- (f) Additional stability test for trucks operating in special conditions of stacking with mast tilted forward and load elevated as specified in ISO 22915-8.
- (g) Counterbalanced trucks with mast handling freight containers of 6 m (20 ft) length and longer as specified in AS ISO 22915.9. (Proposed adoption under preparation.)
- (h) Additional stability test for trucks operating in special conditions with the load substantially laterally displaced by powered devices as specified in AS ISO 22915.10. (Proposed adoption under preparation.)
- (i) Industrial variable-reach trucks as specified in AS ISO 22915.11.
- (j) Industrial variable-reach trucks handling freight containers of 6 m (20 ft) length and longer as specified in AS ISO 22915.12. (Proposed adoption under preparation.)
- (k) Rough-terrain trucks with mast as specified in AS ISO 22915.13.
- (l) Rough-terrain variable-reach trucks as specified in AS ISO 22915.14;
- (m) Counterbalanced trucks with articulated steering as specified in ISO 22915-15.
- (n) Pedestrian-propelled trucks as specified in AS ISO 22915.16.
- (o) Additional stability test for trucks operating in the special condition of offset load, offset determined by utilization as specified in AS ISO 22915.20.
- (p) Order-picking trucks with operator position elevating above 1 200 mm as specified in AS ISO 22915.21.
- (q) Lateral and front-stacking trucks with and without elevating operator position as specified in AS ISO 22915.22.

This Standard is identical with, and has been reproduced from, ISO 22915-1:2016, *Industrial trucks — Verification of stability — Part 1: General*.

As this document has been reproduced from an International Standard, a full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

Contents

Preface	ii
Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	2
3 Terms and definitions	2
4 Stability tests for trucks	4
4.1 Test procedure	4
4.2 Verification procedure	4
4.2.1 Operation of the tilt table and test criteria	4
4.2.2 Calculation	4
4.2.3 Other methods	4
4.3 Test conditions	4
4.3.1 Condition of the truck	4
4.3.2 Position of the truck on the tilt table	5
4.3.3 Test load, lift height, and standard load centre of gravity	5
4.4 Safety precautions for testing	6
4.5 Stability verification for trucks with attachments	7
Bibliography	8

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

The procedures used to develop this document and those intended for its further maintenance are described in the ISO/IEC Directives, Part 1. In particular the different approval criteria needed for the different types of ISO documents should be noted. This document was drafted in accordance with the editorial rules of the ISO/IEC Directives, Part 2 (see www.iso.org/directives).

Attention is drawn to the possibility that some of the elements of this document may be the subject of patent rights. ISO shall not be held responsible for identifying any or all such patent rights. Details of any patent rights identified during the development of the document will be in the Introduction and/or on the ISO list of patent declarations received (see www.iso.org/patents).

Any trade name used in this document is information given for the convenience of users and does not constitute an endorsement.

For an explanation on the meaning of ISO specific terms and expressions related to conformity assessment, as well as information about ISO's adherence to the WTO principles in the Technical Barriers to Trade (TBT) see the following URL: [Foreword - Supplementary information](#)

The committee responsible for this document is ISO/TC 110, *Industrial trucks*, Subcommittee SC 2, *Safety of powered industrial trucks*.

This second edition cancels and replaces the first edition (ISO 22915-1:2008), which has been technically revised.

ISO 22915 consists of the following parts, under the general title *Industrial trucks — Verification of stability*:

- Part 1: *General*
- Part 2: *Counterbalanced trucks with mast*
- Part 3: *Reach and straddle trucks*
- Part 4: *Pallet stackers, double stackers and order-picking trucks with operator position elevating up to and including 1 200 mm lift height*
- Part 5: *Single-side loading trucks*
- Part 7: *Bidirectional and multidirectional trucks*
- Part 8: *Additional stability test for trucks operating in the special condition of stacking with mast tilted forward and load elevated*
- Part 9: *Counterbalanced trucks with mast handling freight containers of 6 m (20 ft) length and longer*
- Part 10: *Additional stability test for trucks operating in the special condition of stacking with load laterally displaced by powered devices*
- Part 11: *Industrial variable-reach trucks*
- Part 12: *Industrial variable-reach trucks handling freight containers of 6 m (20 ft) length and longer*
- Part 13: *Rough-terrain trucks with mast*

- *Part 14: Rough-terrain variable-reach trucks*
- *Part 15: Counterbalanced trucks with articulated steering*
- *Part 16: Pedestrian-propelled trucks*
- *Part 20: Additional stability test for trucks operating in the special condition of offset load, offset by utilization*
- *Part 21: Order-picking trucks with operator position elevating above 1 200 mm*
- *Part 22: Lateral- and front-stacking trucks with and without elevating operator position*
- *Part 24: Slewing variable-reach rough-terrain trucks*

Currently in preview, click buy full version

Introduction

An important step forward in work on the ISO 22915 series was the agreement to put in place a new structure. The stability tests are presented in the form of a basic part describing and defining stability tests in general together with separate parts that each give specific stability test criteria and requirements for a different truck type.

From the very beginning, the task of the Working Group involved was to establish the new structure and revise existing standards to create a series of International Standards complying with the major legislative regulations in the world such as those in force in the EU, USA, Japan, and Australia.

For several problem areas, compromises were needed and will be needed in the future. In order to ensure that these International Standards are actively used in the ISO member countries worldwide, it will be necessary that they replace existing National Standards.

Only in this way will there will be the guarantee that products in accordance with these International Standards can be shipped worldwide, freely and without any technical barriers to trade.

Australian Standard®

Industrial trucks—Verification of stability

Part 1: General

1 Scope

The ISO 22915 series deals with the safety of industrial trucks, as defined in ISO 5053-1, relative to their stability and the verification of that stability. For the purposes of ISO 22915, industrial trucks are wheeled, self-propelled, or pedestrian-propelled vehicles excepting those running on rails. They are either operator-controlled or driverless, and are designed to carry, tow, push, lift, stack or tier in racks.

This part of ISO 22915 specifies basic test criteria and requirements for verifying the stability of industrial trucks, hereafter referred to as *trucks*.

It applies to the following truck types and special conditions:

- a) counterbalanced trucks with mast as specified in ISO 22915-2;
- b) reach and straddle trucks as specified in ISO 22915-3;
- c) pallet stackers, double stackers, and order-picking trucks with operator position elevating up to and including 1 200 mm lift height as specified in ISO 22915-4;
- d) single-side-loading trucks as specified in ISO 22915-5;
- e) bidirectional and multidirectional trucks as specified in ISO 22915-7;
- f) additional stability test for trucks operating in special conditions of stacking with the mast tilted forward as specified in ISO 22915-8;
- g) counterbalanced trucks with mast handling freight containers of 6 m (20 ft) length and longer as specified in ISO 22915-9;
- h) additional stability test for trucks operating in special conditions with the load substantially laterally displaced by powered devices as specified in ISO 22915-10;
- i) industrial variable-reach trucks as specified in ISO 22915-11;
- j) industrial variable-reach trucks handling freight containers of 6 m (20 ft) length and longer as specified in ISO 22915-12;
- k) rough-terrain variable-reach trucks as specified in ISO 22915-14;
- l) counterbalanced trucks with articulated steering as specified in ISO 22915-15;
- m) pedestrian-propelled trucks as specified in ISO 22915-16;
- n) additional stability test for trucks operating in the special condition of offset load, offset determined by utilization as specified in ISO 22915-20;
- o) order-picking trucks with operator position elevating above 1 200 mm as specified in ISO 22915-21.

It also applies to trucks operating under the same conditions when equipped with load-handling attachments.

This part of ISO 22915 does not apply to the following:

- trucks handling suspended loads which may swing freely;
- low-lift trucks with lift height up to and including 500 mm.