

Australian Standard[®]

**Buried, high-impact poly(vinyl chloride)
(PVC-HI) piping systems for the supply
of gaseous fuels**

**Part 2: Fittings for a maximum
operating pressure of 200 mbar (20 kPa)**

STANDARDS
Australia



This Australian Standard® was prepared by Committee PL-021, PVC, ABS and Polyamide Pipe Systems. It was approved on behalf of the Council of Standards Australia on 9 March 2007.

This Standard was published on 12 July 2007.

The following are represented on Committee PL-021:

- Australian Chamber of Commerce and Industry
 - CSIRO Manufacturing and Materials Technology
 - Certification Interests
 - Energy Networks Association
 - Engineers Australia
 - Local Government New Zealand
 - Master Plumbers, Gasfitters and Drainlayers New Zealand
 - New Zealand Water and Waste Association
 - Plastic Industry Pipe Association of Australia
 - Plastics New Zealand
 - Water Services Association of Australia
-

This Standard was issued in draft form for comment as DR 06621.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through public comment received.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting www.standards.org.au

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

STANDARDS AUSTRALIA

RECONFIRMATION

OF

AS ISO 6993.2—2007

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels

Part 2: Fittings for a maximum operating pressure of 200 mbar (20 kPa)

RECONFIRMATION NOTICE

Technical Committee PL-021 has reviewed the content of this publication and in accordance with Standards Australia procedures for reconfirmation, it has been determined that the publication is still valid and does not require change.

Certain documents referenced in the publication may have been amended since the original date of publication. Users are advised to ensure that they are using the latest versions of such documents as appropriate, unless advised otherwise in this Reconfirmation Notice.

Approved for reconfirmation in accordance with Standards Australia procedures for reconfirmation on 27 April 2017.

The following are represented on Technical Committee PL-021:

Association of Accredited Certification Bodies
Australian Building Codes Board
Chemistry Australia
Energy Networks Australia
Engineers Australia
Local Government New Zealand
New Zealand Employer and Manufacturers Association (Central)
Plastics Industry Pipe Association of Australia
Plastics New Zealand
Water New Zealand
Water Services Association of Australia

NOTES

Currently in preview, click buy full vers.

Australian Standard[®]

**Buried, high-impact poly(vinyl chloride)
(PVC-HI) piping systems for the supply
of gaseous fuels**

**Part 2: Fittings for a maximum
operating pressure of 200 mbar (20 kPa)**

First published as AS 1464.1—1974 and AS 1464.2—1974.
Second edition 1984.
Replaced by AS ISO 6993.2—2007.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia
ISBN 0 7337 8179 9

PREFACE

This Standard was prepared by Standards Australia's Committee PL-021, PVC, ABS and Polyamid Pipe Systems, to supersede (in part) the AS 1464 series *Plastics pipes and fittings for gas reticulation—Unplasticized PVC (UPVC)*.

The objective of this revision is to adopt the ISO 6993 series of Standards, *Buried, high-impact poly (vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels*.

This Standard is identical to and has been reproduced from ISO 6993-2:2006, *Buried, high-impact poly (vinyl chloride)(PVC-HI) piping systems for the supply of gaseous fuels—Part 2: Fittings for a maximum operating pressure of 200 mbar (20 kPa)*.

The other parts in this series of Australian Standards are the following:

AS ISO 6993 *Buried, high-impact poly (vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels*

AS ISO 6993.1 Part 1: *Pipes for a maximum operating pressure of 1 bar (100 kPa)* (adoption with modifications of ISO 6993-1:2006)

AS ISO 6993.3 Part 3: *Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)* (adoption of ISO 6993-3:2006)

NOTE: ISO 6993-4:2006 *Buried, high impact poly (vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels, Part 4: Code of practice for design, handling and installation* has not been adopted in this series of Australian Standards. The subject is covered by other existing Australian Standards, particularly AS 3723 *Installation and maintenance of plastic pipe systems for gas* and AS 5601 *Gas installations*.

As this Standard is reproduced from an international standard, the following applies:

- (a) Its number appears on the cover and title page while the international standard number appears only on the cover
- (b) In the source text 'ISO 6993-2' should read 'AS 6993.2'.
- (c) A full point substitutes for a comma when referring to a decimal marker.

References to International Standards should be replaced by references to Australian or Australian/New Zealand Standard, as follows:

Reference to International Standard	Australian/New Zealand Standard
ISO	AS/NZS
2507-1 Thermoplastics pipes and fittings— Vicat softening temperature Part 1: General test method	1462.5 Methods of test for plastics pipes and fittings Method 1: Vicat softening temperature
3126 Plastics piping systems—Plastics components—Determination of dimensions	1462.1 Methods of test for plastics pipes and fittings Method 2: Method for determining the dimensions of pipes and fittings

6993-1	Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa)	6993.1	Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels Part 1: Pipes for a maximum operating pressure of 1 bar (100 kPa)
9080	Plastics piping and ducting systems—Determination of the long-term hydrostatic strength of thermoplastics materials in pipe form by extrapolation	1462.29	Methods of test for plastics pipes and fittings—Plastics piping and ducting systems Method 29: Determination of the long-term hydrostatic strength of thermoplastics materials in pipe form by extrapolation (ISO 9080:2003, MOD)

The terms ‘normative’ and ‘informative’ are used to define the application of the annex to which they apply. A normative annex is an integral part of a standard, whereas an informative annex is only for information and guidance.

CONTENTS

	<i>Page</i>
1 Scope	1
2 Normative references	1
3 Terms, definitions, symbols and abbreviated terms	2
4 Material	2
5 General characteristics of fittings	3
6 Geometrical characteristics	3
7 Physical characteristics	3
8 Mechanical characteristics	8
9 General requirements for fittings	9
10 Performance requirements	9
11 Test methods	11
12 Marking	11
Annex A (normative) Determination of resistance to gas constituents	12
Annex B (normative) Determination of leaktightness of fitting joints by internal air pressure, with and without mechanical loading	14
Annex C (normative) Determination of leaktightness of fitting joints under negative pressure and mechanical loading	16
Bibliography	18

AUSTRALIAN STANDARD

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels —**Part 2:****Fittings for a maximum operating pressure of 200 mbar (20 kPa)****1 Scope**

This part of ISO 6993 gives the requirements for non-end load-bearing fittings made of high-impact poly(vinyl chloride) (PVC-HI) intended to be used for the supply of gaseous fuels through buried pipelines having an operating temperature range of 0 °C up to and including +30 °C and a maximum operating pressure of 200 mbar (20 kPa)¹⁾.

It is applicable only to fittings manufactured from the high-impact PVC materials PVC-A, PVC-CPE and PVC-EPR and having joints with elastomeric sealing elements. The fittings are suitable for those gases not containing potentially damaging components in such concentrations as to impair the properties of the fitting material.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 580:2005, *Plastics piping and ducting systems — Injection-moulded thermoplastics fittings — Methods for visually assessing the effects of heating*

ISO 2507-1, *Thermoplastics pipes and fittings — Vicat softening temperature — Part 1: General test method*

ISO 2507-2, *Thermoplastics pipes and fittings — Vicat softening temperature — Part 2: Test conditions for unplasticized poly(vinyl chloride) (PVC-U) or chlorinated poly(vinyl chloride) (PVC-C) pipes and fittings and for high impact resistance poly(vinyl chloride) (PVC-HI) pipes*

ISO 3126, *Plastics piping systems — Plastics components — Determination of dimensions*

ISO 3127, *Thermoplastics pipes — Determination of resistance to external blows — Round-the-clock method*

ISO 6993-2, *Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels — Part 2: Fittings for a maximum operating pressure of 1 bar (100 kPa)*

ISO 9080, *Plastics piping and ducting systems — Determination of the long-term hydrostatic strength of thermoplastics materials in pipe form by extrapolation*

EN 682:2002, *Elastomeric seals — Material requirements for seals used in pipes and fittings carrying gas and hydrocarbon fluids*

EN 922:1994, *Plastics piping and ducting systems — Pipes and fittings of unplasticized poly(vinyl chloride) (PVC-U) — Specimen preparation for determination of the viscosity number and calculation of the K-value*

1) 1 bar = 0,1 MPa = 10⁵ Pa; 1 MPa = 1 N/mm²