

AS ISO 8813:2021
ISO 8813:1992



STANDARDS
Australia



Earth-moving machinery — Lift capacity of pipelayers and wheeled tractors or loaders equipped with side boom



currently in preview, click buy full version

AS ISO 8813:2021

This Australian Standard ® was prepared by ME-063, Earthmoving Equipment. It was approved on behalf of the Council of Standards Australia on 27 May 2021.

This Standard was published on 11 June 2021.

The following are represented on Committee ME-063:

Australian Industry Group
Better Regulation Division — SafeWork NSW
Construction and Mining Equipment Industry Group
Department of Regional NSW
Department of Resources, Qld
Engineers Australia
Institute of Instrumentation, Control & Automation Australia
Minerals Council of Australia
Mining Electrical and Mining Mechanical Engineering Society
University of Queensland

This Standard was issued in draft form for comment as DR AS ISO 8813:2021.

Keeping Standards up-to-date

Ensure you have the latest versions of our publications and keep up-to-date about Amendments, Rulings, Withdrawals, and new projects by visiting:

www.standards.org.au

ISBN 978 1 76113 382 4

Earth-moving machinery — Lift capacity of pipelayers and wheeled tractors or loaders equipped with side boom

First published as AS ISO 8813:2021.

COPYRIGHT

© ISO 2021 — All rights reserved
© Standards Australia Limited 2021

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher, unless otherwise permitted under the Copyright Act 1968 (Cth).

Preface

This Standard was prepared by the Standards Australia Committee ME-063, Earthmoving Equipment.

The objective of this document is to provide a uniform method of calculating, and a test method for validating, rated lift capacity as presented in commercial literature for pipelayers and wheeled tractors or loaders equipped with a vertical-only pivoted, hydraulic or mechanically operated, side boom.

This document applies to machines having a lift capacity greater than 10 000 N when used in lifting applications. It includes pipelayers as defined in ISO 6165 and AS ISO 7136:2021, and wheeled tractors and loaders as defined in ISO 6165, AS ISO 6747:2021 and AS ISO 7131:2021.

This document is identical with, and has been reproduced from, ISO 8813:1992, *Earth-moving machinery — Lift capacity of pipelayers and wheeled tractors or loaders equipped with side boom*.

As this document has been reproduced from an International Standard, the following applies:

- (a) In the source text “this International Standard” should read “this document”.
- (b) A full point substitutes for a comma when referring to a decimal marker.

Australian or Australian/New Zealand Standards that are identical adoptions of international normative references may be used interchangeably. Refer to the online catalogue for information on specific Standards.

The terms “normative” and “informative” are used in Standards to define the application of the appendices or annexes to which they apply. A “normative” appendix or annex is an integral part of a Standard, whereas an “informative” appendix or annex is only for information and guidance.

Contents

Preface	ii
Foreword	iv
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Lift capacity calculations procedure	4
4.1 Machine preparation	4
4.2 Attachment variations	4
4.3 Tipping load calculation	4
4.3.1 Pipelayers	4
4.3.2 Wheeled machines	5
4.3.3 Machines with outriggers	5
4.4 Lift mechanism lift capacity calculations	5
5 Verification testing, test results and validation of calculations	5
5.1 Test site	5
5.1.1 Dead weight test site	5
5.1.2 Live weight test site	5
5.2 Test equipment	5
5.3 Test equipment accuracy	6
5.4 Test conditions	6
5.5 Verifying test methods	6
5.6 Test results	7
5.7 Validation of calculated values	7
6 Performance requirements	7
6.1 Rope factor	7
6.2 Hoist mechanism	7
6.3 Hooks and rope	8
7 Rated lift capacity	8
8 Load rating chart	8
9 Test summary	17
9.1 Pipelayer or tractor with side boom or loader with side boom ¹⁾	17
9.1.1 Pipelayer ²⁾	17
9.1.2 Tractor or loader ³⁾	17
9.2 Calculations ⁴⁾	17
9.3 Validation measurements	17
9.4 Rated lift capacity	17
9.5 Rope	18
9.5.1 Nominal diameters	18
9.5.2 Breaking strengths	18
9.5.3 Rope factor	18
Annex A (informative) Hook and rope — Maintenance and repair	20

1) Delete as applicable.

2) Delete as applicable.

3) Delete as applicable.

4) See [5.7](#).

Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards bodies (ISO member bodies). The work of preparing International Standards is normally carried out through ISO technical committees. Each member body interested in a subject for which a technical committee has been established has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work. ISO collaborates closely with the International Electrotechnical Commission (IEC) on all matters of electrotechnical standardization.

Draft International Standards adopted by the technical committees are circulated to the member bodies for voting. Publication as an International Standard requires approval by at least 75 % of the member bodies casting a vote.

International Standard ISO 8813 was prepared by Technical Committee ISO/TC 127, *Earth-moving machinery*, Sub-Committees SC 1, *Test methods relating to machine performance*, and SC 2, *Safety requirements and human factors*.

[Annex A](#) of this International Standard is for information only.

Australian Standard[®]

Earth-moving machinery — Lift capacity of pipelayers and wheeled tractors or loaders equipped with side boom

1 Scope

This International Standard provides a uniform method of calculating, and a test method for validating, rated lift capacity as presented in commercial literature for pipelayers and wheeled tractors or loaders equipped with a vertical-only pivoted, hydraulic or mechanically operated, side boom. The rated lift capacity considers hoist mechanism limits, tipping loads and rope factor. After the lift capacity has been calculated and validated, a reduction factor is applied to establish the rated lift capacity for the specific pipelayer or wheeled machine configuration.

This International Standard applies to machines having a lift capacity greater than 10 000 N when used in lifting applications. It includes pipelayers as defined in ISO 6165 and ISO 7136, and wheeled tractors and loaders as defined in ISO 6165, ISO 6747 and ISO 7131.

2 Normative references

The following standards contain provisions which, through reference in this text, constitute provisions of this International Standard. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this International Standard are encouraged to investigate the possibility of applying the most recent editions of the standards indicated below. Members of IEC and ISO maintain registers of currently valid International Standards.

ISO 6016:1982, *Earth-moving machinery — Methods of measuring the masses of whole machines, their equipment and components.*

ISO 6165:1987, *Earth-moving machinery — Basic types — Vocabulary.*

ISO 6747:1988, *Earth-moving machinery — Tractors — Terminology and commercial specifications.*

ISO 7131:1984, *Earth-moving machinery — Loaders — Terminology and commercial specifications.*

ISO 7136:1986, *Earth-moving machinery — Pipelayers — Terminology and commercial specifications.*

ISO 9248¹⁾, *Earth-moving machinery — Units for dimensions, performance and capacities, and their measurement accuracies.*

3 Definitions

For the purposes of this International Standard, the following definitions apply.

3.1

load

External force including the weight of attaching equipment applied at the load hook. See [figures 1](#) and [2](#).

3.2

lift point line

Vertical line through the centre of the load hook.

3.3

outrigger

Extendable or fixed arm attached to the base machine which rests on the supporting surface and defines the tipping line. See [figures 7](#) and [8](#).

1) To be published.