

ASABE/ISO 24347:2019 NOV2021 (R2024)

Agricultural vehicles — Mechanical connections between towed and towing vehicles — Dimensions of ball-type coupling device (80 mm)



ASABE

American Society of Agricultural
and Biological Engineers



**S
T
A
N
D
A
R
D**

ASABE is a professional and technical organization, of members worldwide, who are dedicated to advancement of engineering applicable to agricultural, food, and biological systems. ASABE Standards are consensus documents developed and adopted by the American Society of Agricultural and Biological Engineers to meet standardization needs within the scope of the Society; principally agricultural field equipment, farmstead equipment, structures, soil and water resource management, turf and landscape equipment, forest engineering, food and process engineering, electric power applications, plant and animal environment, and waste management.

NOTE: ASABE Standards, Engineering Practices, and Data are informational and advisory only. Their use by anyone engaged in industry or trade is entirely voluntary. The ASABE assumes no responsibility for results attributable to the application of ASABE Standards, Engineering Practices, and Data. Conformity does not ensure compliance with applicable ordinances, laws and regulations. Prospective users are responsible for protecting themselves against liability for infringement of patents.

ASABE Standards, Engineering Practices, and Data initially approved prior to the society name change in July of 2005 are designated as "ASAE", regardless of the revision approval date. Newly developed Standards, Engineering Practices and Data approved after July of 2005 are designated as "ASABE".

Standards designated as "ANSI" are American National Standards as are all ISO adoptions published by ASABE. Adoption as an American National Standard requires verification by ANSI that the requirements for due process, consensus, and other criteria for approval have been met by ASABE.

Consensus is established when, in the judgment of the ANSI Board of Standards Review, substantial agreement has been reached by directly and materially affected interests. Substantial agreement means much more than a simple majority, but not necessarily unanimity. Consensus requires that all views and objections be considered, and that a concerted effort be made toward their resolution.

CAUTION NOTICE: ASABE and ANSI standards may be revised or withdrawn at any time. Additionally, procedures of ASABE require that action be taken periodically to reaffirm, revise, or withdraw each standard.

Copyright American Society of Agricultural and Biological Engineers. All rights reserved.

ASABE, 2950 Niles Road, St. Joseph, MI 49085-9659, USA, phone 269-429-0300, hq@asabe.org

ASABE/ISO 24347:2019 NOV2021 (R2024)

Approved November 2021; reaffirmed December 2024 as an American National Standard

Agricultural vehicles — Mechanical connections between towed and towing vehicles — Dimensions of ball-type coupling device (80 mm)

These materials are subject to copyright claims of ISO and ASABE. No part of this publication may be reproduced in any form, including an electronic retrieval system, without the prior written permission of ASABE. All requests pertaining to the ASABE/ISO 24347:2019 NOV2021 Standard should be submitted to ASABE.

This standard was reviewed for adoption by the ASABE Power and Machinery Agricultural Machinery — Agricultural Tractor Technical subcommittee, and has been formerly approved by the Technical Committee. Adopted by ASABE and approved as an American National Standard August 2009; adopted revised to adoption with deviations June 2014; reaffirmed and editorial revision December 2018; adopted 2019 version identically November 2021; reaffirmed December 2024.

Keywords: Dimensions, Location, Mechanical connections, Power take-off, Tractors

0 Foreword

0.1 ASABE/ISO 24347: 2019 NOV2021, Agricultural vehicles — Mechanical connections between towed and towing vehicles — Dimensions of ball-type coupling device (80 mm), is an adoption without modifications of the identically titled ISO standard ISO 24347:2019, Agricultural vehicles — Mechanical connections between towed and towing vehicles — Dimensions of ball-type coupling device (80 mm).

0.2 ASABE/ISO 24347 specifies the dimensional requirements and location for a ball coupling device of 80 mm nominal diameter, whose male part is fitted to an agricultural towing vehicle and female part is fitted to a towed, non-balanced vehicle provides mechanical connection between the two vehicles. It defines vertical loading for different positions.

This document specifies a ball coupling device with either a horizontal adjustable version, or a close position version.

0.3 Three normative references are listed in ISO 24347:2019. These references have been reviewed and accepted as part of the adoption of the ISO document in ASABE/ISO 24347:2019.

0.3.1 Please note that Normative Reference ISO 500-1, Farming tractors — Rear-mounted power take-off types 1, 2, 3 and 4 — Part 1: General specifications, safety requirements, dimensions for master shield and clearance zone, has been adopted by ASABE with deviations (ANSI/ASABE AD500-1:2014, Farming tractors — Rear-mounted power take-off types 1, 2, 3 and 4 — Part 1: General specifications, safety requirements, dimensions for master shield and clearance zone). The deviations within that adoption do not apply to the use of ISO 24347:2019.

0.3.2 Please note that Normative Reference ISO 500-2, Agricultural tractors — Rear-mounted power take-off types 1, 2 and 3 — Part 2: Narrow-track tractors, dimensions for master shield and clearance zone, has been adopted by ASABE with deviations (ANSI/ASABE AD500-2:2004, Farming tractors — Rear-mounted power take-off types 1, 2, and 3 — Part 2: Narrow-track tractors, dimensions for master shield and clearance zone). The deviations within that adoption do not apply to the use of ISO 24347:2019.

0.3.3 Please note that Normative Reference ISO 5673-2, Agricultural tractors and machinery — Power take-off drive shafts and power-input connection — Part 2: Specification for use of PTO drive shafts, and position and clearance of PTO drive line and PIC for various attachments, has been adopted by ASABE with deviations (ANSI/ASABE AD5673-2:2005, Agricultural tractors and machinery — Power take-off drive shafts and power-input connection — Part 2: Specification for use of PTO drive shafts, and position and clearance of PTO drive line and PIC for various attachments). The deviations within that adoption do not apply to the use of ISO 24347:2019.

0.4 This standard has been approved as an American National standard by ANSI (American National Standard Institute). The original content of ISO 24347 was not based on ASABE content or developed material. Royalty payments to ANSI are due upon all sales.

Text of ISO 24347:2019, Agricultural vehicles — Mechanical connections between towed and towing vehicles — Dimensions of ball-type coupling device (80 mm), follows.

1 Scope

This document specifies the dimensional requirements and location for a ball coupling device of 80 mm nominal diameter, whose male part is fitted to an agricultural towing vehicle and female part is fitted to a towed, non-balanced vehicle which provides mechanical connection between the two vehicles. It defines vertical loading for different positions.

This document specifies a ball coupling device with either a horizontal adjustable version, or a close position version.

2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

ISO 500-1, Farming tractors — Rear-mounted power take-off types 1, 2, 3 and 4 — Part 1: General specifications, safety requirements, dimensions for master shield and clearance zone

ISO 500-2, Agricultural tractors — Rear-mounted power take-off types 1, 2 and 3 — Part 2: Narrow-track tractors, dimensions for master shield and clearance zone

ISO 5673-2, Agricultural tractors and machinery — Power take-off drive shafts and power-input connection — Part 2: Specification for use of PTO drive shafts, and position and clearance of PTO drive line and PIC for various attachments

3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

— ISO Online browsing platform: available at <https://www.iso.org/obp>

— IEC Electropedia: available at <http://www.electropedia.org/>

3.1

upper location

ball coupling device location above the tractor PTO