

# Standard Practice for the Design and Operation of Supercooled Fog Dispersal Projects

This document uses both the  
International Systems of Units (SI)  
and customary units

**American Society of Civil Engineers**

**Standard Practice for the  
Design and Operation  
of Supercooled Fog  
Dispersal Projects**

This document uses both the International System of Units (SI) and customary units.



## Library of Congress Cataloging-in-Publication Data

American Society of Civil Engineers.

Standard practice for the design and operation of supercooled fog dispersal projects:

ASCE Standard ANSI/ASCE/EWRI 44-13 / American Society of Civil Engineers.

pages cm. – (ASCE standard)

ISBN 978-0-7844-1310-4 (Print : alk. paper) – ISBN 978-0-7844-7798-4

(ebook) 1. Fog—Control. 2. Precipitation (Meteorology) – Modification.

I. Environmental and Water Resources Institute (U.S). Atmospheric Water Management

Standards Committee. II. Title. III. Title: ASCE Standard ANSI/ASCE/EWRI 44-13.

IV. Series: American Society of Civil Engineers. ASCE standard.

QC929.F7A55 2013

551.68'75—dc23

2013031921

Published by American Society of Civil Engineers

1801 Alexander Bell Drive

Reston, Virginia 20191

[www.asce.org/pubs](http://www.asce.org/pubs)

This standard was developed by a consensus standards development process which has been accredited by the American National Standards Institute (ANSI). Accreditation by ANSI, a voluntary accreditation body representing public and private sector standards development organizations in the United States and abroad, signifies that the standards development process used by ASCE has met the ANSI requirements for openness, balance, consensus, and due process.

While ASCE's process is designed to promote standards that reflect a fair and reasoned consensus among all interested participants, while preserving the public health, safety, and welfare that is paramount to its mission, it has not made an independent assessment of and does not warrant the accuracy, completeness, suitability, or utility of any information, apparatus, product, or process discussed herein. ASCE does not intend, nor should anyone interpret, ASCE's standards to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this standard.

ASCE has no authority to enforce compliance with its standards and does not undertake to certify products for compliance or to render any professional services to any person or entity.

ASCE disclaims any and all liability for personal injury property damage, financial loss, or other damages of any nature whatsoever, including without limitation any direct, indirect, special, exemplary, or consequential damages, resulting from any person's use of, or reliance on, this standard. Any individual who relies on this standard assumes full responsibility for such use.

ASCE and American Society of Civil Engineers—Registered in U.S. Patent and Trademark Office.

*Photocopies and permissions.* Permission to photocopy or reproduce material from ASCE publications can be obtained by sending an e-mail to [permissions@asce.org](mailto:permissions@asce.org) or by locating the title in ASCE's online database (<http://cedb.asce.org>) and using the "Permission to Reuse" link.

Copyright © 2013 by the American Society of Civil Engineers.

All Rights Reserved.

ISBN 978-0-7844-1310-4 (paper)

ISBN 978-0-7844-7798-4 (PDF)

Manufactured in the United States of America.

## STANDARDS

In 2006, the Board of Direction approved the revision to the ASCE Rules for Standards Committees to govern the writing and maintenance of standards developed by the Society. All such standards are developed by a consensus standards process managed by the Society's Codes and Standards Committee (CSC). The consensus process includes balloting by a balanced standards committee made up of Society members and nonmembers, balloting by the membership of the Society as a whole, and balloting by the public. All standards are updated or reaffirmed by the same process at intervals not exceeding five years.

The following standards have been issued:

- ANSI/ASCE 1-82 N-725 Guideline for Design and Analysis of Nuclear Safety Related Earth Structures
- ASCE/EWRI 2-06 Measurement of Oxygen Transfer in Clean Water
- ANSI/ASCE 3-91 Standard for the Structural Design of Composite Slabs and ANSI/ASCE 9-91 Standard Practice for the Construction and Inspection of Composite Slabs
- ASCE 4-98 Seismic Analysis of Safety-Related Nuclear Structures
- Building Code Requirements for Masonry Structures (ACI 530-02/ASCE 5-02/TMS 402-02) and Specifications for Masonry Structures (ACI 530.1-02/ASCE 6-02/TMS 602-02)
- ASCE/SEI 7-10 Minimum Design Loads for Buildings and Other Structures
- SEI/ASCE 8-02 Standard Specification for the Design of Cold-Formed Stainless Steel Structural Members
- ANSI/ASCE 9-91 listed with ASCE 3-91
- ASCE 10-97 Design of Latticed Steel Transmission Structures
- SEI/ASCE 11-99 Guideline for Structural Condition Assessment of Existing Buildings
- ASCE/EWRI 12-13 Standard Guidelines for the Design of Urban Subsurface Drainage
- ASCE/EWRI 13-13 Standard Guidelines for the Installation of Urban Subsurface Drainage
- ASCE/EWRI 14-13 Standard Guidelines for the Operation and Maintenance of Urban Subsurface Drainage
- ASCE 15-98 Standard Practice for Direct Design of Buried Precast Concrete Pipe Using Standard Installations (SIDD)
- ASCE 16-95 Standard for Load Resistance Factor Design (LRFD) of Engineered Wood Construction
- ASCE 17-96 Air-Supported Structures
- ASCE 18-96 Standard Guidelines for In-Process Oxygen Transfer Testing
- ASCE 19-10 Structural Applications of Steel Cables for Buildings
- ASCE 20-96 Standard Guidelines for the Design and Installation of Pile Foundations
- ANSI/ASCE/T&D 21-13 Automated People Mover Standards
- SEI/ASCE 23-07 Specification for Structural Steel Beams with Web Openings
- ASCE/SEI 24-05 Flood Resistant Design and Construction
- ASCE/SEI 25-06 Earthquake-Actuated Automatic Gas Shutoff Devices
- ASCE 26-97 Standard Practice for Design of Buried Precast Concrete Box Sections
- ASCE 27-00 Standard Practice for Direct Design of Precast Concrete Pipe for Jacking in Trenchless Construction
- ASCE 28-00 Standard Practice for Direct Design of Precast Concrete Box Sections for Jacking in Trenchless Construction
- ASCE/SEI/SFPE 29-05 Standard Calculation Methods for Structural Fire Protection
- SEI/ASCE 30-00 Guideline for Condition Assessment of the Building Envelope
- SEI/ASCE 31-03 Seismic Evaluation of Existing Buildings
- SEI/ASCE 32-01 Design and Construction of Frost-Protected Shallow Foundations
- EWRI/ASCE 33-09 Comprehensive Transboundary International Water Quality Management Agreement
- EWRI/ASCE 34-01 Standard Guidelines for Artificial Recharge of Ground Water
- EWRI/ASCE 35-01 Guidelines for Quality Assurance of Installed Fine-Pore Aeration Equipment
- CI/ASCE 36-01 Standard Construction Guidelines for Microtunneling
- SEI/ASCE 37-02 Design Loads on Structures during Construction
- CI/ASCE 38-02 Standard Guideline for the Collection and Depiction of Existing Subsurface Utility Data
- EWRI/ASCE 39-03 Standard Practice for the Design and Operation of Hail Suppression Projects
- ASCE/EWRI 40-03 Regulated Riparian Model Water Code
- ASCE/SEI 41-06 Seismic Rehabilitation of Existing Buildings
- ASCE/EWRI 42-04 Standard Practice for the Design and Operation of Precipitation Enhancement Projects
- ASCE/SEI 43-05 Seismic Design Criteria for Structures, Systems, and Components in Nuclear Facilities
- ASCE/EWRI 44-05 Standard Practice for the Design and Operation of Supercooled Fog Dispersal Projects
- ASCE/EWRI 45-05 Standard Guidelines for the Design of Urban Stormwater Systems
- ASCE/EWRI 46-05 Standard Guidelines for the Installation of Urban Stormwater Systems
- ASCE/EWRI 47-05 Standard Guidelines for the Operation and Maintenance of Urban Stormwater Systems
- ASCE/SEI 48-11 Design of Steel Transmission Pole Structures
- ASCE/SEI 49-12 Wind Tunnel Testing for Buildings and Other Structures
- ASCE/EWRI 50-08 Standard Guideline for Fitting Saturated Hydraulic Conductivity Using Probability Density Functions
- ASCE/EWRI 51-08 Standard Guideline for Calculating the Effective Saturated Hydraulic Conductivity
- ASCE/SEI 52-10 Design of Fiberglass-Reinforced Plastic (FRP) Stacks
- ASCE/G-I 53-10 Compaction Grouting Consensus Guide
- ASCE/EWRI 54-10 Standard Guideline for Geostatistical Estimation and Block-Averaging of Homogeneous and Isotropic Saturated Hydraulic Conductivity
- ASCE/SEI 55-10 Tensile Membrane Structures
- ANSI/ASCE/EWRI 56-10 Guidelines for the Physical Security of Water Utilities
- ANSI/ASCE/EWRI 57-10 Guidelines for the Physical Security of Wastewater/Stormwater Utilities
- ASCE/T&D/ICPI 58-10 Structural Design of Interlocking Concrete Pavement for Municipal Streets and Roadways
- ASCE/SEI 59-11 Blast Protection of Buildings
- ASCE/EWRI 60-12 Guidelines for Development of Effective Water Sharing Agreement

## FOREWORD

The Board of Direction approved revisions to the ASCE Rules for Standards Committees to govern the writing and maintenance of standards developed by ASCE. All such standards are developed by a consensus standards process managed by the ASCE Codes and Standards Committee. The consensus process includes balloting by a balanced standards committee and reviewing during a public comment period. All standards are updated or reaffirmed by the same process every five years if at all possible. Requests for formal interpretations shall be processed in accordance with Section 7 of ASCE Rules for Standards Committees, which are available at [www.asce.org](http://www.asce.org). Errata, addenda, supplements, and interpretations, if any, for this standard can also be found at [www.asce.org](http://www.asce.org).

This standard has been prepared in accordance with recognized engineering principles and should not be used without the user's competent knowledge for a given application. The publication of this standard by ASCE is not intended to warrant that the information contained therein is suitable for any general or specific use, and ASCE takes no position respecting the validity of patent rights. Users are advised that the determination of patent rights or risk of infringement is entirely their own responsibility.

This standard, ASCE/EWRI 44-13, is a combination of ASCE/EWRI 44-05 and its supplement. The supplement covers

substantive content and some editorial changes to Sections 1.2.1 through 1.2.5, Section 5.0, and Section 7.0, alone; the content in the remaining ASCE/EWRI 44-05 sections was unchanged. The supplement was prepared and developed through the ASCE consensus standards process, the remainder was undertaken by the AWM SC, then the final consensus for the revision of ASCE/EWRI 44 was conducted before trying to obtain acceptance by ANSI. ASCE/EWRI 44-13 has been prepared in accordance with the ASCE Standards Writing Manual, August 20, 2010, revision with recognized engineering principles and should not be used without the user's competent knowledge of the underlying principles for a given application.

The American Society of Civil Engineers (ASCE) recognizes the work of the Atmospheric Water Management Standards Committee of the Environmental and Water Resources Institute (EWRI). The primary authors of this standard were the EWRI Atmospheric Water Management Standards Committee's Fog Dispersion Ad Hoc Subcommittee members: Thomas P. DeFelice (chair), Conrad G. Keyes, Jr., Darin Langerud, and Maurice K. We also acknowledge the many who contributed their comments, reviews, illustrations, and photographs.

Thomas P. DeFelice, PhD, ASCE Mem,  
WMA CO, PMP, Maryland

# CONTENTS

<b>FOREWORD</b> . . . . .	v
<b>1.0 Introduction</b> . . . . .	1
1.1 Historical Review of Supercooled Fog Dispersal Operations . . . . .	1
1.2 The Status of Supercooled Fog Dispersal Technology . . . . .	2
<b>2.0 Fog Characteristics</b> . . . . .	5
2.1 Fog Droplet Characteristics . . . . .	5
2.2 Fog Characteristics as Applied to Fog Dispersal Operations . . . . .	7
2.3 Seeding Strategy for Dispersing Supercooled Fog . . . . .	7
<b>3.0 The Design of Supercooled Fog Dispersal Projects</b> . . . . .	9
3.1 Project Scope . . . . .	9
3.2 Delivery Methods . . . . .	9
3.3 Seeding Agent Selection . . . . .	11
3.4 Targeting and Delivery Considerations . . . . .	12
3.5 Experience and Training . . . . .	13
3.6 Seeding Suspension Criteria . . . . .	13
3.7 Legal, Environmental, and Social Considerations . . . . .	13
<b>4.0 Supercooled Fog Dispersal Operations</b> . . . . .	15
4.1 Operations Manual . . . . .	15
4.2 Personnel Requirements . . . . .	15
4.3 Operational Decision Making . . . . .	16
4.4 Communications . . . . .	16
4.5 Public Relations, Information, Involvement, and Safety Considerations . . . . .	16
<b>5.0 Evaluation of Supercooled Fog Dispersal Projects</b> . . . . .	19
<b>6.0 Glossary of Acronyms and Terms</b> . . . . .	21
<b>7.0 References</b> . . . . .	25
<b>8.0 Conversion Tables</b> . . . . .	27
<b>INDEX</b> . . . . .	29

## CHAPTER 1.0 INTRODUCTION

Fogs can pose a significant threat to public safety and quality of life in the air, on land, and at sea. For example, the luxury liner *Andrea Doria* collided with the *Stockholm* in fog off New York and sank on its 1956 maiden voyage. Fifty-one people died and millions of dollars in property were lost (Silverman and Weinstein 1974). An airliner (Flight VD8387) overran the runway in heavy fog after landing in Yichun, in northeastern China, killing 43 passengers on August 24, 2010. Extended periods of fog can have large economic impacts on the aviation, tourism, transportation, and mining industries (ASCE/EWRI 2005). For example, in the early 1970s one fog at one U.S. airport caused an estimated \$100,000 loss of revenue due to aircraft diversions, delays, and cancellations (Silverman and Weinstein 1974). The total annual weather impact on U.S. aviation is an estimated \$3 billion for accident damage and injuries, delays, and unexpected operating costs, and weather is a primary contributing factor in 23% of all aviation accidents (Kulsea 2002).

Although extended foggy periods can have negative impacts on agriculture and the mental health of the general public, there are some situations in which fog is beneficial, such as where fog water is collected for drinking water in arid regions (e.g., Schemenauer 1998), and where fog supplies some of the necessary moisture to vegetation. For example, fog supplies needed moisture to the northern California redwood trees during the summer dry season (e.g., Schemenauer 1998). Another example is the notorious winter fog in the San Joaquin Valley of California, which provides an important portion of the winter moisture requirements of many deciduous orchard crops in the region. The San Joaquin valley fogs are also known as “tule” fogs and are in the category of “warm fogs” that are not normally supercooled, as their temperatures are often just above freezing (ASCE/EWRI 2005).

The harmful effects on transportation alone have been sufficient justification for attempts to modify or disperse fogs. Silverman and Weinstein (1974) note that fog was the subject of the first scientifically documented weather modification effort of any kind. This may partially explain why supercooled fog dispersal is perhaps the only weather-modification technology that does not require long experimentation and careful measurement to detect results, because results are both visible and nearly instantaneous. The most frequently cited goal of any supercooled fog dispersal project is to increase visibility. An increase in the local temperature can be a by-product of the clearing activities. Fog dispersal operations reduce the threat to public safety by increasing the visibility over highways and airport runways. Dispersing fog to increase visibility, especially at airports, has tremendous economic value—particularly at the local level—as transportation returns to normal levels. Additional sunshine resulting from fog dispersal operations can often improve the quality of life for specific

populations. Fog clearing in open-pit mines can allow the resumption of mining operations that were suspended due to decreased visibility (ASCE/EWRI 2005).

Ice fogs are a special case and are slower to dissipate than supercooled fogs because they are composed mostly of tiny ice crystals and they generally form at air temperatures below about 243°K (−30°C) (e.g., Huffman and Onizuka 1971). Ice fog dispersal is fundamentally different from the dispersal of supercooled fogs and may be more appropriately labeled *ice fog suppression*. Ice crystals predominate and form by *heterogeneous nucleation* and, in some instances, by *homogeneous nucleation*. Ice fogs are primarily caused by unnatural sources of water vapor, which may include automobile and aircraft exhaust, exhaust from utility plants, and open water, such as cooling ponds (ASCE/EWRI 2005). Benson (1969) indicated that decreasing the ambient temperature of these moisture sources did improve visibility. Most attempts to disperse ice fogs have included electric fields, dehydrators of various types (e.g., gas, furnace, automobile), air movement by helicopters, polyethylene rubber plastic films (e.g., polyethylene), injection wells, cooling covers, and chemical films (e.g., hexadecanal, ethylene glycol monobutyl ether). Presently, the standard technique used to suppress ice fog caused by exposed water sources employs a thin ethylene glycol monobutyl ether film. This film is harmless to marine life (it is biodegradable) and lasts much longer than other films, but it is less effective in suppressing ice fog than hexadecanal film (ASCE/EWRI 2005). McFadden (1976) and McFadden and Collins (1978) provide details of these techniques. Ice fog suppression techniques will not be discussed in this document. The focus of this standard is on the dispersal of supercooled fog.

### 1.1 HISTORICAL REVIEW OF SUPERCOOLED FOG DISPERSAL OPERATIONS

Supercooled fog is colloidally stable but is otherwise in a thermodynamically metastable state (e.g., Silverman and Weinstein 1974). Thus, supercooled fog can be dissipated by growth and sedimentation of ice crystals. Seeding supercooled fog with ice-forming particles (*nuclei*) may yield visibility improvements of at least 1.6 km (1 mi) within 15 min following seeding (Fig. 1-1). The results are so repeatable that randomized statistical verification is generally considered unnecessary. As a result, supercooled fog dispersal has been operational since 1950 in the United States and since 1952 in Russia. The most frequent locations of these operations are at airports. Suitable seeding techniques are primarily dependent upon wind, temperature, and the supercooled liquid water amount. Some involve the introduction of artificial ice nuclei into the air from either ground-based or airborne delivery systems. Other techniques employ liquid carbon dioxide, nitrogen, or propane to disperse fogs. Liquid