

ASCE STANDARD

ANSI/ASCE/EWRI

65-17

Calculation of the Saturated Hydraulic Conductivity of Fine-Grained Soils

Currently in preview, click [here](#) for full version



ASCE STANDARD

ANSI/ASCE/EWRI

65-17

**Calculation of the
Saturated Hydraulic
Conductivity of
Fine-Grained Soils**



PUBLISHED BY THE AMERICAN SOCIETY OF CIVIL ENGINEERS

Library of Congress Cataloging-in-Publication Data

Names: American Society of Civil Engineers.

Title: Calculation of the saturated hydraulic conductivity of fine-grained soils: ASCE STANDARD, ANSI/ASCE/EWRI 65-17.

Other titles: ASCE STANDARD, ANSI/ASCE/EWRI 65-17

Description: Reston, Virginia : American Society of Civil Engineers, [2017] | Includes bibliographical references and index.

Identifiers: LCCN 2017003718 | ISBN 9780784414347 (soft cover) | ISBN 9780784480496 (PDF)

Subjects: LCSH: Soils—Testing—Standards—United States. | Soil permeability—Measurement—Standards—United States. | Groundwater flow—Measurement—Standards—United States.

Classification: LCC TA710.5 .C345 2017 | DDC 624.1/5136—dc23 LC record available at <https://lcn.loc.gov/2017003718>

Published by American Society of Civil Engineers

1801 Alexander Bell Drive

Reston, Virginia, 20191-4382

www.asce.org/bookstore | ascelibrary.org

This standard was developed by a consensus standards development process which has been accredited by the American National Standards Institute (ANSI). Accreditation by ANSI, a voluntary accreditation body representing public and private sector standards development organizations in the United States and abroad, signifies that the standards development process used by ASCE has met the ANSI requirements for openness, balance, consensus, and due process.

While ASCE's process is designed to promote standards that reflect a fair and reasoned consensus among all interested participants, while preserving the public health, safety, and welfare that is paramount to its mission, it has not made an independent assessment of and does not warrant the accuracy, completeness, suitability, or utility of any information, apparatus, product, or process discussed herein. ASCE does not intend, nor should anyone interpret, ASCE's standards to replace the sound judgment of a competent professional, having knowledge and experience in the appropriate field(s) of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the contents of this standard.

ASCE has no authority to enforce compliance with its standards and does not undertake to certify products for compliance or to render any professional services to any person or entity.

ASCE disclaims any and all liability for any personal injury, property damage, financial loss, or other damages of any nature whatsoever, including without limitation any direct, indirect, special, exemplary, or consequential damages, resulting from any person's use of, or reliance on, this standard. Any individual who relies on this standard assumes full responsibility for such use.

ASCE and American Society of Civil Engineers—Registered in U.S. Patent and Trademark Office.

Photocopies and permissions. Permission to photocopy or reproduce material from ASCE publications can be requested by sending an e-mail to permissions@asce.org or by locating a title in the ASCE Library (<http://ascelibrary.org>) and using the "Permissions" link.

Errata: Errata, if any, can be found at <http://dx.doi.org/10.1061/9780784414347>.

Copyright © 2017 by the American Society of Civil Engineers.

All Rights Reserved.

ISBN 978-0-7844-1434-7 (print)

ISBN 978-0-7844-8049-6 (PDF)

Manufactured in the United States of America.

ASCE STANDARDS

In 2014, the Board of Direction approved revisions to the ASCE Rules for Standards Committees to govern the writing and maintenance of standards developed by ASCE. All such standards are developed by a consensus standards process managed by the ASCE Codes and Standards Committee (CSC). The consensus process includes balloting by a balanced standards committee, and reviewing during a public comment period. All standards are updated or reaffirmed by the same process every 5 to 10 years. Requests for formal interpretations shall be processed in accordance with Section 7 of ASCE Rules for Standards Committees which are available at www.asce.org. Errata, addenda, supplements, and interpretations, if any, for this standard can also be found at www.asce.org.

Standard ANSI/ASCE/EWRI 65-17, *Calculation of the Saturated Hydraulic Conductivity of Fine-Grained Soils* was

approved by the Codes and Standards Committee with a waiver for the units in the standard. The waiver is for only International System of Units (SI) to be used in the standard.

This standard has been prepared in accordance with recognized engineering principles and should not be used without the user's competent knowledge for a given application. The publication of this standard by ASCE is not intended to warrant that the information contained therein is suitable for any general or specific use, and ASCE takes no position respecting the validity of patent rights. The user is advised that the determination of patent rights or risk of infringement is entirely their own responsibility.

A complete list of currently available standards is available in the ASCE Library (<http://ascelibrary.org/page/books/s-standards>).

This page intentionally left blank

Currently in preview, click buy full version

CONTENTS

PREFACE	vii
ACKNOWLEDGMENTS	ix
1 SCOPE	1
2 TERMINOLOGY	3
3 SUMMARY OF THE CONSOLIDATION TEST	5
3.1 Incremental Loading	5
3.2 Deformation, Strain, Void Ratio, and Coefficient of Compressibility	5
4 CHANGES IN STRESS AND DEFORMATION OF STRATA	7
5 VARIABLE PROPERTIES OF FINE-GRAINED SOILS	9
6 DATA FOR EXAMPLE CONSOLIDATION TEST	11
6.1 The Axial Strain versus Vertical Effective Stress and Void Ratio versus Effective Stress Curves	11
7 CALCULATION METHODOLOGY FOR VARIABLES K_{sat}, k, AND n OF FINE-GRAINED SOILS	13
7.1 Calculation of the Compressibility Coefficient (a_v).	13
7.2 Calculation of the Coefficient of Consolidation (c_v)	13
7.3 Calculation of the Saturated Hydraulic Conductivity (K_{sat}).	14
7.4 Calculation of the Permeability (k)	15
7.5 Calculation of the Porosity (n)	16
8 ANOTHER APPROACH: FLEXIBLE-WALL PERMEAMETER	17
9 SECONDARY CONSOLIDATION SETTLEMENT: K_{sat} AT CONSTANT STRESS	19
10 REFERENCES	21
11 NOTATION	23
INDEX	25

This page intentionally left blank

Currently in preview, click buy full version

PREFACE

This is a standard guideline for calculating saturated hydraulic conductivity (K_{sat}), permeability (k), and porosity (n) of fine-grained soils using (1) strain-stress data from the incremental loading of a soil sample in a standardized consolidometer (step-load test), (2) one-dimensional vertical consolidation theory relating K_{sat} to the coefficient of consolidation (c_v), (3) the relation between K_{sat} and k , and (4) the relation between the porosity and the void ratio of a soil undergoing primary consolidation. An undisturbed soil specimen is inserted in a consolidometer and subjected to incremental vertical loads allowing axial (vertical) drainage. The vertical axial deformation of the soil specimen is measured as a function of elapsed testing time through various cycles of incremental loading until the end of the consolidation test. The measured deformation is graphed as a function of the \log_{10} of time or the square root of time for each increment of vertical load. These graphs are used to calculate the coefficient of consolidation for each loading increment applied to the soil specimen. Terzaghi's (1925) one-dimensional (1D) vertical consolidation theory relating K_{sat} to c_v is then applied to calculate K_{sat} for each increment of vertical load applied to the soil specimen. The permeability and porosity of the soil sample decrease with increasing applied vertical load according to known laws. The permeability and porosity of the tested soil specimen are calculated for each load increment as well. The calculated K_{sat} , k , and porosity yield a series of pairs of values (K_{sat} , vertical effective stress; k , vertical effective stress; and porosity, vertical effective stress) that are graphed to produce relations between (1) K_{sat} and vertical effective stress, (2) permeability and vertical effective stress, and (3) porosity and vertical effective stress. This standard guideline demonstrates the relation between 1D consolidation and land subsidence driven by groundwater withdrawal, highlighting the relevance of strain-stress phenomena observed in consolidometer testing to the groundwater-induced phenomenon of land subsidence (consolidation of compressible strata by groundwater withdrawal). The increase in vertical effective stress caused by declining pore water pressure during sustained groundwater extraction; the changes effected by groundwater withdrawal on K_{sat} , k , and porosity; and the associated land subsidence are the primary foci of this standard guideline. This standard's methodology can be applied to refine or improve calculations of land subsidence, groundwater flow predictions, and transport of

dissolved solutes moving in groundwater through fine-grained soils. The methods of this standard guideline are limited to fine-grained, compressible, inorganic soils. Highly organic soils (peat) exhibit anomalous primary and secondary consolidation not within the scope of this standard guideline.

This standard guideline represents the consensus of the Standards Committee on Fitting of Hydraulic Conductivity using Statistical Spatial Estimation (called KSTAT) of the Standards Development Council (SDC) of the Environmental and Water Resources Institute (EWRI) of ASCE. This standard guideline is the fourth in a series of standards that seeks to enhance the probabilistic and empirical characterization and understanding of the saturated hydraulic conductivity (K_{sat}), a key groundwater parameter. The KSTAT Standards Committee has published three companion standard guidelines: Standard ASCE/EWRI 50-08 (ASCE 2008a), Standard ASCE/EWRI 51-08 (ASCE 2008b), and Standard ASCE/EWRI 54-10 (ASCE 2010). Standard ASCE/EWRI 50-08 addresses the optimal fitting of saturated hydraulic conductivity (K_{sat}) with skewed probability density functions (pdfs). Standard ASCE/EWRI 51-08 deals with the estimation of the effective saturated hydraulic conductivity, a parameter that relates the average specific discharge to the average hydraulic gradient. Standard ASCE/EWRI 54-10 presents a methodology for the geostatistical interpolation and block averaging of K_{sat} in statistically homogeneous and isotropic aquifers.

The formulas in this standard guideline require that all their values be expressed in the same system of units, be it the international System of Units (SI) (meter, second, Newton, etc.) or the common system of units in the United States (feet, second, pound, etc.).

The provisions of this document are written in permissive language and, as such, offer to the user a series of options or instructions but do not prescribe a specific course of action. Significant judgment is left to the user of this document.

ASCE does not endorse commercial spreadsheets, numerical software, or testing methods produced by other organizations cited in this standard guideline. Any such products are cited in this standard guideline to illustrate possible ways of carrying out calculations and conducting experimental tests. It is left to the user's discretion to choose and verify the accuracy of whichever computational technique or testing method to apply to implement the methodology.

This page intentionally left blank

Currently in preview, click buy full version

ACKNOWLEDGMENTS

The American Society of Civil Engineers and the Environmental and Water Resources Institute acknowledge the work of the Standards Committee on Fitting of Hydraulic Conductivity Using Statistical Spatial Estimation (called KSTAT). The committee members are professionals from academic, governmental, and private sectors. The current members of the Standards Committee on Fitting of Hydraulic Conductivity Using Statistical Spatial Estimation are

Nazeer Ahmed, Ph.D., P.E., M.ASCE
Teresa Culver, Ph.D, M.ASCE
Macan Doroudian, Ph.D, P.E., G.E., M.ASCE
Mohamed M. Hantush, Ph.D., M.ASCE
Paul F. Hudak, Ph.D.

Hugo A. Loáiciga (Chairman), Ph.D., P.E., F.ASCE
Miguel A. Marino, Ph.D., Dist.M.ASCE
Laurent M. Meillier, P.G.
Chin Man W. Mok, Ph.D., P.E., P.G., G.E., D.WRE, D.GE,
F.ASCE, F.EWRI
Kok-Kwang Phoon, Ph.D., P.E., F.ASCE
George F. Pinder, Ph.D., Dist.M.ASCE
Anand J. Puppala, Ph.D., P.E., F.ASCE
Mark Henry Rubarenzya, Ph.D., D.WRE, M.ASCE
Zhuping Sheng, Ph.D. P.E., P.H., F.ASCE
Parmeshwar L. Shrestha, Ph.D., P.E., D.WRE, M.ASCE
Stewart W. Taylor, Ph.D., P.E., F.ASCE
Frank T.-C. Tsai, Ph.D., P.E., M.ASCE
William W.-G. Yeh, Ph.D., Dist.M.ASCE

This page intentionally left blank

CHAPTER 1

SCOPE

This is a standard guideline for calculating the saturated hydraulic conductivity (K_{sat}), permeability (k), and porosity (n) of fine-grained, isotropic, and homogeneous soils using (1) strain-stress data from the incremental loading of a soil sample in a standardized consolidometer (step-load test), (2) 1D vertical consolidation theory relating K_{sat} to the coefficient of consolidation (c_v), (3) the relation between K_{sat} and k , and (4) the relation between porosity and the void ratio of a soil undergoing primary consolidation. An undisturbed soil specimen is inserted in a consolidometer and subjected to incremental vertical loads allowing axial (vertical) drainage. The vertical axial deformation of the soil specimen is measured as a function of elapsed testing time through several cycles of incremental loading until the end of the consolidation test. The measured deformation is graphed as a function of the \log_{10} of time or the square root of time for each increment of vertical load. These graphs are used to calculate the coefficient of consolidation for each load increment applied to the soil specimen. (Casagrande's unpublished work of 1938 and Taylor's 1948 graphical methods are commonly used.) Terzaghi's (1925) 1D vertical consolidation theory relating K_{sat} to c_v is then used to calculate K_{sat} for each increment of vertical load applied to the soil specimen. The permeability and porosity of the soil sample decrease with increasing applied vertical load according to known laws. The permeability and porosity of the tested soil specimen are calculated for each loading increment as well. The calculated K_{sat} , k , and porosity yield a series of pairs of values (K_{sat} , vertical effective stress; k , vertical effective

stress; and porosity, vertical effective stress) that are graphed to produce relations between (1) K_{sat} and the vertical effective stress, (2) permeability and vertical effective stress, and (3) porosity and vertical effective stress.

The classical theory of 1D (vertical) consolidation (Terzaghi 1925) assumes that K_{sat} , k , and porosity remain constant as soils consolidate under increasing vertical effective stress caused by external loads or groundwater extraction. In fact, the poroelastic theory of 3D consolidation makes the same assumption concerning K_{sat} of a deforming soil (Loáiciga 2013). Yet, the experimental evidence from 1D consolidation tests indicates that K_{sat} , k , and porosity decrease when a soil consolidates under increasing vertical effective stress as discussed in this document. The increase in vertical effective stress caused by declining pore water pressure during sustained groundwater extraction; the changes effected by groundwater withdrawal on K_{sat} , k , and porosity; and the associated land subsidence are the primary foci of this standard guideline. This standard guideline demonstrates the relation between 1D consolidation and land subsidence driven by groundwater withdrawal, highlighting the relevance of strain-stress phenomena observed in consolidometer testing to the groundwater-induced phenomenon of land subsidence (consolidation of compressible strata by groundwater withdrawal). This standard's methodology can be applied to calculations of land subsidence, groundwater flow predictions, and transport of dissolved solutes moving in groundwater through fine-grained soils.