

ASME A112.4.1-2009
[Revision of ASME A112.4.1-1993 (R2008)]

Water Heater Relief Valve Drain Tubes

AN AMERICAN NATIONAL STANDARD



The American Society of
Mechanical Engineers



Intentionally left blank

ASME A112.4.1-2009
[Revision of ASME A112.4.1-1993 (R2008)]

Water Heater Relief Valve Drain Tubes

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**



Date of Issuance: January 11, 2010

This Standard will be revised when the Society approves the issuance of a new edition. There will be no addenda or written interpretations of the requirements of this Standard issued to this edition.

Periodically certain actions of the ASME A112 Committee may be published as Cases. Cases are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org> as they are issued.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2010 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With the A112 Committee	vi
1 General	1
2 Requirements	1
3 Test Methods and Performance Requirements	1

Currently in preview, click buy full version

FOREWORD

There are potential hazards associated with the heating of water in a closed vessel, as the potential for excessive temperature or pressure development within such closed systems is always present. In order to reduce the hazards associated with water heating, two special amendments have been added to the plumbing codes and standards over the past few decades that have resulted in much safer installations. The first requirement involved the installation of a high limit control in the water heating assembly, which deactivates the fuel gas control mechanism if the water heating device exceeds a specific temperature. The second requirement involved the installation of a temperature and pressure relief valve, which is designed to open to atmosphere if the water temperature or pressure within a vessel exceeds the defined specifications of the valve. Properly inspected and maintained, these devices provide the "state-of-the-art" in water heater safety.

For many years, relief valve drains were field-fabricated from metallic piping. With the increasing use of plastics and the need for more expedient installations of plumbing components, the ASME A112 Committee undertook the task of developing criteria for the performance of water heater relief valve drains.

It is intended that this Standard serve as a uniform reference document for use by manufacturers, inspectors, contractors, and installers to identify criteria applicable to water heater relief valve drain tubes.

When this Standard was first developed in 1993, the standard relief valve rating of residential water heaters was 100,000 Btu/hr. Today the common industry rating is 105,000 Btu/hr for the relief valves. This revision reflects this change.

Suggestions for improvement of this Standard are welcome. They should be sent to The American Society of Mechanical Engineers, Attn: Secretary, A112 Standards Committee, Three Park Avenue, New York, NY 10016-5990. The ASME A112 Standards Committee approved the Standard and it was subsequently adopted as an American National Standard by the American National Standards Institute on July 10, 2009.