

ASME B1.13M-2005
(Revision of ASME B1.13M-2001)

Metric Screw Threads: M Profile

AN AMERICAN NATIONAL STANDARD



The American Society of
Mechanical Engineers

ASME B1.13M-2005
(Revision of ASME B1.13M-2001)

Metric Screw Threads: M Profile

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Three Park Avenue • New York, NY 10016

Date of Issuance: March 10, 2006

The next edition of this Standard is scheduled for publication in 2010. There will be no addenda or written interpretations of the requirements of this Standard issued to this edition.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Three Park Avenue, New York, NY 10016-5990

Copyright © 2006 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

| | |
|--|-----------|
| Foreword | vi |
| Committee Roster | viii |
| 1 General | 1 |
| 1.1 Scope | 1 |
| 1.2 Interchangeability | 1 |
| 1.3 References | 1 |
| 1.4 Acceptability | 1 |
| 1.5 Reference Temperature | 1 |
| 1.6 General Symbols | 1 |
| 1.7 Units | 1 |
| 1.8 Federal Government Use | 1 |
| 2 Terminology | 2 |
| 2.1 Definitions | 2 |
| 3 Screw Thread Profile | 4 |
| 3.1 Basic M Thread Profile | 4 |
| 3.2 Design M Profiles | 6 |
| 3.3 Crest and Root Forms | 6 |
| 4 Series of Threads | 6 |
| 4.1 Standard Coarse Pitch General Purpose and Mechanical Fastener Series, M Profile | 6 |
| 4.2 Standard Fine Pitch M Profile Screw Threads | 7 |
| 4.3 Preferred Sizes | 7 |
| 4.4 ISO Metric Thread Series | 7 |
| 5 Allowances and Tolerances | 7 |
| 5.1 ISO System of Limits and Fits as Applied to Screw Threads | 7 |
| 5.2 Tolerance Grades | 11 |
| 5.3 Tolerance Position | 12 |
| 5.4 Allowance/Tolerance Formulas and Tables | 12 |
| 5.5 Selected Tolerance Classes | 12 |
| 5.6 Length of Thread Engagement | 12 |
| 5.7 Circular Runout | 12 |
| 5.8 Lead and Flank Angle Tolerances | 12 |
| 5.9 Coated or Plated Threads | 12 |
| 6 Design Formulas and Tabulated Values for Allowances and Tolerances | 12 |
| 6.1 General | 12 |
| 6.2 Rounding Procedure for Tabulated Values | 12 |
| 6.3 Allowances (Fundamental Deviations) | 15 |
| 6.4 Length of Thread Engagement | 15 |
| 6.5 Crest Diameter Tolerances | 15 |
| 6.6 Pitch Diameter Tolerances | 15 |
| 7 Designation of Screw Threads | 19 |
| 7.1 General | 19 |
| 7.2 Designation of Standard Screw Threads | 19 |

| | | |
|----------------|---|-----------|
| 7.3 | Designation of Thread Fit | 20 |
| 7.4 | Designation of Rounded Root External Thread | 20 |
| 7.5 | Designation of Threads Having Modified Crests | 20 |
| 7.6 | Designation of Special Threads | 20 |
| 7.7 | Designation of Multiple Start Threads | 20 |
| 7.8 | Designation of Coated or Plated Threads | 20 |
| 7.9 | Designation of Threads With Adjusted Size Limits | 20 |
| 8 | Dimensional Accommodation of Coating or Plating for 60 deg Threads | 21 |
| 8.1 | Introduction | 21 |
| 8.2 | Material Limits for Coated Threads | 21 |
| 8.3 | Dimensional Effects of Coating | 21 |
| 8.4 | External Thread With Allowance Available for Coating | 21 |
| 8.5 | External Thread With No Allowance for Coating | 23 |
| 8.6 | Internal Threads | 24 |
| 8.7 | Electrodeposited Coatings | 24 |
| 8.8 | Other Considerations | 25 |
| 9 | Limits of Size | 25 |
| 9.1 | Standard Thread Series | 25 |
| 9.2 | Determination of Size Limits | 25 |
| 9.3 | Formulas for Calculating Limiting Dimensions for M Profile Screw Threads | 25 |
| 9.4 | Examples of Calculations of Size Limits | 34 |
| 10 | Lead and Flank Angle Tolerances | 37 |
| 10.1 | Lead and Flank Angle Acceptance | 37 |
| Figures | | |
| 1 | Basic M Thread Profile (ISO 68-1 Basic Profile) | 4 |
| 2 | Internal Thread, Design M Profile With No Allowance (Fundamental Deviation) (Maximum Material Condition) | 5 |
| 3 | External Thread, Design M Profile With No Allowance (Fundamental Deviation) (Flanks at Maximum Material Condition) | 5 |
| 4 | Metric Tolerance System for Screw Threads | 6 |
| 5 | M Profile, External Thread Profile Upper and Lower Limiting Profiles for $r_{min.} = 0.125P$ and for Flat Root Form (Shown for Tolerance Position g) | 7 |
| 6 | Ratio of Pitch Diameter Change to Thickness of Coating on 60 deg Threads | 22 |
| 7 | Effects of Electrodeposited Coating on 60 deg External Threads | 23 |
| 8 | Internal Thread — Limiting M Profile, Tolerance Position H | 34 |
| 9 | External Thread — Limiting M Thread Profile | 37 |
| Tables | | |
| 1 | General Symbols | 2 |
| 2 | Thread Data, M Profile | 3 |
| 3 | Limit Values for M Profile Minimum Rounded Root Radius | 8 |
| 4 | Standard Coarse Pitch M Profile General Purpose and Mechanical Fastener Series | 8 |
| 5 | Standard Fine Pitch M Profile Screw Threads | 8 |
| 6 | ISO 261 Diameter/Pitch Combinations From Which the Standards Were Selected | 9 |
| 7 | Length of Thread Engagement (ISO 965-1) | 13 |
| 8 | Examples of Tolerance Classes Required for Normal Gage Length Contacts With Various Thread Engagement Lengths | 14 |
| 9 | Minor Diameter Tolerances of Internal Thread, TD_1 (ISO 965-1) | 14 |
| 10 | Major Diameter Tolerances of External Thread, Td (ISO 965-1) | 15 |

| | | |
|--------------------------------|--|----|
| 11 | Pitch Diameter Tolerance of External Thread, Td_2 (ISO 965-1) | 16 |
| 12 | Pitch Diameter Tolerance of Internal Thread, TD_2 (ISO 965-1) | 17 |
| 13 | Allowance (Fundamental Deviation) for Internal and External Threads (ISO 965-1) | 18 |
| 14 | External Thread — Limiting Dimensions M Profile..... | 26 |
| 15 | Internal Thread — Limiting Dimensions M Profile..... | 35 |
| 16A | Example of External Screw Thread, Standard Size..... | 39 |
| 16B | Example of Internal Metric Screw Thread, Standard Size | 41 |
| 16C | Example of External Metric Screw Thread, Non-Standard Size..... | 43 |
| 16D | Example of Internal Metric Screw Thread, Non-Standard Size | 45 |
| 17 | Allowable Variations in Lead and Equivalent Change in Functional Diameter | 47 |
| 18 | Allowable Variations in 30 deg Basic Half-Angle of Screw Threads..... | 50 |
| Nonmandatory Appendices | | |
| A | Standard Rules for Rounding | 51 |
| B | Thread Strength Design Formulas | 52 |
| C | Limiting Dimensions M Profile Screw Threads — Inch Translation | 53 |
| D | Basic Dimensions for ISO Series Metric Screw Threads From ISO 724..... | 64 |
| E | Overtapped Nut Thread Class 6AX..... | 68 |
| F | Internal Thread Allowance (Fundamental Deviation) Tolerance Position E..... | 70 |

FOREWORD

In 1966, ANSI Standards Committee B1 — Standardization and Unification of Screw Threads — started preparation of a document for ISO Metric Screw Threads based on the current ISO recommendations and draft documents. Since there were some uncertainties as to the acceptance of this thread by American industries, the information was published in August 1967 with the title, “Interpretative Document Metric Screw Threads B1.13.” This document was never approved as an ANSI standard.

A revision of the information based on the then current ISO standards and recommendation was published in April 1972 with the title “B1 Report — ISO Metric Screw Threads.” Again, the document was never approved as an ANSI standard. The document number was therefore removed and the status changed to a report.

Interest in metric screw threads has grown at a rapid pace over the past several years with the advent of greater import and export business. The American National Standards Institute, in April 1971, established a committee, ANSI Special Committee to Study Development of an Optimum Metric Fastener System (OMFS). Included in the scope was metric screw threads. Recommendations were submitted to a joint ISO/TC1/TC2 working group established in September 1973 to study the OMFS proposals.

An ISO/TC1/TC2 Ad Hoc Advisory Panel meeting in April 1975 in Munich reached a compromise between the OMFS recommendations and the existing ISO screw thread system. This compromise was approved, in the main, by the ISO/TC1 in its eleventh plenary meeting in Stockholm, June 1976.

(a) The first issue of this Standard, designated ANSI B1.13M, was approved as an American National Standard on February 12, 1979. It provided a system of metric screw threads for general fastening purposes in mechanisms and structures and was in basic agreement with ISO screw thread standards and resolutions current at that time. It featured detailed information for diameter-pitch combinations selected as preferred standard sizes.

(b) The 1983 issue of this Standard was designated ANSI/ASME B1.13M-1983 and was approved as an American National Standard on August 5, 1983. It updated the 1979 issue to include

- (1) the addition of the new ISO tolerance position *f*
- (2) the addition of a section on dimensional accommodation of coating or plating
- (3) the addition of a section on lead and flank angle tolerances

(c) The 1995 issue of this Standard was designated ASME B1.13M-1995 and was approved as an American National Standard on February 20, 1995. It updated the 1983 issue to include

- (1) the addition of an 8 mm pitch series
- (2) the addition of standard size M10 × 1
- (3) the provision for adjustment of internal thread tolerance class for short and long lengths of thread engagement, which may be used instead of external thread class adjustment
- (4) changes in rounding procedures that follow the principles of ASME B1.30M

(d) The 2001 issue of this Standard was designated ASME B1.13M-2001 and was approved as an American National Standard on May 22, 2001. It updated the 1995 issue to include

- (1) incorporation of changes made in the 1998 issue of ISO 261, including addition of diameters 125, 130, and 140 in the 8 mm pitch series; and changing of the 7 mm diameter from 3rd to 2nd choice in Table 6.

(2) recognition of changes made in the 1998 issue of ISO 965-1, including the stating of when International practice permits thread designation without thread class (not USA practice); and modifying the designation of multiple lead threads to be more in line with ISO practice.

(3) incorporation of the new 1998 International Standard, ISO 965-5, by adding Nonmandatory Appendix E for Class AX threads.

(4) minor changes in some thread root diameters due to modified calculation and rounding procedures added in ASME B1.30. ASME B1.30 uses rounding upward when the digit following

the last rounded place is a 5 followed by zeros. Prior to issue of ASME B1.30, rounding was to the nearest even digit. Tabulated values appearing in ISO Standards are not subject to rounding rules of ASME B1.30.

- (5) changes in Circular Runout tolerances.
- (6) other required updates and corrections.
- (e) This issue updates the 2001 edition and includes
 - (1) addition of a new Nonmandatory Appendix F to provide a new tolerance position *E*
 - (2) addition of tolerance class 6h as a preferred class
 - (3) addition of M8 x 1.25 – 6AX to Nonmandatory Appendix E
 - (4) revision of section 8 on “Dimensional Accommodation of Coating or Plating...” to include allowances at thread roots and to expand the information on internal threads
 - (5) revision of section 7 to provide thread designations in accordance with ASME Y14.6-2001
 - (6) revision of some tabulated inch translation values in Nonmandatory Appendix C and the examples of calculation of thread size values in para. 9.4, in accordance with ASME B1.10-2002
 - (7) addition of para. 7.9 for designation of a thread with adjusted size limits
 - (8) other required editorial updates and corrections

Suggestions for improvement of this Standard are welcome. They should be sent to Secretary, ASME B1 Standards Committee, Three Park Avenue, New York, NY 10016-5990.

This revision was approved as an American National Standard on September 29, 2005.

ASME B1 COMMITTEE

Standardization and Unification of Screw Threads

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

A. L. Barrows, *Chair*
D. S. George, *Vice Chair*
A. L. Guzman, *Secretary*

STANDARDS COMMITTEE PERSONNEL

G. L. Allen, The L. S. Starrett Co.
A. L. Barrows, Kennametal-IPG
F. G. Calderone, *Corresponding Member*, Quality Systems Implementers
L. N. Dixon, Jr., General Electric
R. Dodge, Penneyer-Dodge Co.
G. A. Flannery, *Corresponding Member*, Mercury Gage Co.
H. N. Frost, Defense Supply Center Philadelphia
J. O. Gehret III, Vermont Thread Gage
D. S. George, Ford Motor Co.
J. R. Gervasi, Kerr Lakeside, Inc.
J. Greenslade, Greenslade and Co.
A. L. Guzman, The American Society of Mechanical Engineers
R. J. Hukari, SPS Technologies
L. C. Johnson, The Johnson Gage Co.
D. D. Katz, Precision Fittings
R. P. Knittel, Leitech-US Ltd.

B. Larzelere, *Corresponding Member*, Deltronic Corp.
L. L. Lord, *Corresponding Member*, Caterpillar, Inc.
M. H. McWilliams, PMC Lonestar
D. Skierski, *Alternate*, Sterling Gage and Calibration
D. Miskinis, Kennametal-Greenfield
W. R. Newman, *Corresponding Member*, Consultant
D. R. Oas, Seaway Bolt and Services Corp.
M. W. Rose, Glastonbury Southern Gage
W. A. Watts, *Alternate*, Glastonbury Southern Gage
E. Schwartz, Consultant
R. H. Searr, *Member Emeritus*, Mak Tool and Gage
B. F. Shepley, Dresser-Rand Co.
A. D. Simpson, Jr., Emuge Corp.
R. D. Strong, General Motors Vehicle Engineering Center
A. F. Thibodeau, *Member Emeritus*, Swanson Tool Manufacturing, Inc.
R. E. Vincent, Jr., General Plug Manufacturing Co.
C. J. Wilson, Industrial Fasteners Institute

SUBCOMMITTEE 15 METRIC SCREW THREADS

E. Schwartz, *Chair*
D. Miskinis, *Vice Chair*, Kennametal-Greenfield
A. L. Barrows, Kennametal-IPG
F. G. Calderone, *Corresponding Member*, Quality Systems Implementers
R. Dodge, Penneyer-Dodge Co.
D. S. George, Ford Motor Co.
J. Greenslade, Greenslade and Co.

L. L. Lord, *Corresponding Member*, Caterpillar, Inc.
W. R. Newman, *Corresponding Member*, Consultant
R. D. Strong, General Motors Vehicle Engineering Center
A. F. Thibodeau, *Corresponding Member*, Swanson Tool Manufacturing, Inc.
R. E. Vincent, Jr., General Plug Manufacturing Co.
C. J. Wilson, Industrial Fasteners Institute

METRIC SCREW THREADS: M PROFILE

1 GENERAL

1.1 Scope

This Standard contains general metric standards for a 60 deg symmetrical screw thread with a basic ISO 68-1 profile designated M profile. The M profile threads of tolerance class 6H/6g are intended for metric applications where inch class 2A/2B have been used. At the minimum material limits, the 6H/6g results in a looser fit than the 2A/2B. Tabular data is also provided for a tighter tolerance fit external thread of class 4g6g, which is approximately equivalent to the inch class 3A but with an allowance applied. Formulation and tolerancing data is included for applications requiring other fits.

NOTE: A 4H5H/4h6h is approximately equivalent to a class 3A/3B fit in the inch system.

1.2 Interchangeability

Threads produced to this Standard are fully interchangeable with threads conforming to other National Standards that are based on ISO 68-1 basic profile and ISO 965-1 tolerance practices.

1.2.1 Assembly. Threads produced in accordance with M profile and MJ profile (ASME B1.21M) data will assemble with each other. However, external MJ threads will encounter interference on the crest radii with internal M thread crests when both threads are at maximum material condition.

1.3 References

The latest issues of the following documents form a part of this Standard to the extent specified herein.

- ASME B1.3, Screw Thread Gaging Systems for Dimensional Acceptability — Inch and Metric Screw Threads (UN, UNF, UNJ, M, and MJ)
- ASME B1.7M, Nomenclature, Definitions, and Letter Symbols for Screw Threads
- ASME B1.16M, Gages and Gaging for Metric M Screw Threads
- ASME B1.21M, Metric Screw Threads: MJ Profile
- ASME B1.30, Screw Threads — Standard Practice for Calculating and Rounding Dimensions
- ASME B47.1, Gage Blanks
- ASME Y14.5, Dimensioning and Tolerancing
- Publisher: The American Society of Mechanical Engineers (ASME), Three Park Avenue, New York, NY 10016-5990; Order Department: 22 Law Drive, Box 2900, Fairfield, NJ 07007-2900

ASTM F568M, Standard Specification for Carbon and Alloy Steel Externally Threaded Metric Fasteners

Publisher: The American Society for Testing and Materials (ASTM), 100 Barr Harbor Drive, West Conshohocken, PA 19428-2959

ISO 3, Preferred Numbers — Series of Preferred Numbers

ISO 68-1, ISO General Purpose Screw Threads — Basic Profile — Part 1: Metric Screw Threads

ISO 261, ISO General Purpose Metric Screw Threads — General Plan

ISO 724, ISO Metric Screw Threads — Basic Dimensions

ISO 898-1, Mechanical Properties of Fasteners — Part 1:

Bolts, Screws, and Studs

ISO 965-1, ISO General Purpose Metric Screw Threads — Tolerances — Part 1: Principles and Basic Data

Publisher: International Organization for Standardization (ISO), 1 rue de Varembe, Case Postale 56, CH-1211, Genève 20, Switzerland/Suisse

SAE J1199, Mechanical and Material Requirements for Metric Externally Threaded Steel Fasteners

Publisher: Society of Automotive Engineers (SAE), 400 Commonwealth Drive, Warrendale, PA 15096-0001

1.4 Acceptability

Acceptability of product threads shall be in accordance with ASME B1.3. Gages and gaging are in accordance with ASME B1.16M.

1.5 Reference Temperature

The reference temperature is 20°C for dimensions defined by this system.

1.6 General Symbols

The general symbols used to describe the metric screw thread forms are shown in Table 1.

1.7 Units

All dimensions and all values in the formulas are expressed in millimeters unless otherwise noted. Values in terms of sharp vee-thread height (height of fundamental triangle), H , are used to be consistent with ISO Standards, but actual formulations and calculations are based on values of pitch, P . See Table 2.

1.8 Federal Government Use

When this Standard is approved by the Department of Defense and Federal Agencies and is incorporated