

ASME B16.20-2023
(Revision of ASME B16.20-2017)

Metallic Gaskets for Pipe Flanges

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B16.20-2023
(Revision of ASME B16.20-2017)

Metallic Gaskets for Pipe Flanges

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: December 22, 2023

The next edition of this Standard is scheduled for publication in 2028.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The standards committee that approved the code or standard was balanced to ensure that individuals from competent and concerned interests had an opportunity to participate. The proposed code or standard was made available for public review and comment, which provided an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity. ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor does ASME assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representatives or persons affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

The endnotes and preamble in this document (if any) are part of this American National Standard.



ASME Collective Membership Mark

“ASME” and the above ASME symbol are registered trademarks of The American Society of Mechanical Engineers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2023 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword		v
Committee Roster		vi
Correspondence With the B16 Committee		vii
Important Information Concerning Use of Asbestos or Alternative Materials		ix
Summary of Changes		x
List of Changes in Record Number Order		xi
Part GR	General Requirements	1
GR-1	Scope	1
GR-2	Quality Systems	1
GR-3	References	1
GR-4	Relevant Units	1
Part RJ	Ring-Joint Gaskets	2
RJ-1	Types	2
RJ-2	Size	2
RJ-3	Materials	2
RJ-4	Marking	2
RJ-5	Dimensions and Tolerances	2
RJ-6	Surface Finish	2
RJ-7	Identification Number	2
Part SW	Spiral-Wound Gaskets	14
SW-1	Size and Class	14
SW-2	Dimensions and Tolerances	14
SW-3	Materials	15
SW-4	Marking	15
Part GM	Grooved Metal Gaskets With Covering Layers	34
GM-1	Size and Class	34
GM-2	Dimensions and Tolerances	34
GM-3	Materials	34
GM-4	Marking	34
Mandatory Appendix		
I	References	44
Nonmandatory Appendix		
A	Quality System Program	45
Figures		
SW-2.1-1	Spiral-Wound Gasket	16

GM-2.1-1	Grooved Metal Gasket With Covering Layers	36
GM-4.1-1	Illustration of Example Markings for Grooved Metal Gaskets With Covering Layers	43
Tables		
RJ-3.2-1	Maximum Hardness for Ring Gaskets	2
RJ-4-1	Ring Gasket Markings	2
RJ-5-1	Type R Ring Gasket Dimensions and Tolerances	3
RJ-5-2	Pipe Sizes for Type R Ring Gaskets Suitable for Referenced Standards	6
RJ-5-3	Type RX Ring Gasket Dimensions and Tolerances	9
RJ-5-4	Pipe Sizes for Type RX Ring Gaskets Suitable for Referenced Standards	11
RJ-5-5	Type BX Ring Gasket Dimensions and Tolerances	12
RJ-5-6	Pipe Sizes for Type BX Ring Gaskets Suitable for Referenced Standards	13
SW-2.1-1	Dimensions for Spiral-Wound Gaskets Used With ASME B16.5 Flanges	17
SW-2.1-2	Dimensions for Spiral-Wound Gaskets Used With ASME B16.47 Series A Flanges	20
SW-2.1-3	Dimensions for Spiral-Wound Gaskets Used With ASME B16.47 Series B Flanges	22
SW-2.1-4	Inside Diameters of Inner Rings for Spiral-Wound Gaskets for Use With ASME B16.5 Flanges	24
SW-2.1-5	Inside Diameters of Inner Rings for Spiral-Wound Gaskets Used Between ASME B16.47 Series A Flanges	25
SW-2.1-6	Inside Diameters of Inner Rings for Spiral-Wound Gaskets Used Between ASME B16.47 Series B Flanges	26
SW-2.5-1	Minimum Pipe Wall Thickness Suitable for Use of Spiral-Wound Gaskets With Inner Rings for ASME B16.5 Flanges	27
SW-2.5-2	Maximum Bore of ASME B16.5 Flanges for Use With Spiral-Wound Gaskets	28
SW-2.5-3	Maximum Bore of ASME B16.47 Series A Flanges for Use With Spiral-Wound Gaskets . .	29
SW-2.5-4	Maximum Bore of ASME B16.47 Series B Flanges for Use With Spiral-Wound Gaskets . .	30
SW-3-1	Color Coding and Abbreviations for Spiral-Wound Gasket Materials	31
SW-4.1-1	Example Markings for Spiral-Wound Gaskets	32
GM-2.1-1	Dimensions for Grooved Metal Gaskets With Covering Layers Used With ASME B16.5 Flanges	37
GM-2.1-2	Dimensions for Grooved Metal Gaskets With Covering Layers Used With ASME B16.47 Series A Flanges	38
GM-2.1-3	Dimensions for Grooved Metal Gaskets With Covering Layers Used With ASME B16.47 Series B Flanges	40
GM-3.1-1	Color Coding and Abbreviations for Grooved Metal Gaskets With Covering Layers Materials	42
GM-4.1-1	Example Markings for Grooved Metal Gaskets With Covering Layers	43

FOREWORD

Ring-joint gaskets and grooves probably originated in the boiler field, where they were used in various forms for manhole covers, autoclaves, and other closures; however, it was in the oil industry (both in the production and refining of oil) that they received the greatest recognition and were developed into their present form. Their use expanded steadily as temperatures and pressures were increased in steam plants. Tests examining their application in flanges and valves were conducted as early as 1928.

In June 1936, the American Petroleum Institute (API) issued Tentative Standard 5-G-3 on Ring-Joints for Steel Flanges and Flange Unions for use with API Tubular Goods. This standard was known as API Specification 6B, Ring-Joint Flanges. Following the acceptance of ring-joints for flanges and valves by API and the issuance of their standard, ASA B16e on Steel Pipe Flanges and Flanged Fittings was revised to include them, and the 1939 edition included standard dimensions for a full line of ring-joint flanges based on the API standard. Development work continued, and API formulated Standard 6E, Specification for Wellhead Equipment, which included ring-joints not covered in ASA B16e-1939.

In 1949, the American Standards Association (ASA), Sectional Committee B16, Subcommittee 3, Steel Flanges and Flanged Fittings, assembled the available information on ring-joint gaskets into a single standard. ASA approved the Standard, with the designation ASA B16.20-1952, on April 30, 1952.

On April 4, 1955, ASA approved an updated edition with the designation ASA B16.20-1955. Ring gaskets for Class 900 (900 lb at that time) in sizes NPS 26 through NPS 36 were added in the next edition, which ASA approved on April 2, 1956. The Standard was again reviewed in 1962, and ASA approved it on April 25, 1962. In 1973, the Standard was revised, and the American National Standards Institute (ANSI) approved it as an American National Standard.

Following publication of the 1973 edition, API requested that ASME convert their gasket standard, API 601, into an ASME American National Standard. As a result of that request, the Standard was expanded to include requirements for spiral-wound and jacketed gaskets that were formerly listed in API 601, 7th edition, 1988. Ring-joint groove dimensions were not included, because they were included in ASME/ANSI B16.5-1988, Pipe Flanges and Flanged Fittings, and ASME B16.47-1990, Large Diameter Steel Flanges. The revised Standard was approved by ANSI on January 22, 1993.

Subsequent editions further expanded the Standard. In the 1998 edition, a quality system program annex was added. In the 2007 edition, metric dimensions were adopted as an independent standard to the U.S. Customary units, and Mandatory Appendix I was added to cover dimensional tables in U.S. Customary units. In the 2012 edition, a new chapter for grooved metal gaskets with covering layers was added.

In the 2017 edition, the entire Standard was reorganized based on the different types of gaskets. In addition, the title of the Standard was revised, as were multiple paragraphs, tables, and figures. Following approval by the ASME B16 Standards Committee, ASME B16.20-2017 was approved by ANSI on October 11, 2017.

In ASME B16.20-2023, all references to double-jacketed gaskets have been removed, material abbreviations have been added as well as guidance for materials not listed in Table SW-3-1; other tables have been updated to align with ASME B16.5 and ASME B16.4. Following approval by the ASME B16 Standards Committee, ASME B16.20-2023 was approved by ANSI on October 9, 2023.

ASME B16 COMMITTEE

Standardization of Valves, Flanges, Fittings, and Gaskets

(The following is the roster of the committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

C. E. Davila, *Chair*
R. M. Bojarczuk, *Vice Chair*
S. J. Rossi, *Secretary*

STANDARDS COMMITTEE PERSONNEL

A. Appleton , Appleton Quality Concepts, LLC	D. Hunt, Jr. , Fastenal
J. E. Barker , DeZURIK, Inc.	G. A. Jolly , Samshin, Ltd.
R. W. Barnes , ANRIC Enterprises, Inc.	A. Kireta, Jr. , Copper Development Association, Inc.
D. C. Bayreuther , Neles Corp.	E. J. Lain , Exelon Corp.
W. B. Bedesem , Consultant	T. A. McMahon , Emerson Automation Solutions
R. M. Bojarczuk , Retired	R. C. Merrick , Consultant
A. M. Cheta , Shell Global Solutions (U.S.)	W. H. Patrick , DGC Chemical Co.
M. A. Clark , Retired	D. W. Rahoi , CCM 2000
G. A. Cuccio , Capitol Manufacturing Co.	D. F. Reid , VSP Technologies
C. E. Davila , Crane Chempharma & Energy	S. J. Rossi , The American Society of Mechanical Engineers
J. G. Dominguez , Welding Outlets, Inc.	R. A. Seismic , Canadoil
B. G. Fabian , Pennsylvania Machine Works	J. Sekeran , CSA Group
K. S. Felder , Valero Energy Corp.	F. Fang , <i>Delegate</i> , China Productivity Center for Machinery
D. R. Frikken , Becht Engineering Co., Inc.	J. D. Travis , <i>Alternate</i> , DeZURIK, Inc.
J. Holstrom , Val-Matic Valve & Manufacturing Corp.	P. V. Craig , <i>Contributing Member</i> , Jomar Group

SUBCOMMITTEE G — GASKETS FOR FLANGED JOINTS

E. J. Lain , <i>Chair</i> , Exelon Corp.	K. E. Guenther , Shell
A. Carrion , <i>Secretary</i> , The American Society of Mechanical Engineers	E. Jamalyaria , Flexitallic Engineering
R. M. Bojarczuk , Retired	Y. Li , Flexitallic, L.P.
G. Briggs , James Walker Mooreflex, Ltd.	L. Melvin , Gasket Resources, Inc.
M. Bush , Marathon Petroleum Corp.	B. Pourchot , SGL Carbon
D. Clover , ERIKS North America	D. F. Reid , VSP Technologies
K. S. Felder , Valero Energy Corp.	M. Ruffin , Teadit North America, Inc.
L. Fernandes , Garlock Sealing Technologies	S. Szemanek , MIPC, LLC
P. R. Francis , Miami Valley Gasket Co., Inc.	R. Taylor , 3S — Superior Sealing Services, LLC
D. R. Frikken , Becht Engineering Co., Inc.	D. Van Der Walt , KLINGER GPI

CORRESPONDENCE WITH THE B16 COMMITTEE

General. ASME codes and standards are developed and maintained by committees with the intent to represent the consensus of concerned interests. Users of ASME codes and standards may correspond with the committees to propose revisions or cases, report errata, or request interpretations. Correspondence for this Standard should be sent to the staff secretary noted on the committee's web page, accessible at <https://go.asme.org/B16committee>.

Revisions and Errata. The committee processes revisions to this Standard on a continuous basis to incorporate changes that appear necessary or desirable as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published in the next edition of the Standard.

In addition, the committee may post errata on the committee web page. Errata become effective on the date posted. Users can register on the committee web page to receive e-mail notifications of posted errata.

This Standard is always open for comment, and the committee welcomes proposals for revisions. Such proposals should be as specific as possible, citing the paragraph number, the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent background information and supporting documentation.

Cases

(a) The most common applications for cases are

(1) to permit early implementation of a revision based on an urgent need

(2) to provide alternative requirements

(3) to allow users to gain experience with alternative or potential additional requirements prior to incorporation directly into the Standard

(4) to permit the use of a new material or process

(b) Users are cautioned that not all jurisdictions or owners automatically accept cases. Cases are not to be considered as approving, recommending, certifying, or endorsing any proprietary or specific design, or as limiting in any way the freedom of manufacturers, constructors, or owners to choose any method of design or any form of construction that conforms to the Standard.

(c) A proposed case shall be written as a question and reply in the same format as existing cases. The proposal shall also include the following information:

(1) a statement of need and background information

(2) the urgency of the case (e.g., the case concerns a project that is underway or imminent)

(3) the Standard and the paragraph, figure, or table number

(4) the editions of the Standard to which the proposed case applies

(d) A case is effective for use when the public review process has been completed and it is approved by the cognizant supervisory board. Approved cases are posted on the committee web page.

Interpretations. Upon request, the committee will issue an interpretation of any requirement of this Standard. An interpretation can be issued only in response to a request submitted through the online Interpretation Submittal Form at <https://go.asme.org/InterpretationRequest>. Upon submitting the form, the inquirer will receive an automatic e-mail confirming receipt.

ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the information submitted, it is the opinion of the committee that the inquirer should seek assistance, the request will be returned with the recommendation that such assistance be obtained. Inquirers can track the status of their requests at <https://go.asme.org/Interpretations>.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME committee or subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Interpretations are published in the ASME Interpretations Database at <https://go.asme.org/Interpretations> as they are issued.

Committee Meetings. The B16 Standards Committee regularly holds meetings that are open to the public. Persons wishing to attend any meeting should contact the secretary of the committee. Information on future committee meetings can be found on the committee web page at <https://go.asme.org/B16committee>.

Currently in preview, click buy full version

IMPORTANT INFORMATION CONCERNING USE OF ASBESTOS OR ALTERNATIVE MATERIALS

Asbestos is referenced for use as a filler material in metallic gaskets. It has served as a universal sealing material, compatible with most fluid services. It has been of extreme usefulness in minimizing fire hazards.

Certain serious adverse health effects are associated with asbestos, among them the serious and often fatal diseases of lung cancer, asbestosis, and mesothelioma (a cancer of the chest and abdominal linings). The degree of exposure to asbestos varies with the product and the work practices involved.

Consult the most recent edition of the Occupational Safety and Health Administration, U.S. Department of Labor, Occupational Safety and Health Standard for Asbestos, Tremolite, Anthophyllite, and Actinolite, 29 Code of Federal Regulations Section 1910.1001; the U.S. Environmental Protection Agency National Emission Standard for Asbestos, 40 Code of Federal Regulations Sections 61.140 through 61.156; and the U.S. Environmental Protection Agency rule requiring the labeling and phased banning of asbestos products, published at 51 Federal Register 738-3759 (January 29, 1986).

There are currently in use and under development a number of substitute materials to replace asbestos in certain applications. Manufacturers and users are encouraged to develop and use effective substitute materials that can meet the specifications for, and operating requirements of, the equipment to which they would apply.

Information concerning safety and health risks and proper precautions with respect to particular materials and conditions should be obtained from one's employer, the manufacturer or supplier of that material, or the Material Safety Data Sheet.

ASME B16.20-2023

SUMMARY OF CHANGES

Following approval by the ASME B16 Standards Committee and ASME, and after public review, ASME B16.20-2023 was approved by the American National Standards Institute on October 9, 2023.

ASME B16.20-2023 includes the following changes identified by a margin note, **(23)**. The Record Numbers listed below are explained in more detail in the “List of Changes in Record Number Order” following this Summary of Changes.

<i>Page</i>	<i>Location</i>	<i>Change (Record Number)</i>
1	GR-1	First sentence revised (12-517)
6	Table RJ-5-2	(1) For ASME B16.5, Class 900, entries for R-14, R-18, R-20, R-24, and R-27 revised (21-2166) (2) For ASME B16.5, Class 150 and Classes 300–600, entries for R-80 and R-81 revised (21-2144) (3) Note (3) added (21-2166)
14	SW-2.5	Sentence below subpara. (c) revised (21-2168)
15	SW-2.6	First paragraph and subpara. (b) revised (21-929)
15	SW-3	Revised (18-2515)
15	SW-4.1	Subparagraph (f) revised (21-2168)
17	Table SW-2.1-1	(1) NPS 22 added (19-856) (2) Note (5) revised and Note (6) added (19-856)
24	Table SW-2.1-4	(1) NPS 22 added (19-856) (2) Note (1) revised and Note (2) added (19-856)
27	Table SW-2.5-1	NPS 3½ and NPS 22 added (19-856)
28	Table SW-2.5-2	(1) NPS 3½ and NPS 22 added (19-856) (2) For NPS ½ through NPS 3½, Classes 400 and 900, entries revised (19-856)
31	Table SW-3-1	Revised in its entirety (18-2515)
33	Part JA	Deleted (12-517)
37	Table GM-2.1-1	(1) NPS 3½ and NPS 22 added (21-2145) (2) Note (4) revised (21-2145)
44	Mandatory Appendix I	Updated

LIST OF CHANGES IN RECORD NUMBER ORDER

<u>Record Number</u>	<u>Change</u>
12-517	Removed all references to double-jacketed (DJ) gaskets from ASME B16.20.
18-2515	Revised Table SW-3-1 material abbreviations and para. SW-3. Included a larger range of materials used in construction. Added guidance for abbreviations for materials not listed in the table.
19-856	Added NPS 22 in Tables SW-2.1-1, SW-2.1-4, SW-2.5-1, and SW-2.5-2 to match what is currently in B16.5 and B16.47, and added new Notes.
21-929	Clarified spiral-wound gasket performance testing requirement.
21-2144	Added ring-joint gasket for 22 in. NPS ASME B16.5 flanges to ASME B16.20.
21-2145	Updated Table GM-2.1-1 to include 3½ in. NPS and 22 in. NPS ASME B16.5 flanges.
21-2166	Revised Table RJ-5-2 to add a Note to ½ in. to 2 in. for Class 900.
21-2168	Corrected "outer ring" to "centering ring." The term "outer ring" exists only within para. SW-2.6.

INTENTIONALLY LEFT BLANK

PART GR

GENERAL REQUIREMENTS

(23) **GR-1 SCOPE**

This Standard covers materials, dimensions, tolerances, and markings for metal ring-joint gaskets, spiral-wound metal gaskets, and grooved metal gaskets with covering layers. These gaskets are dimensionally suitable for use with flanges described in reference flange standards ASME B16.5, ASME B16.47, API Specification 6A, and ISO 10423.

GR-2 QUALITY SYSTEMS

Requirements relating to the product manufacturers' quality system programs are described in [Nonmandatory Appendix A](#).

GR-3 REFERENCES

Standards and specifications adopted by reference in this Standard are shown in [Mandatory Appendix I](#).

GR-4 RELEVANT UNITS

This Standard states values in both SI (Metric) and U.S. Customary units. These systems of units are to be regarded separately as standard. Within the text, the U.S. Customary units are shown in parentheses. The values stated in each system are not exact equivalents; therefore, it is required that each system of units be used independently of the other. Combining values from the two systems constitutes nonconformance with the Standard.