

ASME B16.47-2020
(Revision of ASME B16.47-2017)

Large Diameter Steel Flanges

NPS 26 Through NPS 60
Metric/Inch Standard

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B16.47-2020
(Revision of ASME B16.47-2017)

Large Diameter Steel Flanges

NPS 26 Through NPS 60
Metric/Inch Standard

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: January 29, 2021

The next edition of this Standard is scheduled for publication in 2024.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Periodically certain actions of the ASME B16 Committee may be published as Cases. Cases and interpretations are published on the ASME website under the Committee Pages at <http://cstools.asme.org/> as they are issued.

Errata to codes and standards may be posted on the ASME website under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be based on the date posted.

The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting "Errata" in the "Publication Information" section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures agreed to as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" an item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2021 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	v
Committee Roster	vii
Correspondence With the B16 Committee	viii
Summary of Changes	x
List of Changes in Record Number Order	xii
1 General	1
2 Pressure-Temperature Ratings	2
3 Component Size: Nominal Pipe Size	3
4 Marking	3
5 Materials	4
6 Dimensions	5
7 Tolerances	6
8 Pressure Testing	7
 Mandatory Appendix	
I References	113
 Nonmandatory Appendices	
A Methods Used for Establishing Pressure-Temperature Ratings	115
B Gaskets (Other Than Ring-Joint)	119
C Quality System Program	121
D Method for Calculating Bolt Lengths	122
 Figures	
1 Welding Ends (Welding Neck Flanges, No Backing Rings)	8
2 Welding Ends (Welding Neck Flanges With Backing Rings)	9
3 Welding Ends (Welding Neck Flanges)	10
D-1 Specified Stud Bolt Length	123
 Tables	
1 List of Material Specifications	11
2 List of Bolting Specifications (Applicable ASTM Specifications)	13
3 Pressure-Temperature Ratings for Group 1.1 Materials	14
3C Pressure-Temperature Ratings for Group 1.1 Materials	15
4 Pressure-Temperature Ratings for Group 1.2 Materials	16
4C Pressure-Temperature Ratings for Group 1.2 Materials	17
5 Pressure-Temperature Ratings for Group 1.3 Materials	18
5C Pressure-Temperature Ratings for Group 1.3 Materials	19

6	Pressure–Temperature Ratings for Group 1.4 Materials	20
6C	Pressure–Temperature Ratings for Group 1.4 Materials	21
7	Pressure–Temperature Ratings for Group 1.5 Materials	22
7C	Pressure–Temperature Ratings for Group 1.5 Materials	23
8	Pressure–Temperature Ratings for Group 1.7 Materials	24
8C	Pressure–Temperature Ratings for Group 1.7 Materials	25
9	Pressure–Temperature Ratings for Group 1.9 Materials	26
9C	Pressure–Temperature Ratings for Group 1.9 Materials	27
10	Pressure–Temperature Ratings for Group 1.10 Materials	28
10C	Pressure–Temperature Ratings for Group 1.10 Materials	29
11	Pressure–Temperature Ratings for Group 1.11 Materials	30
11C	Pressure–Temperature Ratings for Group 1.11 Materials	31
12	Pressure–Temperature Ratings for Group 1.13 Materials	32
12C	Pressure–Temperature Ratings for Group 1.13 Materials	33
13	Pressure–Temperature Ratings for Group 1.14 Materials	34
13C	Pressure–Temperature Ratings for Group 1.14 Materials	35
14	Pressure–Temperature Ratings for Group 1.15 Materials	36
14C	Pressure–Temperature Ratings for Group 1.15 Materials	37
15	Pressure–Temperature Ratings for Group 1.17 Materials	38
15C	Pressure–Temperature Ratings for Group 1.17 Materials	39
16	Pressure–Temperature Ratings for Group 1.18 Materials	40
16C	Pressure–Temperature Ratings for Group 1.18 Materials	41
17	Pressure–Temperature Ratings for Group 2.1 Materials	42
17C	Pressure–Temperature Ratings for Group 2.1 Materials	43
18	Pressure–Temperature Ratings for Group 2.2 Materials	44
18C	Pressure–Temperature Ratings for Group 2.2 Materials	45
19	Pressure–Temperature Ratings for Group 2.3 Materials	46
19C	Pressure–Temperature Ratings for Group 2.3 Materials	47
20	Pressure–Temperature Ratings for Group 2.4 Materials	48
20C	Pressure–Temperature Ratings for Group 2.4 Materials	49
21	Pressure–Temperature Ratings for Group 2.5 Materials	50
21C	Pressure–Temperature Ratings for Group 2.5 Materials	51
22	Pressure–Temperature Ratings for Group 2.6 Materials	52
22C	Pressure–Temperature Ratings for Group 2.6 Materials	53
23	Pressure–Temperature Ratings for Group 2.7 Materials	54
23C	Pressure–Temperature Ratings for Group 2.7 Materials	55
24	Pressure–Temperature Ratings for Group 2.8 Materials	56
24C	Pressure–Temperature Ratings for Group 2.8 Materials	57
25	Pressure–Temperature Ratings for Group 2.9 Materials	58
25C	Pressure–Temperature Ratings for Group 2.9 Materials	59
26	Pressure–Temperature Ratings for Group 2.10 Materials	60
26C	Pressure–Temperature Ratings for Group 2.10 Materials	61
27	Pressure–Temperature Ratings for Group 2.11 Materials	62
27C	Pressure–Temperature Ratings for Group 2.11 Materials	63
28	Pressure–Temperature Ratings for Group 2.12 Materials	64

28C	Pressure-Temperature Ratings for Group 2.12 Materials	65
29	Dimensions of Ring-Joint Facings	66
29C	Dimensions of Ring-Joint Facings	67
30	Permissible Imperfections in Flange Facing Finish	68
30C	Permissible Imperfections in Flange Facing Finish	68
31	Dimensions of Class 150 Series A Flanges	69
31C	Dimensions of Class 150 Series A Flanges	70
32	Dimensions of Class 300 Series A Flanges	73
32C	Dimensions of Class 300 Series A Flanges	73
33	Dimensions of Class 400 Series A Flanges	77
33C	Dimensions of Class 400 Series A Flanges	79
34	Dimensions of Class 600 Series A Flanges	81
34C	Dimensions of Class 600 Series A Flanges	83
35	Dimensions of Class 900 Series A Flanges	85
35C	Dimensions of Class 900 Series A Flanges	87
36	Dimensions of Class 75 Series B Flanges	89
36C	Dimensions of Class 75 Series B Flanges	91
37	Dimensions of Class 150 Series B Flanges	93
37C	Dimensions of Class 150 Series B Flanges	95
38	Dimensions of Class 300 Series B Flanges	97
38C	Dimensions of Class 300 Series B Flanges	99
39	Dimensions of Class 400 Series B Flanges	101
39C	Dimensions of Class 400 Series B Flanges	103
40	Dimensions of Class 600 Series B Flanges	105
40C	Dimensions of Class 600 Series B Flanges	107
41	Dimensions of Class 900 Series B Flanges	109
41C	Dimensions of Class 900 Series B Flanges	111
42	Flange Bolting Dimensional Recommendations	112
A-1	Rating Ceiling Values in bar	117
A-2	Rating Ceiling Values in psi	118
B-1	Gasket Groups and Typical Materials	120
D-1	<i>F</i> Values	122
D-2	<i>n</i> Values	123

FOREWORD

In November 1980, a task force was appointed within Subcommittee C of the American National Standards Institute (ANSI) B16 Committee to develop a standard for pipe flanges in sizes NPS 26 through NPS 48. Every attempt was made to standardize those dimensions that existed within the industry for the materials covered by ANSI B16.5.

Prompted by suggestions from committee members, the task force was authorized to increase the size range to NPS 60. The first draft was developed in December 1982 to include Class 75 through Class 1500 for the size range NPS 26 through NPS 60. Flange dimensions were based on the Manufacturers Standardization Society, Standard Practice (MSS SP), 44 flanges, except for Class 75 flanges that are ANSI/API 605 flanges.

At the request of the American Petroleum Institute (API), flange dimensions, in accordance with the API Standard 605, were included in the subsequent drafts. Class 1500 flanges were deleted due to a lack of interest in using large-size flanges in that pressure-temperature rating.

The API 605 flanges for Classes 150 and 300 and for sizes NPS 36 and smaller for classes higher than Class 300 are not compatible with the MSS SP-44 flanges. Thus, the MSS SP-44 flanges are designated as Series A flanges, and the API 605 flanges are designated as Series B flanges in this Standard. Materials covered in this Standard are those in ANSI B16.5, except nickel base alloys are excluded. Pressure-temperature ratings are in accordance with ANSI B16.5.

In 1982, American National Standards Committee B16 was reorganized as the American Society of Mechanical Engineers (ASME) B16 Committee operating under procedures accredited by ANSI. Following approval by the Standards Committee and ASME, approval as an American National Standard was given by ANSI on June 12, 1990.

The 1996 edition allowed flanges marked with more than one material group or specification, revised flange face finish requirements, revised pressure-temperature ratings for several material groups, added permissible flange facing imperfections, added blind flanges for Series B flanges, and included several other revisions. Following approval by the Standards Committee and ASME Boiler and Pressure Vessel Committee, ANSI approved the 1996 edition as an American National Standard on October 3, 1996, with the new designation ASME B16.47-1996.

In 2006, several revisions were made, including use of metric units as primary units, with U.S. Customary units in either parenthetical or separate forms. [Mandatory Appendix I](#) was provided after the main text for convenience to cover ratings and dimensions in U.S. Customary units. Inch dimension bolt holes were retained for flanges manufactured to metric dimensions to avoid fit-up problems. Development of metric dimensions was done to reflect the intended precision of the dimension rather than by numerical conversion. For some materials, pressure-temperature ratings were revised to reflect revisions to material strength properties (tensile and yield) listed in the ASME Boiler and Pressure Vessel Code, Section II. Some materials were assigned to different rating tables in order to minimize changes to ratings for commonly used materials. Following the approvals of the Standards Committee and ASME, approval for the revised edition was granted by ANSI on November 6, 2006.

In the 2011 edition, the References section was revised to cover the requirements of material specification editions other than those listed in [Mandatory Appendix III](#). Following approval by the Standards Committee and the ASME Board on PTCS, the 2011 edition was approved as an American National Standard by ANSI on August 17, 2011, with the new designation ASME B16.47-2011.

In the 2017 edition, pressure-temperature ratings for Group 1.18 materials were revised at 650°C (1,200°F). A reference was made to MSS SP-44 for some classes of flanges made with materials having a high yield strength. A forging requirement was made explicit, and references were updated. Following approval by the ASME B16 Standards Committee, the 2017 edition was approved by ANSI as an American National Standard on March 6, 2017, with the new designation ASME B16.47-2017.

In ASME B16.47-2020, the U.S. Customary tables formerly in [Mandatory Appendix I](#) have been relocated to the main text and redesignated with a "C" suffix (e.g., Table I-1 is now [Table 3C](#)). Former [Mandatory Appendix I](#) has been deleted, and the subsequent [Mandatory Appendix](#) has been redesignated. Cross-references have been updated accordingly. In addition, this edition includes a new [Nonmandatory Appendix D](#) and new language describing ASME Cases, and bolt lengths have been added to the dimension tables. Following approval by the ASME B16 Standards Committee, this revision to the 2017 edition was approved by ANSI as an American National Standard on November 13, 2020, with the new designation ASME B16.47-2020.

ASME B16 COMMITTEE

Standardization of Valves, Flanges, Fittings, and Gaskets

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

C. E. Davila, *Chair*
R. M. Bojarczuk, *Vice Chair*
C. Ramcharran, *Secretary*

STANDARDS COMMITTEE PERSONNEL

A. Appleton , Alloy Stainless Products Co., Inc.	T. A. McMahon , Emerson Process Management
J. E. Barker , DeZURIK, Inc.	R. C. Merrick , Fluor Enterprises
R. W. Barnes , ANRIC Enterprises, Inc.	W. H. Patrick , The Dow Chemical Co.
D. C. Bayreuther , Neles Corp.	D. W. Raho , CCM 2000
W. B. Bedesem , Consultant	C. Ramcharran , The American Society of Mechanical Engineers
R. M. Bojarczuk , ExxonMobil Research and Engineering Co.	D. F. Reid , VSP Technologies
A. M. Cheta , Qatar Shell GTL	R. A. Schmidt , Canadoil
M. A. Clark , Consultant	J. Sekerak , CSA Group
G. A. Cuccio , Capitol Manufacturing Co.	J. P. Tucker , Flowserve
J. D'Avanzo , Fluoroseal Valves	F. R. Volgast , Volgstadt and Associates, Inc.
C. E. Davila , Crane ChemPharma and Energy	F. Wang , <i>Delegate</i> , China Productivity Center for Machinery
K. S. Felder , Valero Energy	J. D. Frank , <i>Alternate</i> , DeZURIK, Inc.
D. R. Frikken , Becht Engineering Co., Inc.	P. V. Craig , <i>Contributing Member</i> , Jomar Group
J. R. Holstrom , Val-Matic Valve and Manufacturing Corp.	G. Fabian , <i>Contributing Member</i> , Pennsylvania Machine Works
D. Hunt, Jr. , Fastenal	A. G. Kireta, Jr. , <i>Contributing Member</i> , Copper Development Association, Inc.
G. A. Jolly , Samshin, Ltd.	
E. J. Lain , Exelon Nuclear	

SUBCOMMITTEE C - STEEL FLANGES AND FLANGED FITTINGS

A. M. Cheta , <i>Chair</i> , Qatar Shell GTL	J. R. Holstrom , Val-Matic Valve and Manufacturing Corp.
A. Carrion , <i>Secretary</i> , The American Society of Mechanical Engineers	G. A. Jolly , Samshin, Ltd.
A. Appleton , Alloy Stainless Products Co., Inc.	R. C. Merrick , Fluor Enterprises
W. B. Bedesem , Consultant	W. H. Patrick , The Dow Chemical Co.
C. E. Davila , Crane ChemPharma and Energy	D. W. Raho , CCM 2000
B. Dennis , Kerkau Manufacturing	T. V. Ramakrishnan , Forged Components, Inc.
J. G. Dominguez , Welding Concepts, Inc.	R. A. Schmidt , Canadoil
J. P. Ellenberger , Retired	D. E. Tezzo , Emerson
D. R. Frikken , Becht Engineering Co., Inc.	J. A. Tubb , JCM Industries, Inc.
E. Gulgun , International Standard Valve, Inc.	J. P. Tucker , Flowserve
G. B. Hailegiorgis , Al Global	G. T. Walden , Ferguson
M. M. Haynie , Bechtel	M. M. Zaidi , Worley

CORRESPONDENCE WITH THE B16 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions or a case, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B16 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued to provide alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee web page.

Requests for Cases shall provide a Statement of Need and Background information. The request should identify the Standard and the paragraph, figure, or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the B16 Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B16 Standards Committee.

Requests for interpretation should preferably be submitted through the online Interpretation Submittal Form. The form is accessible at <http://go.asme.org/InterpretationRequest>. Upon submittal of the form, the Inquirer will receive an automatic e-mail confirming receipt.

If the Inquirer is unable to use the online form, he/she may e-mail the request to the Secretary of the B16 Standards Committee at SecretaryB16@asme.org or mail it to the above address. The request for an interpretation should be clear and unambiguous. It is further recommended that the Inquirer submit his/her request in the following format:

Subject: Cite the applicable paragraph number(s) and the topic of the inquiry in one or two words.
Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.
Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. Please provide a condensed and precise question, composed in such a way that a "yes" or "no" reply is acceptable.
Proposed Reply(ies): Provide a proposed reply(ies) in the form of "Yes" or "No," with explanation as needed. If entering replies to more than one question, please number the questions and replies.
Background Information: Provide the Committee with any background information that will assist the Committee in understanding the inquiry. The Inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in the format described above may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

Moreover, ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the inquiry information submitted, it is the opinion of the Committee that the Inquirer should seek assistance, the inquiry will be returned with the recommendation that such assistance be obtained.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B16 Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the B16 Standards Committee.

ASME B16.47-2020

SUMMARY OF CHANGES

Following approval by the ASME B16 Standards Committee and ASME, and after public review, ASME B16.47-2020 was approved by the American National Standards Institute on November 13, 2020.

In ASME B16.47-2020, the U.S. Customary tables formerly in Mandatory Appendix I have been relocated to the main text and redesignated with a “C” suffix (e.g., Table I-1 is now Table 3C). Former Mandatory Appendix I has been deleted, and the subsequent Mandatory Appendix has been redesignated. Cross-references have been updated accordingly. In addition, this edition includes the following changes identified by a margin note, **(20)**. The Record Numbers listed below are explained in more detail in the “List of Changes in Record Number Order” following this Summary of Changes.

<i>Page</i>	<i>Location</i>	<i>Change (Record Number)</i>
1	1	Title revised (18-869)
1	1.1	Title revised (18-869)
2	1.12	Added (18-869)
4	4.2.9	Added (18-869)
5	6.1.1	Revised (19-1684)
6	6.5.2	Added and subsequent paragraph redesignated (18-1108)
6	7.1	Subparagraphs (a) and (b) revised (19-1684)
6	7.2	In-text table revised (19-1684)
6	7.3.1	Revised (19-1684)
6	7.3.2	Subparagraphs (a) and (b) revised (19-1684)
7	7.4	Revised (19-1684)
8	Figure 1	U.S. Customary values added
9	Figure 2	U.S. Customary values added
10	Figure 3	U.S. Customary values added
11	Table 1	For Material Group 1.15, "Forgings" entry revised (20-887)
36	Table 14	(1) Forgings material revised (20-887) (2) For 600°C, 625°C, and 650°C, working pressures revised (20-887)
37	Table 14C	(1) Forgings material revised (20-887) (2) For 1,100°F, 1,150°F, and 1,200°F, working pressures revised (20-887)
66	Table 29	Tolerances revised (18-1108)
67	Table 29C	Tolerances revised (18-1108)
68	Table 30	Revised
68	Table 30C	Former Table I-28 revised
69	Table 31	Revised
71	Table 31C	Former Table I-29 revised
73	Table 32	Revised
75	Table 32C	Former Table I-30 revised
77	Table 33	Revised
79	Table 33C	Former Table I-31 revised

<i>Page</i>	<i>Location</i>	<i>Change (Record Number)</i>
81	Table 34	Revised
83	Table 34C	Former Table I-32 revised
85	Table 35	Revised
87	Table 35C	Former Table I-33 revised
89	Table 36	Revised
91	Table 36C	Former Table I-34 revised
93	Table 37	Revised
95	Table 37C	Former Table I-35 revised
97	Table 38	Revised
99	Table 38C	Former Table I-36 revised
101	Table 39	Revised
103	Table 39C	Former Table I-37 revised
105	Table 40	Revised
107	Table 40C	Former Table I-38 revised
109	Table 41	Revised
111	Table 41C	Former Table I-39 revised
112	Table 42	Spelling of “coarse” corrected by errata
113	Mandatory Appendix I	References updated
122	Nonmandatory Appendix D	Added (18-1108)

LIST OF CHANGES IN RECORD NUMBER ORDER

<u>Record Number</u>	<u>Change</u>
14-2169	Revised para. 5.3.4 to reference para. 5.4.2 and Nonmandatory Appendix B.
17-655	Revised General Note (g) in Tables 31 through 41 (Tables 31C through 41C) to address reducing flanges or pressure taps made in blind flanges for testing, vents, or drains.
18-869	Revised titles of Section 1 and para. 1.1 and added new paras. 1.12 and 4.2.9 to provide guidance on ASME Cases.
18-1108	Added new para. 6.5.2 and Nonmandatory Appendix D so that information on minimum bolt length matches that in ASME B16.5.
19-1684	Revised metric dimensions to align with U.S. Customary dimensions.
20-887	Revised Tables 1 and 14 (14C) to add a material nomenclature change from A182 Gr. F91 to A182 Gr. F91 Type 1.

LARGE DIAMETER STEEL FLANGES

NPS 26 Through NPS 60

Metric/Inch Standard

(20) **1 GENERAL**

(20) **1.1 Scope**

This Standard covers pressure–temperature ratings, materials, dimensions, tolerances, marking, and testing for pipe flanges in sizes NPS 26 through NPS 60. Included are flanges with rating class designations 75, 150, 300, 400, 600, and 900 with requirements given in both SI (Metric) and U.S. Customary units, with diameter of bolts and flange bolt holes expressed in inch units.

This Standard is limited to

- (a) flanges made from cast or forged materials
- (b) blind flanges made from cast, forged, or plate materials (see [Tables 1](#) and [2](#))

Also included in this Standard are requirements and recommendations regarding flange bolting, flange gaskets, and flange joints.

1.2 Flange Series

This Standard provides two series of flange dimensions. Series A specifies flange dimensions for general use flanges. Series B specifies flange dimensions for compact flanges that, in most cases, have smaller bolt circle diameters than Series A flanges. These two series of flanges are, in general, not interchangeable. The user should recognize that some flanged valves, equipment bolted between flanges, and flanged equipment may be compatible with only one series of these flanges.

1.3 References

Codes, standards, and specifications, containing provisions to the extent referenced herein, constitute requirements of this Standard. These references are listed in [Mandatory Appendix I](#).

1.4 Time of Purchase, Manufacture, or Installation

The pressure–temperature ratings in this Standard are applicable upon its publication to all flanges within its scope that otherwise meet its requirement. For unused flanges maintained in inventory, the manufacturer of the flange may certify conformance to this edition, provided that it can be demonstrated that all require-

ments of this edition have been met. Where such components were installed in accordance with the pressure–temperature ratings of an earlier edition of this Standard, those ratings are applicable, except as may be governed by the applicable code or regulation.

1.5 User Accountability

This Standard cites responsibilities that are to be assumed by the flange user in the areas of, for example

- (a) application
- (b) installation
- (c) system pressure testing
- (d) operation
- (e) material selection

1.6 Quality Systems

Requirements relating to the product manufacturer's quality system program are described in [Nonmandatory Appendix C](#).

1.7 Relevant Units

This Standard states values in both SI (Metric) and U.S. Customary units. As an exception, diameter of bolts and flange bolt holes are expressed in inch units only. These systems of units are to be regarded separately as standard. Within the text, the U.S. Customary units are shown in parentheses. The values stated in each system are not exact equivalents; therefore, it is required that each system of units be used independently of the other. Except for diameter of bolts and flange bolt holes, combining values from the two systems constitutes nonconformance with the Standard.

1.8 Selection of Materials

Criteria for selection of materials suitable for particular fluid service are not within the scope of this Standard.

1.9 Convention

For determining conformance with this Standard, the convention for fixing significant digits where limits (maximum and minimum values) are specified shall be as defined in ASTM Practice E29. This requires that an observed or calculated value be rounded off to the