

**ASME B30.3-2004**  
**(Revision of ASME B30.3-1996)**

# **Construction Tower Cranes**

---

**Safety Standard for Cableways, Cranes, Derricks, Hoists,  
Hooks, Jacks, and Slings**

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

**ASME B30.3-2004**  
(Revision of ASME B30.3-1996)

# Construction Tower Cranes

**Safety Standard for Cableways, Cranes, Derricks, Hoists,  
Hooks, Jacks, and Slings**

**AN AMERICAN NATIONAL STANDARD**



**The American Society of  
Mechanical Engineers**

Three Park Avenue • New York, NY 10016

Date of Issuance: November 15, 2004

The next edition of this Standard is scheduled for publication in 2007. There will be no addenda issued to this edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the ASME Web site under the Committee Pages at <http://www.asme.org/codes/> as they are issued, and will also be published within the next edition of the Standard.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,  
in an electronic retrieval system or otherwise,  
without the prior written permission of the publisher.

The American Society of Mechanical Engineers  
Three Park Avenue, New York, NY 10016-5990

Copyright © 2004 by  
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS  
All rights reserved  
Printed in U.S.A.

# CONTENTS

Foreword .....	v	
Committee Roster .....	vi	
B30 Series Introduction .....	viii	
Summary of Changes .....	ix	
<b>Chapter 3-0      Scope, Definitions, and References</b> .....	<b>1</b>	
Section 3-0.1    Scope of B30.3 .....	1	
Section 3-0.2    Definitions .....	1	
Section 3-0.3    References .....	8	
<b>Chapter 3-1      Erection and Dismantling, Characteristics, and Construction</b> .....	<b>11</b>	
Section 3-1.1    Site Preparation and Erection .....	11	
Section 3-1.2    Load Ratings .....	14	
Section 3-1.3    Stability .....	14	
Section 3-1.4    Documentation .....	15	
Section 3-1.5    Load Hoisting and Boom Luffing (Boom Hoist) Equipment .....	16	
Section 3-1.6    Slewing (Swing) Mechanism .....	17	
Section 3-1.7    Travel Equipment .....	18	
Section 3-1.8    Climbing Equipment .....	18	
Section 3-1.9    Load Trolleys .....	18	
Section 3-1.10   Brakes .....	18	
Section 3-1.11   Operator Aids .....	19	
Section 3-1.12   Pendants, Stay Ropes, and Guys .....	19	
Section 3-1.13   Reeving Accessories .....	19	
Section 3-1.14   Counterweights and Ballast .....	19	
Section 3-1.15   Controls .....	20	
Section 3-1.16   Electrical Equipment .....	20	
Section 3-1.17   Operator's Cabs .....	21	
Section 3-1.18   General Requirements .....	21	
<b>Chapter 3-2      Inspection, Testing, and Maintenance</b> .....	<b>23</b>	
Section 3-2.1    Inspection .....	23	
Section 3-2.2    Testing .....	24	
Section 3-2.3    Maintenance .....	25	
Section 3-2.4    Rope Inspection, Replacement, and Maintenance .....	25	
<b>Chapter 3-3      Operation</b> .....	<b>28</b>	
Section 3-3.1    Qualifications for and Conduct of Operators and Operating Practices .....	28	
Section 3-3.2    Operating Practices .....	29	
Section 3-3.3    Signals .....	31	
Section 3-3.4    Miscellaneous .....	32	
<b>Figures</b>		
1	Hammerhead Tower Crane — Fixed-Base, Free-Standing Crane .....	2
2	Luffing Tower Crane — Fixed-Base, Free-Standing Crane .....	3
3	Travel Base for Free-Standing Crane .....	4
4	Types of Fixed Bases .....	5
5	Guyed Tower Crane .....	6
6	Braced Crane .....	7
7	Internal Climbing Crane .....	9
8	Dead Ending Rope in a Socket .....	19

9	Core Failure in Rotation-Resistant Rope .....	26
10	Standard Hand Signals for Controlling Construction Tower Cranes .....	34
11	Danger Zone for Cranes and Lifted Loads Operating Near Electrical Transmission Lines .....	35
<b>Table</b>		
1	Required Clearance for Normal Voltage in Operation Near High-Voltage Power Lines .....	32

Currently in preview, click buy full versi

## FOREWORD

This American National Standard, Safety Standard for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings, has been developed under the procedures accredited by the American National Standards Institute (formerly the United States of America Standards Institute). This Standard had its beginning in December 1916 when an eight-page Code of Safety Standards for Cranes, prepared by an ASME Committee on the Protection of Industrial Workers, was presented to the annual meeting of the ASME.

Meetings and discussions regarding safety on cranes, derricks, and hoists were held from 1920 to 1925, involving the ASME Safety Code Correlating Committee, the Association of Iron and Steel Electrical Engineers, the American Museum of Safety, the American Engineering Standards Committee (later changed to American Standards Association and subsequently to the USA Standards Institute), Department of Labor—State of New Jersey, Department of Labor and Industry—State of Pennsylvania, and the Locomotive Crane Manufacturers Association. On June 11, 1925, the American Engineering Standards Committee approved the ASME Safety Code Correlating Committee's recommendation and authorized the project with the U.S. Department of the Navy, Bureau of Yards and Docks, and ASME as sponsors.

In March 1926, invitations were issued to 50 organizations to appoint representatives to a Sectional Committee. The call for organization of this Sectional Committee was sent out October 2, 1926, and the committee organized November 4, 1926, with 57 members representing 29 national organizations. The Safety Code for Cranes, Derricks, and Hoists, ASA B30.2-1943, was created from the eight-page document referred to in the first paragraph. This document was reaffirmed in 1952 and widely accepted as a safety standard.

Due to changes in design, advancement in techniques, and general interest of labor and industry in safety, the Sectional Committee, under the joint sponsorship of ASME and the Naval Facilities Engineering Command, U.S. Department of the Navy, was reorganized as an American National Standards Committee on January 31, 1956, with 39 members representing 27 national organizations.

The format of the previous code was changed so that separate volumes (each complete as to construction and installation; inspection, testing, and maintenance; and operation) would cover the different types of equipment included in the scope of B30.

In 1982, the Committee was reorganized as an Accredited Organization Committee, operating under procedures developed by ASME and accredited by the American National Standards Institute.

This Standard presents a coordinated set of rules that may serve as a guide to government and other regulatory bodies and municipal authorities responsible for the guarding and inspection of the equipment falling within its scope. The suggestions leading to accident prevention are given both as mandatory and advisory provisions; compliance with both types may be required by employers of their employees.

In case of practical difficulties, new developments, or unnecessary hardship, the administrative or regulatory authority may grant variances from the literal requirements or permit the use of other devices or methods, but only when it is clearly evident that an equivalent degree of protection is thereby secured. To secure uniform application and interpretation of this Standard, administrative or regulatory authorities are urged to consult the B30 Committee, in accordance with the format described in Section III, before rendering decisions on disputed points.

This volume of the Standard, which was approved by the B30 Committee and by ASME, was approved by ANSI and designated as an American National Standard on January 22, 2004.

Safety codes and standards are intended to enhance public safety. Revisions result from committee consideration of factors such as technological advances, new data, and changing environmental and industry needs. Revisions do not imply that previous editions were inadequate.

# ASME B30 COMMITTEE

## Safety Standards for Cableways, Cranes, Derricks, Hoists, Hooks, Jacks, and Slings

(The following is the roster of the Committee at the time of approval of this Standard.)

### STANDARDS COMMITTEE OFFICERS

**P. S. Zorich**, *Chair*  
**B. D. Closson**, *Vice Chair*  
**J. D. Wendler**, *Secretary*

### STANDARDS COMMITTEE PERSONNEL

**N. E. Andrew**, Northrop Grumman Ship Systems  
**W. T. Hargrove**, *Alternate*, ManTech International Corp.  
**R. E. Bluff**, Gantry Constructors, Inc.  
**R. J. Bolen**, E. I. DuPont  
**G. B. Hetherston**, *Alternate*, E. I. DuPont  
**A. D. Brown**, A. D. Brown Co.  
**L. D. DeMark**, International Union of Operating Engineers  
**S. C. Buck**, *Alternate*, International Union of Operating Engineers  
**T. A. Christensen**, Alliance of American Insurers/Liberty Mutual Insurance  
**M. W. Mills**, *Alternate*, Liberty Mutual Group  
**B. D. Closson**, NACB Technical Services, Inc.  
**T. L. Blanton**, *Alternate*, NACB Group, Inc.  
**J. P. Colletti**, John P. Colletti & Associates, Inc.  
**R. A. Dahlin**, Walker Magnetics Group  
**J. W. Downs, Jr.**, *Alternate*, Downs Crane and Hoist Co.  
**D. W. Eckstine**, Eckstine & Associates  
**R. J. Edwards**, Schwing America, Inc.  
**R. H. Fowler**, U.S. Department of the Air Force  
**J. L. Franks**, Consultant  
**R. C. Slater**, *Alternate*, McKay International Engineering  
**J. L. Gordon**, FKI Industries, Inc.  
**R. R. Reisinger**, *Alternate*, FKI Industries, Inc.  
**N. C. Hargreaves**, Power Crane & Shovel Association/Terex Corp.  
**E. D. Fidler**, *Alternate*, Terex Corp.  
**J. J. Headley**, Crane Institute of America  
**R. M. Parnell**, *Alternate*, Industrial Training International  
**C. W. Ireland**, National Oilwell  
**A. Egging**, *Alternate*, National Oilwell  
**L. S. Johnson**, American Equipment Co.  
**R. M. Kohner**, Landmark Engineering Services  
**H. I. Shapiro**, *Alternate*, Howard I. Shapiro & Associates Consulting Engineers  
**H. G. Leidich**, Ingersoll-Rand  
**J. T. Perkins**, *Alternate*, Ingersoll-Rand  
**C. E. Lucas**, The Crosby Group  
**P. A. Boeckman**, *Alternate*, The Crosby Group  
**E. K. Marburg**, Columbus-Mckinnon  
**M. G. Miller**, *Alternate*, Columbus-Mckinnon  
**L. D. Means**, Wire Rope Technical Board/Means Engineering and Consulting  
**D. M. Sleightholm**, *Alternate*, Bridon America Corp.  
**K. J. Miller**, Group Engineering Group  
**D. W. Smith**, *Alternate*, Chicago Bridge and Iron Co.  
**G. L. Owens**, Granite Construction, Inc.  
**J. E. Richardson**, U.S. Department of the Navy  
**W. P. Keams**, Manitowoc Crane Group  
**T. E. Ward-Robichaux**, *Alternate*, Lift Solutions, Inc.  
**J. W. Rowland III**, Consultant  
**E. E. Rudy**, U.S. Department of the Army  
**J. C. Ryan**, BOH Bros. Construction Co.  
**A. Ruud**, *Alternate*, Phillips and Jordan  
**D. Sayenga**, Associated Wire Rope Fabricators  
**D. J. Bishop**, *Alternate*, Bishop Lifting Products, Inc.  
**G. W. Shields**, Caterpillar, Inc.  
**R. G. Strain**, Advanced Automation Technologies, Inc.  
**A. R. Toth**, Morris Material Handling  
**B. E. Weir, Jr.**, National Erectors Association/Norris Brothers Co., Inc.  
**S. Conant**, *Alternate*, Conant Crane Rental Co.  
**J. D. Wendler**, The American Society of Mechanical Engineers  
**R. C. Wild**, U.S. Army Corps of Engineers  
**S. G. Testerman**, *Alternate*, U.S. Army Corps of Engineers  
**D. N. Wolff**, National Crane Corp.  
**A. L. Calta**, *Alternate*, National Crane Corp.  
**P. S. Zorich**, RZP International Ltd.

## HONORARY MEMBERS

**J. M. Klibert**, Lift-All Co., Inc.  
**R. W. Parry**, Consultant

## B30.3 SUBCOMMITTEE PERSONNEL

<b>P. R. Juhren</b> , <i>Chair</i> , Morrow Equipment Co., LLC	<b>L. K. Shapiro</b> , Howard I. Shapiro & Associates Consulting Engineers
<b>B. D. Closson</b> , NACB Technical Services, Inc.	<b>C. H. Smith</b> , Crane and Lift Equipment Associates
<b>M. Kohler</b> , Noell Crane and Services, Inc.	<b>C. R. Thorenson</b> , Manitowoc Crane Group
<b>D. Ritchie</b> , The Construction Safety Council	<b>K. L. Handland</b> , <i>Alternate</i> , Manitowoc Crane Group
<b>H. I. Shapiro</b> , Howard I. Shapiro & Associates Consulting Engineers	

# SAFETY STANDARD FOR CABLEWAYS, CRANES, DERRICKS, HOISTS, HOOKS, JACKS, AND SLINGS

(04)

## B30 SERIES INTRODUCTION

### GENERAL

This Standard is one of a series of safety standards on various subjects which have been formulated under the general auspices of the American National Standards Institute. One purpose of the Standard is to serve as a guide to governmental authorities having jurisdiction over subjects within the scope of the Standard. It is expected, however, that the Standard will find a major application in industry, serving as a guide to manufacturers, purchasers, and users of the equipment.

For the convenience of the user, the Standard has been divided into separate volumes:

- B30.1 Jacks
- B30.2 Overhead and Gantry Cranes (Top Running Bridge, Single or Multiple Girder, Top Running Trolley Hoist)
- B30.3 Construction Tower Cranes
- B30.4 Portal, Tower, and Pedestal Cranes
- B30.5 Mobile and Locomotive Cranes
- B30.6 Derricks
- B30.7 Base Mounted Drum Hoists
- B30.8 Floating Cranes and Floating Derricks
- B30.9 Slings
- B30.10 Hooks
- B30.11 Monorails and Underhung Cranes
- B30.12 Handling Loads Suspended from Rotorcraft
- B30.13 Storage/Retrieval (S/R) Machines and Associated Equipment
- B30.14 Side Boom Tractors
- B30.15 Mobile Hydraulic Cranes  
Note: B30.15-1993 has been withdrawn. The revision of B30.15 is included in the latest edition of B30.5.
- B30.16 Overhead Hoists (Underhung)
- B30.17 Overhead and Gantry Cranes (Top Running Bridge, Single Girder, Underhung Hoist)
- B30.18 Stacker Cranes (Top or Under Running Bridge, Multiple Girder With Top or Under Running Trolley Hoist)
- B30.19 Cableways
- B30.20 Below-the-Hook Lifting Devices
- B30.21 Manually Lever Operated Hoists
- B30.22 Articulating Boom Cranes
- B30.23 Personnel Lifting Systems

- B30.24 Container Cranes<sup>1</sup>
- B30.25 Scrap and Material Handlers
- B30.26 Rigging Hardware<sup>1</sup>
- B30.27 Material Placement of Systems
- B30.28 Balance-Lifting Units<sup>1</sup>

If adopted for governmental use, the references to other national codes and standards in the specific volumes may be changed to refer to the corresponding regulations of the governmental authorities.

The use of cableways, cranes, derricks, hoists, hooks, jacks, and slings is subject to certain hazards that cannot be met by mechanical means but only by the exercise of intelligence, care, and common sense. It is therefore essential to have personnel involved in the use and operation of equipment who are competent, careful, physically and mentally qualified, and trained in the safe operation of the equipment and the handling of the loads. Serious hazards are overloading, dropping or slipping of the load caused by improper hitching or slinging, obstructing the free passage of the load, and using equipment for a purpose for which it was not intended or designed.

The Standards Committee fully realizes the importance of proper design factors, minimum or maximum sizes, and other limiting dimensions of wire rope or chain and their fastenings, sheaves, sprockets, drums, and similar equipment covered by the Standard, all of which are closely connected with safety. Sizes, strengths, and similar criteria are dependent on many different factors, often varying with the installation and uses. These factors depend on the condition of the equipment or material; on the loads; on the acceleration or speed of the ropes, chains, sheaves, sprockets, or drums; on the type of attachments; on the number, size, and arrangement of sheaves or other parts; on environmental conditions causing corrosion or wear; and on many variables that must be considered in each individual case. The rules given in the Standard must be interpreted accordingly, and judgment used in determining their application.

Some of the provisions of this Standard require compliance with information found in manuals or other

<sup>1</sup> B30.24, B30.26, B30.27, and B30.28 are in the developmental stage.

documents supplied by the manufacturer with the equipment. This information includes recommendations, requirements, and instructions (e.g., “the reeving shall be checked for compliance with the recommendations of the manufacturer”).

Compliance with the provisions should not preclude the possibility of consulting a qualified person. This is true particularly when: the equipment has been altered, repaired, or modified; the manuals or documents supplied by the manufacturer are no longer available; or the manufacturer or a successor is no longer in business and the manuals are no longer available. However, the purpose of consulting a qualified person shall not be to avoid contacting the manufacturer and using the information supplied by the manufacturer.

The Standards Committee will be glad to receive criticisms of this Standard’s requirements and suggestions for its improvement, especially those based on actual experience in application of the rules.

Suggestions for changes to the Standard should be submitted to the Secretary of the B30 Committee, ASME, Three Park Avenue, New York, NY 10016, and should be in accordance with the following format:

- (a) cite the specific paragraph designation of the pertinent volume;
- (b) indicate the suggested change (addition, deletion, revision, etc.);
- (c) briefly state the reason and/or evidence for the suggested change;
- (d) submit suggested changes to more than one paragraph in the order that the paragraphs appear in the volume.

The B30 Committee will consider each suggested change in a timely manner in accordance with its procedures.

## SECTION I: SCOPE

This Standard applies to the construction, installation, operation, inspection, and maintenance of jacks; power-operated cranes, monorails, and crane runways; power-operated and manually operated derricks and hoists; lifting devices, hooks, and slings; and cableways.

This Standard does not apply to track and automotive jacks, railway and automobile wrecking cranes, shipboard cranes, shipboard cargo-handling equipment, well-drilling derricks, skip hoists, mine hoists, truck body hoists, car and baggage pullers, conveyors, excavating equipment, or equipment falling within the scope of the following Committees: A10, A17, A90, A92, A120, B20, B56, and B7.

## SECTION II: PURPOSE

This Standard is designed to:

- (a) guard against and minimize injury to workers, and otherwise provide for the protection of life, limb,

and property by prescribing safety requirements;

- (b) provide direction to owners, employers, supervisors, and others concerned with, or responsible for, its application; and

- (c) guide governments and other regulatory bodies in the development, promulgation, and enforcement of appropriate safety directives.

## SECTION III: INTERPRETATIONS

Upon request, the B30 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B30 Committee, ASME, Three Park Avenue, New York, NY 10016.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his request utilizing the following format.

**Subject:** Cite the applicable paragraph number(s) and provide a concise description.

**Edition:** Cite the applicable edition of the pertinent volume for which the interpretation is being requested.

**Question:** Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for approval of a proprietary design or situation. The inquirer may also include any plans or drawings which are necessary to explain the question; however, they should not contain any proprietary names or information.

Requests that are not in this format will be rewritten in this format by the Committee prior to being answered, which could change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information which might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

## SECTION IV: NEW AND EXISTING INSTALLATIONS

- (a) *Effective Date.* The effective date of this volume for the purpose of defining new and existing installations shall be 1 year after its date of issuance.

- (b) *New Installations.* Construction, installation, inspection, testing, maintenance, and operation of equipment manufactured and facilities constructed after the effective date of this volume shall conform with the mandatory requirements of this volume.

(c) *Existing Installations.* Inspection, testing, maintenance, and operation of equipment manufactured and facilities constructed prior to the effective date of this volume shall be done, as applicable, in accordance with the requirements of this volume.

It is not the intent of this volume to require retrofitting of existing equipment. However, when an item is being modified, its performance requirement shall be reviewed relative to the current volume. If the performance differs substantially, the need to meet the current requirement shall be evaluated by a qualified person selected by the owner (user). Recommended changes shall be made by the owner (user) within 1 year.

## **SECTION V: MANDATORY AND ADVISORY RULES**

Mandatory rules of this volume are characterized by use of the word *shall*. If a provision is of an advisory nature, it is indicated by use of the word *should* and is a recommendation to be considered, the advisability of which depends on the facts in each situation.

## **SECTION VI: METRIC CONVERSIONS**

This Standard contains SI (metric) units as well as U.S. Customary units. The values stated in customary units are to be regarded as the standard. The SI units are a direct (soft) conversion from the customary units.

# ASME B30.3-2004 SUMMARY OF CHANGES

Following approval by the ASME B30 Committee and ASME, and after public review, ASME B30.3-2004 was approved by the American National Standards Institute on January 22, 2004.

ASME B30.3-2004 includes editorial changes, revisions, and corrections introduced in ASME B30.3a-1997, B30.3b-1998, and B30.3c-1999, as well as the following changes identified by a margin note, (04).

<i>Page</i>	<i>Location</i>	<i>Change</i>
viii, x	B30 Series Introduction	General and Section VI revised
1-3, 6, 8	3-0.2.2	(1) Definitions of <i>base, tower crane; climbing; climbing frame; pitch diameter; service, heavy; service, light; service, normal;</i> and <i>trolley</i> revised (2) Definitions of <i>base, fixed</i> and <i>telescoping</i> deleted
11	3-1.1.1(e)	Revised
12	3-1.1.3	Revised in its entirety
	3-1.1.4(i)	Revised
13	3-1.1.6(c)	Revised
	3-1.1.6(d)	Revised
14	3-1.2.1(c)	Revised
16	3-1.5.1	Revised in its entirety
	3-1.5.2	Revised in its entirety
17	3-1.5.3(a)	Revised
	3-1.5.4(a)	Revised
18	Section 3-1.8	(1) Title revised (2) Subparagraphs 3-1.8(a), (b), (c), and (e) revised
19	Section 3-1.11	(1) Title revised (2) Revised in its entirety
	3-1.13(d)	Last sentence added
20	3-1.15.1(j)	Added
24	3-2.1.6	Added
25	3-2.3.3(a)	Revised

<i>Page</i>	<i>Location</i>	<i>Change</i>
28–30	3-3.1.3	<ul style="list-style-type: none"> <li>(1) New subparagraph (l) added</li> <li>(2) Former subparagraphs (l) through (p) redesignated as (m) through (q), respectively</li> <li>(3) Subparagraphs (m) and (n) revised</li> </ul>
	3-3.2.1	<ul style="list-style-type: none"> <li>(1) New subparagraph (b) added</li> <li>(2) Former subparagraphs (b) through (d) redesignated as (c) through (e), respectively</li> </ul>

# CONSTRUCTION TOWER CRANES

## Chapter 3-0 Scope, Definitions, and References

### SECTION 3-0.1: SCOPE OF B30.3

Within the general scope as defined in Section I, B30.3 applies to construction tower cranes, powered by electric motors or internal combustion engines, and any variations thereof which retain the same fundamental characteristics. The scope includes cranes of the above type that adjust operating radius by means of a boom luffing mechanism, or by means of a trolley traversing a horizontal boom, or by means of a combination of the two. Construction tower cranes may be mounted on fixed or traveling bases. Additional mounting means may include arrangements that permit the crane to climb in the structure being built, or that permit increasing the tower height as the structure rises and utilizing braces attached to the host structure as needed.

The requirements of this volume are applicable only to cranes when used in lifting work. Permanently mounted tower cranes (refer to ASME B30.4) and mobile crane tower attachments (refer to ASME B30.5) are not within the scope of this volume.

### SECTION 3-0.2: DEFINITIONS

#### 3-0.2.1 Types of Cranes

##### (a) By Type of Application

*construction tower crane*: a hammerhead, luffing, or other type of tower crane that is regularly assembled and disassembled for use at various sites. It is usually characterized by provisions to facilitate erection and dismantling and may include features to permit climbing or telescoping.

*permanently mounted tower crane*: a hammerhead, luffing, or other type of tower crane that is erected for longer term use at one location, (five years or more). The configuration of the crane usually remains unchanged during the entire installation period. Permanently mounted tower cranes are covered under ASME B30.4.

##### (b) By Type of Boom

*hammerhead tower crane*: a tower crane with a horizontal boom and a load trolley that traverses the boom to change load radius (see Figs. 1 and 5).

*luffing tower crane*: a crane with a boom pinned to the superstructure at its inner end and containing load hoisting tackle at its outer end, and with a hoist mechanism to raise or lower the boom in a vertical plane to change load radius (see Figs. 2 and 6).

##### (c) By Support Arrangement

*braced or guyed tower crane*: a tower crane with braces or guys attached to the tower (mast) to permit the crane to be erected to greater than the maximum free-standing height (see Figs. 5 and 6).

*free-standing tower crane*: a tower crane that is supported on a foundation or structural frame without assistance from braces, guys, or other means (see Figs. 1 and 2).

*internal climbing tower crane*: a tower crane arranged to raise itself from floor to floor in a building as construction advances (see Fig. 7).

##### (d) By Ability to Travel

*fixed-base tower crane*: a free-standing, braced, or guyed tower crane that is mounted on a foundation or structural frame and does not travel (see Figs. 1 and 2).

*traveling tower crane*: a free-standing tower crane mounted on a ballasted platform furnished with trucks that ride along rails (see Fig. 3).

#### 3-0.2.2 General

(04)

*accessory*: a secondary part or assembly of parts that contributes to the overall function and usefulness of a machine.

*administrative or regulatory authority*: governmental agency, or the employer in the absence of governmental jurisdiction.

*appointed*: assigned specific responsibilities by the employer or the employer's representative.

*authorized*: approved as satisfactory by a duly constituted administrative or regulatory authority.

*axis of rotation*: the vertical line about which a crane swings.

*balance*: the condition of the superstructure of a tower crane necessary for telescoping and climbing; the load or the boom is positioned at that radius which causes the