

ASME B89.3.7-2013

Granite Surface Plates

AN AMERICAN NATIONAL STANDARD



The American Society of
Mechanical Engineers

ASME B89.3.7-2013

Granite Surface Plates

AN AMERICAN NATIONAL STANDARD



The American Society of
Mechanical Engineers

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: June 26, 2013

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Periodically certain actions of the ASME B89 Committee may be published as Code Cases. Code Cases and interpretations are published on the ASME Web site under the Committee Pages at <http://cstools.asme.org/> as they are issued.

Errata to codes and standards may be posted on the ASME Web site under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The Committee Pages can be found at <http://cstools.asme.org/>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting “Errata” in the “Publication Information” section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent nor assumes any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2013 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword	iv
Committee Roster	v
Correspondence With the B89 Committee	vi
Introduction	vii
1 General	1
2 Definitions	1
3 References	1
4 General Requirements	2
Figures	
1 Exaggerated View of a Surface Plate With Twist	2
2 Surface Plate, Style 1, No Ledge, Rectangular or Square	3
3 Surface Plate, Style 2, Two-Ledge, Either Direction, Rectangular or Square	3
4 Surface Plate, Style 3, Four-Ledge, Rectangular or Square	3
5 Surface Plate, Style 4, No Ledge, Round	3
6 Support Layout for Rectangular Surface Plate	5
7 Support Layout for Round Surface Plate	5
Tables	
1 Common Sizes and Flatness Tolerances	4
2 Tolerances for Local Variations in Flatness Using a Repeat Reading Gage	6
3 Restrictions on Surface Area for Flatness and Twist	6
Mandatory Appendix	
I Testing	9
Nonmandatory Appendices	
A Mineralogical and Physical Properties	14
B Thickness	15
C Supports	20
D Factors Distorting the Work Surface	21
E Care of Granite Surface Plates	24
F Guidance to Estimating Uncertainty in Surface Plate Measurement	25
G Traceability	31

FOREWORD

This ASME Standard is a revision of the 1973 Federal Specification GGG-P-463c which has been used extensively in American industry since its publication. Although the measurement methods for surface plates had already been in use some decades prior to the Federal Specification, it did serve to document these methods. In addition, it provided common language and terms of classification for surface plate manufacturing and commerce. While little has changed with regard to measurement methods and the flatness tolerances of the various plate grades are still relevant today, ASME B89 Division 3 decided an effort was justified to modernize the document. Most notably, a more complete glossary was added with currently accepted definitions, metric units were added where appropriate, and a new format was used that should be more familiar to current users of the Standard. This Committee also recognized the need for updates to a surface plate specification to incorporate modern concepts, such as traceability and measurement uncertainty, that have undergone considerable development since 1973. This new document under ASME B89 ownership will provide the platform for these and other updates periodically through the revision process.

This edition of B89.3.7 was approved by ANSI on April 12, 2013.

ASME B89 COMMITTEE

Dimensional Metrology

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

B. Parry, *Chair*
S. Phillips, *Vice Chair*
F. Constantino, *Secretary*

STANDARDS COMMITTEE PERSONNEL

D. E. Beutel , <i>Honorary Member</i> , Caterpillar, Inc.	M. P. Krystek , Physikalisch-Technische Bundesanstalt
J. B. Bryan , <i>Honorary Member</i> , Bryan and Associates	M. Liebers , Professional Instruments Co.
T. E. Carpenter , <i>Honorary Member</i> , U.S. Air Force Metrology Lab	E. P. Morse , University of North Carolina
T. Charlton, Jr. , Charlton Associates	B. Parry , The Boeing Co.
D. J. Christy , Mahr Federal, Inc.	P. H. Pereira , Caterpillar, Inc.
F. Constantino , The American Society of Mechanical Engineers	S. D. Phillips , National Institute of Standards and Technology
G. A. Hetland , International Institute of Geometric Dimensioning and Tolerancing	J. G. Salsbury , Mitutoyo America Corp.
R. J. Hocken , <i>Honorary Member</i> , University of North Carolina	D. Sawyer , National Institute of Standards and Technology
R. B. Hook , <i>Honorary Member</i> , Metcon	B. R. Taylor , <i>Honorary Member</i> , Renishaw
	R. L. Thompson , U.S. Air Force Metrology Lab
	K. L. Skinner , <i>Alternate</i> , U.S. Air Force Metrology Lab

SUBCOMMITTEE 3: GEOMETRY

J. D. Meadows , <i>Chair</i> , James D. Meadows & Associates, Inc.	M. Liebers , Professional Instruments Co.
J. B. Bryan , Bryan and Associates	J. Salsbury , University of North Carolina

PROJECT TEAM 1.7/8: SURFACE PLATES

D. H. Rahn , <i>Chair</i> , Consultant	K. J. Haynes , Electro Rent Corp.
R. Barta , Barta Precision Granite Surface Plates	K. W. John , U.S. Air Force Metrology Lab
E. W. Blackwood , The Boeing Co.	R. L. Knake , American Association for Laboratory Accreditation
D. J. Christy , Mahr Federal, Inc.	D. A. Lorenzen , The Boeing Co.
J. D. Drescher , Pratt and Whitney	E. V. Lundquist , AA Jansson

CORRESPONDENCE WITH THE B89 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B89 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued for the purpose of providing alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee Web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the Standard, the paragraph, figure or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the B89 Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B89 Standards Committee.

The request for interpretation should be clear and unambiguous. It is further recommended that the inquirer submit his or her request in the following format:

Subject: Cite the applicable paragraph number(s) and the topic of the inquiry.
Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.
Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. The inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in this format may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B89 Standards Committee regularly holds meetings that are open to the public. Persons wishing to attend any meeting should contact the Secretary of the B89 Standards Committee.

Introduction

One primary purpose of specifying values for surface plate parameters such as flatness, or for measuring these parameters, is to predict or estimate the level of accuracy that may be accomplished in measurements when the surface plate serves as a reference for those measurements, i.e., the measurement errors will tend to be smaller when a flatter (higher grade) surface plate is used as a reference, and measurement errors will generally be larger when a lower grade surface plate is used. Although, in general, it is difficult to quantitatively relate surface plate flatness to measurement errors, for specific applications, a certain flatness parameter may correlate very well with measurement errors, e.g., a measurement task involving a height standard with support spacing the same as that of a repeat reading gage may have measurement errors that are close to the repeat readings from the gage. It is safe to say, in general, the correlation will be useful but qualitative. The definitions and procedures in this Standard can also allow fair comparisons between surface plates, and they can help to identify and quantify changes in a given surface plate that occur over time, either from use or from changes in the environment.

GRANITE SURFACE PLATES

1 GENERAL

1.1 Scope

This Standard covers igneous rock (granite) plates for use in high accuracy locating, layout, and inspection work. It encompasses new certification, recertification in the field, and recertification after resurfacing. In general, the standard covers any size granite surface plate. Information for the sizes in common use is presented in tabular form.

1.2 Classification: Styles and Grades

Surface plates shall be of the following styles and grades:

(a) Styles (shapes)

- Rectangular, no ledge (see Fig. 2)
- Rectangular, 2 ledge, either direction (see Fig. 3)
- Rectangular, 4 ledge (see Fig. 4)
- Round, no ledge (see Fig. 5)

(b) Grades

- AA
- A
- B

2 DEFINITIONS

bow: the condition of a surface plate when the middle of the plate is higher or lower than the two ends.

F.I.M.: Full Indicator Movement

flatness: the condition of a surface or derived median plane having all elements in one plane.

grade: the classification of a surface plate according to the flatness and repeat reading tolerance of the work surface. (This Standard covers three grades: AA, A, and B.)

inserts: typically made of metal (usually stainless steel, to prevent rusting) and are “plugs,” usually predrilled and tapped to various thread diameters and pitches, and are pushed into a granite surface plate. They can also be furnished as a “solid” insert — no predrilling or tapping. Threaded inserts allow for hold-down capabilities and fixturing on a granite surface plate.

ledge: an undercut made along the sides or across the ends (or both) of a surface plate.

repeat reading: a measure of flatness over localized areas of a surface plate. This measure is usually obtained using

a repeat reading gage (see following definition) that measures height variation of the surface plate from a reference established by the base of the repeat reading gage. The range of readings taken with a repeat reading gage represents local deviation from flatness over the area sampled.

repeat reading gage: a gage used to obtain repeat readings (see Fig. I-3). This instrument estimates the ability to reproduce a measurement of a fixed height at any place on the surface plate. The repeat reading gage is sensitive to short wavelength variation in flatness when readings are taken over small intervals of movement of its base.

twist: the condition of a surface plate where the plate takes on the shape of a surface whose ends have been turned in opposite directions (e.g., like the shape of a propeller). The four corners of plates having this condition do not lie within the same plane. The lines characterizing opposite ends of a surface plate that exhibits twist have some relative angle between them (see Fig. 1).

3 REFERENCES

3.1 Normative References

- ASME B46.1, Surface Texture, Surface Roughness, Waviness and Lay
- ASME B89.6.2, Temperature and Humidity Environment for Dimensional Measurement
- ASME B89.7.3.1, Guidelines For Decision Rules: Considering Measurement Uncertainty in Determining Conformance to Specifications
- ASME Y14.5M, Dimensioning and Tolerancing
- Publisher: The American Society of Mechanical Engineers (ASME), Two Park Avenue, New York, NY 10016-5990; Order Department: 22 Law Drive, P.O. Box 2900, Fairfield, NJ 07007-2900 (www.asme.org)
- ASTM C119-99b, Terminology Relating to Dimension Stone
- ASTM C615-99, Standard Specification for Granite Dimension Stone
- Publisher: American Society for Testing and Materials (ASTM International), 100 Barr Harbor Drive, P.O. Box C700, West Conshohocken, PA 19428-2959 (www.astm.org)
- Research Paper 1320, Physical, Mineralogical, and Durability Studies on the Building and Monumental Granites of the United States, Journal of Research of