

ASME HST-2-2023
(Revision of ASME HST-2-2018)

Performance Standard for Hand Chain Manually Operated Chain Hoists

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME HST-2-2023
(Revision of ASME HST-2-2018)

Performance Standard for Hand Chain Manually Operated Chain Hoists

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: October 16, 2023

The next edition of this Standard is scheduled for publication in 2028.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The standards committee that approved the code or standard was balanced to ensure that individuals from competent and concerned interests had an opportunity to participate. The proposed code or standard was made available for public review and comment, which provided an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity. ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor does ASME assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representatives or persons affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

The endnotes and preamble in this document (if any) are part of this American National Standard.



ASME Collective Membership Mark

“ASME” and the above ASME symbol are registered trademarks of The American Society of Mechanical Engineers.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2023 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved

CONTENTS

Foreword		v
Committee Roster		vi
Correspondence With the HST Committee		vii
Summary of Changes		ix
Chapter 2-0	Scope, Definitions, References, and Appendix	1
Section 2-0.1	Scope	1
Section 2-0.2	Definitions	1
Section 2-0.3	References	4
Section 2-0.4	Appendix	4
Chapter 2-1	Performance	5
Section 2-1.1	General	5
Section 2-1.2	Characteristics	5
Section 2-1.3	Application Analysis	5
Section 2-1.4	Specifications of Lift, Headroom, and Reach	5
Section 2-1.5	Trolleys	5
Section 2-1.6	Overload Limiting Device	6
Section 2-1.7	Load Sprockets (Pocket Wheels)	6
Section 2-1.8	Load Chain	6
Section 2-1.9	Hooks	6
Section 2-1.10	Load Blocks	6
Section 2-1.11	Brakes	6
Section 2-1.12	Overtravel Restraint	7
Section 2-1.13	Typical Hoist Inquiry Data Form	7
 Nonmandatory Appendices		
A	Performance Requirements for Hand Chain Manually Operated Chain Hoists Used in Marine and Other Applications as Required by the U.S. Department of Defense	12
B	Mechanical Spark Resistance Guidance for Applications in Hazardous (Potentially Explosive) Locations	20
 Figure		
2-0.2.1	Headroom, Lift, and Reach	3
 Tables		
2-1.2-1	Typical Hoist Characteristics — Hook Suspended or Clevis Suspended	8
2-1.2-2	Typical Trolley-Suspended Hoist Characteristics (Hoist Suspended From a Separate Trolley)	9
2-1.2-3	Typical Trolley-Suspended Hoist Characteristics (Integral)	10
A-2.3.3-1	Type D, Hand-Chain-Operated Hoist, Link Chain, Low Headroom, Plain Trolley Suspension	14

A-2.3.4-1	Type E, Hand-Chain-Operated Hoist, Link Chain, Low Headroom, Geared Trolley Suspension	14
A-3.4-1	Hook Throat Openings	16
Form		
2-1.13-1	Typical Hoist Inquiry Data Form	11

Currently in preview, click buy full versi

FOREWORD

ASME HST-2 is one in a series that provides performance requirements for hoists. Originally published in 1983, ASME HST-2 was developed by the ASME HST Standards Committee, Hoists — Overhead to guide manufactures, purchasers, and users of hand chain manually operated chain hoists.

Standards in the ASME HST series are as follows:

Designator	Title
ASME HST-1	Performance Standard for Electric Chain Hoists
ASME HST-2	Performance Standard for Hand Chain Manually Operated Chain Hoists
ASME HST-3	Performance Standard for Lever Hoists
ASME HST-4	Performance Standard for Overhead Electric Wire Rope Hoists
ASME HST-5	Performance Standard for Air Chain Hoists
ASME HST-6	Performance Standard for Air Wire Rope Hoists

ASME HST-2-2023 contains a Nonmandatory Appendix B that provides guidance to assist both the manufacturer and the end user in configuring a hoist for use in a potentially explosive environment. The requirements of this Standard shall be applied with the requirements of ASME B30.16.

This Standard is available for public review on a continuing basis. This provides an opportunity for additional public review input from industry, academia, regulatory agencies, and the public-at-large.

ASME HST-2-2023 was approved by the American National Standard Institute as an American National Standard on August 18, 2023.

ASME HST COMMITTEE

Hoists — Overhead

(The following is the roster of the committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

J. R. Burkey, *Chair*
M. A. Martinez Correa, *Vice Chair*
J. Cassamassino, *Secretary*

STANDARDS COMMITTEE PERSONNEL

J. R. Burkey , Columbus McKinnon Corp.	E. K. Marburg , Columbus McKinnon Corp.
B. M. Casey , Electric Boat Corp.	M. A. Martinez Correa , Chevron Upstream & Gas
J. Cassamassino , The American Society of Mechanical Engineers	S. A. Smith , Naval Sea Systems Command Headquarters
J. E. Eaglin , JON Mechanical Systems, Inc.	K. Sprague , INEOS Olefins & Polymers USA
M. Elza , WSP	D. C. Staber , Nuclear Waste Partnership, LLC
J. D. Hoke , Harrington Hoists, Inc.	W. E. Osborn , <i>Honorary Member</i> , Ingersoll Rand

CORRESPONDENCE WITH THE HST COMMITTEE

General. ASME codes and standards are developed and maintained by committees with the intent to represent the consensus of concerned interests. Users of ASME codes and standards may correspond with the committees to propose revisions or cases, report errata, or request interpretations. Correspondence for this Standard should be sent to the staff secretary noted on the committee's web page, accessible at <https://go.asme.org/HSTcommittee>.

Revisions and Errata. The committee processes revisions to this Standard on a continuous basis to incorporate changes that appear necessary or desirable as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published in the next edition of the Standard.

In addition, the committee may post errata on the committee web page. Errata become effective on the date posted. Users can register on the committee web page to receive e-mail notifications of posted errata.

This Standard is always open for comment, and the committee welcomes proposals for revisions. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent background information and supporting documentation.

Cases

(a) The most common applications for cases are

(1) to permit early implementation of a revision based on an urgent need

(2) to provide alternative requirements

(3) to allow users to gain experience with alternative or potential additional requirements prior to incorporation directly into the Standard

(4) to permit the use of a new material or process

(b) Users are cautioned that not all jurisdictions or owners automatically accept cases. Cases are not to be considered as approving, recommending, certifying, or endorsing any proprietary or specific design, or as limiting in any way the freedom of manufacturers, constructors, or owners to choose any method of design or any form of construction that conforms to the Standard.

(c) A proposed case shall be written as a question and reply in the same format as existing cases. The proposal shall also include the following information:

(1) a statement of need and background information

(2) the urgency of the case (e.g., the case concerns a project that is underway or imminent)

(3) the Standard and the paragraph, figure, or table number(s)

(4) the edition(s) of the Standard to which the proposed case applies

(d) A case is effective for use when the public review process has been completed and it is approved by the cognizant supervisory board. Approved cases are posted on the committee web page.

Interpretations. Upon request, the committee will issue an interpretation of any requirement of this Standard. An interpretation can be issued only in response to a request submitted through the online Interpretation Submittal Form at <https://go.asme.org/InterpretationRequest>. Upon submitting the form, the inquirer will receive an automatic e-mail confirming receipt.

ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the information submitted, it is the opinion of the committee that the inquirer should seek assistance, the request will be returned with the recommendation that such assistance be obtained. Inquirers can track the status of their requests at <https://go.asme.org/Interpretations>.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME committee or subcommittee. ASME does not "approve," "certify," "rate," or "endorse" any item, construction, proprietary device, or activity.

Interpretations are published in the ASME Interpretations Database at <https://go.asme.org/Interpretations> as they are issued.

Committee Meetings. The HST Standards Committee regularly holds meetings that are open to the public. Persons wishing to attend any meeting should contact the secretary of the committee. Information on future committee meetings can be found on the committee web page at <https://go.asme.org/HSTcommittee>.

Currently in preview, click buy full version

ASME HST-2-2023 SUMMARY OF CHANGES

Following approval by the ASME HST Committee and ASME, and after public review, ASME HST-2-2023 was approved by the American National Standards Institute on August 18, 2023.

ASME HST-2-2023 includes the following changes identified by a margin note, **(23)**.

<i>Page</i>	<i>Location</i>	<i>Change</i>
1	Section 2-0.1	Subparagraph (c)(7) added
1	Section 2-0.2	In-text Notes under <i>chain, hand</i> and <i>chain load</i> revised
4	Section 2-0.3	Updated
4	Section 2-0.4	Revised
11	Form 2-1.13-1	Revised
12	A-1.2	In-text reference citation updated
12	A-1.4	Updated
13	A-2.2	Revised
14	Table A-2.3.3-1	First row, last column and Note (4) added
13	A-2.4	Revised
14	A-2.5	Revised in its entirety
15	A-2.6	Last sentence added
15	A-3.1	Revised in its entirety
14	Table A-2.3.4-1	First column and Note (4) added
15	A-3.2	First sentence added
15	A-3.2.1	In-text reference citation updated
15	A-3.2.3	Revised in its entirety
15	A-3.2.4	First sentence revised
15	A-3.3	Revised
16	A-3.4	Revised in its entirety
16	A-3.5	Last two sentences added
16	Table A-3.5.1	First row added
16	A-3.5.2	First sentence added
17	A-3.5.2.1	Revised in its entirety
17	A-3.5.2.3	In first sentence, cross-reference citation updated
17	A-3.5.2.4	Added
17	A-3.8.3	Reference updated
17	A-3.8.4	References updated
17	A-4.1.1	Revised
18	A-4.1.2	(1) Title revised (2) First paragraph revised and designated as A-4.1.2.1 and subsequent paragraph redesignated (3) In para. A-4.1.2.2, last sentence added
18	A-4.1.3	Revised

<i>Page</i>	<i>Location</i>	<i>Change</i>
18	A-4.1.4	Last sentence added
18	A-4.1.5	Last sentence added
18	A-4.1.6	Last sentence added
19	A-4.3	Revised
19	A-5	Revised
20	Nonmandatory Appendix B	Added

Chapter 2-0

Scope, Definitions, References, and Appendix

SECTION 2-0.1: SCOPE

(23)

(a) This Standard establishes performance requirements for hand chain manually operated chain hoists for vertical lifting service involving material handling of freely suspended (i.e., unguided) loads, using a welded link type load chain as a lifting medium, with one of the following types of suspension:

- (1) hook or clevis
- (2) trolley

(b) This Standard is applicable to hoists manufactured after the date on which this Standard is issued. Differential pulley and self-locking worm drive type hoists are not covered in this Standard.

(c) This Standard is not applicable to

- (1) damaged or malfunctioning hoists
- (2) hoists that have been misused or abused
- (3) hoists that have been altered without authorization of the manufacturer or a qualified person
- (4) hoists used for lifting or supporting people
- (5) hoists used for the purpose of drawing both the load and the hoist up or down the hoist's own load chain
- (6) hoists used in applications where the load on the hand chain hoist is not freely suspended from the hand chain hoist

(7) hoists used for marine and other applications as required by the Department of Defense (DOD) unless [Nonmandatory Appendix A](#) has been invoked

The requirements of this Standard shall be applied together with the requirements of ASME B30.16. Please also refer to ASME B30.16 for requirements pertaining to marking, construction, installation, inspection, testing, maintenance, and operation.

SECTION 2-0.2: DEFINITIONS

(23)

ambient temperature: the temperature of the atmosphere surrounding the hoist.

beam: an overhead standard structural shape or specially fabricated shape on which a trolley operates.

chain, hand: the chain provided to control movement of a hand-chain-operated hoist or trolley (see [Figure 2-0.2-1](#)).

NOTE: Hand chain properties do not conform to those shown in ASME B30.9.

chain, load: the load-bearing chain in the hoist.

NOTE: Load chain properties do not conform to those shown in ASME B30.9.

conditions, abnormal operating: environmental conditions that are unfavorable, harmful, or detrimental to or for the operation of a hoist, such as excessively high or low ambient temperatures, exposure to weather, corrosive fumes, dust-laden or moisture-laden atmospheres, and hazardous locations.

conditions, normal operating: conditions during which a hoist is performing functions within the scope of the original design.

hand chain drop: the distance to the lowest point of the hand chain measured from the saddle of the load hook at its upper limit of travel (see [Figure 2-0.2-1](#)).

hand chain overhaul: the number of feet (meters) the hand chain must travel to raise the load hook 1 ft (1 m).

hand chain pull: the average force measured in pounds (kilonewtons) exerted by the operator on the hoist hand chain to lift the rated load.

hand chain wheel: a wheel with formed pockets on its periphery to allow torque to be transmitted when a force is applied to the hand chain.